CHEMICAL & Metallurgical E N G I N E E R I N G

1944 MARCH

Volume 51

Number 3

95

In this Issue

From War Plants to Cornfields.

FROM THE LOG OF EXPERIENCE..... 159

NAMES IN THE NEWS..... 163

INDUSTRIAL NOTES 168

S. D. KIRKPATRICK.....Editor HENRY M. BATTERS Market Editor JOHN R. CALLAHAM ... Assistant Editor NORMAN G. FARQUHAR. Assistant Editor LESTER B. POPE Assistant Editor

EDITORIAL REPRESENTATIVES

E.	S.	STATELERChicago
R.	S.	McBRIDEWashington
EA	RI	E MAUDLINAtlanta

M. A. WILLIAMSON.....Publisher DISTRICT MANAGERS

E. H. BEDELL.....New York R. G. FREDERICK New York FRED GRANT.....Cleveland L. A. CUNNINGHAM Chicago W. D. BOYD.....Boston J. R. VAN ARSDALE Philadelphia

Published monthly. Price 35 cents per copy. Publication office, 99-129 North Broadway, Albany I, N. Y. Address communications about subscriptions to Director of Circula-tion, Chem. & Met., 330 West 42nd St., New York 18, N. Y. Subscription rates: United States, Mexico, Central and South American Countries, \$3 per year, \$4 for two years, \$5 for three years. Canada, \$3.50 per year, \$5 for two years, \$6 for three years (payable in Canadian funds). Great Britain and British Possessions, 30 shillings years (payable in Canadian funds). Great Britain and British Possessions, 30 shillings per year, 60 shillings for three years. All other countries, \$5 per year, \$10 for three years. Entered as second class matter Sep-tember 3, 1936, at Post Office at Albany, N. Y., U. S. A., under act of March 3, 1879. Contents copyrighted, 1944 by Mc-Graw-Hill Publishing Company, Inc. Branch offices: 520 North Michigan Avenue, Chicago 11; 68 Post Street, San Francisco 4; Ald-wych House, Aldwych, London, W. C. 2; Washington 4; Philadelphia 2; Cleveland 15; Detroit 2; St. Louis 8; Boston 16; Los Angeles 13; Atlanta 3. Return Postage Guaranteed

Return Postage Guaranteed

McGRAW-HILL PUBLISHING CO., INC.

JAMES H. McGRAW Founder and Honorary Chairman

Publication Office 99-129 North Broadway, Albany 1, N. Y.

Editorial and Executive Offices 330 West 42 Street, New York 18, N. Y. JAMES H. McGRAW, Jr.....President HOWARD EHRLICH Executive Vice-President

MASON BRITTON......Vice-President CURTIS W. McGRAW......Treasurer J. A. GERARDI.....Secretary J. A. OLININGURN, Jr. J. E. BLACKBURN, Jr. Director of Circulation

Member A.B.P. Member A.B.C. Cable Address McGRAWHILL, New York

EDITORIAL FOREWORD	
Gas Turbines Offer Opportunity for I By STANLEY A. TUCKER	Process Use 96
Ammonium Picrate for Military Expl By COL. T. C. GERBER	osive Requirements 100
Penicillin, Wartime Growing Pains o By ALBERT L. ELDER and LAWRENCE A	f the Industry
How Wartime Buildings Can Be Red By C. A. HARWICK	conditioned 106
Inter-Relationship of Plastics and Ch By J. W. RAYNOLDS	emicals 109
Chem. & Met. Plant Notebook	116
Engineers in War and Postwar Chemi A CHEM. & MET. REPORT	ical Industry 119
Bleaching Sulphate Pulp A CHEM. & MET. PICTURED FLOWSHEE	т 132
WATCHING WASHINGTON 84	CONVENTION PAPER ABSTRACTS 17
FROM AN EDITORIAL VIEWPOINT 114	FOREIGN LITERATURE ABSTRACTS 19
PROCESS EQUIPMENT NEWS 127	CHEM. & MET. BOOKSHELF 19
New Products and Materials 139	GOVERNMENT PUBLICATIONS 19
CHEMICAL ENGINEERING NEWS 145	MANUFACTURERS' PUBLICATIONS 20
NEWS FROM ABROAD 152	CHEMICAL ECONOMICS 20

AN INDEX TO ADVERTISERS WILL BE FOUND ON PACE 400.

PRODUCTION AND CONSUMPTION... 206 CURRENT PRICES 212

New CONSTRUCTION 214

- M	
CHANGE OF ADDRESS	MeGRAW-HILL PUBLISHING COMPANY 330 West 42nd Street, New York 18, N. Y. Director of Circulation: Please change my address on Chemical & Metallurgical Engineering From
	To
	Signed



The BRINELL testing machine, shown above in Tube Turns' laboratories, scientifically determines the hardness, or wear resistance, of finished fittings.

Endurance is indispensable in welding fittings, for the destructive forces in piping — strain, pressure, vibration, corrosion and erosion — are more highly concentrated at the fittings.

Tube Turns' exclusive manufacturing process

forges fittings which virtually eliminate premature wear, leakage, and maintenance throughout the life of piping. Systematic hardness tests *insure* the enduring qualities possessed by all Tube-Turn seamless welding fittings.

TUBE TURNS (Inc.) Louisville, Kentucky. Branch Offices: New York, Chicago, Philadelphia, Pittsburgh, Cleve land, Dayton, Washington, D. C., Houston, San Francisco, Seattle . . . Distributors located in all principal cities.





ward the Course

Westward from the Hudson and up through the fertile, rolling valleys of 'York State, came the Dutch and other traders in their great lumbering Conestoga wagons. They brought with them the necessities and luxuries sought by the settlers and the pioneers who were ever pushing the frontier westward. Even then, Niagara was a thriving center of activity, a link between the busy East and the growing West, a young and energetic locality ready for new trade, agricultural and industrial development. As a pioneer chemical manufacturer in the Niagara area and the first to produce several important chemicals in America, Niagara Alkali Company is applying the full force of its pioneering experience and energy to supplying increasing quantities of essential products for which there is a growing demand to fill vital wartime needs. Thus is Niagara Alkali carrying on the pioneering traditions of its background. CAUSTIC POTASH - CAUSTIC SODA - PARADICHLOROBENZENE CARBONATE OF POTASH - LIQUID CHLORINE

n Essential Part Of America's Great Chemical Enterprise



iagata Alkali COMPANY



"Look what a big baby our Pilot Plant had!"

It's the never-ending research of America's chemists and technicians which have put this country far out in front in both the development and production of things for better living.

Pilot Plants designed and built by Blaw-Knox have been the incubators for products and processes now requiring plants measured in acres rather than a few square feet.

Blaw-Knox technical specialists can carry your process through from flow-sheet to mass-production. Glad to consult with you without fee or obligation ... your request for the new catalog No. 1957, Blaw-Knox Pilot Plants, will bring you a copy by return mail.

BLAW-KNOX Equipment for the Process Industries:

Absorbers Autoclaves Blenders Calciners Chlorinators Crystallizers Dehydrating Equipment Deodorizers Digesters Dryers

Evaporators Heat Exchangers Kettles Kilns Nitrators Oil Cracking Equipment **Pilot Plants** Solvent Extraction Equip. Solvent Recovery Systems Stills Vacuum Processing Equipment

BUY U.S. WAR BONDS AND STAMPS

DIVISION OF BLAW-KNOX COMPANY 2090 FARMERS BANK BLDG., Pittsburgh, Pa. PHILADELPHIA BIRMINGHAM WASHINGTON



NINE FOOT TWO

SEAMLESS . . . TRUE

Another example of Taylor Forge "know-how" that means extra value in WeldELLS

Turning out a 110" O.D. SEAMLESS Steel Flange to rigid specifications of accuracy isn't exactly the easiest job in the world. But tough jobs are not unusual here at Taylor Forge. In fact, this one is quite typical of the kind that is so often assigned to us by engineers who feel we are a little better at it than any other organization.

For a good many years these "unusual" things have been the usual at Taylor Forge . . . doing things with hot metal that nobody else does . . . knowing just how to control its flow and form under pressure and impact.

And in the final analysis there is no better example of this than your old friends WeldELLS and other Taylor Forge welding fittings themselves. For while WeldELLS represent our regular line of welding fittings, they reflect forging operations that are *far* beyond the usual!

Check down the list of WeldELL features and you will see how true this is. Only Taylor Forge knowledge and methods could give you a fitting with tangents and selective distribution of metal in an extremely accurate, seamless forging! Add to this the features of WeldELLS which cut welding time and costs, and you have the fittings that . . . "bave everything"!

WeldELLS have everything

TAYLOR FORGE & PIPE WORKS, General Offices & Works: Chicago, P. O. Box 485 New York Office: 50 Church Street • Philadelphia Office: Broad Street Station Bldg.

No other welding fittings combine these features:

• Seamless --- greater strength and uniformity.

• Tangents-keep weld away from zone of highest stress-simplify lining up.

• Precision quarter-marked ends ---simplify layout and help insure accuracy.

• Selective reinforcement — provides uniform strength.

• Permanent and complete identification marking—saves time and climinates errors in shop and field. • Wall thickness never less than specification minimum—assures full strength and long life.

• Machine tool beveled ends provides best welding surface and accurate bevel and land.

• The most complete line of Welding Fittings and Forged Steel Flanges in the World — insures complete service and undivided responsibility.

SOLVAY*

... KEYED TO TODAY AND TOMORROW!



Official U. S. Navy Photo

Today. Solvay Alkalies are all mobilized for Victory Production! They are a vital, basic factor in the construction of war materiel. Caustic Soda, Soda Ash and many other vital and related products are now being supplied from three strategically located plants. Established in 1881, Solvay is America's largest producer of alkalies.



Tomorrow...Solvay products will contribute immeasurably to chemical achievements that will enrich the world of tomorrow. Drawing upon its extensive resources, broad and varied experience and continuous research, Solvay will produce the finest alkalies. As in the past, its resources of technical knowledge and services will be available to industry.

-	S	DDA	ASH	•	CAU	USTI	C SC	DDA
æ,	=) AN	MONI	JM CHLO	ORIDE	•	CAUST	IC PC	TASH
(BB	M	DDIFIED	SODAS	• AM	MONI	UM BIC		NATE
sor	MUIC	NITRIT	Ε.	PARA	-DICI	HLORC	DBEN	ZENE
CAL	CIUM	CHLO	RIDE	• (CHLO	RINE		SALT
		POT	ASSIUN		RBON	ATE		

SOLVAY SALES CORPORATION Alkalies and Chemical Products Manufactured by The Solvay Process Company 40 RECTOR STREET NEW YORK 6, N. Y. BRANCH SALES OFFICES:

Boston • Charlotte • Chicago • Cincinnati • Cleveland • Detroit New Orleans • New York • Philadelphia • Pittsburgh • St. Louis • Syracuse

WATCHING WASHINGTON-

R. S. McBRIDE, Editorial Consultant · PAUL WOOTON, Chief of McGraw-Hill Washington Bureau · MALCOLM BURTON, Washington Correspondent

Here is your chance to buy a war plant ... Congress appropriates \$30,000,000 for development of synthetic fuels ... Dewey announces \$30,000,000 expenditure for modifications to make synthetic rubber plants more efficient ... A hunt is on in New Mexico for more potash reserves ... Specialized training program for engineers has been cancelled ... Sulphur will move to market by a new route ... Barium chemicals are giving Washington concern ... Federal Trade Commission challenges advertising ... Rye may be substituted as a raw material for some alcohol manufacture ... Difficulties in Army contract cancellation clauses.

SELLING ARMY PLANTS

THE WAR Department is working out a definite procedure for the disposal of surplus manufacturing capacity which has been used during the war period for making Ordnance, Chemical Warfare, or other materials, and which is now an excess capacity no longer required by the Army.

What might be called process industry facilities are already being so identified for disposal in the case of TNT, smokeless powder, shell filling, and related equipment. Included are facilities for the manufacture of ammonia, sulphuric acid, nitric acid, and a variety of explosives. All of these projects will apparently be handled by a division in the Office of the Chief of Engineers headed by O. S. Sieder, the only civilian chief of any major part of the Engineer Corps.

MORE OIL FOR PAINT

EVIDENTLY believing in the old adage, "If at first you don't succeed, try, try again," the paint industry has been successful in promoting a 16 percent increase in the allocation of fats and oils for the current quarter. The increase from 60 to 70 percent of the average used in the corresponding calendar quarter of 1940 and 1941 applies to essential paints, varnishes, lacquers and other protective coatings, linoleum, oilcloth, felt base floor coverings and coated fabrics.

The increase is granted for the first quarter of this year only, but provision is made to carry over into the second quarter any unused portions of the first quarter's allocation. It is a hope that a similar increase in the allocation will be made for the second quarter if the relation of supply and requirements for linseed oil remains approximately the same and the tuture picture continues to be unclouded. But in late February indications were that the allocation rate would be dropped back to the 60 percent level in the second quarter. Shortage of chromium and titanium oxide pigments will bring an increase in lead and zinc combinations and some lithopone combinations.

The amendment to FDO 42 which controls the use of fats and oils also removes from restriction finishes for containers, closures and closure liners for foods, drugs, beverages and pharmaceuticals.

MRO RATINGS PUT ON SAME BASIS

ACTION has been taken to prevent war plants from extending their AA-1 and AA-2 blanket ratings for maintenance, repair and operating supplies. In effect it has put all MRO ratings on the same basis. This has been accomplished by an amendment to Direction No. 5 of Priorities Regulation No. 3.

The practice of war plants in the chemical industry of extending their blanket ratings for their maintenance and operating supplies brought about a maldistribution of some of the chemicals and resulted in their being placed under allocation. Under the new procedure it is hoped that the difficulties that have resulted in some of the allocations can be avoided elsewhere. There even is hope that the distribution problems can be alleviated sufficiently to permit a relaxation or total abandonment of some of the allocation orders. At the present this remains only a hope.

SYNTHETIC FUELS AUTHORIZED

THE House of Representatives late in February voted approval of the bill which authorizes the U. S. Bureau of Mines to build demonstration plants for manufacture of synthetic liquid fuels from coal, oil shale, and lignite. The House also authorized comparable investigations on agricultural and forest raw materials. The appropriations authorized by the bill, which was previously approved by the Senate, are 530,000,000. Only a small part of this will be used in the coming fiscal year, it is expected. Early projects contemplate a pilot unit test of the Fischer-Tropsch process at Bruceton, Penn., and further determination of necessary engineering data

MARON TOAL

for the design of a Bergius process plant for hydrogenation of coal. It is not expected that actual demonstration plants will be built during the first year. However, design work will begin and substantial expenditure for such demonstration plants of commercial size will be undertaken in the second or third year. As initiated, the program contemplates five years of experimental and demonstration work, with no intimation as to plans thereafter.

RUBBER TRENDS NOTICED

SYNTHETIC rubber supplies, though more adequate now than every before, are still less than the urgent demand for military and civilian applications. Hence almost daily Washington announces modified rulings and forecasts. Rubber Director Bradley Dewey announced that the January production of synthetic rubber was 50,000 tons; but he forecast that the average output for the second half of 1944 would be about 75,000 tons per month.

Efforts are being continued to get as much natural rubber as possible. Rubber Development Corp. announced an increase by one-third in the price for natural rubber from Brazil which was originally established in 1942. The recent price has been approximately 45c. per lb.

Scrap rubber collections since 1942 amount to about 750,000 tons, of which about 35,000 tons per month is being used.

Neoprene and special rubber supplies continue in greater demand than supply. Hence more stringent restrictions were imposed recently on neoprene and neo prene cement. These restrictions have become necessary despite the expectation of some months ago that these special rubbers would be more abundant at this time. Allocations continue in accordance with end-product uses.

The new synthetic rubber plant at Port Neches, Texas, has been dedicated with total capacity shortly operable of 120,000 tons of butadiene per year. That is oneseventh of the country's wartime demand. In connection with this and other synthetic developments Washington has also been making a great point of the large requirement for industrial soap for use in Buna-S making. The slogan is almost "no soap, no rubber." Approximately 100,000,000 lb. of soap are used annually in the synthetic rubber program which is a new market for soap.

BUNA S PLANT IMPROVEMENT

CHEMICAL & METALLIBOICAL ENGINEEDING

EXPENDITURE of \$30,000,000 to improve plants producing synthetic rubber during the year 1944 was announced by Bradley Dewey, rubber director, in mid-February. This expenditure is for the purIt's easy to secure the advantages of **VARIABLE**

SPEEDRANGERS

Mighty impressive is the number of companies who are using large numbers of Master Speedrangers. They have found that the many advantages of variable speed operation can be secured more easily by using this drive.

It's easier because the Speedranger is a compact integral unit . . . only one unit to mount . . . saves space, saves money.

It's easier because Speedrangers are available for every current specification, every type enclosure, with gearheads, unibrakes . . . and in the whole wide range of types in the Master line. This wide flexibility makes it easier to secure just the right drive for each installation.

And it's easier to keep right on enjoying these advantages because the all-metal construction of the Speedranger insures much longer trouble free service than units in which less durable materials are used. In addition, the complete Speedranger is designed and manufactured as a unit in one plant by one manufacturer, so there is no division of responsibility for its satisfactory operation.

Investigate how easily you can secure the many advantages of variable speed operation if you use Master Speedrangers. THE MASTER ELECTRIC COMPANY • DAYTON 1, OHIO Each of the Quantumpers of the Antoinerine is supplied for solary assuming, and in taking taky thes provides for asymptic transic solarist of the speed.



pose of changing designs and making minor additions to bring about a more efficient operation of some of the units. Butadiene from alcohol facilities has been allocated \$3,000,000 and butadiene from petroleum \$10,000,000. Styrene plants will receive \$3,000,000 and copolymer plants \$10,000,-000. The sum of \$3,000,000 will be distributed to butyl facilities and \$1,000,-000 will be used for miscellaneous improvements. In making the announcement, Director Dewey emphatically stated that the projects are in no sense an expansion of the synthetic program.

POSTWAR PLANS MERGED

COOPERATION in postwar planning between labor and management, between management and agriculture, and between all three and career officials of the government is now observable in Washington. A few politically minded officials still play one group against another. But many legislators and most career executives of departments, including the military, recognize that all groups have a common problem in finding an equitable, workable basis for readjustment. Perhaps the most con-spicuous leader of cooperative effort is Eric Johnston, president of the Chamber of Commerce of the United States. His organization, abandoning the old guard philosophy, is proving something of a rallying ground for the meeting of what were formerly conflicting interests.

POTASH DRILLING PLANNED

USING the inflated estimates of potash demand furnished by zealous spokesmen for agriculture, the Department of Interior is planning further explorations for potash this spring. Late in February they took bids for drilling certain areas in New Mexico near Carlsbad intending to block out reserves there. The Department obviously hopes that minable occurrences will be proven by a dozen or more core drillings in an area where one or two wells have shown a small occurrence.

wells have shown a small occurrence. Plenty of criticism has been offered of this hasty plan. Some object to the diversion of funds from other mineral investigation. Others charge that it is merely an effort to use claimed shortages of potash for doing work which Congress would not approve at this time through direct appropriation. There is, however, no criticism of the idea that soon after the war there should be approval for drilling further to block out potash reserves in the Carlsbad arca.

Most bitter are the critics who claim that it is a further effort of the Department of Interior to get the government into the mining business. This latter charge arises principally from the nonpreference of those backing this plan. They, in previous undertakings, have sought to establish the equivalent to TVA for other minerals and other power areas.

Some of the talk even implies that if the Department proves the minable occurrence of potash mineral they will undertake to use it as a club over present producers. This interpretation comes at least in part from the efforts made heretofore to secure a cut in the price of potash. Whatsoever the motive, it is evident that

these officials do not intend to use present abundant hoisting capacity by urging the building with government money of more refineries.

The present hoisting capacity would certainly equal a million tons per year of K_2O . The refinery capacity is about three quarters of this amount. The refineries are now supplying all immediate demands; but obviously cannot meet the extreme of requirement estimated for the next fertilizer year (1944-1945) which some enthusiasts say should be as much as a million tons of K_2O . It is stated that the only way this larger production could be reached in time would be to build new refineries for processing the larger quantities of lowgrade mineral which can be hoisted from proven reserves already being worked.

MORE POTASH AVAILABLE

DURING February more potash became available for agriculture. Additional supplies will make 580,000 short tons of K_2O available for the current fertilizer year. Allocations for chemical usage are now 100,000 tons of K_2O , an all-time record.

MOLASSES AGREEMENT MADE

NEGOTIATIONS at Havana by United States representatives provide for better working relations between this country and Cuba on blackstrap molasses and industrial alcohol. The agreement for 1944 includes the following four provisions:

1. The United States is to purchase an initial minimum of 65,000,000 gal. of blackstrap molasses, at 13.6 c. per gal. base and with other terms and conditions similar to those in the 1944 invert molasses contract.

2. The United States is to purchase up to 12,500,000 gal. of 190 proof industrial alcohol, at 65 c. per gal., f.o.b. Havana, Cuba. To the extent that any of this alcohol is not produced by Cuban distilleries, Cuba has agreed to sell the United States the molasses which would have been required to produce it.

3. An estimated 85,000,000 gal. of blackstrap molasses will be required to produce the alcohol necessary for Cuban domestic motor fuel (carburante) and for Cuban industrial uses.

4. Cuba has agreed that the export of beverage alcohol to the United States in 1944 will not exceed the amount imported into the United States from Cuba during 1943—approximately 14,300,000 proof gal.

It is hoped that additional molasses above the initial minimum provided in paragraph one will be available either as blackstrap or more alcohol. Perhaps as much as 8,000,000 gal. of industrial alcohol may be so supplied.

ENGINEER TRAINING CANCELLED

URGENT need of young brain power in the combat forces compelled cancelation during February of most plans under Army Specialized Training Program contracts. A few advanced students of engineering as well as medical training groups at several levels are to be continued. But the flow of engineers from the basic groups into professional training is likely to be com-

pletely cut off by or soon after April 1. Few chemical engineering students will be affected as the groups in this specialty were small. The change in the Army program will probably not stop the plan for exemption of a few civilians to take engineering courses under the National Roster's quotas described in Chem. & Met. last month.

INDUSTRY TO BE HEARD

AN OFFICIAL announcement of WPB states that "no limitation or conservation order or amendment may be issued without prior consultation with an industry advisory committee if the change will result in a substantial alteration in the operations of that industry."

The new order also points out that it is the duty of WPB to protect the representatives of industry against anti-trust prosecution which might grow out of their active cooperation if it were not arranged in the interest of the public and in cooperation with the government. It is emphasized that such group action must be limited to the needs of the government and the public, or immunity from prosecution cannot be promised where improper agreements are being entered into.

NATURAL GAS SHORTAGE

INDUSTRIAL users of natural gas have been cut off from supplies of this fuel in a number of areas. It is believed that from February through April there may be serious difficulties recurring in the territory extending from Missouri to the Eastern Scaboard, insofar as this territory gets natural gas. But forecasters who seem to know what they are talking about say that this difficulty will not occur again next year, as completion of pipelines into the Eastern territory will be accomplished late in the Spring. Obviously, the shortage will not be serious in summer as the space-heating demands of the warm months are small, and space heating has been the cause of most of the peak demands which have gone beyond the capacity of pipelines.

MORE AEROSOLS PROMISED

ARMY NEED for insect sprays to control mosquito-borne malaria and worse diseases has been emphasized by the tremendous number of casualties from exposures in Africa and the Pacific war areas. Strenuous efforts have been made, therefore, to increase both the propellent production and the manufacture of substitutes for pyrcthrum. During February it was announced that Du Pont would build a large plant for manufacture of DDT (dichlorodiphenyltrichloroethane). This is the Geigy product which has been most widely accepted in recent months as an almost adequate replacement material for pyrethrum. It is used also very effectively as a dust on clothing to give protection againt body lice.

WPB has also announced plans for the new production by Du Pont of Freon. That refrigerant gas is the dispersing agent used in the aerosol bombs. After the new capacity is completed at Deep-

• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

CERATHERM . A NEW CHEMICAL STONEWARE

UNAFFECTED BY VIOLENT Thermal Shocks

LOW IN POROSITY HIGH IN SEVENGTH

A glance at the chart will tell you why engineers are specifying chemical equipment made from the new Ceratherms, the amazing dense-bodied, heat-shock resistant chemical stoneware.

Here for the first time is a chemical stoneware, rugged and strong, a body that doesn't have to be handled with kid gloves, a body able to withstand abrupt changes in temperature up to as high as 750 degrees F.

The new Ceratherms retain all of chemical stoneware's well-known advantages: ease of fabrication, low cost, unrivalled corrosionresistance, freedom from contamination.

*With the exception of hot caustics and hydrofluoric acid, these new Ceratherms will handle all acids, alkalies and solvents in any concentration.



	Typical Commercial Chemical Stoneware	New Normal Service ''U. S.'' Chemical Stoneware	Ceratherm 500	Ceratherm 750
POROSITY	2.5	0.3	0.5	1.5
MODULUS OF RUPTURE (Ibs. per sq. inch)	4900	6200	6500	6900
COMPRESSIVE STRENGTH (lbs. per sq. inch)	45,000	63,600	78,000	82,800
RELATIVE PERCENTAGE OF LOSS OF STRENGTH IN U. S. S. CO. STANDARD QUENCH TESTS	Failure	90%	15%	5%
RELATIVE IMPACT- SHOCK RESISTANCE	1.0	1.45	1.78	1.96

Chart comparing physical properties of Ceratherm 500 and Ceratherm 750 with new normal service U. S. Standard Chemical Stoneware and with typical Commercial chemical stoneware.

Specify Ceratherm for such products as these:

Pumps, Suction Filters, Cooling and Condensing Coils, Tanks, Jars, Pots, Pipe, Fittings, Laboratory Sinks, Ventilating Pipe and Exhausters.

Write for new Bulletin today!



Ceratherm actually shows an increase in mechanical strength (note chart at right) when heated to 400 degrees F. and quenched more than 100 degrees beyond the point where ordinary bodies begin to lose strength.



water, N. J., and East Chicago, Ind., the monthly production of Freon will be 4,800,000 lb. The new output will also permit extension of the supply of this chemical to refrigerant users who have been working on restricted supplies recently.

Aggressive work is also being done by the Army to supply mosquito repellents for use on the skin of soldiers while actively in the field in infested areas. These are employed in either lotion or other forms to minimize the danger of bites by typhusbearing or malarial insects. Several satisfactory synthetic repellents have been developed by chemical research guided by practical field tests under the direction of entomologists.

INSECTICIDE NEED IS LARGE

EVERY available raw material for insecticide manufacture is being carefully conserved this year for urgent needs in agriculture, victory gardens, and health and sanitary uses at home as well as for the Army. Arsenic, though still scarce, will come much nearer this year to meeting agricultural and victory garden needs, according to WPB's February estimates. That agency has even withdrawn its objection to the use of arsenicals for shade trees, nurseries, lawns, and golf courses. With reference to their packaging, insecticides have been accorded considerable preference aid, thus permitting the use of steel drums, bottles, bottle closures, and even multiwall bags.

GOVERNMENT SHIPMENTS TAXED

MANY shipments of government goods are being taxed 3 percent of the freight charge through error. The Internal Revenue Regulations provide in Section 3475 that property owned by, or shipped for, the federal government, any state, any political subdivision thereof, or the District of Columbia is exempt from this transportation tax. Shippers are warned that they should not pay such tax, as they are not permitted to re-collect from the government.

STOCKPILE LEGISLATION

MEMBERS of Congress from the western mining states have thus far dominated the thinking and the planning for legislation regarding postwar mineral stockpiles. These legislators are centering their efforts on support of S. 1582, proposed by Senator Scrugham of Nevada. That bill, if enacted, would provide for the building of huge mineral stockpiles with surpluses from the war period plus some production from American mineral occurrences. The effort is to prevent the domestic mining industry, which has been stimulated by war demand for scarce minerals, from finding competition. The mining industry hopes that it can secure a sterilization of these surplus stocks and some form of restriction on imports. Legislation even goes so far as to prevent free working of scrap from the war period. The objective is, of course, to maintain a high price tor domestic producers irrespective of postwar supply.

A somewhat different view was expressed by W. L. Batt, vice-chairman of

WPB, in a recent address in which he stated that after the war we will have a surplus of ships and of manufactured goods. We will have goods to sell and facilities for shipping them to countries where they will be sorely needed but where the ability to pay for them will be doubtful. Batt suggested that in return for such shipments abroad, we accept payment in the form of imports of critical materials. He pointed out that this country no longer had unlimited supplies of low cost iron, zinc, and copper, that our petroleum reserves had been strained and that we never had much high-grade bauxite, nickel, or tin. Under proper controls, he felt that imports of vital materials would be helpful not only in conserving our dwindling supplies but also in creating stockpiles for emergency use.

STARCH PRICE RAISED

THE CEILING price on corn starch and dextrine products in bulk was raised by OPA during February by 62c. per 100 lb. Compounded materials containing starch or dextrine may be increased in price in proportion to the content of these materials.

This price rise is made in partial compensation for the rise in price of corn, which went up about 34c. per bushel between March, 1942, and the present. It takes three bushels of corn to make 100 lb. of starch or dextrine. Hence the increase in cost from corn alone amounted to \$1.02 per 100 lb. of finished product. The fact that a majority of the 11 companies making these products were operating currently at a loss was the persuasive argument used by the industry in getting this permission of OPA to raise the ceiling.

NEW SULPHUR ROUTE

ABOUT a quarter-million tons of sulphur will be moved from Louisiana and Texas to the New York Harbor by Federal Barge Line in new steel barges. This sulphur will move by way of the Mississippi River, the Great Lakes, and the Eric Canal to supply normal sulphur requirements of the Eastern States. The movement will begin as soon as navigation is possible in the spring and will be completed before the freeze-up in the fall. Coastwise ships are thus released for the hauling of coal, a transportation need that is exceeding ship capacity.

SMALL BUSINESS FIRST

SMALL business establishments are to be given preference when surplus materials are available beyond the need for immediate war or war stockpile purposes. Chairman Donald M. Nelson of WPB announced this as a part of the effort of his organization to protect or re-establish small enterprise which has suffered serious disturbances during the war period. Recognizing "You have had many heartaches and the job ahead is a difficult one", he pointed out that the purpose of this plan is to provide small companies with an opportunity to use their own initiative and ingenuity. It is definitely not a subsidy, but a bit of a head start in reconversion.

BARITE SCARCITY

WASHINGTON is beginning to worry about the scarcity of barite and barium chemicals. The prospective shortage is caused by having too few trucks and too little mining equipment for the mining division of this industry. It now appears necessary to give much higher priority in order to insure repairs and replacements promptly.

ADVERTISING CHALLENGED

FEDERAL Trade Commission proceedings have been started against a leading soap company demanding a change in the advertising practices of that firm. It is charged that the advertising has "misrepresented" the goods sold. If the Commission can make its plans stick, it proposes to go into the courts and compel the elimination of all the charm and distinctive service claims which are commonly associated with toiletries, cosmetic materials, and other such products. The whole matter is significant for the process industries because this is only one symptom of the trend of F.T.C. toward domination of all merchandising practices, including censorship of the text of advertising "copy".

ALCOHOL FROM RYE

Ryre is slightly more abundant than wheat, corn, or barley, and War Food Administration would like to substitute it as a raw material for some alcohol manufacture. Early reports from industry indicated that this substitution would reduce the capacity of alcohol plants. Hence a joint inquiry is being conducted by WPB and WFA to determine both feasibility and desirability of this change of raw material.

Initial tests include experiments with various types of granular rye flour. It is hoped that some of the industrial establishments making tests for the government will develop a know-how suitable for use with some of the types of raw material which can readily be made available from existing flour mills. No decision as to the quantity of change-over which will be planned can be attempted until results are had from several weeks' experimental work, first on a laboratory scale and then on a plant scale.

CANCELLATION CLAUSES

SUBCONTRACTORS supplying raw materials such as chemicals find difficulty in dealing with Army business. The military place prime contracts with certain cancellation clauses. They then go out and stimulate material suppliers to enlarged activity so that the prime contractor will not be delayed by lack of raw materials. But the Army does not give any formal authorization for expansion of the materials business. Mere assurance of need of the goods is not an enforceable contract. Chemical manufacturers are finding it difficult and are seeking for some form of real order so that sudden cancellation will not leave them with large amounts of goods in process or in inventory without any market. Prime contractors are being asked to demand for their subcontractors a suitable protection of this sort.

When repairs call for <u>ACTION</u> -- depend on PENNSALT CAUSPLIT CEMENT REG. U.S. PAT. OFF.



1000 WIDENER BUILDING, PHILADELPHIA 7, PA. New York • Chicago • St. Louis • Pittsburgh • Minneapolis • Wyandotte • Tacama

*Trade-marks Reg. U. S. Pot. Off.

At a leading oil refinery emergency repairs were required on the lining of a Mercaptan Tower . because of sulphur erosion at the intake area.

The engineers in charge thought they were faced with a three-day shut-down for repairs, with the

resultant loss of production.

A Penn Salt technician was called in and after going over the situation he recommended Causplit Cement in conjunction with corrosion-resistant brick. He gave installation instructions and four courses of the brick were used with Causplit Cement as the bonding material throughout. Drying was speeded by heating the tower to 100 degrees F. and the equipment was back in service the next day!

Pennsalt Causplit* and Asplit* are resin cements —exceptionally strong, abrasion-resistant and easy to handle. Causplit is used where conditions are alternately acid and alkali . . . Asplit where conditions are always acid.

Pennsalt Penchlor* Acid-proof Cement is a quicksetting, self-hardening sodium silicate cement that will save time in construction and stand up well under severe acid conditions.

Consult Penn Salt technicians about your acid or alkali handling problems. Their wide experience is available without obligation. Write fully or return the coupon.

Causplit and Asplit can be supplied only for essential service...Penchlor Acid-proof Cement is available without restriction.

PENNSYLVANIA SALT MANUFACTURING COMPANY Dept.CME, 1000 Widener Bidg., Philadelphia 7, Pa. I would like to have a free capy of your new booklet No. 6 on Penchlor Acid-proof Cement.
NAME
TITLE
COMPANY
ADDRESS

This installment covers orders rules and regulations issued by the War Production Board and the Office of Price Administration during February, 1944. Copies of each item interpreted here may be obtained from the appropriate federal agency.

CITRIC ACID

QUARTERLY ALLOCATION of citric acid will replace monthly allocation as a result of shifting control to General Allocation Order M-300. Order M-321 which formerly controlled citric acid has been revoked.

PEROXIDE AND PERBORATE

HYDROGEN PEROXIDE, sodium peroxide and sodium perborate, have also been placed under control of General Allocation Order M-300 after three months control by WPB directive. A substantial cut in consumption is required in order to balance supplies and requirements. Use of the product for such vital applications as antiseptics will not be seriously curtailed, but textile finishing and other less essential processes will be forced to take a big cut in consumption of these products.

NAPHTHAS AND SOLVENTS

INDUSTRIAL NAPHTHAS and solvents have been placed under the price control of MPR-510. Previously they were under MPR-88, but have been shifted in order to eliminate any misunderstanding in connection with the base price period. All the products under Regulation 88 have the base period of October, 1941, whereas naphtha and solvent prices are based on March, 1942.

RUBBER COATED FABRICS

OPA HAS ISSUED an order under MPR-478 to provide manufacturers of rubber coated fabrics with a method for determining the price of their products when they substitute a more expensive coating material. For instance, when Buna-N is substituted for neoprene GR-M or GN, manufacturers may add to their prices an amount not exceeding the increase in cost of rubber, thus eliminating the need for individual applications. As yet, price changes due to other substitutions must be established as formerly.

VALVES, FLOATS AND TRAPS

ELIMINATION OF SOME simplification and standardization in the manufacture of radiator supply valves, low-pressure thermostatic radiator traps, combination float and thermostatic traps and boiler return traps was accomplished by amendment to Order L-42, Schedule VIII. This action was taken because simplified models have

not proved satisfactory in all cases. Former restrictions as to sizes, design, patterns and types of low-pressure thermostatic radiator and drip traps, combination float and thermostatic traps and boiler return traps have been removed, except that the bodies of these items are still required to be made of cast iron.

DEGREASERS ALLOCATED

TRICHLORETHYLENE, used extensively for degreasing metal, and perchlorethylene, important ingredient of smoke generating materials, were placed under allocation for the first time on February 11 by WPB. Order M-371, issued to control the allocation, provides that each person ordering more than 700 lb. of these products in the aggregate during any one month shall furnish each supplier with a use-certificate in accordance with Appendix C of the Order. For orders of 10,000 lb. or more, the customer must file a report on Form WPB-3442 on or before the twentieth day of the month preceding date of delivery. Suppliers receive authorization from WPB by submitting their application on Form WPB-3947.

COPPER FOR CONDENSERS

RESTRICTIONS ON the use of copper and copper base alloys that have limited the inclusion of these metals in the manufacture of tube and tube sheets for steam condensers have been lifted by WPB. It is expected that the use of copper will lengthen the average useful life of condenser tubes and sheets, eliminate costly shutdowns, and reduce the quantities of replacement and maintenance parts which were necessary as a result of the unsatisfactory performance of alternate materials. The lifting of restrictions was effected by amendment of Limitation Order No. L-154, Schedule II.

STEEL CYLINDER DEMURRACE

IN AN ATTEMPT to speed the return of empty compressed gas cylinders, the OPA has provided all sellers of compressed gas with a means of charging demurrage for each additional day a cylinder is retained by buyers beyond the normal period necessary to empty the cylinder. Revised Supplementary Regulation 14 to the GMPR, Amendment 89, provides that any seller instituting or modifying a cylinder demurrage charge must furnish the buyer with a written notice that OPA has given permission for the charge.

PHENOLIC RESINS

GENERAL PREFERENCE ORDER M-246, which covers phenolic resins and phenolic resin molding compounds, was simplified by WPB on February 15 to save paper work. This latest revision puts application for allocation of plywood, laminates and specialties on a quarterly rather than a monthly basis. End use certificates are no longer necessary if the product manufacturer can determine the end use from the nature of the customer's purchase order. In addition, a purchaser may use up to 2,000 lb. of phenolic resin in any end product which was previously described by him on his Form WPB-2945 under Order M-246, and approved in writing by WPB at any time since Sept. 30, 1943. The above permission does not apply to cast phenolic resins, phenolic resins containing tung oil or para phenyl phenol, or resins in which para tertiary butyl phenol is the sole phenolic reactant. A 50 lb. small order provision is applicable to cast phenolic and a 5 lb. exemption has been added for the latter resins.

Para phenyl phenol resins have been consolidated in this Order for the first time, permitting the revocation of Order M-254 under which they were formerly allocated. Resorcinol resins are not included in the Order since their high prices prohibit their use in non-essential products.

OTHER CONTROLS

IN ORDER to relieve the domand for maleic resins, Conservation Order M-53 has been amended to permit application to be made for allocation of phenolic resins for use in printing inks.... Chemical cotton linters have been redefined as linters sold on the basis of cellulose content as determined by chemical analysis, whereas free cotton linters are defined now as those sold, not on the basis of cellulose content, but according to the grade set forth in amended MPR No. 191.... Application for authorization to sell, transfer or convert industrial power trucks under Limitation Order L-112 must be made on Form WPB-1319 in accordance with instructions currently available with the form The authorized form for delivery of resistance welding equipment under Limitation Order L-298 has been changed from WPB-2752 to WPB-1319....Reserve production capacity under Conservation Order M-241 has been increased from 35 to 45 percent for paperboard, and from 15 to 20 percent for paper....Anhydrous aluminum chloride may now be furnished by a supplier in quantities of 600 lb. or less to each customer, except to those whom the supplier has reason to believe are not entitled to accept delivery under the exemption included in Order No. M-287....Yellow cypress lumber has been provided with dollars and cents ceiling prices by OPA through issuance of MPR-513....Amendment to Conservation Order M-6-b makes available for all purposes permitted by existing regulations, nickel anodes, nickel salts and plating solutions which were frozen in nickel platers' inventories on Jan. 20, 1942.

Through this new Material you will see more clearly in the future

... Clevelands help to produce it—without a flaw

Some day this interesting new Process Material probably will be doing an important job in your business—then you can thank Cleveland Worm Gear Speed Reducers for maintaining its high quality for you.

The machines that produce it must operate with uniform angular velocity, as even the slightest variation in speed will show on the finished product in the form of a streak or ridge. Drives of another type failing to meet this requirement caused a high percentage of scrap.

The manufacturer has used Clevelands successfully on other applications for more than 20 years—so he welcomed the suggestion to install them on this equipment too. Clevelands smoothed out the operation—quickly eliminating defective production.

You can depend on Cleveland Worm Gear

Speed Reducers to continue the fine performance you have enjoyed heretofore: dependable operation under heavy shock loads—no lost production time—no parts-replacement costs. Send for the Cleveland Representative—specify Cleveland Worms and Gears for your new equipment.

The Cleveland Worm & Gear Company, 3273 East 80th Street, Cleveland 4, Ohio.

All

Affiliate: The Farval Corporation, Centralized Systems of Lubrication IN CANADA: Peacock Brothers Limited





INDUSTRIAL ENGINEERS EVERYWHERE RELY ON THE UNFAILING PURITY AND UNIFORMITY OF

Diamond Liquid Chlorine

Always uniform, dependable, pure—Diamond Liquid Chlorine comes to you in individual cylinders, multi-unit or single-unit tank cars, whichever best suits your requirements.

DIAMOND ALKALI COMPANY PITTSBURGH, PA. AND EVERYWHERE





The Spark that Lights the Flame of Victory

A pinpoint of fighting metal placed in the arc

of the spectograph writes its own signature on a photographic plate. Inside the instrument, the light from that flame is broken up by a prism as a prism breaks up sunlight. Each element identifies itself by a series of characteristic lines, always the same for the same basic element. It reveals to the spectrographer each constituent, what impurities are present and in what quantities.

Thus spectrography helps in controlling inspection. It keeps tough fighting steels tough, helps in development of new fighting metals. Spectrography is used too in other fields . . . chemicals, foodstuffs, vitamins. It speeds research, control, and analysis. Today, spectrography is helping to build the tools of Victory as in peacetime it helps to make better cars and better breakfast foods.

Because Bausch & Lomb had long experience with such precision optical equipment needed in education, research, and industry, it was ready for quantity production of precision optical instruments of war such as gunfire control instruments, binoculars, and aerial photographic lenses. When the last gun is fired, Bausch & Lomb will devote its enlarged experience to peacetime optical production. Through war and peace, Bausch & Lomb has continued ... and will continue ... to do the job it knows how to do best. Here again optical science is seeing it through.

For Bausch & Lomb Instruments essential to Victory—priorities govern delivery schedules.

BAUSCH & LOMB OPTICAL CO. • ROCHESTER, N. Y. ESTABLISHED 1853

AN AMERICAN SCIENTIFIC INSTITUTION PRODUCING OPTICAL GLASS AND INSTRUMENTS FOR MILITARY USF, EDUCATION, RESEARCH, INDUSTRY AND EYESIGHT CORRECTION



Refrigeration-plant operator reads Micromax Temperature-Difference Recorder in plant of Atlantic Refining Co.

ANDTHER STEP-UP IN REFRIGERATION EFFICIENCY can follow use of micromax short-range temperature-difference recorder

Refrigeration production is of course expected to be efficient at the Atlantic Refining Co.; its engineers and operators have for years kept their eyes on the heat-balance, ' and have applied dozens of ideas, machines and services which increase the efficiency of refrigeration-machine operation. The regular use, by this company, of the short-range Micromax Temperature - Difference Recorders seems, therefore, to indicate that this instrument has widespread value in many plants, for closer control of commercial-refrigeration operations.

The features of this Recorder which make it particularly valuable in this service are its short range (as little as 0-5 F) and its micro-responsiveness.

The equipment employs our standard Thermohm resistance-thermometer bulbs as temperature detectors. These are especially designed to make full use of the remarkably high sensitivity which may be attained with resistors. Also, these units are matched in resistance for the low temperature and for the five-degree range—conditions which require considerable skill and experience to overcome, but which are no longer problems to the Micromax equipment.

One of these specially-matched Thermohms is in the brine inlet, and the other in the outlet of the cooler.



A Slogan For Every American

The Micromax Recorder measures the difference between them with a microresponsiveness so great that some of its motion may be hard to see. But the effect shows in the record; the five degrees of temperature difference are spread across a chart almost ten inches wide, so that each degree has almost two inches. This extremely detailed showing of the temperature difference on which efficiency largely depends, helps the refrigeration-ma-



Close-up of Micromax Temperature-Difference Recorder. Range is only 0.5 F; note open, easy-toread record curve. This instrument operates directly from 115-volt line; no dry cell is employed; thus its sensitivity is not impaired by voltage changes.

chine operator to anticipate temperature changes — head them off while they're still only beginning — hold temperature with the steadiness essential to highly efficient refrigeration.

This Micromax and all other models are described in Catalog N-33C, sent on request. If you have a specific problem in refrigeration, however, we suggest that you outline it so that additional specific facts can be submitted.

Jrl Ad N-33C-706(1)



CHEMICAL & Aletallargical ENGINEERING

ESTABLISHED 1902

MARCH, 1944

S. D. KIRKPATRICK, Editor

From War Plants to Cornfields

DEMOBILIZATION of chemical industry has already begun. Late last month the workers started tearing down the great Gopher Ordnance Works at Rosemount, 1Minn., thereby releasing more than 20,-000 acres of fertile farmland for needed food production. The wrecking crews, according to Time magazine, found sardonic pleasure in putting into reverse the 1942 boasting of many Midwestern munition plants. "You'd never believe it," they said, "but this cornfield was once a war plant!"

Thus begins a long unravelling, unscrambling process that is bound to bring with it some serious problems for all of us. They loom even larger than the original program of providing facilities for war production. Looking back now it is easy to see how far we over-planned and over-built but we must realize that these powder plants were put up at a time when we were faced with the possible necessity for supplying the munition requirements of England and Russia as well as our own. Hence we can and should charge off many of these tremendous expenditures as insurance against an international danger that no longer exists. Now their demobilization brings with it a domestic danger that is not yet fully appreciated.

That danger is political more than it is economic or technical. Pressure groups are already working to force the disposition or continued operation of these plants in order to serve the selfish interests of local communities or larger regional units. We need but think back to the agitation over Muscle Shoals in the twenties to realize how many TVA's would be needed to take care of our present commitments were we to adopt the political solution for the problem of the forties. The better course is that which has been charted in broad outline in the recent report on War and Post-war Adjustment Policies by Bernard M. Baruch and his associate, John M. Hancock. They would put the job largely up to the private initiative and resourcefulness of American industry in order to make certain that there would be no surrender to Governmental control and inevitable socialization of business. They would have the Congress set up the reconversion agencies and define by law their functions, powers and responsibilities. Thus they would avoid, if possible, the instability and uncertainty that have characterized so many of the wartime agencies that have been set up by executive decree with "blank-check" appropriations but with vaguely defined fields of authority.

Unfortunately President Roosevelt did not see fit to wait for Congressional action on the Baruch-Hancock report but instead proceeded immediately with the appointment of key personnel to put its recommendations into effect. The selection of Will Clayton to become Surplus Property Administrator and of General Hines to direct retraining and re-employment has met with little enthusiasm yet both are able public servants who can be expected to do their best in the difficult jobs to which they have been assigned. Yet their work would have been much more effective and they would have been under less political pressure had the President waited for Congress to have created an enduring legal framework for this new agency.

Those who are most pessimistic feel that demobilization is going to have to proceed on the same trialand-error basis that characterized the mobilization of our war effort during 1941 and 1942. If so, we may expect an accumulation of political pressures that will make the winning of the peace much more difficultif not impossible. It is better by far that we now move slowly but surely. Let us chart our immediate and longtime objectives, set up a sound program, industry by industry, and then give it the power and stability of federal law.

GAS TURBINES Offer Opportunities for Process Use

Although the gas turbine has been well known in the petroleum industry for the past seven years, where some 35 are now used as an auxiliary to the Houdry process, interest is rapidly increasing owing, perhaps, to dramatic announcements in connection with their use in jet propulsion for aircraft, and in airplane engine supercharging. As the most versatile type of prime mover, the gas turbine can produce compressed air, hot gas and byproduct steam, in addition to power. In some cases it can operate on byproduct heat from exothermic reactions.- Editors

WERE IT NOT for the happenstance that the Houdry refining process requires large volumes of air under pressure for burning off carbon deposits on the catalyst, gas-turbine development in the United States would have been largely confined to internal-combustion engine supercharging. As it is, however, the gas-turbine, axialcompressor combination shown in Fig. 1 has become an essential auxiliary to this process. Some 35 sets in sizes from 23,000 to 60,000 c.f.m. are now in operation, eight built by Brown, Boveri & Co., Ltd., in Baden, Switzerland, and the remainder by Allis-Chalmers Mfg. Co., in Milwaukee.

The gas turbine is similar in construction to the low pressure stages of a steam turbine, but instead of operating on steam under pressure, it operates on hot combustion gases under pressure. In this respect it is related to the internal combustion engine. Since the fuel used must be burned under pressure, the combustion air for the gas turbine must be compressed, but the compressor does not require all of the power produced by the turbine, so

Fig. 1—One of 35 gas-turbine, axial-compressor sets, a 60,000 c.f.m. unit built by Allis-Chalmers, now serving in a Houdry process refinery



that a surplus is available for the production of mechanical power, or electricity, or for compressing additional air for process use. The gas turbine is therefore essentially a pressure recovery device, and in this respect bears a resemblance to the well known scheme of pressure recovery used in the scrubbing of CO_a from the synthesis gases in the synthetic ammonia process.

In this process, as in Fig. 2 (a), the high pressure scrubbing water is pumped into the scrubber tower by a pump which is on the same shaft as a Pelton wheel and a motor. Part of the energy of the water leaving the tower is recovered by the Pelton wheel, while the losses in handling the water are made up by the motor. The comparable case for the gas turbine is shown in Fig. 2 (b) where a compressor supplies compressed air to a process, from which the exit gases pass through a gas turbine on the same shaft as the compressor. The pressure losses in the process can be supplied in one of three ways. If the process is exothermic, as in the Houdry process, the leaving gas may contain enough energy to drive the compressor and even leave a surplus. Or a combustion chamber for burning gas or oil in the leaving air can be added. Finally, in the case directly comparable to Fig. 2 (a), the energy not recovered by the gas turbine can be provided by a motor.

While the "application engineering" for gas turbines has hardly begun, there are many indications that the continuous-combustion, compressor-turbine cycle is destined to play an important part in both chemical and metallurgical processes by affording means of completing chemical or physical reactions under pressure. The gas-turbine unit has potentialities far beyond that of a mere competitor of the steam turbine or diesel engine.

For example, the relatively simple process of supplying air for reducing iron ore in a blast furnace is traditionally carried out by burning blast-furnace gas under a steam boiler, expanding the steam through reciprocating engines driving compressors, or a turbine driving a centrifugal blower, and returning blast air to the furnace through preheating stoves. This re-



Fig. 2—Essentially a pressure recovery machine the gas turbine is comparable to the Pelton wheel used in partial recovery of the pressure of scrubber water in ammonia synthesis; it can return part of the work to processes operating under pressure

quires considerable building space for boilers, prime movers and compressors, a condensing water supply, and a relatively large investment in equipment. A gasturbine unit capable of supplying 60,000 c.f.m. of blast air at desired pressure would occupy a space only 60 ft. long by 13 ft. wide, would require no cooling water and would cost only a fraction as much as a steam turbine and boiler installation.

Application in the Houdry process and in iron smelting are only two illustrations of how the gas-turbine unit can perform certain process functions in an entirely different manner from existing practice. Others suggest themselves, such as exothermic pressure oxidation reactions (e.g., oxidation of benzene), but await the realistic evaluation of economic factors that must accompany introduction of radically new devices. In the meantime, forward looking engineers will do well to become acquainted with (1) the fundamentals of the gas cycle, and (2) present forms of equipment which utilize products of combustion directly for the production of mechanical power.

GAS-TURBINE THEORY

The basic equipment for turbine-compressor units such as now used in the Houdry process is illustrated schematically in Fig. 3. On a single shaft are grouped the turbine, the compressor and some means of starting rotation. The generator may be either geared or direct driven depending on the best speed for the compressor. The combustion chamber, limited for the present at least to oil or gas firing, is little more than a piece of pipe. A fuel pump and a combined governor and lubricating oil pump complete the list of auxiliaries. In event of overspeed, a safety valve bypasses hot gas to the exhaust.

Blading of the turbine, shown in Fig. 4, differs little in shape from conventional low pressure stages of steam turbines. The adiabatic efficiency of blading for one unit on test reached 88 percent, equalling that of the steam turbine. Although it must be able to stand high temperatures, however, even for 1,200 deg. F. operation, only the first row of blading has to run continuously at top temperature, as the gas is cooled by performing mechanical work in each stage. Exit gas temperature normally does not exceed 700 deg. F.

High efficiency is a prime requirement of the compressor, in fact, the inherently low efficiency of centrifugal compressors led to the conclusion in the 1920's that the continuous-combustion process would never be practical. However, aerodynamic research has resulted in greatly improved designs of axial-flow blading and compressors can now be built with over-all efficiency of over 85 percent, adiabatic basis.

In principle, ordinary air is compressed to any convenient pressure, say 60 lb. per sq.in. gage and passed through a combustion chamber where enough oil is fired to bring the "flue" gas up to operating temperature, say 1,200 deg. F. Products of combustion, together with the excess air, expand through the turbine blades to atmosphere. Since more work is available from the expanding high-temperature gas than is required by the low-temperature compression, the turbine has an excess of power available for the generator.

Essentially the same process occurs as in a diesel cylinder. In the engine, air is compressed on the upstroke by absorbing energy from the flywheel. Oil is forced into the cylinder and burned under practically constant pressure conditions. On the downstroke, the hot gas expands and delivers more work to the flywheel than was absorbed in compressing the charge. Work required for the compression stroke is a large fraction, around two-thirds, of the work of the power stroke.

All these operations are duplicated in the gas-turbine unit, except that the flow is continuous. The total heat-temperatureentropy chart of Fig. 5 could apply to either turbine or diesel engine. For the gas turbine, compressing 1 lb. of air from atmospheric pressure and 60 deg. F. to 60 lb. per sq.in. gage and approximately 420 deg. F. requires 87 B.t.u. in the form of mechanical work at 85 percent compressor efficiency. Burning oil raises the temperature to 1,200 deg. F. at the expense of 193 B.t.u. In expanding through the turbine at 88 percent efficiency, 130 B.t.u. of useful mechanical work can be realized with actual blades. The exhaust gas carries away 150 B.t.u. at about 700 deg. F., part of which can, of course, be reclaimed in a

Fig. 3—Basic gas-turbine assembly includes a multi-stage compressor, combustion chamber, small starting motor and the power-producing gas turbine





Fig. 4—Allis-Chalmers gas-turbine, axial-compressor unit for a Houdry plant, rated at 23,000 c.f.m. of air at 45 lb. ga. pressure

heat exchanger or waste-heat boiler. In all, the unit can put out 130 minus 87 or 43 B.t.u. per pound of air flowing, at the expense of 193 B.t.u. from fuel oil, or approximately 22.3 percent thermal efficiency.

This efficiency, for the basic cycle, compares poorly with perhaps 30 percent for steam power plants and around 40 percent for the best diesel engines. As presently constructed, gas-turbine units are limited to 1,200 deg. F. operating temperature and a compression ratio of around four, instead of perhaps 30 for diesel practice.

Only one unit has been built to date designed solely for power generation. This 4,000-kw. single-shaft machine is installed in an underground tunnel at Neuchatel, Switzerland, for standby service. Because it was expected to run only infrequently, efficiency was not a prime consideration. On test it developed 4,180 kw. net power (4,040 kw. at the generator terminals) from 15,660 gross turbine kilowatts, 11,-480 kw. being used by the compressor. Thermal efficiency was reported as 17.38 percent at the coupling, corresponding to a heat rate of 19,600 B.t.u. per kw.-hr. and a fuel rate of 1.08 lb. of fuel oil per kw.-hr. Temperature at the gas-turbine inlet on test was 1,025 deg. F.

The apparent handicap in efficiency compared with steam and diesel practice is at least partly balanced by simplicity of construction as compared to the former and ability to burn bunker oil instead of the premium fuel required by the latter. Moreover, accumulated experience and improved shop practices indicate that the efficiency of the Neuchatel type could be raised to about 21 percent for operation at 1,000 dcg. F., while with 1,200 dcg. F. definitely in sight and within reach when war conditions permit, the efficiency of this simplest machine reaches 25 percent. At 1,500 dcg. F., which is still in the future as far as materials are concerned, this basic unit could deliver power to the coupling at 28.5 percent thermal efficiency.

Even with present materials, that is, at 1,200 deg. F. temperature, the efficiency can be increased 3-4 percent by adding a heat exchanger of reasonable size, corresponding to the air preheater or economizer of a steam plant. By an intercooler between stages of the air compressor and a twoshaft, two-stage arrangement, another 2-3 percent may be had.

For a relatively small unit around 4,000 kw. intended for power generation at vary-

ing load, there would be two gas turbines supplied by a single combustion chamber, one driving the compressor at variable speed to suit load conditions, and another driving the generator at constant speed. For 8,000 kw. or larger, it would probably be desirable to go to two pressure stages (120 lb. gage) and add a reheater combustion chamber between turbines as well as one stage of intercooling.

Brown, Boveri states that such a unit, in 4,000–10,000-kw. size, built for 1,200 deg. F. at 60 lb. gage pressure, would have an over-all heat rate approaching 12,000 B.t.u. per net kw.-hr. (28.5 percent over-all thermal efficiency) and could be delivered and installed in the United States for a cost of around \$50 per kw. including auxiliaries and generator switchboard. The machine could burn any grade of fuel oil or gas, but for gas fuel an additional small compressor would be required.

Much discussion has been occasioned by the simple factual statement that it is possible for the efficiency of gas turbines to approach or even exceed that of diesel engines. Fifty years ago the same could have been said of steam turbines as regards the steam engine, but few could have then outlined the halting steps by which the modern high-efficiency steam station has evolved. Similar factors are involved now, so that one cannot predict with clarity more than a few near-future chapters of gas-turbine history.

One factor affecting future development



Fig. 5—Skeleton Mollier chart for air indicates the approximate performance of a gas turbine working at 1,200 dcg. F., and 60 lb. ga.

stands out above all others. Like the steam turbine, the gas turbine is inherently a large-power device. At present the smallest size of power unit for even reasonable efficiency might be set somewhere around 2,000 hp. Since few diesel engines over this size are found in stationary plants, competition between the two prime movers would seem limited to the marine and railroad field.

Waiting only on release of critical materials is the gas-turbine locomotive, already a reality in Switzerland. Allis-Chalmers designs call for two gas-turbine units to deliver about 5,000 hp. to the drivers of an 87-ft. locomotive, as compared to the two 100-ft, elements of the Union Pacific steam-turbine-electric experimental type or the three- or four-unit articulated diesel propulsion of the streamliners. Gas-turbine drive would have an efficiency of 17 percent or more as compared with 12-14 percent for stcam turbine drive and 6-8 percent for standard reciprocating steam engines. They would, however, not equal the 23-25 percent performance of diesel locomotives but would have the advantage of containing equal power in a single car (plus fuel tender), would require no water and would fire bunker oil of considerably less cost than diesel fuel.

A "natural" application of gas-turbine drive, already contracted for by the Maritime Commission, will be for merchantship propulsion. The first such unit, obviously for experimental purposes, will drive a 7,200-ton coastwise freighter of the C1-M-AV1 type. The drive unit, to be built by Elliott Co., will develop between 2,000 and 3,000 hp. Designs have been presented by others indicating that a 4,000hp. gas turbine would occupy no more space in a 10,000-ton Liberty ship than its present conventional 2,500-hp. steam engine plant and give substantially more speed.

Many stubborn details remain for marine engineers to work out, but a power plant weight of around 20 lb. per hp. and a space occupancy of about 3 cu.ft. per hp. for the gas turbine itself (to which must be added weight and space for reductiongear and reversing equipment) offer a powerful incentive, plus the probability of fuel consumption below 0.7 lb. per hp., comparable with best modern steam-turbine drive.

Another factor affecting the future development of gas turbines for power and process use is the war-fostered airplane supercharger. The single-stage gas-turbine, centrifugal-compressor combination known as the turbo-supercharger first operated commercially in 1923 on a 500-hp. diesel engine. Even before the war, supercharging stationary and marine diesel engines had become a recognized means of increasing the power output of a given internal combustion engine cylinder.

The turbo-supercharger is not expected to produce mechanical power beyond that



Fig. 6—Gas turbines offer the most versatile heat-balance arrangements of any prime mover: (a) Basic power unit requires no cooling water or auxiliary apparatus (b) Two-stage power unit approaches best steam plant efficiency if provided with heat exchanger and intercooler (c) Useful output can be taken as compressed air at any pressure up to about 75 lb. ga. (d) Some 35 of these process units are helping make aviation gasoline (e)
First practical application of the gas-turbine combination was as an auxiliary to the high-pressure Velox boiler (f) Byproduct steam from waste-heat boilers can be had in limited quantities

required to drive its own compressor. Invariably associated with a reciprocating engine, the turbo-supercharger interposes a single-stage turbine wheel between the engine exhaust manifold and the atmosphere. In the most common form, this wheel drives a single-stage centrifugal blower at speeds up to 30,000 r.p.m. to produce a pressure above that of the surrounding atmosphere in the intake manifold of the engine.

Because supercharging induces a greater weight of air to enter the cylinder on each stroke, a greater weight of fuel can be burned and maximum horsepower is increased. Efficiency of the turbine and compressor are such that an intake manifold pressure greater than the corresponding exhaust manifold pressure is easily obtained.

Superchargers for diesel engines normally operate at exhaust gas temperatures below 1,100 deg. F. More recent airplane gasoline engine types must sustain temperatures of 1,800 deg. F. and above. It is from development of high temperature materials for the latter service, now veiled by wartime censorship, that power type gas turbines can hope for alloys to stand temperatures above 1,200 deg. F.

Applications in the stationary power field can be outlined only vaguely. For the immediate future at least, size range will be restricted to a minimum of 2,000 kw. and a maximum of 10,000 kw. While experiments with burning pulverized fuel were undertaken some time ago on a 1,500-kw. unit in Switzerland, no information is yet available in this country as to the results. It is to be expected that considerable time must elapse before satisfactory performance can be surely predicted with solid fuels.

It would seem that the versatility of the gas-turbine unit would make it eventually more important in process work than in straight power generation. Briefly stated, the continuous-combustion unit can produce either high- or low-pressure steam, compressed air and power in any proportions desired. Possibilities can best be illustrated by the six schematic sketches of Fig. 6.

A conventional unit, Sketch (a), represents the arrangement of the only machine thus far built for power alone, the 4,000kw. standby plant at Neuchatel. Sketch (b) indicates typical refinements in heat balance that can lower the heat to about 12,000 B.t.u. per kw.-hr.

Sketch (c) indicates the manner of air takeoff at any pressure up to about 75 lb. per sq.in. for a single-shaft machine. By compounding, pressures up to 120 lb. are available. High temperature gas can be had after the combustion chamber, or air free of combustion gas can be obtained by addition of a heat exchanger. This set-up is typical of the blast-blower previously mentioned, which takes intermediate pressure air for the blast and high pressure air for combustion. Sketch (d) represents the present application for the Houdry process.

Sketch (e) diagrams the Velox boiler. The present form of gas-turbine, axialcompressor set was originally developed as an auxiliary to this boiler which depends

(Continued on page 108)

AMMONIUM PICRATE Production for Military Explosive Requirements

In World War I, ammonium picrate was the secret high explosive of the United States and was known as Explosive D in order to avoid common knowledge of its chemical composition. The present program for this product was started in 1940 as an Ordnance-Industry project and has involved erection of new buildings, installation of machinery and equipment, and training of operators. Two methods are being used for the production of this important explosive; one starting with phenol as the raw material, and the other starting with dinitrochlorobenzene. It is the latter process which is described in this article.-Editors.

ROM THE STANDPOINT of explosive strength alone, ammonium picrate is inferior to TNT, but, nevertheless, is still important as a military explosive because of its marked insensitiveness to shock and friction. It is this latter property which makes it well suited for use as a bursting charge in armor piercing shells, in projectiles for seacoast cannon and in other types of projectiles which must withstand severe shocks and stresses before detonating. Like TNT and picric acid, ammonium picrate liberates free carbon on explosion, giving a black smoke. The products of the explosion, although more disagreeable in odor, are less poisonous than those from TNT and picric acid, in that they contain less carbon monoxide.

Ammonium picrate is a powder of light yellow color which will not melt on heating, but if raised to a temperature of 300 deg. C. will decompose with explosive violence. Loading is therefore accomplished by pressing or tamping the powder into the projectile.

There is only a slight tendency for ammonium picrate to absorb moisture, but if it does become wet, it can form sensitive and dangerous picrates with copper and lead. No explosive compounds are formed with steel, but in order to avoid corrosion, the interior of the shell is coated with a suitable non-metallic paint or varnish before it is filled, and a moisture-proof seal is provided at the base of the projectile.

THE PROCESS

To summarize the process used by some of the government-owned, contractoroperated facilities program, dinitrochlorobenzene (DNCB) is hydrolized with a hot aqueous solution of caustic soda, the resultant sodium salt of dinitrophenol (DNP) is precipitated by sulphuric acid,

In a cast iron kettle similar to the one shown in this illustration, dinitrochlorobenzene is hydrolyzed with a hot aqueous solution of caustic soda. The resultant sodium salt of dinitrophenol is then precipitated by sulphuric acid, filtered and sent to the nitrators



Colonel Gerber is Field Director of annualtion plants and recently was appointed Director of Safety, and Chief of the Ordnance Department's Safety and Security Branch.

Raw Materials Required in DNCB Process for Ammonium Picrate

Process Step	Material	Pounds Per Batch ("as is" basis)	Pounds Per Batch (100% basis)
Hydrolysis	DNCB Caustic Soda	1153	1153
Neutralization	(50% Soln.) Surphuric Acid	968	484
Nitration	(97%) Sulphuric Acid	340	330
	(97%) Mixed Acid	3960-5040	3840-4890
Ammoniation	(70:25:5) Aqua Ammonia	596 362	417 (HNO ₃) 94

and the DNP itself isolated as a wet filter cake. This filter cake is slurried with strong sulphuric acid and nitrated to picric acid (TNP) by means of mixed acids. The TNP is filtered, neutralized with aqua ammonia in hot aqueous solution and crystallized as ammonium picrate (AP) which is filtered and dried.

RAW MATERIALS

Standardized equipment for the manufacture of ammonium picrate by the DNCB process accommodates a batch size which is equivalent to 1,250 lb. of ammonium picrate, provided optimum process yields are obtained. Raw material requirements for this size batch are indicated in the table above.

HYDROLYSIS OF DNCB

This step in the process is carried out by charging water, caustic soda solution and molten DNCB to an agitated cast iron kettle. After closing the kettle and venting it, steam jets are used to heat the contents to 70 deg. C., the heat of reaction taking the temperature up to 100 deg. C. without further use of steam. On slackening of the reaction rate, the entire batch is boiled for about one-half hour after which it should still be alkaline to phenolphthalein.

While the kettle batch is in progress, a wooden vat is charged with 5,600 lb. of water and 340 lb. of 97 percent sulphuric acid, the mixture then being agitated and heated to 75 deg. C. with open steam. The completed hydrolysis batch is then blown by steam pressure through a preheated transfer line to the vat, where the final mixture must test acid to Congo red paper. Sudden drowning of hydrolyzed DNCB in sulphuric acid results in a fine precipitate of DNP which must be digested and converted to the form of coarse granular crystals.

Atmospheric cooling aided by agitation lowers the temperature of the slurry to 80 deg. C., further lowering of the temperature down to 40 deg. C. being accomplished through use of cooling water in the coils. DNP Crystals are then separated from the mother liquor by filtration on a wood vacuum filter and washed with water to remove excess chloride. The moist filter cake is heated to 90 deg. C. and again dried as much as possible by application of vacuum. After as much moisture has been evaporated as possible, the DNP filter cake is lowered into boxes for temporary storage and subsequent transfer to nitrators. Analysis of the DNP for strength must reveal a melting point of 111 deg. C. or higher.

NITRATION OF DNP

Each batch of DNP is nitrated individually to form one batch of TNP. Prior to nitration, the DNP is slurried with sufficient sulphuric acid to give a fluid suspension of whatever solids are present at the temperature prevailing during nitration. The acid must also be adequate in quantity to take up both the residual moisture in the DNP and the water produced by nitration without becoming weaker than 91 percent. For DNP batches which are above 87 percent in strength, the minimum quantity of 97 percent sulphuric acid which can be employed is 3,960 lb. For batches which are below 87 percent in strength, an additional 210 lb. of 97-percent sulphuric acid must be charged for each percent by which the DNP strength is below 87 percent. DNP below 82 percent in strength requires special handling.

Nitration is accomplished in a jacketed nitrator. One batch from the DNP filter (approximately 1,015 lb. on 100 percent basis) is shoveled into the nitrator through a hopper with screen bottom to provide for crushing all lumps. The temperature is then adjusted to between 35 deg. and 45 deg. C. by admitting steam or cold water as required. Mixed acid containing 70 percent HNO₄, 25 percent H₂SO₄ and 5 percent H₂O is fed to the nitrator over a period of about $1\frac{1}{2}$ hr. allowing the batch

This diagrammatic flowsheet indicates the various processing operations required in the manufacture of ammonium picrate



CHEMICAL & METALLURGICAL ENGINEERING . MARCH 1944 .



Filtered dinitrophenol is slurried with strong sulphuric acid and nitrated with mixed acid (70:25:5) in jacketed nitrators like this one. The dinitrophenol is fed through a hopper with screen bottom to insure that all lumps are crushed, thus aiding formation of a fluid suspension

temperature to rise slowly, so that at the end of the acid feed the temperature will reach approximately 95 deg. C. For 30 minutes the batch is held at 95 deg. C. and agitated, then cooled to 80 deg. C. and diluted with 2,400 lb. of previously produced ammonium pierate mother liquor. This dilution must be done_carefully to avoid excessive foaming which results from too vigorous an evolution of nitrogen oxide.

The batch dilution is continued using picric acid wash water from previous batches until a total of 6,500 lb. of water has been added as diluent. During dilution, the batch temperature must not be allowed to exceed 100 deg. C. nor drop below 65 deg. C.

After dilution, the batch is cooled to 35 deg. C. and filtered, the acid filtrate being sent to spent acid storage, and the filter cake washed and dried by application of vacuum for about one hour. The batch production of picric acid is approximately 1,212 lb. of 100 percent material. Acceptable TNP has a melting point of 121 deg. C., or above, and contains no more than 0.5 percent sulphate as H_2SO_4 .

AMMONIATION OF PICRIC ACID

Two and one-half nitrator batches (the equivalent of 3,125 lb. of AP) are combined to make one ammoniation. Before charging this material, approximately 3,600 lb. of fresh water are added to the ammoniator and heated to 100 deg. C. with jacket steam. Air agitation is then begun and the two and one-half batches of picric acid filter cake plus aqua ammonia are added to the ammoniator over a period of $1\frac{1}{2}$ hr. in such a manner that the batch remains slightly alkaline to brom thymol blue test paper at all times. The batch is maintained at 100 deg. C. throughout the operation and great care is necessary to insure that all picric acid is in solution when the final adjustment for neutrality is made.

A period of 12 hours is required to cool the batch to 40 dcg. C., using automatic

controllers to regulate the temperature of the jacket cooling water by external means in accordance with a planned rate-of-cooling curve. It is essential to supply good agitation with the air agitator throughout the cooling cycle. When the ammoniator batch has reached the temperature of 40 deg. C., it is filtered, washed with mother liquor, dried by application of vacuum for two hours and loaded into boxes for temporary storage and transfer to the dryer house. In each line the entire 24-hour production of wet ammonium picrate is transferred to the. line dry-house on day shifts, and divided between three dryer tubs. The contents of these tubs are dried by passage of forced-draft air preheated to a temperature of 70 deg. C. When dry, the ammonium picrate is unloaded into a hopper, screened to remove material too coarse to pass specifications, and packed in the prescribed container.

SULPHURIC ACID RECOVERY

The spent acid used to liberate DNP from hydrolized DNCB is transferred to sulphuric acid concentration units where it is concentrated to approximately 96 percent strength. This 96-percent concentrated sulphuric acid is then mixed with sufficient purchased 20-percent oleum to produce 97-percent sulphuric acid for re-use in the process. It has been found that about 500 lb. of 20-percent oleum must be purchased per 1000 lb. of AP in order to compensate for the sulphuric acid consumed in the DNP process and off-set all sulphuric acid handling and concentration losses.

Trinitrophenol (pieric acid) formed in the nitrators is filtered and washed in vacuum filters. When thoroughly washed and dried, the pieric acid is slurried with water and ammoniated with aqua ammonia



• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

ALBERT L. ELDER AND LAWRENCE A. MONROE

Respectively, Chemicals Bureau and Office of Production Research and Development, WPB

PENICILLIN Wartime Growing Pains of the Industry

From a "seed" in 1942 to an industry of 20 plants valued at \$20,000,000 is the record of penicillin. In early stages it was made in milk bottles, but new processes require vessels of capacities up to several thousand gallons, and other large-scale chemical engineering equipment. As improvements raise output penicillin may be expected in adequate quantities for all essential uses. However, companies are working desperately to synthesize the materials although as a result barely completed fermentation plants may become obsolete.-Editors

Penicillium solution Penicillium notatum. Prof. Alexander Fleming at St. Mary's Hospital, London, first noted that staphylococcus colonies contaminated with mold failed to grow, and deduced that the staphylococcus was inhibited by some material produced by the fungus. In 1929 Fleming published results showing that filtered mold broth contained an antibacterial substance affecting any gram-positive organism. Ten years elapsed before any appreciable impetus was given to this work. Chain and Florey of Oxford reported results confirming Fleming's early work and isolated the impure active principle as a brown watersoluble substance. With sufficient purification this brown substance could be injected into the body without toxic effects.

Through the cooperation of the British, full information regarding the status of penicillin was transmitted to this country in 1941 and 1942, and laboratory work was



A deep fermentation tank for production of penicillin by the so-called submerged fermentation process, one of three processes in use at present

started in the United States. Only experimental quantities were produced in 1942, and very little during the first half of 1943. Process developments and clinical results during the first months of last year were sufficient to warrant consideration of large scale production and the approval of coustruction of 18 plants in the United States and two in Canada. These plants are: Allied Molasses Co., Brooklyn, N. Y. Ben Venue Laboratories, Bedford, Ohio Cheplin Biological Labs., Syracuse, N. Y. Commercial Solvents Corp., Terre Haute, Ind. Connaught Laboratories, Toronto, Canada Cutter Laboratories, Berkeley, Calif. Heyden Chemical Corp., Gatfield, N. J. L. F. Lambert Co., Coatesville, Penn. Lederle Laboratories, Pearl River, N. Y. Eli Lilly and Co., Indianapolis, Ind. Merck and Co., Inc., Rahway, N. J. Parke, Davis and Co., Detroit, Mich.

The editors wish to thank Chas. Pfizer & Co. for use of these pictures.

Abbott Laboratories, North Chicago, Ill.

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •

Chas. Pfizer and Co., Brooklyn, N. Y. Reichel Laboratorics, West Chester, Penn. Schenley Research Institute, Lawrenceburg, Ind.

E. R. Squibb and Sons, New Brunswick, N. J. Upjohn Co., Kalamazoo, Mich. Winthrop Chemical Co., Rensselaer, N. Y. Averst McKenna & Harrison, Montreal

This construction program, rushed through on high priority rating, was 90 percent complete on Mar. 1. The critical materials required for process equipment have been extremely difficult to obtain and in some instances it will be mid-year before all of the finishing equipment is installed. The British production is at present only a fraction of that of the United States, and their proposed expansion program, because of lack of critical materials and manpower, is also comparatively small.

The publicity given to the penicillin program and the uses of the drug have been perhaps greater than is warranted by the clinical results obtained thus far. It is far from being a "cure-all" drug and has the additional disadvantage that no successful procedure is known for its oral administration at this time. Many types of organisms are unaffected by penicillin, and hence disease caused by such organisms cannot be treated with this drug.

Penicillin may be applied to surface infections, or administered intravenously and intramuscularly. The drug is particularly effective against gram-positive organisms although gonococcus and meningococcus are affected. Remarkable results have been attained against hemolytic streptococcus, pneumococcus, and staphylococcus aureus. As new uses have been found for penicillin through clinical researches, the ceiling to which production must rise has continuously lifted. Uncertainties as to the course of the war are, of course, a key to this situation. Almost equally important, however, in this picture, may be the addition of one after another to the list of human disabilities which may be treated with penicillin.

It is made by three principal processes: surface fermentation in shallow vessels such as bottles; submerged fermentation in vessels of capacities up to several thousands of gallons; and fermentation by the mold penicillium notatum growing on moist bran held in large containers and trays. The earliest-developed surface fermentation has until recently been the mainstay of the limited production. Within recent weeks, however, the success of the submerged and bran processes has been clearly demonstrated on large scale with attendant economies of manpower and cost. While many improvements remain to be made, successful operation of commercial submerged and bran fermentors proves now that these units can and will continue to supply about threefourths of our penicillin. As new plants come into production and as process improvements raise the output of existing

plants perhaps several-fold, penicillin may assuredly be expected in adequate quantities for all essential uses that this drug can supply.

The development has suffered all the difficulties of construction materials, manpower, and raw materials shortages that beset other wartime developments. It has been further complicated in that plant construction was started while the process was still under development in laboratory and pilot plant. Many persons have learned that a mold fermentation does not always follow the chemical and engineering generalizations that have formed the groundwork of the commercialization of chemical processes. Since every unit of penicillin that has been produced to date has been needed for medical use, the initiation of the study of every processing improve-ment has necessarily been preceded by a careful balance of the benefits to be increases in penicillin requirements to be met through modification of present plants so far as possible, rather than through the slower and more wasteful process of constructing new plants. Third, but perhaps most important, is the necessity to improve the quality of the product with regard to its chemical stability in order that in the future penicillin may be shipped and stored under adverse conditions without danger of deterioration.

Effort on a nation-wide scale is being applied to the solution of the above and related problems. The development in this country was planted and carefully tended throughout its early life by the Fermentation Division of the Northern Regional Research Laboratory of the U.S. Department of Agriculture, under the leadership of Dr. Robert D. Coghill. The work of this group, allied with the Committee on Medical Research of the Office



Principal processes are: surface fermentation in shallow vessels, submerged fermentation in large deep vessels, and fermentation on bran

gained in increased production, if the study proved successful, against the temporary diversion of production to experimental use while the study was under way. Pressure to supply a material whose value is calculated in terms of human lives weighs heavily in such considerations and has necessarily led to the conduct of a maximum amount of experimentation on processing methods in the laboratory on small scale. Any engineer recognizes the requirement of high skill necessary to transfer results of such investigation directly into the plant.

Although it has been established that the fundamentals of contemplated penicillin production methods are sound, there remains a host of problems to be solved. First is the problem of bringing all plants to full production rate. Second are those of increasing plant capacities through technological improvement to enable future of Scientific Research and Development, continues in its far-reaching influence over the entire field of penicillin in this country and abroad. Other groups brought together by the Office of Production Research and Development are also contributing technologically to the industry in the period of plant construction and conversion of processes to large scale. These include biochemists, bacteriologists, and botanists concerned with fermentation problems and working under Dr. W. H. Peterson at the University of Wisconsin; chemists, bacteriologists, and chemical engineers at the Pennsylvania State College headed by Dean F. C. Whitmore on developing processes for the recovery of penicillin from the fermentation broth; chemical engineers headed by Dr. T. K. Sherwood at the Massachusetts Institute of Technology studying and advising on methods of drying the final product for packaging and shipment; and plant pathologists led by Dr. E. C. Stakman at the University of Minnesota and Dr. G. W. Beadle at Stamford University in search for better mold strains. Intensive effort by corn products industry is being devoted to improvement of nutrient factors for the growth medium.

Synthesis of penicillin is under the control and direction of the Office of Scientific Research and Development. Companies are working desperately to synthesize the material even though it may make obsolete fermentation plants barely completed. Those familiar with the trials and tribulations of research work know how optimism and pessimism fluctuate day by day. As of the time of writing, success may come today, tomorrow, or never.

The construction, allocation, and program coordination of penicillin by fermentation methods has been in the Chemicals

duction of adequate supplies of penicillin. Efforts of the technical research and development groups are closely coordinated to avoid overlapping in their complicated pattern of interrelationships. Their results are transmitted on restricted basis to WPB and to the scientists and engineers of the penicillin manufacturers approved by WPB, who, being on the actual firing line of production, carry directly the responsibility for our present and future supply of penicillin, as well as to other governmental and research groups. The untiring effort of the staffs of the 20 companies in the United States and Canada which are producing or preparing to produce penicillin are the direct basis for present and future production. The performance of these men have been equaled by and coordinated with the effort of the manufacturers of equipment and the suppliers of raw ma-terials to the penicillin industry. The



The first penicillin produced in America was made by surface fermentation in shallow vessels such as the flasks shown in this picture

Bureau of the War Production Board. The drug is allocated by the Drugs and Cosmetics Section headed by Fred J. Stock, who is assisted by Roy S. Koch of the Biologicals and Parenteral Solutions Unit.

Civilian requirements for penicillin and clinical research are controlled by Dr. Chester Keefer, of the Evans Memorial Hospital in Boston, under direction of Dr. A. N. Richards, chairman of the Committee on Medical Research of OSRD.

Extraordinarily valuable contributions to the industry come also from the laboratories of the Food and Drug Administration, the National Institute of Health, the Army, the Navy, and other groups too numerous to mention.

Above outlined research is considered essential for the guidance of both governmental groups and industry, regarding both raw material and processing problems on whose solution depends the successful proefforts of all of the above groups are needed for many months to come to assure maximum production through attainment of optimum processing mehods.

Newspaper reports from time to time have placed the potential production of penicillin from the existing plants at 200 billion units per month. It is anticipated that this goal will be attained though it is impossible at this moment to estimate with accuracy what these plants will be producing in June when they should be in complete operation. The production has increased about twenty-fold between August, 1943, and February, 1944. In the latter month the output is expected to equal the entire production for the year of 1943. It is expected that the production will increase further between five and ten fold, from March to June, 1944.

Recovery and packaging of penicillin is hampered by the unstable nature of the

compound. The concentration in the broth at harvest is in the same order of concentration as bromine in sea water; however, penicillin separation and recovery is far more complicated. Standards of purity and methods of testing for toxicity and pyrogens are closely coordinated by Food and Drug Administration.

The raw material requirements for the production of a few pounds per month of finished product are staggering, and it is in this field that great progress may still be made. Search for a new mold strain which might double the production from this \$15,000,000 to \$20,000,000 plant investment is being rushed forward as rapidly as possible. Seeking a new strain is as tedious as looking for the "needle in the hay-stack" but if found would make possible immediate increase in output which would be measured directly in terms of human lives.

Output Climbs

THE output of penicillin in the United States during 1943 is estimated by WPB to have been over 21 billion Oxford units. The Oxford unit is the amount of penicillin which completely inhibits the growth of a test organism, staphylococcus aureus, under certain specific conditions. Each milligram of penicillin as commercially manufactured contains more than 100 Oxford units. A patient often requires as much as a million units for a series of treatments of a serious infection.

Production in the United States at the new government aided plants has stepped up rapidly; 40 percent of last year's production was made in December alone. Increases are continuing as production capacity goes into operation at the 20 American establishments which will be operating by July. The price of the product last year was \$200 per million units. It is now \$47.50. Further price reductions are expected this year, despite the difficulty of manufacture through growth of molds.

Manufacture requires critical equipment such as refrigeration machinery, centrifuges, vacuum pumps, tanks, and special packaging devices. The fermentation cycle is unusually long, and exacting conditions of sterility, temperature and atmosphere control are required to obtain any yield whatever. More than 20 quarts of culture fluid are required to yield one gram of the dry powder. Work is still being done to determine the most productive strains of mold and to improve culture media, methods of extraction, purification, standardization and packaging. Chemical research studies are currently being carried on for determining the structure of penicillin, with a view to eventual synthetic production.

Postwar Plans for Reconditioning WARTIME STRUCTURES

Certain trends in the housing of the chemical process industries that had become noticeable before the war upset the world will be resumed when peace is once more restored, C. A. Harwick predicts. Other trends naturally are expected to develop as a result of changing conditions. But the buildings that were constructed during the war with a minimum of critical materials need not be discarded as unserviceable if some replacements are made when materials become available. Attention to the "soft spots" will increase the lifetime of a war structure. -Editors

D ON'T BUILD yourself up to expect ultramodern plant facilities in the chemical industry as soon as the war is over! The main reason is that you probably will not get them.

A fundamental principle governing well designed industrial buildings is that one of their main purposes is to protect equipment and men from the weather. Following that principle, buildings are only of secondary importance in the chemical industry. Processing equipment is given prime consideration.

Better looking plants, however, can be expected after the war. Their design will be predicated on equipment—not on buildings. Already many chemical manufacturers are studying the example set years ago in the petroleum industry of leaving major equipment out of doors, uncovered, exposed to the weather. They have visited new butadiene, styrene and polymerization plants in the rubber industry and new high-octane plants in the petroleum industry and have marvelled at the appearances



Wooden operating platforms around stripping columns and handrails along stairs may be replaced. Firestone synthetic rubber plant, Lake Charles, La.

gained through effective design treatment of cracking towers, stripping columns and other process units.

The trend is that more and more chemical processes will be put out of doors. Every square foot of covered floor space will have definite utilitarian value. Few new chemical plants of the future will have structures whose value is entirely ornamental.

Two points bear out this statement. First, the chemical industry can well expect a highly competitive market for its products in the postwar period. Ornamental buildings, with no real purpose, are not conducive to the lowest possible unit cost of a product. Second, chemical plants can be made more attractive without benefit of a lot of buildings. These structures usually are designed around equipment; in many instances, they are odd-shaped, grotesque affairs that cannot be tied into any definite pattern. Equipment is interesting regardless of shape, and the fact that it is interesting makes it appealing to the cye.

There is no intention to predict that all chemical plants of the future will be "buildingless." The process will be the governing factor in the future as it has in the past. If equipment can be exposed without damage and without undue hardship on employees, it likely will be placed outside.

Some chemical manufacturers are wondering whether wartime buildings constructed with a minimum of critical materials will be serviceable after the war. The only general answer that can be given is "yes."

In the buildings housing equipment there are certain "check list" items which may be taken care of when materials become available. Attention to them will increase materially the lifetime of a war structure. No good list will omit the possible "soft" spots.

"SOFT SPOTS" IN WARTIME BUILDINGS THAT WILL NEED CHECKING

ROOFS-Often the first source of trouble is the roof. By the time the war is over, if the wartime factory roof has not started leaking, it can be expected to do so soon. War roofs in many cases have been 3 ply, 60 lb. asphalt pitch waterproof composition. It will be advisable to change to 5 ply, 100 lb. asphalt pitch for permanent insurance.

FLASHINGS-Substitutes have varied. None is as satisfactory as copper for general purposes. This work can be done at the same time the new roof is put on.

SIDE WALLS-On some buildings, side walls may be wood sheathing. These should be changed to Transite, masonry or protected metals.

SASH-Chances are the entire plant has wood frame sash made from green lumber which is not satisfactory over a long period. If so, it should be changed to steel sash.

GLASS—As a wartime expedient, cheap, lightweight glass has been used in many instances as substitutes for doublestrength or even wire glass and other specialized types. Wartime putty instead of satisfactory glazing compounds or prewar putty also has been used as an expedient and may need attention.

FLOOR-There are several points to check. Was a concrete hardener used in the original floor? Is a stronger slab required in spots than was provided for with limited quantities of reinforced steel? Is it desirable to have a covering of asphalt tile, mastic, or even wood block-none of which has been used usually in "temporary" war plants?

PARTITIONS-In many plants, they are all wood. You will probably want steel, tile, brick or some other fireproof material.

SPRINKLER SYSTEM AND FIRE ALARM-Not all plants have adequate sprinkler systems and fire alarms. They were omitted because of shortages in critical materials. To reduce insurance rates, a plant should have both.

RAILINGS, STAIRWAYS AND OPERATING PLAT-FORMS-Steel should be used instead of the now prevalent timber.

DOORS-Metal and special fireproof types should be substituted for wood.

VENTILATION-Many ventilator ducts have been built of wood, rather than more dependable sheet metal. Forced-draft systems have been omitted in many plants because of a shortage of blowers, fans and starters.

ELECTRICAL—Much wiring is exposed. It should be placed in conduits to take advantage of lower fire insurance rates and because it affords added protection. Make-shift fixtures should be replaced with standard fixtures. More adequate panel boards, including automatic gear and remote controlled equipment, may be wanted.

SEWERS-Storm and sanitary sewers have been made from vitreous clay tile and lightweight cast iron "victory" pipe. In many cases, standard cast iron pipe should be installed.

TRUSSES—In hundreds of buildings trusses are wood instead of steel. It is not necessary to consider replacing wood trusses and columns. That would be too costly. They should be checked and defective members replaced with sound timber. A great deal of this type replacement is likely in view of the green timber used in war construction. It is probable, too, that plant owners will want to fireproof wood trusses, either through the application of fire-resistant coatings or the addition of Transite coverings, which would serve also as a break against any fire that started in the roof. In this connection, trusses made from green timber usually undergo considerable shrinkage which loosens bolts to the point where they need checking and tightening periodically—otherwise, they may become unsafe.

PIPING--Insulation materials have been of poor grade, thus causing undue temperature losses. Better quality insulation should be installed if needed. Some steel piping possibly should be replaced with copper or brass at an early date.

BOILER HOUSE-Addition of stoker equipment, conversion to oil burners, substitution of turbine-driven for motor-driven equipment and addition of fire-control instruments to provide automatic operation of equipment are a few of the changes which should be studied.

PROCESS EQUIPMENT-This depends entirely upon each individual process. Certainly, there have been some substitutions to save critical materials in every plant. Typical of most of them are manual controls which may be replaced by automatic controls when they become available or the addition of more integrating, recording or metering equipment, probably omitted in the first installation.

In spite of the fact that the chemical industry has expanded to its greatest point in history, engineering and building organizations with special experience in process work can expect a reasonable volume of postwar business. According to studies of the market, there will be four principal sources: (1) consolidation programs around established sites; (2) a few complete plants for production of plastics and other new products and processes now in pilot plants; (3) foreign building to replace facilities destroyed by bombing and to develop new chemical industries in South America and elsewhere, and (4) the usually expected "maintenance" work in the chemical industry with an added program of replacing wartime substitute materials.

Consolidation programs will affect chemical producers who have been operating plants at widely scattered locations because of the war. This consolidation will represent a good portion of the postwar building program in the chemical industry. Constructing new plants will not be involved to any large extent, rather the addition of new structures at established sites, removal of equipment from one site and erecting it at another, increasing capacities of certain chemicals to fill requirements made necessary through discovery of new products or new processes. At many "old" plants, production techniques will be changed, brought up to date. Piping will be rearranged. Entire plants may even be converted for new materials.

The manufacture of new products likely will result in a few new plants when corporations are ready to introduce their products to the consumer market, but it seems logical that the trend will be toward utilizing, as far as practical, existing facilities. Different manufacturing methods developed by the war and different processes will also serve as a justification for modification of existing facilities—or construction of new facilities.

Foreign countries already have indicated

a desire to establish their own chemical industries. South American nations and countries in the Orient have started detailed investigations. In Europe many chemical plants will be rebuilt. One approach to this demand will be salvaging equipment in some American plants that will be useless to us after the war and shipping it abroad. Entire chemical plants may be dismantled and sent abroad.

The fourth source of postwar work in the chemical field is the usual "backlog" built up year after year in the industry in the form of maintenance construction. Processing equipment depreciates after a time. After that point has been reached, it is cheaper to replace it. Processes also change rapidly. They require adjustments in layout and rearrangements of equipment. Also, the replacement of all the "ersatz" building materials will be a big item in the postwar business cycle for industrial engineers and builders in the chemical field.

Ordinarily this hopper would have been made of steel, but plywood could be obtained more readily. When construction materials become available the management of this synthetic rubber plant of the Copolymer Corp. at Baton Rouge, La., may find it desirable to change to steel

GAS TURBINES

(Continued from page 99)

for its compactness (about one-tenth the space of watertube boilers of conventional construction) on supercharging the combustion space to 20–35 lb. per sq.in. In a sense, the Velox unit represents a gasturbine application where it is desired to take the entire output of the fuel as highpressure steam and such small amounts of power as may be incidental to the gasturbine auxiliary set are purely a welcome byproduct. Some 75 of these steam generators are (subject to correction by the Royal Air Force) in operation in land plants throughout the world.

It will be entirely practicable to utilize only a small amount of steam generating surface around the combustion chamber of the gas turbine to supply any specified quantity of process steam. Additional electric power can be taken from the gas-turbine set, eliminating need for a steam turbine-generator.

Sketch (f) indicates the possibilities of waste heat recovery for low-pressure steam, approximately the same as for diesel engine exhaust. Gas leaves the turbine at about 700 deg. F. and any part of its heat may be absorbed in a conventional waste-heat



boiler instead of, or in combination with, a heat exchanger.

While the foregoing schematic arrangements indicate that it is mechanically possible to take any desired proportion of net output as steam or power, the process engineer should remember that the gas-turbine combination is inherently a "bottom" as constrasted to the back pressure steam turbine "top." Where relatively large quantities of moderate- or low-pressure steam are needed for process, and power needs can be generated by a steam turbine working on the difference between boiler pressure and process pressure, the steam plant offers much higher utilization of fuel energy.

In contrast, where relatively small amounts of steam (in comparison to power requirements) are needed at quite high pressure, the steam can be supplied by what amounts to a small steam generating attachment to the gas-turbine combination. Steam making "skims the cream" of the high temperature fuel energy without appreciably affecting the efficiency of the power making function of the gas-turbine unit. In this, as in other ways, the gasturbine unit shows prospects of becoming a new factor in power service applications by providing an efficient method of "bottoming," just as superposing the back-pressure and extraction types of steam turbine have improved the over-all economy of steam-and-power supply for industrial plants.

Prediction of future application for gas turbines becames difficult because the gas cycle is only one phase of a rapidly moving age. For example, the conventional gasturbine unit weighs upwards of 20 lb. per hp. and as such would hardly be expected to compete with the 0.8 lb. per hp. of the gasoline engine for airplane propulsion. Requirements for greater power per engine, however, and possibilities of jet propulsion of ultra-high-speed planes offers a new field for which the gas-turbine combination has no competitor. If high rotating speed and short life of parts can be accepted, gas turbine weight decreases out of all proportion, and the useful work is available immediately to the jet in the form of compressed air.

These are but the elements of possible future gas-turbine cycles. Many combinations and variations are possible, particularly with respect to chemical processes. It will remain for engineers associated with the special problems of individual industries to adapt this versatile new prime mover to their particular requirements. A forward looking observer would conclude that the future of gas turbines depends more on the differences between it and other prime movers than on replacement of existing machinery that functions reliably and satisfactorily.

Inter-Relationship of PLASTICS and CHEMICALS

Even the man in the street knows of the brilliant progress that has been made by the plastics industry, but much less is known about its importance as a market for chemicals. As the production of cellulose resins soars to a rate of 135,560,000 lb., and vinyl resins expand from a production of 72,000,000 lb. in 1941 to 212,000,000 projected for the coming year, and others likewise make great strides, so goes the demand for chemical raw materials, styrene, chlorine, phenol, and a host of others. In order to meet these requirements, it has been necessary to construct many new facilities. __Editors

IN THE FIRST World War the United States did not have a synthetic resin industry worthy of specific recognition. It is true that cellulose acetate dopes and cellulose nitrate plastics were in use at that time. Phenolic resins were known and were struggling for recognition. However, the industry did not play a significant role in the war period, save possibly the contribution of cellulose acetate dopes.

From the end of the World War until 1940 a substantial synthetic resin industry was developed in the United States. This was indeed fortunate, for many of the resins are playing a most important role in the present World War. In fact, had it not been for certain of these resins, we would have had a rather critical military equipment problem resulting from the loss of natural rubber supplies. Other synthetic resins are being used to replace critical metals in the form of plastic parts. In many cases, it has been found that the synthetic resin product served the purpose



Thin liquid methyl methacrylate monomer is transformed into crystal clear practically unbreakable solid

as well or better than the material for which it was substituted. The story of all the functions of synthetic resins in the war program cannot be told in detail at this time, hence in this paper the emphasis will be on the relationship of the chemicals and the synthetic resin industries.

The Chemicals Bureau of the War Production Board has the responsibility of determining the requirements of chemicals for the war program. In order to arrive at proper figures for the basic chemicals, it is first necessary to determine the requirements in terms of compounded products like plastics, protective coatings, pharmaceuticals, dyes, synthetic rubber, and many other classifications. Once these requirements are known, the specialists in the various branches of the Bureau prepare a breakdown into the many chemical components. When the total basic chemical components are known for the end products, they are added to the requirements for the basic chemicals as such. Each important chemical has been studied in this manner to determine the supply and requirements for the war program. As a result of these individual chemical programs, new production facilities have been planned where and when needed.

The chemical requirements for synthetic resins do not cease with the resins themselves. In addition, there are substantial requirements for chemical plasticizers and organic solvents necessary for the industrial application of the various synthetic resins. Catalysts and pigments augment the chemical requirements but they will not be treated in detail in this paper.

There are a number of groups into which these synthetic resins may be classified. In each group there are several classes, types, and brands. Each resin has achieved a place in the commercial picture because



Homogenized vinyl chloride-acetate plasticized resin in the feed bank of a four-roll calender. Production of vinyl resins has been sharply increased

of one or more properties which render it useful in some industrial application. The principal industrial fields where synthetic resins are employed are: plastics, including film and rubber replacements; protective coatings, including coated fabrics and paints; and printing inks, including lithographic finishes.

The expected demand for plastics and protective coatings for war purposes made it necessary to plan a substantial plant expansion program for synthetic resins and the basic chemical components necessary for their production and use. In spite of this increased capacity, there are times when the military demand for certain resins cannot be met in full. In most cases, the military and essential civilian uses absorb the entire productive capacity, leaving many ordinary civilian uses without material. Since the bottleneck of shortage is now primarily one of basic chemicals, it would require much too long and a disproportionate utilization of critical materials to readily justify further expansion for most synthetic resin purposes.

In order to summarize the expansion which has taken place, each group of resins will be treated separately and the basic chemicals necessary will be indicated. This will be followed by similar treatment for the plasticizers and solvents.

Resins may be classified into two general classes, thermoplastic and thermosetting. There are four major groups of the former type which will be discussed. These are cellulose compounds, vinyl compounds, rubber derivatives, and a miscellaneous group.

The first to be considered are the cellu-

lose compounds used for lacquers, many specialty finishes, and for plastics. Nitrocellulose, cellulose acetate, cthyl cellulose, and cellulose acetate butyrate, are the principal cellulose compounds. Cellophane and vulcanized fiber are important specialties which are not classed as resins in this article. Cellulose is the basic raw material and a variety of chemicals are required to make the final products.

The use of nitrocellulose was severely restricted early in the war because nitric and sulphuric acids, essential for its manufacture, were more urgently needed to make explosives. By the time the acid supply was reasonably available, other resins had become established to meet many military specifications and had demonstrated superior properties for most plastic and many protective coating uses. During late 1943 and projected into 1944, increased military requirements for certain basic chemicals, plasticizers, and solvents, have made it necessary to deny most of these materials for the civilian uses to which nitrocellulose would normally go.

Production of the lacquer and plastic grades of nitrocellulose has increased from 37,000,000 lb. in 1940 to 60,000,000 lb. in 1943. This has accordingly increased the demand for nitric and sulphuric acids which are used in converting cellulose into nitrocellulose. There has, of course, been an attendant increased demand for solvents, such as butyl and ethyl acetate, amyl alcohol, and various chemical plasticizers.

Cellulose acetate uses have increased sharply during this war, increased demands for rayon by the rubber industry and for essential civilian use have been the most significant factors. Unlike the last war, there has been no large demand for acetate dopes for airplane fabric. On the other hand, there have been and will continue to be many military uses for cellulose acetate plastics. Considerable acetate has been available for civilian plastic uses. However, as in the case of nitrocellulose, increased military requirements for the basic chemicals, plasticizers, and solvents, threatens the continued civilian usage of the resin for less essential purposes.

Production of plastic grade cellulose acetate has increased from 24,000,000 lb. in 1940 to 55,000,000 lb. in 1943, with production projected at the same rate for 1944. There have been plant expansions for cellulose acetate flake which has been increased to meet the rayon requirements. In addition, there has been a substantial increase in the production of acetic acid and acetic anhydride, both of which are used to react with cellulose to produce cellulose acetate.

Four principal methods are currently used for producing acetic anhydride. These four processes require or produce the fol lowing chemicals in the course of the vari ous reactions: ethly alcohol, isopropyl alco hol, actone, ketene, acetylene, and acetic acid.

Five processes are currently employed to produce acetic acid. The following chemicals are involved in these processes: ethyl alcohol, acetylene, butane, methanol and formaldehyde.

Ethyl cellulose has found a high order of essential war uses. As a result, there is none available for many military purposes and virtually no civilian uses are allowed. This heavy demand was foreseen late in 1942 and limited plant expansion was planned before military requirements became firm. No major plant expansion was authorized because of the requirements for critical metals and the problems involved in going back to produce more ethyl chloride, the chemical which is reacted with cellulose to form ethyl cellulose. Ethyl chloride is made by reacting ethylene or ethyl alcohol with hydrochloric acid under carefully controlled conditions.

Subsequently, ways and means were found whereby the manufacturers could increase their capacity without using critical metals. Changes in other programs made it possible to provide more ethyl chloride so that some increased production will soon be realized.

Cellulose acetate butyrate is currently used in about equal parts for military and civilian purposes. Plastics consume over 60 percent of the production. The continued civilian use of cellulose acetate butyrate for plastics may be difficult to sustain. This is because butyl alcohol is required to make butyric acid which is used, along with acetic acid, in the manufacture of cellulose acetate butyrate. Currently, butyl alcohol is denied to most civilian uses.

• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

Figures on ethyl cellulose are here combined with cellulose acetate butyrate and cellulose acetate propionate. The total production of this group was 8,000,000 lb. in 1941 and had been increased to 32,-000,000 lb. in 1943, with production scheduled to rise to 36,000,000 lb. in 1944.

To summarize, the cellulose resins as a group are finding important uses in the war program. At the close of 1943, production for the entire group, including acetate for rayon, was at a rate of 360,-000,000 lb. per year. Rayon was receiving 62 percent of the total. Plastics and film uses took 27 percent, and the balance, or 11 percent of the production, was used for protective coatings, special printing inks, and the like.

The chemicals required for the cellulose group are: coal, limestone, salt, and sulphur as basic or elemental materials. Acetylene, acetaldehyde, acetic acid, acetic anhydride, ammonia, butane, butyl alcohol, butyric acid, calcium carbide, caustic soda, chlorine, hydrochloric acid, ethyl alcohol, ethylene, ethyl chloride, formaldehyde, isopropyl alcohol, ketene, propionic acid, nitric acid, and sulphric acid. are all required as intermediate chemicals.

The demand on certain of these chemicals is quite significant. For instance 46 percent of the acetic acid and over 90 percent of the actic anhydride are consumed in making these cellulose resins and cellulose acetate rayon. A large facility is now being constructed in order to provide additional acetic acid to meet the future demand for increased rayon production for civilian requirements.

Vinyl resins constitute a second group of the thermoplastic resins. Included in the vinyl group are polymers of styrene, isobutylene, methyl acrylate, methyl methacrylate, vinyl acetate, vinyl butyral, vinyl chloride, vinyl formal, vinyl alcohol, and certain co-polymers, such as the wellestablished vinyl chloride-vinyl acetate combination, or the newer vinyl chloridevinylidene chloride resins.

Styrene for production of polystyrene is now restricted for military uses in plastics. The other allowed usage is for the production of synthetic rubber. Polystyrene for plastics will be limited to those uses where it is considered indispensable. Current production of polystyrene is about 4,000,000 lb. per year. The total production of monomeric styrene has been expanded from 15,000,000 lb. in 1940 to a total of 350,000,000 lb. in 1943, with 405,000,000 lb. projected for 1944.

Benzol is the basic raw material for the production of styrene. It is combined with ethylene to form ethyl benzene from which two atoms of hydrogen are removed to form monomeric styrene. Over 27,000,000 gal. of benzol per year are now going to make styrene. This is almost the equivalent of our total prewar production of refined benzol. These benzol requirements have been an important factor in preventing the use of benzol or its derivatives for anything but military or extremely important civilian purposes.

Isobutylene is produced by the dehydrogenation of isobutane. This resin has been extremely useful as a rubber substitute in certain types of electrical insulation. Its use has been restricted to military and a few important civilian items.

Methyl acrylate, methyl methacrylate, and other special acrylates, have been used almost exclusively for military purposes. Production was expanded from about 19,-000,000 lb. in 1941 to 37,000,000 lb. in 1943, and the capacity is expected to reach 50,000,000 lb. in 1944, with actual production at a somewhat lower level.

The methyl acrylate resins start with ethylene chlorohydrin which is reacted with sodium cyanide to form hydracrylic nitrile which can be combined with methanol to form the monomer of methyl acrylate.

Methyl methacrylate starts from acetone which is reacted with hydrogen cyanide to form acetone cyanohydrin which is combined with methanol to form the monomer of methyl methacrylate.

Vinyl acetate is an intermediate in its monomeric form. It is used in the production of sulfa drugs, polyvinyl alcohol, polyvinyl butyral, polyvinyl formal, and polyvinyl chloride-acetate. Vinyl acetate is produced either directly from calcium carbide or from acetylene produced from it. The acetylene is reacted with acetic acid in the presence of a catalyst. Sulphuric acid is required in the process.

The use of polyvinyl acetate has been restricted to a high order of essentiality. Currently, shoe adhesives are the marginal use and, in this application, vinyl acctate is replacing rubber. Production of the monomer in 1941 was 15,000,000 lb. This was increased to 40,000,000 lb. in 1943, and in 1944 the capacity will be 50,-000,000 lb.

The group consisting of polyvinyl acetate, polyvinyl alcohol, polyvinyl chloride, polyvinyl butyral, and the co-polymers of vinyl chloride and vinyl acetate are most extensively used for rubber replacement. At the present time, total military demands cannot be met in full. Nevertheless, a few highly essential civilian uses are permitted. A small amount of scrap material is allowed to flow into essential civilian uses because the material cannot be reconditioned for a military use. Production of this class of vinyl resin has been sharply increased from a total of 18,000,000 lb. in 1940 to 83,-000,000 lb. in 1943 and with 108,000,000 lb. capacity to be available in 1944.

To summmarize, the entire vinyl resin group has been expanded from a production of 72,00,000 lb. in 1941 to 178,000, 000 lb. in 1943, with 1944 production projected at 212,000,000 lb. Of this production, 30 percent is used for protective coatings and adhesives and 70 percent goes into plastics. The styrene for synthetic rubber is not included in the above figures.

The chemical requirements for the vinyl group are most significant. Raw materials include acetic acid, acetic anhydride, acetone, acetylene, benzol, butyl alcohol, butyric acid, calcium carbide, caustic soda, chlorine, cholohydrin, cyanamide, ethylene, ethylene dichloride, ethylene oxide, isobutane, isobutylene, methanol, sodium,

Urea formaldehyde resin being mixed. Production of urea resins has increased from 22,000,000 lb. in 1940 to 115,000,000 projected for 1944



sodium cyanide, vinyl alcohol, and vinyl acetate.

Rubber derivatives constitute a third group of thermoplastic resins. These are chlorinated rubber, rubber hydrochloride, and isomerized rubber. In spite of the critical rubber shortage, limited quantities of these resins are still being manufactured for uses where there is no known substitute.

The miscellaneous group of thermoplastic resins include the widely used coumarine-indene resins and the resins derived from beta-pinene. These resins have found a wide utility in the war program and continue to be used in many civilian applications. To date, the supply has been adequate for all needs. There is no immediate problem in the raw materials, which are coal-tar distillates, turpentine and sulphuric acid. Production capacity for these types has not been expanded during the past three years and is believed to be in the order of 55,000,000 lb. per year for all grades.

POLYETHYLENE

Polyethylene is an important new resin that has been put in commercial production in order to meet important military demands. This resin should find many useful industrial applications in the postwar era.

In the aggregate, the production of these resins consumes a significant proportion of the production of many chemicals. Under war conditions and because of military demands, some of these chemicals, such as benzol and butyl alcohol, are in critical supply. Therefore, any resin, which requires such a critical component in its manufacture, can only be used for purposes having an essentiality equivalent to the other end uses of the critical components. For example, benzol is used for the production of: styrene for synthetic rubber; phenol for plastics; aniline for dyes, drugs, rubber chemicals, miscellaneous essential chemicals, and the balance of all available benzol is channelled to aviation gasoline. Therefore, the use of styrene or phenol for plastics and for other purposes must have an essentiality equivalent to aviation gasoline. In other words, if the resin use is indispensable to the war effort, including some essential civilian need, it is a justified use. The Chemicals Bureau endeavors to find these "common denominators" through the medium of allocation orders in which the producer applies for authority to make products for certain specific end uses. These applications are handled on a monthly basis for extremely critical materials and on a quarterly basis for the less critical materials. These allocations do not apply to materials in free supply.

There are three general groups of resins that may be classed as thermosetting. Those which will be discussed in this paper are the following: phenol-formaldehyde resins (including cresol and substituted phenolic resins), urea-formaldehyde resins (including melamine resins), and alkyd resins (including phthalic, maleic, and pentaerythritol types).

PHENOLIC RESINS

The phenolic resins are widely used for military purposes. This is partly because they are derived from benzol and hence usage must stand a rigorous essentiality test. Approximately 16 percent of the phenol for resins goes into those grades of resin required for protective coatings, the balance being the plastic grades.

Phenolic resins are made by condensing phenol or cresol and formaldehyde. Some phenol and most of our cresol is produced as a byproduct of coal-tar. However, by far the largest proportion of our current supply of phenol is made synthetically. Some cresol or cresylic acid is produced from petroleum and some is produced synthetically, but in neither case is the product considered fully suitable for resin production. There is, however, a limited production of petroleum cresylic resin that is quite useful.

The production of phenolic resins has been substantially increased to meet the war needs. In 1940, according to U. S. Tariff Commission reports, the industry manufactured 93,000,000 lb. of resin. This would be equivalent to 180,000,000 lb. when compounded for sale as molding powder, laminates, adhesives, and the other commercial forms.

The figures on production from 1942 have been as follows:

		Production			
	Taracid		Resin Comp.		
rear	Consumption	Dry Resin	as Sold		
	(In million	is of pound	18)		
1942	104	116	217		
1943	13(152	300		
1944	198	176	346		

The 1943 production of phenolic resin compound was divided as follows:

Molding po	wders	100,000,000	1b.
Laminates		80,000,000	1b.
Specialties		50,000,000	lb.
Protective	coatings	36,000,000	lb.
Adhesives		34.000.000	lb.

The principal chemicals required for this production include: benzol, caustic soda, chlorine, cresylic acid, formaldehyde, methanol, monochlorbenzene, phenol, sulphuric acid. About 16 percent of our benzol goes into synthetic phenol. Phenolic resins consume 62 percent of this phenol. About 46 percent of our methanol is converted to formaldehyde, and 31 percent of the formaldehyde is consumed by the phenolic resin industry. In order to meet these requirements, it has been necessary to construct new facilities for phenol and formaldehyde. This, in turn, has required new facilities or new sources for all of the other chemicals required to produce phenol and formaldehyde.

Urea-formaldehyde resins are becoming increasingly important in the war program. They are widely used as adhesives, and over 80 percent of this use is for military purposes. In the molded materials, civilian uses predominate. However, the melamine resins are used almost entirely for military purposes.

The production of this group of resins has increased markedly in the past four years. In 1940, the Tariff Commission reports indicated a total production of 22, 000,000 lb. In 1942, 40,000,000 lb. were produced. For 1943, the production has been estimated at 100,000,000 lb., and 1944 is projected at 115,000,000 lb.

The principal chemicals required for this group of resins are: ammonia, calcium carbide, carbon dioxide, cyanamide, formaldehyde, melamine, methanol, urea.

In making these resins there is consumed over 50 percent of the urea production and nearly 40 percent of the formaldehyde. In order to meet the heavy increased demand for these resins, it has been necessary to build facilities for the raw materials as well as the resins themselves. Alternate uses for ammonia and methanol will determine how much formaldehyde can be used for resins for civilian end uses.

ALKYD RESINS

Alkyd resins are used chiefly by the protective coatings industry.

Naphthalene is combined with oxygen to form phthalic anhydride which is then reacted with glycerine to form glycerolphthalate which, in turn, is modified with a drying oil to produce the finished alkyd resin. Another type is produced from maleic anhydride and glycerine. Still other modifications are made by substituting pentaerythritol for glycerine in the reaction with the anhydrides or other dibasic acids. For a time during 1942 and early in 1943 glycerine was in short supply which greatly restricted the civilian use of alkyd resins. As a result of improved glycerine supply, more alkvd resins were produced during the latter half of 1943. However, phthalic and maleic anhydride availability have now halted production at a level of 170,000,000 lb. per year.

The chemicals required for the alkyd resin group include: allyl alcohol, ammonia, benzol, carbon dioxide, coal tar, dipentene, glycerine, linoleic acid, maleic anhydride, methanol, naphthalene, pentaerythritol, phthalic anhydride, rosin, Sorbitol.

Approximately 66 percent of our naphthalene production now goes into phthalic anhydride and over 40 percent of the latter chemical is converted into alkyd resins with another 47 percent going into chemical plasticizers. Thus, about 87 percent of our phthalic anhydride may be said to be consumed directly and indirectly for synthetic resins. There is, however, a substantial amount of the current production of phthalate esters being used for non-resin military purposes.
In general, the synthetic resins require plasticizers or softeners to modify their physical characteristics to meet particular requirements. The thermoplastic resin uses are the major consumers of these plasticizers. Chemical industry has provided for this demand to supplement castor oil and camphor which were widely employed in the early days of synthetic resin development. It has been stated that there are 30 manufacturers producing 150 different chemical plasticizers. There are probably a number of new chemicals that have been found useful during the past few years which would increase both totals. However, the list of known chemicals which may be called plasticizers will be many times 150. Unfortunately, only a comparative few are really useful in compounding synthetic resins. On the other hand, it is indeed fortunate that the different resins require somewhat different plasticizers in most of their applications.

By far the largest number of plasticizers are made by combining an alcohol, ether or ether-alcohol with an acid or an anhydride. A group of this type are the phthalate plasticizers. diethyl, dimethyl, dibutyl, diamyl, dicapryl, and diactyl phthalate. The corresponding alcohols. ethyl, methyl, butyl, amyl, capryl or octyl, are reacted with phthalic anhydride to form the esters. The ether-alcohol esters are also quite important phthalates.

Among the organic acids making esters useful as plasticizers are the following: abietic, acetic, adipic, benzoic, butyric, caprylic, citric, glycolic, lauric. linolenic, maleic, oleic, phthalic, propionic, ricinoleic, sebacic, stearic, tartaric, and toluene sulphonic.

Phosphoric acid is the principal inorganic acid which appears in plasticizer form. The first chemical plasticizers to attract attention were tricresyl phosphate and triphenyl phosphate which were found useful with nitrocellulose as a replacement for camphor. The chemicals required for the production of the various phosphate plasticizers include: coal-tar, benzol, cresylic acid, phenol, phosphoric, chlorine, phosphorus oxychloride, phosphorus pentoxide, caustic soda, and, in addition various alcohols.

SPECIALTY PLASTICIZERS

In addition to these broad groups, there are a few specialty plasticizers deserving separate comment. The amyl naphthalenes, glycerol triacetate, chlorinated biphenyl, and the nitriles are all important for certain special purposes.

There are no early records on plasticizer production which are wholly adequate for reference, however, the following table has been prepared from data which are available. It is presented in the hope that it will serve as a comparative measure of the ratio of chemical plasticizer production to thermoplastic resin production.

Plasticizer-Resin Production Ratio Estimated 1941 1943 1944 hemical plasticizers* 70 130 136

	TOTT	70.70	1011
Chemical plasticizers*	70	130	136
Thermoplastic resins	224	363	418
Ratio, lb. plasticizer			
per lb. of resin	312	.359	.325

 These figures do not include dibutyl phthalate and dimethyl phthalate produced for smokeless powder and insetifuque purposes. The figures do not include any sophean castor or linseed oil plasticizers. Camphor is included.
 The resins in this group are the plastic and lacquer

The resins in this group are the plastic and larguer grades of the cellulose group, the vinyl group, and the commarine-indene, and other miscellaneous thermoplastics.

The wide use of vinyl resins for rubber replacement probably necessitated higher plasticizer ratios in many formulations. This might account for the higher ratio in 1943. If so, we may expect a shortage of chemical plasticizer in 1944 unless the use of synthetic rubber relieves the demand for the vinyl resins.

The use of synthetic resins has created a tremendous demand for new chemical solvents. These solvents are required in processing and in application. The protective coatings industry is by far the major consumer of these various solvents. In general, each class of synthetic resin will yield the best results in some special class of solvent. Moreover, each application will require special solvent properties because of some conditions connected with the method of application, time cycle or mechanical limitations.

The coal-tar solvents, benzol, toluol, xylol, and solvent naphtha, are widely used both as solvents and diluents. The demands for benzol for aviation fuel and synthetic rubber have practically eliminated its use with synthetic resins. Toluol has been required for the production of TNT. More recently, any xylol not required for extremely essential protective coatings uses has been turned over to aviation fuel. Thus, use of the principal coal-tar solvents has been restricted so far as synthetic resins are concerned.

This has placed an added burden on the various esters and ketones. It has made it necessary to provide increased production facilities for the finished solvents and, in many cases, a number of intermediate chemicals.

The ester solvents, such as ethyl acetate, butyl acetate, etc., are made by reacting the corresponding alcohol and acetic acid. Thus, it is first necessary to translate our requirements back to the alcohols, for the bulk of our acetic acid is made from ethyl alcohol. The production of the acetate solvents currently consumes about 20 percent of our acetic acid production. Owing to the heavy military demand for these esters, practically no civilian use is authorized.

In 1941 the production of the principal items in this group of esters was estimated at 210,000,000 lb. In 1943 this production has increased to 212,000,000 lb. The solvents included in the above figures are ethyl acetate, normal butyl acetate, secondary butyl acetate, isopropyl acetate, and pentacetate.

The use of butyl acetate is far greater

than normal. This is because of its strong solvent power for many synthetic resins. The boiling point and evaporating rate are about the same as toluol. In the past the shortage of acetic acid discouraged increasing the ester productive capacity. At the present time, we could advantageously use considerably more butyl acetate. Steps have been taken to increase the production of butyl alcohol which must be made available before an increase in butyl acetate can be realized. In the meantime, military needs are being met.

The alcohols have many important uses as resin solvenfs. Methyl, ethyl, butyl, isopropyl, and amyl are used to varying degrees. However, only a small percentage of the total production is used directly as solvent. The Cellosolves are ether-alcohols and are useful because of their high solvent power and slow evaporation. They are used with many different resins in a wide variety of applications.

KETONE SOLVENTS

The ketones are another group of solvents of special significance. Acetone, diacetone, methyl ethyl ketone, cyclohexanone, methyl isobutyl ketone, and isophorone are the principal ketones in general use as solvents for resins. Virtually all civilian end use of these ketones has been eliminated because of the requirements for direct and indirect military purposes. Acetone has many important uses aside from its solvent use. It is used in the manufacture of other ketones, acetylene, synthetic resin, explosives, and acetic anhydride.

Our production of these ketones has been increased from 331,000,000 lb. in 1941 to 505.000,000 lb. in 1943. Synthetic resin use and application will consume about 25 percent of the 1943 production. The balance will be for a variety of uses, including the conversion from one ketone to another as, for example, from acetone to diacetone alcohol which may be converted to methyl isobutyl ketone.

Finally, there are solvents produced from petroleum. These are useful with many of the synthetic resins either as solvents or diluents. At present, there are some grades that are off the market due to the aviation gas program. The aromatic petroleum solvents have been in great demand as coal-tar solvent replacement. The current usage has been considerably restricted in order to insure adequate supplies for military and most essential civilian uses.

During the war period we will have learned better formulations for resin products. The fabricators of plastics have developed new techniques which have increased their potential uses for plastics. The commercial and civilian aviation development of the future should consume large quantities of resins. All told, the future looks promising for the chemical and synthetic resin industries.

FROM THE VIEWPOINT OF THE EDITORS-

S. D. KIRKPATRICK, Editor • JAMES A. LEE, Managing Editor • THEODORE R. OLIVE, Associate Editor • HENRY M. BATTERS, Market Editor J. R. CALLAHAM, Assistant Editor • N. G. FARQUHAR, Assistant Editor • L. B. POPE, Assistant Editor • R. S. McBRIDE, Consulting Editor

LABOR, TOO, HAS ITS PLANS

SPRING is in the air, and hopes for an early peace have at last, perhaps prematurely, begun to warm the hearts of men. Budding plans for our postwar future are beginning to blossom in every industry. Labor leaders, not to be outdone by the capitalistic planners, hasten from their holes of patriotic hibernation to cast their own postwar shadows before them—and, incidentally, to grab a few pies while the grabbing is good.

These shadows are worth close watching, for a large number of labor planners are growing increasingly more coherent regarding demands for postwar job security and income. This trend has an immediate significance to chemical employers, who should begin considering these demands now—not after an ultimatum has been issued.

Such demands, according to the Labor Relations Institute, are crystallizing into well-defined patterns. The "Guaranteed Wage Agreement," increasingly popular, has a number of variations: (1) the "2,080-hour clause," which would provide for guaranteed employment for that many hours per year. (This is actually equivalent to 52 weeks of 40 hours each.) (2) The "partial guarantee" which would permit seasonal fluctuations to affect only a certain part of the staff; (3) the "volume-of-business" clause in which the percentage of employees guaranteed steady employment would increase in proportion to the growth of business volume; (4) the "annual bonus plan;" (5) the "52-pay-check plan," which would provide employees with some compensation every week of the year, whether they carned it or not.

More and more unions are pressing for two-year agreements, with the goal of sustaining wages and union strength at present levels, despite reconversion letdowns! So far, however, the War Labor Board has indicated that it will not force employers into two-year pacts against their will.

Granting of severance pay by companies which cannot point to past policy may be interpreted as a "hidden" increase and hence a violation of the Wage Stabilization Act.

Now that Congress has provided a "mustering out" pay for soldiers, comparable payments for war workers are being pressed by some labor leaders, and it appears inevitable that some scheme will emerge—probably in the form of compelling industries to set aside "rehabilitation" funds for employees who are laid off. The Labor Relations Institute has warned its members to hold off on severance pay pending clarification in Washington, unless they already have established plans which were in force prior to the passage of the Wage and Salary Stabilization Act.

Such, then, is the basic nature of some of the plans of the labor leaders which will add seriously to management's problems after the war. Regardless of the shape and shade of these individual plans, one master plan is clearly emerging: those labor unions, leaders and individuals that did not hesitate to hold up the war effort in America's most critical moments certainly do not intend to tremble before the prospects of wrecking the economic structure of postwar industry.

MORE MARKETS AT LOWER PRICES?

POSTWAR marketing studies must give increased attention to volume and price relationships. This is particularly true at this time when many chemical industries are getting ready to market their products at prices very much below those which prevailed five years ago.

Questions of this sort require much more than the usual sales approach. The director of research and the production manager are almost equally involved. Every product must be studied to determine how much more could be sold for new uses if a new price schedule or a new quality of product could be adopted as standard. These problems must be studied just as thoroughly for old products as for new ones.

As the postwar opportunities of lower costs develop it will be important to identify as soon as possible those new markets which are opened to the industrial chemical producers at new price levels.

AN INSIDE STORY FROM LOS ANGELES

ONE READS funny things in the newspapers, especially in Los Angeles. Recently we came across a story in the Daily News about a potential byproduct of the fallenanimal industry which our good friend Dr. Robinson seemed to have overlooked in his excellent but slightly unappetizing article last August. The News refers to the experimental manufacture of paper from an amazing and hitherto unused source of cellulose. "This source of raw cellulose," it reports, "which is ideally adapted to paper making because some of it has already undergone two elementary steps in the process, (maceration and digestion), is grass and hay from the stomachs of slaughtered cattle."

The Los Angeles inventor, one W. D. Hoppie, has applied for a patent on the new paper-making process and is making arrangements to license its use. Already to his credit is the Hoppie process for making quinine from sagebrush, which according to the News, is now being exploited by a local manufacturer.

Hoppie, who had been taken in by the old saw about the packers using every bit of the pig, including the squeal, was amazed to find large piles of semi-digested hay recovered from the storage stomachs of cattle being slaughtered at a local abattoir. Here was some good raw material going to waste so he decided to put his inventive mind to work.

"When wood or cornstalks (?) are made into paper," according to Mr. Hoppie, "the first thing done is to moisten the stuff, then grind it up and soak it in hydrochloric acid (?) (The question marks are ours—Ed.). Exactly this same thing happens when a cow eats. First grass or hay is cropped and swallowed. Then it passes through a series of two or three stomachs of the animal where the food is moistened and bacterial action begins to convert the less resistant or non-fibrous cellulose into sugar."

Finally, after a further maceration and recycling (regurgitation) during the cud-chewing stage, the material passes to the fourth stomach for its digestion with HCl. (It is in this stage that Mr. Hoppie prefers to recover his cow-pulp and his investigations showed that as much as 85 tons per week were available from the local packers. He has been told that much larger amounts might be obtained at such midwestern packing centers as Kansas City and Chicago, but, as a loyal Californian, he believes that "western cattle whose food consists largely of grass, would prove a better source of paper-making fiber than the cornfed cattle of the Midlands."

Some there are who will hold that Brother Hoppie is as "balmy" as the climate of which California sometimes boasts. However, in these days of pulpwood shortages and the difficulty in obtaining stainless steel digesters, we can't be too sure he hasn't got something good especially if he can make up the cow paper into nice, crisp, prettily engraved stock certificates to be sold to gullible newspaper reporters and chief editors in California's City of the Angels.

IS UNDERGROUND STORAGE FEASIBLE?

CHEMICAL ENGINEERS must face a new problem of conservation which has political as well as technical angles of great importance. In fact, it appears that the political considerations of underground storage of fuel and mineral reserves may become dominant. Under these circumstances it is all the more important that the technical angles be first understood. Then our profession can exert its maximum influence in the right direction, even though we may not altogether eliminate decisions based on political expediency.

The basic question is likely to become very simple. Perhaps it could well be stated this way: Shall we exhaust our domestic resources of natural gas, petroleum, and strategic minerals to furnish employment in the United States; or shall we conserve them for the future and use more imported raw material?

For a few commodities there is a middle course. We can actually repressure natural gas wells and petroleum sands by pumping back into the ground either gas or liquid fuels. In some parts of the United States this is done with gas every year so that the long-distance pipelines may carry more nearly a capacity load in the seasons of light demand, and the user communities can take from the ground nearby supplies that could not be brought during peak-demand periods because of limited pipeline capacity. There is no doubt as to the technical feasibility. There seems little question as to the economic advantage for natural gas in a considerable expansion of this policy. But when one goes that far, he enters a new and uncharted field, especially in the case of petroleum.

It is now being proposed that we bring crude petroleum from abroad and pump it into the ground for storage. The advocates of that plan would have us simultaneously pump wells in areas that are still producing actively and produce much of our oil products from that domestic material. Obviously, they also anticipate that some of the crude run to stills will come from abroad. One does not need to have a keen imagination to see the multitude of labor and industry controversies that any such mixture of petroleum policies will present.

Still more controversial is the question of leaving our strategic minerals in the ground and using currently only foreign raw materials. Bauxite, manganese, lead and zinc, copper, and a half dozen other minerals and metals are going to be fought over in this area of debate and dispute.

There is no one answer to these questions. Nevertheless they must be faced, and the more technical facts that are presented for official consideration, the better will be the ultimate decision. Light rather than heat is needed now.

DEMOTING DE LUXE PACKAGES

EVERY sales manager wants to package his products most attractively. This is a commendable practice in peacetime for it promotes sales and pleases the customer even when the flossy packaging does not add any superior or intrinsic property to the goods.

Just now, however, we are faced with embarrassing shortages of practically all packaging materials—even in the case of barrels, drums and paper bags. To add unnecessarily to the cost of packing any product is unfair to other, perhaps, more essential users of packaging materials. In wartime, no commodity deserves a better package than it really requires. Each commodity should, therefore, be demoted to the lowest grade or type of package which will safely and properly deliver it to the customer.

When present shortages are over, we can again consider the promotional value of superior containers. Right now the chemical industry as a whole cannot afford such luxury as pretty packages.

LEO HENDRIK BAEKELAND, 1863-1944

THE American chemical industry has lost one of its most distinguished inventors and business men. Dr. Leo H. Baekeland has passed away. He had developed the first synthetic resin, pioneered the modern plastics industry and lived to see it blossom into a young giant with remarkable vitality and promise. He served as president of the American Institute of Chemical Engineers, the Electrochemical Society, and the American Chemical Society. His fellow chemists and engineers had awarded him for his contributions to the progress of American science and invention, the William Perkins, the Willard Gibbs, the Chandler, the William H. Nichols and the John Scott medals. Dr. Baekeland was loved and respected by all who were fortunate enough to know him. He will be sorely missed.

CHEM. & MET. PLANT NOTEBOOK-

THEODORE R. OLIVE, Associate Editor

War Bond Awarded Each Month

Until further notice the contest which was first announced in our November 1943 issue will be continued. For the best short article received each month and accepted for publication in the "Chem & Met. Plant Notebook," a \$25 Series E War Bond will be awarded, in addition to payment at our usual space rate for this department. The award for each month will be announced in the issue of the following month. The judges will be the editors of Chem. & Met. Any item submitted may be published in this department, but all items so published will be paid for at our usual space rate for such material.

The contest is open to all readers of Chem. & Met., other than employees of the McGraw-Hill Publishing Co., Inc.

Any number of entries, without limit, may be submitted by one person. Articles must be previously unpublished, and should be short, preferably less than 300 words, but should include one or more illustrations if possible. Finished drawings are not required and literary excellence will not be a factor

January Contest Prize Winner

NEW METHOD OF PHOTOELECTRIC LEVEL CONTROL PREVENTS OVERFLOW OF STORAGE TANKS

THEODORE A. BECK

Industrial Engineer, A. O. Smith Corp., Milwaukee, Wis.

MANY paper companies have had a considerable loss of paper coating solutions owing to the overflow of reservoir tanks located above the Fourdrinier machines. Like other solutions such a glue and starch, paper coatings tend to gum up ordinary level control equipment and make the equipment unreliable in operation. One particular company investigated several methods of control and still had to use the inefficient float system. After a lapse of many years of experimentation and failures, the idea discussed in this article was presented and developed successfully.

The new method conserves solutions effectively, preventing all waste from overflowing tanks caused by carelessness or by the inaccuracy of instruments, since it is impossible for the solution to pass the "full" level. The method requires little maintenance once the mechanism is adjusted. Filling becomes automatic once the pump is started, thus saving manpower, since no attendant is needed to watch the tank while it is being filled

watch the tank while it is being filled. Various conditions have been found which cripple equipment used to control the filling of tanks. The mixing plant for coating solutions is generally at a considerable distance from the reservoir tank located over the paper machine, making necessary remote control for pumping the solution and keeping the reservoir full. Conventional methods, such as floats, air pressure systems, and gage glasses, rapidly become inefficient and lose their accuracy after a little use in the fast-drying viscous solution. Floats acquire "stalactitic" layers of the solution which continually increase their number and weight, thus making the float ride at an inaccurate and increasingly lower level. Air pressure systems readily become clogged since the orifice becomes filmed with a hardened solution which causes its calibration to become misleading. Finally, glass gages, after one or two uses, become covered and opaque, thus making them worthless.

Thus, the common photoelectric method of tank gaging which sights the level in a gage glass is worthless and it might appear that a satisfactory use of a photoelectric cell could not be developed. However, by the application of the simple and well known physical principle of the angle of incidence being equal to the angle of reflection, a suitable method of

Reflective type photoelectric level control for gummy solutions



in the judging. Winning articles will be selected on the basis of appropriateness, novelty and the usefulness of the ideaa described.

Articles may deal with any sort of plant or production "kink" or shortcut which in the opinion of the judges will be interesting to chemical engineers in process industries, as well as with cost reducing ideas, and novel means of presenting useful data. Material to be entered in this contest should be addressed to Plant Notebook Editor, Chem. & Met., 330 West 42nd St., New York 18, N. Y.

FEBRUARY WINNER!

A \$25 Series E War Bond will be issued in the names of

> D. M. PEPPARD and D. S. DAVIS Wyandotte Chemicals Corp. Wyandotte, Mich.

For an article dealing with a substitute slide rule blank which has been adjudged the winner of our February contest.

This article will appear in our April issue. Watch for it!

applying photoelectric equipment was worked out. The method is illustrated in the accompanying drawing and is evidently applicable to most types of liquids, since most liquid surfaces will reflect sufficient light to operate the equipment.

The spotlight-type light source is mounted at an angle at one side of the tank, throwing the beam so as to strike the solution approximately at the center of the tank when the level is at the desired maximum. The photoelectric cell is then situated on the opposite side of the tank and pointed so as to receive reflected light from the spot on the solution illuminated by the lamp. This is best done experimentally.

How the control works when the solution is at various levels will be clear from the sketch. When the solution is at level a-a, b-b, or c-c, the light will be reflected from points m, n, and o, along the lines mA, nB, and oC. Only when the solution level is at d-d (i.e., a full tank) will the light reflect from point p along line p-D and thus strike the photoelectric cell, which by means of a relay system will turn off the pump as this level is reached.



Nomograph for percentage tolerances

NOMOGRAPH FOR ANALYZING PERCENTAGE TOLERANCES

W. E. PATTE

Engineer Brownsburg, Que., Canada.

MANY non-mathematically inclined engineers do not appreciate the importance that the size of a sample has in determining the significance of percentages derived from it. For example, if 0.5 percent scrap is considered satisfactory in a certain operation, and if one unit in a sample of 50 is scrap, does this 2 percent of scrap indicate that the sample is poorer than average? On the face of it, the answer might be yes, except for the fact that in a sample of 50, with any scrap at all, the least possible percentage would be 2 percent.

The proper approach, of course, is through mathematical statistics, employing the theory of small samples, which has yielded the formula $\sigma = \sqrt{Q(100-Q)/N}$ where σ is the standard deviation of the reference percentage; N is the size of the sample; and Q is the standard or reference percentage. The equation is conveniently solved by the accompanying nomograph. The significance of a percentage arrived at by means of a sample is determined by its relation to Q and σ . If the percentage is outside the value of $Q \pm 2\sigma$ the percenage is probably significant. If outside $Q \pm 3\sigma$ it is extremely significant.

Examples of Use

The use of the nomograph will be clear from a number of examples, including the aforementioned example dealing with scrap:

Example 1—It has been found that an operation may be run satisfactorily at 0.5 percent scrap. When 50 objects are examined, one is found to be scrap or 2 percent of the sample. Is this production poorer than standard? In this case N = 50 and Q = 0.5 percent. Therefore, σ from the nomograph, is found to be 1 percent. From the rule mentioned above, significant percentages will be those outside $0.5 \pm 3 \times 1$. However, the percent obtained is

not even of probable significance since it is less than 0.5 + 2 percent. The production sampled is not therefore significantly poorer than standard quality.

Example 2—A plant is operating at 8.0 percent absenteeism, based on the number of working hours. In a small department, 71 hours is lost in a total of 750 hours work, or a percentage of 9.5 percent. Another department loses 690 hours out of a total of 7,500, or a percentage of 9.2 percent. Which department has the poorer record?

The standard for the plant is 8 percent. In the first case, connecting N = 750 with Q = 8.0 yields $\sigma = 0.95$. Therefore, a percentage absenteeism outside $8.0 \pm 2 \times 0.95$ is probably significant, while a percent absenteeism outside $0.8 \pm 3 \times 0.95$ is extremely significant. The percentage for the small department, namely, 9.5, is within both limits.

For the larger department, connecting N = 7,500 and Q = 8.0 yields $\sigma = 0.31$. A percent absenteeism outside $8.0 \pm 3 \times 0.31$ for this department is extremely significant. This amounts to a range from 7.1 to 8.9 percent. Since the larger department has an absentee rate of 9.2 percent, the difference from the standard is more significant than that of the smaller department with a higher absentee rate.

Example 3—Suppose that the standard moisture content for a certain material is 10 percent and that the usual test sample is 5 gram, weighed to four decimal places before and after evaporation of the moisture. In this case, Q = 10.0 and N =50.000 (5 plus four significant figures). From the chart $\sigma = 0.14$ percent. From the rule, a sample percentage outside $10.0 \pm 2 \times 0.14$, or 9.7 to 10.3 percent, is probably significant, while sample percentages outside $10.0 \pm 3 \times 0.14$ are extremely significant.

If all tests of samples are made in duplicate, combined sample size then becomes 100,000 and the chart gives a value of σ of 0.10 percent. In this case the combined samp'e percentage will probably be significant if it is outside $10.0 \pm 2 \times 0.10$, or 9.8 to 10.2 percent, and it will be definifelv off standard quality if outside $10.0 \pm$ 3×0.10 , or 9.7 to 10.3 percent. If. however, the weighings before and

If, however, the weighings before and after driving off the moisture content are not made so accurately, say, to three decimal places, then the leeway must be greater. In this case, for a single test, N = 5,000 and Q = 10 percent, so that $\sigma = 0.42$ percent and sample percentages outside $10.0 \pm 3 \ge 0.42$, or 8.7 to 11.3 per-

Steam or water ejector prevents dust rising from a manhole



cent, will be extremely significant. Obviously this method will give an immediate benefit when applied to several different analyses in that the specification tolerances for all analyses will be mathematically identical. When sample percentages consistently fall outside $Q \pm 3 \sigma$, this is a definite indication of lack of precision in the method of analyzing, or lack of control of the variable, or both.

USING AN EJECTOR FOR DUST ELIMINATION

W. A. WELCH Philadelphia, Pa.

IN MANY chemical processes, it is necessary to add dry solids through a manhole into a tank or kettle for mixing with a hot liquid. For example, it may be necessary to add activated decolorizing carbon, diatomaceous earth, or certain dry chemicals which can create a dust nuisance owing to the natural up-draft of vapors rising from the liquid in the treating tank.

The accompanying diagram illustrates one method of overcoming this difficulty by installing a water- or steam-operated ejector at the side of the vessel near the level of the manhole. When the dusty material is to be introduced into the tank, the ejector is turned on, thus creating a substantial down-draft through the manhole and eliminating the dusting. In addition to overcoming the dust nuisance, this device results in some saving of material since it is possible to lower the bags or containers directly into the manhole where the entire contents can be conveniently shaken out.

HOW TO CHECK UP ON ENGINEERING REPORTS

D. S. DAVIS

Wyandotte Chemicals Corp. W: andotte, Mich.

FOLLOWING are suggestions for examining engineering reports which are drawn from discussion, oral and written, with (1) several well-known authors of chemical engineering texts and handbooks, (2) editors of technical journals, (3) practicing engineers, and (4) chemical engineering professors in some of the leading colleges and universities. They should be of assistance to those who are (1) preparing material for publication, (2) responsible for correct and well-written engineering reports, and (3) spending a great deal of time checking reports written by engineering students.

General—A report should be read once, at the usual reading rate, for sense and logic and twice, slowly and at intervals for typographical, computational and other errors. During the latter readings literally everything should be questioned and an attitude which accepts little on trust is generally helpful.

Text and Proof—The author is usually not his own best proofreader since he tends to read with his memory rather than with his eyes and frequently overlooks glaring and seemingly obvious errors. However it is necessary for him to examine final drafts and galley proof at least once in order to

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •

make the inevitable changes and to answer the manuscript editor's queries.

Team-work is worth while: in reading the galleys a typist or technical assistant should follow the manuscript while the author reads aloud from the proof. The second reading can often be done by a typist or assistant without the aid of the author. Girls usually excel in attention to detail and make better proofreaders than men. One reading, in tandem, suffices for page proof and the author should be onc of the participants since it is his last chance to make a few, preferably a very few, corrections.

Reading aloud, even when working alone, is helpful since it slows one to an efficient rate and reveals unfortunate repetitions, rhymes, distracting words and "verbal bums." Proof should be read in small amounts, never more than an hour at a time and in the morning when one feels fresh or after a brisk walk. When particularly crowded, 15 minutes spent outdoors or in a relaxed position on even a table top will work wonders!

Calculations-Each step of every computation should be examined carefully and checked with a colored dot if correct. Particular attention should be given to the location of the decimal and to algebraic signs. In addition to the slide rule some of the rapid means of checking numerical computation should be employed, such as testing addition by casting out nines and multiplication and division by noting the terminal digits in the factors and product. Mere inspection of a calculated quantity to determine whether or not it seems of reasonable magnitude will often detect embarrassing errors.

Drawings-Drawings and tracings should be examined up-side-down and from the wrong side as well as in the usual manner since altered conditions seem to sharpen the perceptions remarkably. When a plot is held so that the line of sight makes a very acute angle with the plane of the paper it is possible to test curves for smoothness, to spot even slight breaks and flat portions and to test nomographic and other scale graduation marks for length.

Curve of moisture content versus weight per cubic foot for pine chips



The line of vision should be perpendicular to the scale when checking for omissions of graduation marks and for uneven or Vertical legends, inequitable spacing. dimensions, and numbering should always be brought into a horizontal position for examination since superficial attention results when there is even a small amount of eve-strain.

Common Errors-The most frequent errors include split infinitives, disagreement in number between subject and verb, Spooncrisms, misspelling, inconsistent styling, colloquialisms, incorrect and incomplete references, and interchanged figure and equation numbers. Particular attention should be given chemical formulas and equations, mathematical material, abstracts and conclusions. Indexing should always be tested for coverage.

RAPID METHOD OF DETERMINING MOISTURE IN **WOOD CHIPS**

MALCOLM G. LYON

Champion Paper & Fibre Co. Canton, N. C.

MOISTURE CONTENT of wood chips greatly affects the amount of wood to be put into a pulp digester, and is a factor to be considered when computing liquor volumes and concentrations. To obtain uniform cooking, it is therefore necessary to know the moisture content of the chips in each digester.

Weighing a standard can or pail which is just level full with moist chips is the simplest and quickest method of obtaining the moisture percentage for a sample representative of the chips charged into a digester. Within the normal range of chipping, there is not sufficient variation in chip size to affect the accuracy of this testing method. Also, it is readily possible to fill the standard can in such a way that bulk density variations will not affect the results significantly. Wood chips cannot be packed to any appreciable extent and a few shakes and jars will settle them to a stable position.

A suitable method of filling the can is to fill it about one-third full and shake briefly by lifting and dropping the can 2 or 3 in. several times. The same procedure is then repeated with the can two-thirds full and again when full. The can is then leveled off at the top with any additional chips necessary and weighed.

Simple and inexpensive equipment can be used for this test. A 1-cu.ft. pail can be constructed easily, or the result can be calibrated for a pail of other dimensions. A common milk scale, which can be set to give a zero reading with the empty pail and can be hung anywhere, is suitable for the weighing. The total cost of the equipment is only about \$15 and results can be read well within 2 percent of the correct moisture percentage.

The accompanying chart shows a curve of moisture content versus weight which was prepared here for pine chips. A similar curve should, of course, be prepared for the type of chips being used. The chips can readily be sampled throughout the loading period of the digester, or they can be taken from the chip conveyor.



Simple high-low alarm for tanks

HIGH-LOW ALARM FOR ACID TANKS

J. F. FURRH Instrument Foreman Monsanto Chemical Co., Waskom, Tex.

The ACCOMPANYING DRAWING illustrates a simply constructed high-and-low-level alarm for acid tanks (or tanks containing other corrosive, conductive liquids) which does not require scarce materials.

The electrodes, of which there are three, are made of Pyrex glass tubing, with a carbon plug in the lower end to make contact, the plug being connected to a top connection with a single insulated wire. No. 2 electrode is common to both high and low circuits. No. 2 electrode is the low-level contact, and No. 3, the highlevel contact. The relays are selected so that relay No. 1 is open when energized, while No. 2 is closed when energized. Any suitable power source can be used. Low voltage can be used on the electrodes by selecting relays with low-voltage operating coils.

No. 1 electrode is connected to No. 1 relay, No. 2 electrode to the hot side of the power supply, and No. 3 electrode to No. 2 relay. When the liquid rises high enough to touch No. 3 electrode, No. 2 relay closes and sounds the alarm until the level has dropped below this electrode. When the level drops below No. 2 electrode, No. 1 relay closes and sounds the alarm until the liquid level has again risen high enough to touch this electrode. If desired, a pump may be connected to No. I relay so as to start pumping when the low level is reached, or to No. 2 relay to start pumping out of the tank when the high level is reached.

IT'S DOLLARS TO DONUTS

that you have an idea worth publishing in the Plant Notebook section. If you haven't read the prize contest offer on page 116, do it now! Your article will bring at least \$5 if accepted, and it may win a \$25 War Bond in addition.



REPORT ON.....

CHEMICAL ENGINEERS In War and Postwar Industry

Equally essential to America's production of a thousand and one vital materials of war is each of the chemical trio of equipment, skilled operators and engineers. Strategically located throughout our factories, these chemical engineers, largely under 30 years of age, have helped to mold industry in their own image. Some 22,000 of them are now accomplishing the greatest miracle in mass production of chemicals ever conceived and, at the same time, are catalyzing new technological developments at an unprecedented rate. Yet, now threatening the maintenance of this production and the acceleration of these developments is the tightening squeeze on industry to release to the combat army its technical men up to 26 years of age. Simultaneously, the supply of chemical engineering graduates has been effectively decimated, probably for years to come. What are the war contributions of these young engineers, what postwar problems must they solve? This report endeavors to indicate the answers.

MERICA's chemical industry may A have been born in World War I, but there is no doubt that it has fully come of age during World War II. To soldier and scientist alike, it has become evident that "civilized" war-fare is a mechanized destruction of physico-chemical forces, for always behind the machine and the machine shop is a chemical plant made possible by research chemists and maintained by chemical engincers. Backing our giant plane factories stand aluminum and magnesium lines, petroleum refineries that synthesize fighting fuels, oxygen units to save the lives of pilots, the alcohol and synthetic rubber industries, TNT, hexamine and other chemcials that make bombing missions effective.

Flame throwers, anti-malarials and sulfa drugs, dehydrated foods and



potable sea water, tank turrets, plastic parts and camouflage paints, cartridge shells and blood plasma, battleships and booby traps—all depend, in their final analysis, upon chemistry and the alchemy of metallurgy for their perfection. Modern wars are fought by men, materials and technology: an inferiority, even slight, in any one of these can drag out or lose the struggle for the less progressive combatant.

Equally as important as the plants are our engineers, chemists, trained

Industry's estimated overall demand and supply of chemical engineers: danger lies in the gap that would result from loss of considerable men under 26 years old

operators and other technical personnel. Without these our chemical, process and mechanical plants would soon disintegrate as completely as the famous one-hoss shay. Let us investigate just one group, the chemical engineers, and find out where they are located and what they are doing.

HOW MANY AND WHERE

Chemical engineering, a young profession hardly existent at all prior to 1920, has come into its own largely since about 1935. In fact, of the estimated present total supply of 25,000 chemical engineers (including those in the armed forces), more than half have entered the profession since 1935.1 Less than a year ago, the National Roster of Scientific and Specialized Personnel made a survey that covered over 14,000 professional chemical engineers and found the median age to be 26.8 years! This was by far the lowest median age of any of the groups in all the engineering, agricultural, medical, physical and social sciences.

It is probably true, though startling, that at least 10-12 percent of the nation's chemical engineers are under 22 years of age. Many of these, of course, are already in the armed forces. Yet, at least 1,500-1,800 of these young engineers are now in industry, representing probably 7-8 percent of all chemical engineers serving industry."

With such a preponderance of young men, it is only natural that some concern should be felt by industry as to the effect that the loss of these young engineers would have on the continuation of the war effort. This report endeavors to analyze the present situation and to forecast the effect that the present trend in Selective Service thinking may have on our chemical and process industries for the duration of the war and during the early postwar years.

Up until the present, both state and national Selective Service officials have been highly cognizant of the part that engineers play in the war effort and leniency toward deferring professional chemical engineers has been the rule rather than the exception. Industry is highly appreciative of this intelligent and liberal attitude. The reaction of the local boards, as should be expected, has been spotty, so that many firms have found it necessary to put up a strenuous and running fight to retain their key men. This has been especially true of the smaller concerns.

Actually, industry as a whole has lost very few experienced chemical engineers to the armed forces, probably not many in excess of 500. Many of these were reserve officers. A number of young engineers with a year or less of industrial experience have been lost, partly because some firms did not press deferment claims with sufficient vigor and partly because the young engineers preferred to enter the services.

By far the largest loss, however, has been among the "engineers-to-be," the young graduates who leave for the armed forces directly from the graduating exercises. Probably about 2,500 chemical engineers belong in this category, making total losses about 3,000 or some 12 percent of the

which reduces all engineering and science student deferments above the age of 18 to a total of 10,000 (exclusive of medical and theological), and amended Memorandum 115, which eliminates deferments for all registrants under 22 years old except in certain special cases.

THE SPRING DRIES UP

Engineering and scientific students that will graduate on or before July 1, 1944, of which there will be about 1,200 in chemical engineering, are still subject to



nation's estimated total supply. Thus, out of a total potentiality of about 25,000 chemical engineers, industry has at present a working supply of about 22,000.

The danger lies not so much in the number of engineers that have already been lost, although these are needed now more than ever, but in those that may soon be taken through "tightening up" processes by Selective Service at the very time that the supply of new graduates will be cut off almost completely. This double-barreled threat is reflected in two recent Selective Service directives, amended Bulletin 33-6 deferment in more or less the usual manner until graduation and for 30 days thereafter. This month's grace is to permit the graduate to become employed in war industry. Probably at least half of these chemical engineering graduates are already committed to the armed forces, so that industry will have about 600 new graduates which it must try to get and then fight to keep.

To realize the seriousness of the situation, this graduating class of 1,200 should be compared to those of about 2,500 for 1943, 2,700 for 1942 and 2,400 for 1941,

⁴ Due to the lack of exact and comprehensive data, the fournes in this report, unless otherwise that of otherwise the estimates by the edi-tors of Chem. d Met. They are intended to be indicative rather than absolute. ¹ Throughout this report, the term "in indus-try" includes all entineers actually not in the armed forces, since consultants, teachers, research without exception, contributing directly to indus-try's war effort.

of which probably 70 percent have been available to industry. Figure 2 shows the trend in size of graduating classes and the proportion of new graduates entering industry.

Amended Bulletin 33-6, effective March 15, 1944, states that "students occupationally deferred should be limited to a number sufficient to meet civilian needs in war production and in support of the war effort." The quota, which is exclusive of medical and theological students, was arbitrarily set at 10,000 to be graduated within 24 months after certification. The

be small. How many will be in chemical engineering courses is not known, but the figure must necessarily be very small, probably not more than 6 percent of normal enrollment. Anyone who believes that such a picayune quota can ever amount to much more than as a teaser to industry's inflated war needs must Be' a super-optimist indeed, nor can anyone produce a convincing argument why less technically trained men are needed during a technological war than during peace time. Evidently Selective Service is committed to the theory of a short war. It is now esti-



EXPLANATION OF CHARTS

Fig. 1 shows the accumulative proportion of the nation's approximated total supply of chemical engineers entering the armed forces directly upon graduation, the experienced men lost by industry and those under 26 that may soon be lost. Fig. 2 shows the same data on a yearly basis, giving the distribution of each graduating class. Postwar conditions are visualized to show the two-year return of engineers to industry

total was divided somewhat as follows:

All engineering. 6,750 2,250 850 150

Thus, a total of about 6,700 engineering students of all types and classes above 18 will be deferred as compared to a total engineering enrollment of over 111,000 for 1942-43 (see Table I). Presumably, 4-F students will not be counted against this quota, but since such students do not amount to more than about five percent of total enrollments, the increment will

mated that industry could very well use some 3,500-4,000 more chemical engineers alone, and last year the National Roster made a survey which indicated that essential manufacturing concerns would like to have had 12,000 engineers of all types just for the first six months of 1943.

This curtailment of deferable students together with the drastic reduction in the Army Specialized Training Program, 90 percent of which has centered around the training of engineers, from about 145,000 students to 30,000 advanced students by

Table I-Disappearance of Engineering Education-Our Source of Supply for Engineers Dries Up

Enrollment of Engineering Students at Colleges

005.0	All	AU	Chemical Engineering
100	Students	Seniors	Seniors
1939-40	105,900	17,700	3,200
1940-41	110,600	17,700	3,000
1941-42	110,500	18,100	3,200
1942-43	111,700	17,300	3,200
1943-44	43,100	8,000	1,700
Present			
Quota ¹	6,750		
1.0000 10 11		and the o	2 1 2

April 1, may force a number of the colleges

and universities to close simply because there won't be any students. Actually, the chemical engineering phase of ASTP was discontinued in 1943 since the armed forces had no further need for chemicallytrained personnel.

It is obvious, therefore, that unless the basic policies of Selective Service are changed by the vociferous demands of industry, after the present emaciated class there will be only a negligible number of new chemical engineering graduates until the end of the war, nor will anything approaching a normal class be graduated until a minimum of three years after the war! Industry must reconcile itself to the fact that it will not be able to obtain any new engineering graduates no matter how acute the needs, for "that's all there is and there'll be no more." It's about as final as that.

22 AND UNDER

The present situation in regards to deferment of men under 22 seems to be full of confusion, although such should not be the case. This state of affairs has been caused by Selective Service amended Memorandum 115, effective February 1, 1944, which eliminates the deferment of all men between the ages of 18 and 22 except in very special cases.

Memorandum 115 requires that requests for occupational deferment for all registrants under 22 be made on a special 42-A form which must be endorsed by the state director of Selective Service and then returned to the local board for action. Soon after this directive was issued a considerable number of state directors gave out the definite impression that no person, regardless of requests for occupational deferment, would be exempted. At least one director, it is rumored, jumped the gun on official thinking and implied that he did not intend to recommend occupational deferment for any person in industry under 26 years of age. Just why the state directors should be so unanimous and simultaneous in their change of attitude on the question is somewhat of a mystery.

Naturally, the rumor that no deferments would be permitted in this age group spread like wild-fire, and considerable damage was done before it was checked. It

Table II—Overall Balance Sheet for Chemical Engineers ¹

Total graduates since 1921	29,000
Probably active in profession	25,000
In armed forces	
Experienced	500
Inexperienced	2,500
In industry, total	22,000
Under 22 years old	1,500
Under 26 years old	5,000
Probable needs of industry	26,000
Present accumulated shortage	4,000

¹ Approximated as of early 1944.

was even believed for a time in some quarters that the special provision for occupational deferment was never intended to be so applied. This is entirely erroneous.

Some individuals and even a few government war agencies have jumped to the conclusion that it would be better not to request deferment of these young men, to make "sacrificial goats" or "bargaining points" of them, so to speak, and thereby have a better chance of holding their older men. Still others are beginning to think that the expense and executive man-hours necessary to keep a young engineer for possibly only a few months are not justifiable. Such attitudes are not only shortsighted, but they actually damage the chances of deferment for some of the older men. If a man under 22 is not essential, who can defend the man of 23, or 24, or 25? Certainly industry would have little voice in determining just where the line should be drawn. In fact, considerable thought has already been given to upping the general no-deferment class to include men under 26, and this attitude will probably dominate official Selective Service thinking very soon.

REPLACEABILITY MYTH

Some individuals seem to doubt the essential importance of the young engineer in our war chemical and process industries. The chemical industry is geared almost completely toward contributing to the war effort, and probably at least 90-95 percent of all chemical engineers, most especially the younger men, can be legitimately classified as 2A or 2B. There may be considerable executive thinking and planning on postwar problems, but there are very few engineers actually doing work on such developments. In addition, the practical limit has just about been reached in "diluting" or "exploding" technical jobs. Make no mistake about it, the young chemical engineer is vital to our war effort, triply so because (1) the source of supply of engineers has now been cut off, (2) industry demands for these men are still increasing for expanding research and development programs and for enlarging and maintaining production facilities, (3) losses by industry are continuing and may soon be sharply accelerated.

The stage has now been reached that arguments about the "replaceability" of

any chemical engineer doing essential work in an essential industry have lost all meaning. Taking the field as a whole, the replacement of one engineer by another is now merely a matter of robbing Peter to pay Paul. Production operations and technological developments are bound to suffer from such practices.

One executive of a large chemical concern which has already made outstanding contributions to our war effort put the situation somewhat as follows: ". . . we shall need additional technical men to maintain effective operations, but we have concluded that we are not going to get them and hence have keyed our thinking toward making every effort to do the best with what we have. We think the company's technical efforts are going to suffer, but such are the facts. We feel that it is a major mistake in judgment to curtail creative technical effort for the sake of a negligible number of additional service raw material in terms of the total armed services. This thinking is also predicated on the assumption that some personnel now in our war plants can be transferred to regular operations in the near future. If this does not materialize, we shall be in much worse shape." This concern, which has been recruiting technical personnel at the rate of more than 100 for each of the past four years, feels that its yearly requirements will continue to be in the neighborhood of five percent of its technical staff.

FIGHTING IDEAS

It is easy for men familiar with the situation to give generalities as to the warimportance of chemical engineers under 22 and under 26 now in our plants and development laboratories, but nothing short of specific examples and lots of them can impress Selective Service. Here are a few actual cases, gathered at random, of some of the fighting ideas and contributions of our young engineers under 26.

1. One chemical engineer was assigned at the age of 23 to set up production capacity for sulfa drugs in the pilot plant of a large concern. This man helped to rearrange pilot plant equipment and organize a production program to a point where the firm could supply the major portion of WPB requirements of these drugs without the erection of a new plant, which would have been time-consuming and costly in critical materials and labor. At least a million pounds of sulfa drugs, potentially equivalent to hundreds of thousands of soldiers' lives, have been turned out by this unit. This was an unusual assignment for such a young man, but no plant facilities and no production men were available for the job, a direct request

by WPB. 2. A chemist under 26 years old has developed a catalyst which has given a much improved yield in the preparation of a new highly important and highly confidential plastic material for the armed forces.

3. One company which figures heavily in the program for producing dichlorodiphenyl-trichloro-ethane, the remarkable new insecticide developed for our troops and known as DDT, reports that its work on this material has been done largely by technical men under 26, and that close to 65 percent of all its pilot plant work on war developments has been done by men of the same age group.

4. Another concern has three men under 22 who occupy key positions in the production of anhydrous hydrofluoric acid, highly important in the aviation gasoline program. The average age of plant supervisors in this concern has declined from 27 to 23 years during the war period. This company needs 40 more chemical men for 100 percent war projects.

5. A Ph.D. chemical engineer was assigned immediately upon graduation in 1943 to a Chemical Warfare plant, where he has conducted process research on improving output, quality and yields from critical raw material and manpower requirements. This work has been successful in all of the above aspects and this particular engineer is responsible for a substantial portion of the success. Ordinarily, this man would not have been placed in such a responsible position without extensive pre-training, but no other person was available.

6. Although no overall figures are now available, the nation's penicillin program is largely dependent upon chemists, chemical engineers and other technical men under 26 years of age. A number are under 22. One of the largest producers of penicillin, for instance, is in imminent danger of losing a chemical engineer under 22, while another has three of its ten chemists under 22 on production of this drug.

7. One chemical engineer under 26 has contributed substantial creative developments in the preparation of a formula now being used for protecting clothing, army raincoats, ponchos and similar articles from chemical warfare gases.

8. Another, assigned to laboratory research for the National Defense Research Council within a few months after his graduation, did excellent work on the development of a process for making a new chemical badly needed in the war effort. After completion of the work, this man was transferred to the laboratory portion of a pilot plant investigation, assigned to the firm by the Chemical Warfare Service, where he is now doing an excellent job.

9. One leading firm has two chemists under 22 doing important work on antimalarial material being shipped to our troops in the tropics. A similar situation undoubtedly reaches back into all the corners of the industry, for at least 38 different chemicals are vital for the production of this one life-saving drug.

10. A large unit producing butadiene

for the synthetic rubber program has two of its twelve chemical engineers under 22 years of age and three additional ones under 28.

11. One of the country's largest producers of war plastics has approximately 40 percent of its technical personnel working on these materials under the age of 26.

12. Probably 10 percent of the chemical personnel in the synthetic rubber program is less than 22 years old, possibly 50 percent less than 26. The research and development phases of this program, employing a total of approximately 500 chemists, chemical engineers and physicists, will be greatly curtailed and possibly eliminated to a large extent if all personnel under 26 were lost to the armed forces (unless some government authority would assume the task of replacing them by robbing other industries). There are approximately 1,500 chemists and chemical engineers now located in all governmentowned and private synthetic rubber plants, of which probably 950 are chemical engineers, according to the U.S. Bureau of Labor Statistics. These figures exclude personnel in research development outside the plants.

13. In all petroleum establishments, it is estimated that nearly six percent of all personnel vulnerable to Selective Service is under 23. Approximately 30 percent of the technical personnel in refining research now vulnerable to Selective Service call is 25 years of age or less and about 70 percent is less than 29. These figures are based on schedules filed for research laboratories of petroleum companies and do not include those for research carried on in the laboratorics of petroleum refineries. The petroleum industry has a total of about 12,000 technical men, a large proportion of which is chemical and process engineers. The Bureau of Labor Statistics has estimated the following age classification breakdown for technical men in all petroleum establishments:

	Total Technical Personnel, Percent	Total Personnel Vulnerable to Selective Service, Percent
Less than 23	3	6
Less than 24	6	11
Less than 26	8	

14. One large chemical concern very heavily engaged in direct war work has a total technical personnel of 900, of which probably at least 400 are chemical engineers, including a research department of 325 technical graduates. The age breakdown of the group is as follows:

	Total Technical Personnel, Percent	Research Departments, Percer t
18 through 21	2	3
21 through 25	25	30
26 through 30	24	25
31 through 37	22	1.0
Over 37	27	1 42

16. Of the 14,115 chemical engineers

surveyed by the National Roster as of July 1, 1943, the median age was 26.8 years. The age breakdown of the entire group was as follows:

		Percent of Tota I
29 a	nd under	. 64
30 t	o 39	. 19
40 t	o 49	. 11
50 t	0 59	. 4
60 a	nd over	. 2

If anyone seriously doubts the importance of the young chemical engineer in our present industrial war set-up, let him first talk to responsible persons in the synthetic rubber and aviation gasoline programs, the plastics and synthetic organic chemical fields before expressing his opinion publicly.

TWO REGIMENTS

Assume that the armed forces need these chemical engineers, not for technical reasons, which they do not, but for sheer manpower. What would they get? The estimated 1,500 chemical engineers under 22 still in industry (2,500 are already in service) would amount to some 0.013 percent of the total estimated armed forces as of July 1, 1944. If every chemical engineer under 26 still in industry were taken, the equivalent of about two regiments would be added to our men in uniform. Are two regiments of chemical engineers more important in the combat army, most likely as ordinary soldiers, or in industry serving the war effort as engineers?

There is another statistical way of looking at the situation. There are about 3.5 times as many persons employed in nonagricultural activities as in agriculture itself. Of the total number of registrants deferred in agriculture, about 400,000 are single men under 22 years of age. Yet, in all war-producing and war-supporting activities, about 115,000 non-fathers below the age of 22 were deferred as of the first of this year. Of these, it is estimated that probably not more than 15,000 represent engineers of all types and about 1,500 represent chemical engineers alone. One of the reasons for this discrepancy, of course, lies in the fact that agriculture has been protected by law, whereas industry has found it necessary to shuffle for itself.

MENTAL OR MORAL

The basic argument, of course, behind this trend toward the squeezing from industry of badly needed non-father engineers under 22, and soon under 26, is that of the moral pressure put on Selective Service by those people who do not like to see fathers drafted before non-fathers, older men before youths, even though these youngsters may be contributing much more toward victory than many of those more mature in years. Yet, mentally, it is our duty always to remember that this war, of all wars in history, is a struggle of technologies rather than of moral pressures.

It is significant to note that of our allies, England and Canada and probably Russia and China, clearly recognize this fact. In all of these countries, and also in Germany at least until fairly recently, the pressure has been on keeping technically trained men in the ranks of the production army rather than absorbing them into the combat army, as may soon occur in this coun-

Probably half of the 1,500 chemical personnel now helping to turn out the nation's yearly needs of 850,000 tons of synthetic rubbers are under 26. Can we lose these men to the armed forces and have our rubber too?





In war as in peace, chemical engineers are vital to development work. This group is working in a pilot plant at the Northern Regional Laboratory

try, the most technologically advanced of all nations. All this tends to make one wonder if we in America are as bright as the rest of our allies, or even our enemies. Other factors, of course, enter into the situation, so that direct comparisons do not necessarily give an impartial picture.

Several definite conclusions can be drawn of the situation as it now exists: (1) the chemical and process industries are short of chemical engineers to maintain and increase production of essential materials and at the same time to keep war research and development at a high level; (2) industry cannot count on obtaining any additional chemical engineers for the duration of the conflict; (3) it will become increasingly difficult for industry to retain its non-father technical men under 26.

What can be done? There are several answers: (1) industry must plan on ways and means to maintain production and development activities at the highest possible level without any new technical personnel;

(2) all chemical and other technical personnel sould see to it that they are located in the most essential industries and performing the most essential duties for which their training and experience entitle them; (3) industry must locate its engineers in those activities in which they are most neded for the war effort and then make a vigorous and determined effort to retain them in these activities, regardless of their age classification; (4) if certain plants or departments have any engincers, including those under 22 years old, who are not vitally needed or for whom claims for deferment will not be vigorously pressed, these men should immediately be released to those industries which are badly in need of them and which will fight to get and to keep them.

POSTWAR POSTULATES

Before predicting what will happen in the chemical engineering field in the post-

 Taable III—Estimated Requirements of Engineers and Chemists for Synthetic Rubber Industry by Branch of Industry and Occupation 1

to the second second	Number of Employees				
and service at the	11 M	C. Maile		1.48	Neoprene and
Occupation	All Plants	Butadiene	Styrene	Copolymer	Butyl
Chief engineer	27	19	8	S Love Way =	
Engineer 1	466	298	62	20	70
Technical director	21	21	. 6	15	10
Total, engineers.	514	303	05	10	20
	444	010	00	20	10
Chief chemist	20	10	0		
Chemist	136	20	60		24
Laboratory (oreman (chemist)	107	17	04		.34
Total, chemista.	279	90	110	29	. 9
		60	112	29	-15
General foremen	169	64	40	1. 3	the second
Shift foremen.	570	00	10	41	17
Total, foremen 4	747	167	303	69	58
	1.21	105	288	110	75
Total chemical engineers (est.)	0.13	270	0.0		13.5
	010	012	343	101	127
A ofai, all chemical personnel	1.533	579	FOC		-2- IP
	~1000	014	290	167	198

part of 1943. Includes general management personnel who are clearly chemical engineers. Of the total engineers listed

Includes in departmental and the not chemical engineers. Of the total engineers listed

known to be chemical engineers; probably 460 of the remaining 600 are chemical engineers. 34) were

war period, a hazardous thing to do under any circumstances, it will first be necessary to assume that certain trends will materialize, certain conditions be assured. The first of such assumptions, naturally, is the point that Mr. Baruch emphasized in his recent report: a depression is not a necessary corollary of the war. Certain readjustment pangs will be felt, but if the economic halter, is used promptly and properly, there are no reasons to believe that a gradual and controlled reconversion cannot very well buffer the shock of sudden peace.

The initial postwar period, those first five years after the complete collapse of our enemies, will present serious problems to the chemical and process industries and hence to chemical engineers. Broadly, speaking, there will probably develop two postwar worlds for chemical engineersone for the young engineer and a different one, in general, for the older, more established men. The older man will, as a generality, be fairly well stabilized in the niche he has carved out for himself in the profession. In many cases, his will be merely an accelerated version of the prewar world. It will be the young chemical engineer who may lose his job, be forced suddenly to change his location, have his income drastically reduced, and bear the brunt of union pressures.

OUT ON A LIMB

At the end of the war, industry will find itself in a highly unsaturated condition insofar as chemical engineers are concerned because of losses to the combat army and practical elimination of the source of supply at the time that demands for war-expanded activities have been increasing. It is estimated roughly that this deficit will amount to the neighborhood of 4,000 chemical engineers. Such a war deficit, however, may have little meaning in the postwar because of the radical changes that will without doubt occur in the industrial set-up.

Confirmation of the war's end to a number of young chemical engineers will be the sudden and practically complete curtailment of all-war plants such as TNT, smokeless powder, CWS and other munitions. Fortunately there will not be so many chemical men involved, probably not in excess of 1,000. The welltrained and key men who had been transferred from other jobs by the operating companies will almost certainly be returned to their former positions. Actually, it is likely that all but possibly a few hundred of these munition engineers will be absorbed in other plants almost immediately.

Very soon after peace becomes final, a number of other industries such as those producing ammonia, alcohol, aviation fuels, chlorine, magnesium and similar products for which production facilities have been highly inflated, may make extensive revisions in their production schedules, at least until the market situation for these commodities becomes clarified. Petroleum refining, for instance, will probably revert to a large extent to the production of improved pre-war automobile fuels. It is unlikely that this industry, now the largest or second largest employer of chemical engineers, will release any substantial numbers of its technical personnel. Unfortunately, this situation may not hold true for those plants producing such chemicals as nitric acid and chlorine for which vast new markets must be developed to absorb the surplus.

Reduced operations all along the chemical front during the initial readjustment phase will necessarily cause a reshuffling of considerable technical operating personnel. It can be expected that intercommodity competition will increase sharply among most chemicals, and efforts to develop new markets and outlets will be intensified. Such a trend will eventually absorb a considerable number of engineers back into development work, largely curtailed during the war in favor of increased production and war research. Short-term prospects thus indicate a considerable reshifting of chemical personnel after the war, but there is little likelihood that the chemical engineers in industry at the end of the war will be without jobs for more than a brief period of time.

THE ARMY RETURNS

What about the 3,000 or more chemical engineers that will be in the armed forces? Presumably, these men will be demobilized over a period of a year or two so that at least industry will not be deluged as was the case in World War I. Probably about 500 are experienced engineers that went in as reserve officers. Even though many of these chemical officers may not return for some time after the peace, most of them will find their former jobs in industry waiting for them. They will have little difficulty in making up for lost time by advancing in their organizations.

More serious problems will be posed by the return of the inexperienced engineers, the men who went in to the service directly from the universities. War experiences will help to develop these as leaders of men, but unfortunately not as chemical engineers. The men in this class that return soon after the peace may find competition for jobs from the returning experienced engineers as well as from those young engineers who remained in industry and who, about that time, will be in the process of being absorbed from direct war work into regular operations. The men who return latest may encounter increasing competition from large and fresh batches of postwar graduates. Of course the fact that the returnees are ex-service men will tend to neutralize these disadvantages to a considerable degree.

Most representatives of industry emphasize the fact that they are perfectly willing to absorb these inexperienced ex-service engineers by placing them in plant operations for a "refresher" period, after which they can advance in the usual manner. This retraining-in-industry phase will ary according to the individual's abilities and "remembrance of things past" learned.

The ideal place, of course, for the higher caliber men would be back in the graduate departments of our engineering schools, for there will be a stimulating demand for postgraduate engineers, a casualty of the war on education. Something more concrete than logical persuasion, however, will be necessary to persuade many of these men to resume their studies. The answer probably lies in providing graduate fellowships and grants from industry and government.

Thus, while industry's immediate postwar capacity to absorb all engineers dumped from war plants and the services may cause some initial difficulty, there is little question that the long-term outlook is bright. The prospects from this viewpoint are very well discussed in a special report to engineers in the services which appeared in this February's issue of Chem. & Met. Table V outlines the potential opportunities in some of the process industries, both old and new, such as food processing, plastics, air conditioning, synthetic textiles and instrumentation, all of which are rapidly becoming more conscious of the potentialities of applied chemical engineering.

Within the first postwar decade there will be golden opportunities for engineers to be absorbed simply by means of a more thorough penetration both vertically and horizontally in the chemical and especially the process industries. Diversification of activities from the more strictly engineering occupations such as equipment

design, plant operations and development work, into technical sales and service, management, labor relations, safety engineering, packaging and shipping, market development and chemical economics can easily sponge up all available engineers for years to come. Actual materialization of these opportunities will depend to a large extent, naturally, upon the ability of engineers to sell themselves into such services.

Out of this war of technologies there will emerge a new vast horde of semi-skilled men and women, an army of technicians such as the country has never before seen. Industry's acute needs, accentuated by a shortage of professional personnel, is creating large numbers of over-accelerated and therefore undertrained engineers, "quickie" course graduates, women technicians who responded to the call of industry, sub-standard graduates who ordinarily would have been squeezed out of the profession by a healthy competition, up-graded industry trainces, army "special course" students, personnel graduated into technicians by special union edict, and other "90-day wonders." Industry has used these technicians to great advantage, and their numerous contributions have made possible our coming victory. Nevertheless, after the war's end what will happen to these "in-betweens," these creations of a technological struggle that deserve more consideration than skilled workers and yet cannot quite make the grade into a profession?

TECHNICIANS GALORE

To elevate all these technicians to the professional level would tend to dilute the profession to the extent that it would soon become a mockery to technical and professional men alike. To push them back into low-prestige jobs would not only be a grave injustice to the technicians themselves but would provide unquenchable fuel to the fires of unionism.

One possible answer: we have created a class of technicians, now we must retain it as a class and endow it with a dignity and prestige all its own. Industry, from war necessity, has learned that it can profitably use large numbers of such persons, reserving its professional personnel for work requiring more initiative and creativeness.

The public, as never before, has become conscious of the value of a technical education. One canvass of nearly 400 trainees in a military training program found that

Union leaders will work overtime to capitalize on this drop in green engineers' postwar incomes



Table IV—How Chemical Engineers Can Be Absorbed in the Postwar Industrial Set-Up

	Present	Postwar
	Rel-	Absorp-
	ative	tive
	Absorp-	Capa-
Activity	tion1	city1
Slightly Saturated		
Industrial management.	S	м
Technical service	S	L
Fouinment sales	M	L
Product sales	S	L
Public relations	S	S
Labor relations	S	S
Market development	S	M
Safety engineering	S	M
Packaging development	S	M
Foreign rehabilitation	S	M
South American development	S	M
Advertising	ŝ	S
Process improvement	M	T.
Postaraduota studu	S	M
Toolgradiate study	6	S
Trance and supping	G	M
Moderately Seturated	0	-14
Production supervision	T.	T.
Plant maintanance	M	Ň
Plant maintenance	M	e
Plat plant engetion	T	T.
Phot plant operation	C C	E C
rersonnel problems	0	M
Industrial fenowamps	D N	M
Consulting	MI O	
Literature & patent searching.	0	5
Chemical economics	8	D
Largely Saturated	-	
Equipment design	L	M
Laboratory research	5	5
Federal government	M	S
College teaching	M	S
Pinance	S	S
Armed forces (CWS)	M	S
Patent developments	S	S
Municipal & State govern-		
ments	S	S
Jobbers & representatives	S	S
Independent manufacturing.	S	S

⁴ These columns are intended to indicate very roughly the estimated present absorption of engineers according to activity classifications and the visualized capacity of these activities to absorb additional chemical engineers in the postwar period after the initial readjustment phase. The letters indicate relative numbers of engineers, as follows: S = small, M = medium, L = large.

nearly half planned to go to college after the war and that more than 80 percent of these wanted to study engineering. This is just one instance of how the spectacular achievements of engineering and science in the war have captured the imagination of young men. Yet, it is very likely that most of these students are uninformed as to the exact distinction between vocational and professional training. Many of them will visualize themselves doing the work of a technician when they enroll without realizing the difference between the work of the technician and that of the engineer.

The inevitable result of trying to attain a profession for which they are not suited will be disappointment, failure and the stigma attached to having missed one's goal. Yet, even in the past, only about 40 percent of our freshmen engineering students have succeeded in securing their degrees at the end of four years. Possibly a solution could be worked out by stressing the fact, found by a study made by the Society for the Promotion of Engineering Education, that industry needs about three technicians for every college graduate and that the carning power of these men, as shown by the study of a group of 1,000 two-year technical graduates, is

within five percent of a large group of four-year college graduates. If industry and our schools should refuse to define and give the proper recognition to these technicians as a class, it is certain that the unions would do so, with full and vengeful success.

If such should happen, then our professional men, especially the inexperienced and young engineers, may suddenly find themselves sucked in and absorbed by this large group of technicians, either through sheer moral pressure or by Goebbelsian glibness on the part of certain outside labor unions. The engineer will then lose all his identity as a professional man. All his freedom of action and decision, his responsibilities for which he has groomed and conditioned himself and worked so hard to attain, will vanish completely.

Make no mistake about it, the unions will have powerful arguments to present to the young engineers, especially to those men who, for one reason or another, do not or cannot advance fairly rapidly. The monthly earnings of the engineering graduate just entering industry will drop from the present bloated average of about \$200 to \$210 a month for the first year to about \$150 a month. Some unionized technicians are now receiving a starting salary of \$145-200 a month. The unionized man is fairly well assured that his salary will not drop too drastically, so that it may not be uncommon for the sub-professional worker to be at a higher income level than many young engineers. Such realities may tend to blunt the edge of arguments about long-range career and professionalism insofar as the young individual engineer is concerned.

BY THE HORNS

That the threat of outside unionization to the professional worker has now been fully recognized is proved by the recent action of the American Society of Civil Engineers. This organization has appropriated \$50,000 to engage four full-time regional field representatives to sponsor local collective bargaining agencies of professional engineers, under A.S.C.E. auspices, in areas where the Society has local sections. Officers of this organization have become convinced that many qualified engineers have already been faced with the unpleasant choice of joining an existing union or of losing opportunities for desirable jobs. The only alternative for many professional engineers, so argue A.S.C.E. officials, is to organize with their professional fellows and to choose members from

Reprints of this report are available at 25 cents per copy. Address the Editorial Department, *Chem & Met.*, 330 West 42nd St., New York 18, N. Y.

Table V—Where Chemical Engineers Can Be Absorbed in the Postwar Industrial Set-Up

Rel- ative ative Absorp- tion ¹ Absorb- ative ing Absorp- Capa- tion ¹ Capa- city ¹ Petroleum refining L M Food processing L M Food processing L M Synthetic rubber processing M L Air conditioning S M Synthetic textile fibers M L Light metals M M Synthetic organic chemicals. S M Synthetic organic chemicals. S M Glass and ceramics M M Chemurgy S S Smokelees fuels S S Protective coatings M M
ative Absorp- tion ¹ ing Capa- city ¹ Petroleum refining L M Food processing S M Synthetic rubber processing M M Plastics M L Air conditioning S M Aviation S M Synthetic textile fibers M L Light metals M M Synthetic oparmaceuticals S M Synthetic organic chemicals S M Synthetic organic chemicals S M Idquid fuels from coal S M Glass and ceramics M M Chemurgy S S Industrial waste utilization S S Smokeless fuels S S Protective coatings M M
Absorp- tion1 Capa- city1 Petroleum refining. L M Food processing. S M Synthetic rubber processing. L M Plastics. M L Air conditioning. S M Aviation S M Synthetic textile fibers. M L Light metals. M M Synthetic organic chemicals. S M Synthetic organic chemicals. S M Synthetic organic s M M Synthetic organic s M M Synthetic organic s S M Industrial chemicals. S M Class and ceramics. M M Chemurgy. S S Smokeless fuels. S S Protective coatings. M M Solvents. M M
Industry tion ¹ city ¹ Petroleum refining L M Food processing S M Synthetic rubber processing L M Plastics M L Air conditioning S M Aviation S M Light metals M L Light metals M M Synthetic textile fibers M L Light metals M M Synthetic organic chemicals, M M Synthetic organic chemicals, M M Glass and ceramics M M Chemurgy S M Solvents S S Protective coatings M M
Petroleum refining. L M Food processing. S M Synthetic rubber processing. L M Phastics. M L Air conditioning. S M Aviation. S M Synthetic textile fibers. M L Light metals. M M Synthetic pharmaceuticals. S M Liquid fuels from coal. S M Liquid fuels from coal. S M Synthetic organic chemicals, misc. L L Agricultural chemicals. S M Chemurgy. S M Industrial waste utilization. S S Protective coatings. M M Solvents. M M
Petroleum renning L M Food processing S M Synthetic rubber processing L M Plastics M L Aviation S M Avintion S M Synthetic textile fibers M L Light metals M M Synthetic opharmaceuticals S M Synthetic organic chemicals, M M Synthetic organic chemicals, S M Glass and ceramics M M Chemurgy S M Industrial waste utilization S S Smokeless fuels S S Protective coatings M M Solvents M M Packaging S S
Food processing
Synthetic rubber processing L M Plastics M L Air conditioning S M Aviation S M Synthetic textile fibers M L Uight metals M M Synthetic oparmaceuticals S M Liquid fuels from coal S M Synthetic organic chemicals L L Agricultural chemicals L L Glass and ceramics M M Chemurgy S S Smokeless fuels S S Protective coatings
Plastics M L Air conditioning S M Aviation S M Synthetic textile fibers M L Light metals M M Synthetic pharmaceuticals S M Liquid fuels from coal S M Synthetic organic chemicals, M M Misc L L Agricultural chemicals S M Glass and ceramics M M Chemurgy S M Industrial waste utilization S S Smokeless fuels S S Protective coatings M M Solvents M M
Air conditioning
Aviation S M Synthetic textile fibers M L Uight metals M M Synthetic pharmaceuticals S M Liquid fuels from coal S M Synthetic organic chemicals, M M misc L L Agricultural chemicals S M Glass and ceramics M M Chemurgy S S Smokeless fuels S S Protective coatings M M Solvents S S
Synthetic textile fibers
Light metals. M M Synthetic pharmaceuticals. S M Liquid fuels from coal. S M Synthetic organic chemicals, M M Synthetic organic chemicals, L L Agricultural chemicals. S M Glass and ceramics. M M Chemurgy. S S Industrial waste utilization. S S Smokeless fuels. S S Protective coatings. M M Solvents. M M Packaging S S
Synthetic pharmaceuticalsS M Liquid fuels from coalS M Synthetic organic chemicals, I miscL L Agricultural chemicalsS M Glass and ceramicsS M ChemurgyS M Smokeless fuelsS S Protective coatingsM M SolventsS S Packaging S
Liquid fuels from coal. S M Synthetic organic chemicals, misc. L misc. L L Agricultural chemicals. S M Glass and ceramics. M M Chemurgy. S M Industrial waste utilization. S S Smokeless fuels. S S Protective coatings. M M Solvents. M M Packaging S S
Synthetic organic chemicals, misc. L L Agricultural chemicals. S M Glass and ceramics. M M Chemurgy. S M Industrial waste utilization. S S Smokeless fuels. S S Protective coatings. M M Solvents. M M Packaging S S
misc. L L Agricultural chemicals. S M Glass and ceramics. M M Chemurgy. S M Industrial waste utilization. S S Smokeless fuels. S S Protective coatings. M M Solvents. M M Packaging S S
Agricultural chemicals. S M Glass and ceramics. M M Chemurgy. S M Industrial waste utilization. S S Smokeless fuels. S S Protective coatings. M M Solvents. M M Packaging S S
Glass and ceramics M M Chemurgy S M Industrial waste utilization S S Smokeless fuels S S Protective coatings M M Solvents M M Packaging S S
Chemurgy S M Industrial waste utilization S S Smokeless fuels S S Protective coatings M M Solvents M M Packaging S S
Industrial waste utilization S S Smokeless fuels S S Protective contings M M Solvents M M Packaging S S
Smokeless fuels
Protective coatings M M Solvents M M Packaging S S
Solvents
Packaging S S
A MUMICIPATION FIT
Pulp & paper M M
Heavy inorganic chemicals L L
Leather & leather substitutes S M
Control instruments S M
Lime & cement S S
Pigments & dyes M M
Industrial explosives
Perfumes & cosmetics S S
Equipment design & manufacture L M
Soans & detergents M M
Fats & oils S M

¹ These columns are intended to indicate very roughly the estimated present absorption of engineers according to industry classifications and the visualized capacity of these industries to absorb additional chemical engineers in the postwar period after the initial readjustment phase. The letters indicate relative numbers of engineers, as follows: S = small, M = medium, L = large.

the group thus formed to bargain in their behalf. The Society takes the view that the situation has already become too critical to await national or state legislative correctives. The outcome of this bold and unorthodox move will certainly be watched with interest by all professional men throughout the country.

Just recently the American Institute of Electrical Engineers authorized the appointment of a committee to study broadly the whole subject of employment of electrical engineers, including security and employment, compensation and collective bargaining. Similar investigations are being made by a number of other groups. Obviously, if results of these studies show that engineers should organize as a body, then they should certainly provide the strongest kind of an organization possible.

A little prophecy is a dangerous thing, but the editor of this report still dares to predict that the chief postwar difficulties of the chemical engineer, especially the young man, will lie more in threats to his professional standing from outside union and social forces than in any problem of getting located in his preferred work in industry. Until a general solution is found, the engineer's only answer to such outside threats will be to hold even more steadfastly to all the ideals and ethics of his profession, the code of the man who serves unselfishly.

PROCESS EQUIPMENT NEWS-

THEODORE R. OLIVE, Associate Editor

PIPE LINING MATERIAL

INTERNAL insulation permitting the use of carbon steel pipe of ordinary weight and construction for the handling of high temperature fluids such as petroleum gases, superheated steam and mixed vapors at temperatures as high as 1,000 to 1,500 deg. F., has been developed by Baldwin-Hill Co., Trenton, N. J. Known as Insidline, the new construction consists of a layer of high temperature insulating material placed against the inner surface of the pressure piping, retained and protected by metal liners so arranged as to provide adequate expansion clearances, with the minimum of heat flow through the metal. The inner liner is not required to resist pressure and therefore is not made pressure tight. The insulating material is a felted block with a diatomaccous earth base reinforced with amosite asbestos fibers. The composition and thickness of the inner liner can be varied to meet conditions of temperature, corrosion, erosion and velocity encountered in various installations.

The primary objective of this new construction is to hold the temperature of the pressure piping to 650 dcg. F. or below and so prevent creep under usual stress allowances. An incidental advantage is heat sav-

Applying lining to inside-lined steel pipe



Flexflo remote-control valve



ing, together with simplification of the design of the piping through reduction in the number of expansion joints and other provisions for pipe expansion.

Insidline applications have been made for flue gases, steam, petroleum gases, hydrogen and fluid catalysts, for pressures up to 300 lb., at temperatures to 1,500 deg. F. in various combinations. Such linings have been placed in pipes ranging in size from 2 in. up to 100 in. diameter and single lengths up to 60 ft.

REMOTE-CONTROL VALVE

New IN PRINCIPLE, the Flexflo remotecontrol valve shown in an accompanying illustration has been developed and introduced by the Grove Regulator Co., 6527 Green St., Oakland 8, Calif. The new valve operates by manual or automatic remote control, employing the pressure of the fluid handled to open or close its ports. Since virtually no external force is required, even a large 24-in. valve can be opened or closed as readily as 1½-in. valve, according to the manufacturer.

The valve is intended for cold fluid service, for handling water, salt water, chemical solutions, oils, gases and air. Owing to the fact that only one non-metallic operating part is employed, the valve is claimed to be extremely resistant to corrosion and erosion, as well as to electrolytic action. Furthermore, it is self-compensating for wear, Capacity is said to be considerably greater than that of a globe type valve of the same pressure drop.

Construction is illustrated in the cutaway view. The valve consists of a body within which is a slotted pipe-like core containing a solid barrier at its center. A resilient tube of some material such as rubber or synthetic rubber is slipped over the core. Outside the resilient tube is a control chamber which can be connected by means of the small three-way control valve shown beneath the main valve,

Typical welds with new electrode



either to the upstream pressure or to the atmosphere. In operation, when the upstream pressure is applied to the control chamber outside the tube, thus balancing the pressure on both sides, the valve seats tight. When the three-way control valve handle is turned to disconnect the upstream pressure from the control chamber and vent the latter to the atmosphere, the unbalanced pressure inside the tube distends it and causes the valve to open wide.

Since the valve employs no seat, disks, springs or weights and has no packing gland, stuffing box or exposed members, it is said to be very simple to maintain and to require no more headroom than a pipe. It can be controlled from a central remotecontrol station if desired, and can be operated hydraulically or pneumatically by various systems.

GENERAL-PURPOSE ELECTRODE

FOR THE ARC welding of mild steel in all positions, with either alternating or direct current, the Lincoln Electric Co., Cleveland, Ohio, has developed Flectweld 37, a new general-purpose electrode. The electrode is said to operate with absolutely no slag interference when welding vertical down, the fastest position for 8- to 16-gage steel. The electrode permits higher welding speeds since it is capable of withstanding higher currents, both alternating and direct. With the proper current it is claimed neither to stick to the work nor to burn through. Tests on welds so pro-duced are said to have shown tensile strengths from 70- to 80,000 lb. per sq.in., yields strengths from 60- to 68,000 lb. per sq. in. and ductility of 18 to 25 percent.

ULTRA VIOLET PHOTOMETER

AN ULTRA VIOLET photometer, developed by engineers and scientists of E. I. du Pont de Nemours & Co., primarily for the detection of low concentration of carbon disulphide vapors in air, is expected also to be suitable for the detection of dangerous concentrations of other gases and vapors. According to present plans, instruments of this general type will be manufactured by the Mine Safety Appliances Co., Pittsburgh, Pa. The new instrument is much faster and simpler than analyzers previously used and is so sensitive that it can detect one part of CS₂ in 1,000,000 parts of air. Giving instantaneous readings, it is capable of operating on continuous samples.

Operation of the photometer is based on light absorption by gases. Most gases, including the constituents of the air itself, absorb light of some particular wavelength, in effect casting a shadow where that particular wavelength of light would otherwise have fallen. Carbon disulphide, for example, strongly absorbs light of 3,132 angstrom units wavelength. Therefore, the



Protected squirrel-cage motor

carbon disulphide analyzer is operated on ultra-violet light from a mercury lamp and is provided with an optical system, including filters, so selected that about 60 percent of the photometric response of the electric eye is due to light of this wavelength. Air to be analyzed is pumped through several small chambers in the analyzer which filter out dust, oil and moisture, and then into a pair of parallel tubes about 31 in. long. Contaminated air flows through the first tube and then through a canister of activated charcoal which removes the CS2 and returns the purified air into the second tube. In this way a continuous comparison of the purified and contaminated air is made, one part of vapor in 1,000,000 parts of air producing an absorption of 0.02 percent, which is detectible by the instrument.

PROTECTED MOTOR

FOR USE in all kinds of industries, a new type all-purpose, continuous-duty, polyphase squirrel-cage induction motor has recently been announced by Fairbanks, Morse & Co., 600 South Michigan Ave., Chicago, Ill. The motor is said to be fully protected against flying particles and dripping liquids as well as other industrial motor hazards. It employs this company's recently developed centrifugally cast Copper-spun rotor and is equipped with ball bearings sealed in cartridge-type housings. Cross-flow ventilation is obtained through protected inlets and exhausts at the ends of the motor, designed to assure uniform cooling and the elimination of hot spots. The new construction is available in frame sizes from 224 to 365, inclusive. Among the special features may be mentioned the fact that the frame is cast in one piece with rib sections to give added strength without increase in weight. Another new feature is an innovation in the conduit box. Where space is limited, the conduit can be brought up between the motor feet to a tapped hole in the motor frame and the conduit box cover assembled flush with the frame, thus eliminating the external box.

PORCELAIN-FRAME THERMOMETER

To SIDESTEP the difficulty of securing metals, the H-B Instrument Co., 2502 North Broad St., Philadelphia 32, Pa., has developed a porcelain-frame thermometer which is used chiefly in the petroleum field



Porcelain-frame thermometer



Flexible-mounting blower

for determining the temperature of liquids in tank cars and other containers. As shown in the accompanying illustration, the frame, handle and cup are all in onc piece. The thermometer tube is attached to the frame with two Monel metal bands. Units are available in a range of 0 to .160 deg. F., with a red-liquid-filled thermometer, graduated in single degrees, but other ranges can easily be made up to a top limit of 700 deg. F. or even higher, if necessary. Advantages for the new design include reduction in number of parts from 14 to4, and an increase in weight from 4 oz. to 1 lb., permitting the thermometer to sink freely in viscous liquids.

MOTOR-DRIVEN BLOWER

DEVELOPED especially for building into machines is a new all-purpose blower designated as Model No. 6S Utility Blower, which is being manufactured by the Ilg Electric Ventilating Co., 2850 North Crawford Ave., Chicago 41, Ill. As appears from the accompanying illustration, the housing and stand of the new blower are made of die-stamped steel, power being supplied by a series-wound, 110-volt, single phase. 60-cycle motor operating at 3,400 r.p.m. Various arrangements are available including different combinations of blower, stand, and inlet and discharge flanges.

LOCK-ON SHEAVE

QUICK and easy mounting and demounting are features of the new Magic-Grip sheave which has recently been announced by Allis-Chalmers Mfg. Co., Milwaukce, Wis. The sheave employs a tapered split bushing which slides almost all the way into the tapered bore of the sheave without forcing. A slight clearance is left between the bushing collar and the sheave hub. Tightening of hollow headed cap screws draws the bushing deeper into the tapered bore, compressing the split sleeve and



Cross section of constant-level Dorrco Vacuator



Removing Magic-Grip sheave

locking the entire sheave uniformly to the shaft. Torque is transmitted through keys. Removal is accomplished by employing two of the cap screws as jack screws which are inserted into tapped holes in the bushing collar and turned, separating the bushing from the sheave. The bushing then regains its natural expansion and automatically breaks its grip on the shaft.

VACUUM FLOTATION UNIT

DEVELOPED primarily for the removal of grease and light, difficult-to-settle solids from sewage and trade wastes prior to clarification, a new unit known as the Dorrco Vacuator which has recently been introduced by the Dorr Co., 570 Lexing-ton Ave., New York 22, N. Y. When a trade waste is aerated, the largest air bubbles rise rapidly and escape to the atmosphere, while the finer bubbles are released slowly at ordinary pressures. When a vacuum is applied immediately after the escape of the large bubbles, the minute bubbles are released rapidly and attach themselves to light, suspended solid particles, carrying them to the surface. This principle is applied in the new equipment for the separation of grease, scum and light solids in handling sewage, as well as industrial wastes such as those produced in tanneries, gelatin plants and oil refineries.

The Vacuator accomplishes the action described in three steps, the first two taking place outside the Vacuator tank proper. The first step is aeration in a mechanical aerator. Deaeration then takes place in a small compartment or connecting channel where the larger air bubbles are released. Finally, the light-solids fraction is floated and removed in the Vacuator itself. Sometimes, where sufficient entrained gases are present in the feed, pre-aeration is unnecessary.

The equipment consists of a cylindrical tank with a dome-shaped cover in which a constant vacuum of about 9 in. Hg is maintained. The feed enters through a central draft tube and is distributed radially close to the liquor surface: Floated solids, buoyed up by the fine air bubbles, are continuously removed from the surface by means of a skimmer mechanism having hinged blades which push the light solid matter up a ramp and into a trough at one point in their rotation around the periphery of the tank. The grease or scum drops to a barometric leg for continuous discharge, while the clean effluent passes under a circular baffle and discharges over a weir into a peripheral channel from which it flows to a sealed chamber and discharges through a barometric leg. Coarse solid particles which settle are raked to a central sludge outlet which is also sealed off to prevent loss of vacuum.

At present the equipment is available in sizes ranging from 10 to 60 ft. in diameter and in two types, the constantlevel type described here, and a variablelevel type intended particularly for separation of floating material which is extremely light and cannot readily be raked up a ramp.

HOT-GAS FURNACE

FOR THE PRODUCTION of hot gases for heating spray towers and dryers, Air Devices, Inc., 17 East 42nd St., New York 17, N. Y., has developed the Agitair furnace which delivers a hot gas consisting of a mixture of products of combustion and

Agitair hot gas generating furnace



New corrosion resisting motor



air or recirculated gases at discharge temperatures up to 1,700 deg. F. The furnace is oil or gas fired and may be used, according to the manufacturer, for the processing of all types of materials not affected by contact with hot combustion gases. The furnace consists of an air-jacketed combustion chamber provided with a draft regulator. Adjustable fresh-air intake dampers control the amount of air admitted into the air jacket, and this air, after taking up heat radiated from the inner furnace shell, mixes with the outgoing combustion gases. Control of the furnace is fully automatic, with constant discharge temperature maintained by modulating controls and a reversing type burner control motor. The furnace can operate at rates down to 25 percent of full capacity, according to the manufacturer, without producing smoke or odor, except the odor due to sulphur in the fuel.

SEALED MOTOR

FOR USE in atmospheres containing corrosive gases and vapors, or abrasive dust, as well as excessive moisture, the Crocker-Wheeler Division of the Joshua Hendy Iron Works, Ampere, N. J., has developed the Sealedpower corrosion-resistant motor which is built in sizes from 1 to 15 hp., for operation on any polyphase power supply. The new motor is totally inclosed and fan cooled but has no cooling ducts to collect wet or sticky dust. All exposed parts are said to be highly resistant to acid and alkaline conditions. In addition to mechanical sealing of the entire motor, each coil is individually sealed against moisture, fumes, vapor and dust by a vacuum impregnation process.

SELF-BALANCING POTENTIOMETER

REDESIGN of its Pyromaster self-balancing potentiometer has been announced by The Bristol Co., Waterbury 91, Conn. The new model 431 instrument has a universal wall or flush mounting case, considerably deeper than the previous model, and an internal hinged panel on which are mounted the pen, indicator drive mechanism and control mechanism. This arrangement makes possible servicing and

Improved Pyromaster recorder controller



replacing of any part without disturbing other parts, and permits including control relays in electric type instruments within the instrument case, thus eliminating considerable external wiring. The instrument is available in both electric control and pneumatic control types, employing the same basic principle as previous models of the Pyromaster, which required no continually moving mechanical elements and were said to be unaffected by vibration.

FLAT-SPRAY NOZZLE

A SPECIAL FEATURE which permits cleaning of the orifice during operation has been incorporated in a new flat-spray nozzle recently put on the market by Spraying Systems Co., 4023 West Lake St., Chicago 24, III. This nozzle employs a long-wearing hardened steel orifice and is provided with a clean-out needle which makes it unnecessary to cease operation for cleaning. Various capacities and spray angles are available, while the nozzle may be built of many materials besides steel, if desired.

HIGH CAPACITY PRESS

MODEL T-4 is the designation of a new high-capacity press for ceramics and powder metallurgy recently designed by F. J. Stokes Machine Co., Tabor Road, Olney P. O., Philadelphia 20, Pa. Pieces up to 21 in. in diameter with a die-fill of 11 in. are compressed by this machine at rates of 20 to 60 per minute. Pressures up to 12 tons are applied from both top and bottom and pressure adjustments may be made while the machine is in operation. The new press includes such features as separate ejection and compression levers; screw adjustments for compression; independent ejection cam; special clutch and combined brake which starts and stops the machine instantly, even under full compression load; variable speed drive; and adjustable gibs to maintain close accuracy in punch and die alignment.

MANUAL CONTROL VALVE

DESIGNATED as Type 461M, a new manual control valve for all liquids, gases and for steam service, has been announced by the Fisher Governor Co., Fisher Building, Marshalltown, Iowa. The valve is intended for throttling control on installations where high pressure drop or other

Type T-4 high capacity press



CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •

severe conditions are encountered and has been designed primarily for refinery service for handling residual oils with coking properties, or for pressure breakdown from reaction chambers.

The valve body construction employs a single-seated, plug-type inner valve which is sleeve guided, and a streamlined body contour to ensure low head loss and minimize possibility of deposition of solids within the valve structure. The inner valve, sleeve guide and seat ring are of hardened stainless steel, the valve being chrome plated. A connection is provided to permit flushing the inner valve sleeve guide with a clean flushing oil to prevent coke formation and insure free movement of the inner valve member. The heavy manual operating mechanism is spiral geared for ease in operation. A special indicator plate provides for accurate valve positioning. The valve is easily converted to automatic diaphragm motor operation while retaining possibility for manual positioning of the inner valve, if necessary.

VACUUM SWITCHES

SUITABILITY for use in hazardous locations where fire and explosion are a constant risk is an important characteristic of four new vacuum switches recently announced by the Tube Division of General Electric Co.'s Electronics Department, Schenectady, N. Y. Mounting the contacts in a vacuum makes the switches relatively free from corrosion and arcing and frees them from the effects of dirt and oxidation. Vacuum construction also permits these switches to handle additional current for their size. Three of the four types are rated at 8, and one at 10 amp., at 250 volts a.c. Motion is transmitted to the contacts through a flexible diaphragm which scals the tube interior from the atmosphere and at the same time acts as a natural fulcrum point for the operating arm.

ROTARY PUMP IMPROVEMENTS

SEVERAL new developments have been introduced into the line of rotary pumps manufactured by the Blackmer Pump Co., Grand Rapids, Mich. Several of these developments have occurred in marine-type pumps which are believed to have industrial applications. One is a new pump with built-in relief valve for lubricating oil handling which has a capacity of 50 g.p.m. at a discharge pressure of 20 lb. per sq.in., and is operated by a direct-connected 3-hp. motor at 870 r.p.m. The motor is supported by a bracket made of welded steel plate which, in marine use, is bolted to a bulkhead. The pump is mounted vertically on the base of the bracket, permitting free access for lubrication and adjustment. Another marine type pump having a capacity of 100 g.p.m. at 100 lb. pressure, powered by a 15-hp. gearhead motor, is mounted on a fabricated steel base designed to permit free access for lubrication and other service. operations. A twin pumping unit having pumps of 90 g.p.m. capacity each, at pres-sures up to 100 lb., uses a single motor drive, connected to the two pumps through reduction gearing and twin clutches so that the pumps may be operated singly or together. Designed primarily for petroleum



Arco Microknife for film testing

blending operations, the pump provides double capacity to take care of temporary peak requirements or permit handling two different liquids simultaneously without contamination.

EOUIPMENT BRIEFS

DEVELOPED by Battelle Memorial Institute at Columbus, Ohio, a new silver babbitt said to have the same bondability and corrosion resistance as tin-based babbitt, and to retain its hardness at operating temperatures without squeezing out of the bearing, has been announced by National Bearing Metal Corp., St. Louis, Mo. Silver alloyed with a properly balanced lead-base babbitt is employed as a means of circumventing the shortage of tin.

EXTENSION of its line of explosion-proof laboratory equipment, to include electrically heated temperature control cabinets and constant temperature baths, has been announced by Precision Scientific Co., 1750 North Sheffield Ave., Chicago 47, Ill. Wiring is inclosed in vapor-tight explosion-proof conduit fittings and electrical controls are mounted in explosion-proof housings to conform with Class 1, Group D hazardous-location requirements. Heating elements operate at low wattage density and at black heat to minimize temperature differential between the air and the heater surface.

ACCURACY of plus or minus 1 percent of full scale deflection up to 5,000 r.p.m. is claimed for a new electric tachometer announced by the Ideal Commutator Dresser Co., 1344 Park Ave., Sycamore, Ill. The instrument, which may be used either as a hand or as a separable type, consists essentially of a small generator and an electric meter. A switch is provided to give a high and a low range. Since the meter and generator are separable, connected together by a bayonet lock, they may be separated and wired to each other by several hundred feet of two-conductor wire for separate mounting of the two parts.

PAINT FILM TESTERS

DEVELOPMENT of two new machines for controlled testing, measurement and evaluation of the flexibility, scratch hardness and adhesion of paints and other coatings has been announced by the Arco Co., Cleveland, Ohio, manufacturers of industrial and other finishes. Test measure-



New Masonry Treatment

New Masonry Treatment The two views above show before-and-after appearance of a brick and concrete factory building which has been treated with Waterfoll, a new product of the A. C. Horn Co., 43-36 Tenth St., Long Island City 1, N. Y. This product is manu-factured from irreversible inorganic gels which, when applied to concrete, brick or stucco surfaces, reacts chemically with the lime in the masonry to form a heavy coating which is said literally to "weld" itself to the structure. The resulting coating is said to permit the masonry to "breathe." an essential quality, but to impede the absorption of water in liquid form, thus inhibiting the rusting of steel reinforcing bars. The new material is said not only to restore masonry surfaces and keep up appearances but to increase the life expectancy of the structure.

ments of flexibility are made on a machine known as the Arco Elongauge. This machine has been developed around a conventional Erichson sheet metal testing machine which was adapted to provide automatic control and accurate measurement for cycle testing. Mounted with the observation well in a vertical position, the machine permits water from a hypodermic syringe to contact the paint film being tested. The steel of the test panel and the copper of the hypodermic needle are connected to a galvanometer. A constant speed drive geared to thrust a spindle against the back of the test panel distorts the panel until the insulating paint film fails. When water contacts the metal of the panel, the bimetal of steel and copper causes an instantly detected current flow. Thus the exact elongation at which film failure takes place is detected.

For measurement of scratch hardness and adhesion, the company has developed the Arco Microknife. This consists of a diamond point cutting tool which is applied to the surface being tested under a measurable load as the point moves across the surface at constant speed and cuts re-peatedly in a fixed position until the sub-surface is revealed. The load and number of strokes required to wear through the film are the measure of scratch hardness. The same machine is used for adhesion measurements by lateral adjustment of the movable sample carrying platform. A standard stress is applied at progressively smaller spacings of the cuts until the stress is sufficient to displace the coating in the area between cuts.

DAYS of able performance grow into YEARS CASH STANDARD Statamlinsd Type REDUCING VALVES

normal size diaphragm. Made for delivery pressures over 30 lbs.

> Right - Type 1000-LP has large diaphragm. Made for delivery pressures under 30 lbs.

The "1000" STREAMLINED Valve is a performer of top rank, rated on a basis of capacity — tight closing characteristics and close delivery pressure control.

and the second

The straight line flow promotes greater capacity — the "1000" is single seated and its valve makes line contact with its seat ring which accounts for its tight closing characteristics — the unusually long diaphragm spring insures sensi-



tive pressure control and also a wide range of adjustment.

The benefits from this kind of top performance include: - practically zero in maintenance — elimination of failures -speedier production-smooth operation and no spoilage.

Write for Bulletin "1000" for full details.





Cash Standard Type 34 Pressure **Reducing Valve.** For practically all fluids. Has roller bearing, also roller guides that kill side strains and stop packing trouble -no lost motion.

Sizes: 1/2" to 12" inclusive. Highest initial pressure 800 lbs.; reduced pressure vacuum to 150 Ibs. Bodies: iron, bronze, steel. Trim: Iron, bronze, stainless steel. Ends: screwed, flanged, ammonia type, welding type. Bulletin 968.



Cash Standard Type 30-AP Valve gives precise control of fluid pressures, through a pilot connected to the pressure under control. For steam, water, air, and most fluids.

Can be a pressure reducing valve or a back pressure valve depending on the way the control lines are connected. Pressures up to 600 lbs. Sizes 1/2" to 12" screwed; 1" to 12" flanged ends; wide variety of metals.

Pulp Sulphate Bleaching

TN THE bleaching of chemical wood pulp, it must be remembered that any flow diagram or description is subject to modification dependent on the conditions at individual mills and the end use of the product.

The unbleached or "brown" stock resulting from the sulphate (kraft) pulping process is of varying composition in regard to its bleachability characteristics, although it is possible by proper adjustments to hold the variations within a fairly narrow range.

The multistage process of bleaching is essentially an integrated system of units which are interrelated to allow a continuous flow of the stock from one to the one following. In each unit or stage, the d to chemicals under varying conchemical and stock concentration, time nperature, degree of alkalinity dependent on those factors which effect efficient and economical operation. Then he stock is thoroughly washed after each treatment o remove those materials which have been solubilized by the chemicals before passing on to the next stage.

The consistency of the brown stock is first egulated before the addition of chlorine. In this, ic first stage, the materials are chlorinated to form three types of end products; the major constituent being water-soluble, the second type is oluble in caustic solutions, and the remaining matter of such nature that it must be oxidized before it is soluble in alkaline solutions. In some cases lime is added to the chlorinated stock to neutralize the acid, but this practice is not necessary if the mill equipment is made of corrosion-resistant

After the stock has been chlorinated, it is washed free of soluble residue before passing to the second stage, where it is treated with caustic solution. This treatment makes it possible to wash out that portion of the chlorinated lignin which is soluble in alkali.

The oxidation of the remaining lignin is accomplished by the addition of sodium hypochlorite solution which completes the purification and raises the brightness of the pulp. It is usually performed in at least two stages so that the chemical charge can be decreased according to the requirements of the pulp thus preventing excessive degradation of the pulp.

When the bleaching process is complete, a weak acid, such as sulphurous, is added to the washed stock. The purpose of this addition is primarily to prevent color reversion, because the acid in addition to removing the residual active chlorine which would cause overbleaching with a consequent loss of strangell 1 111 1 washed from the pull

> CHEMICAL & METALLURGICAL ENGINEERING MARCH, 1944 PAGES 132 to 135



CHLORINE HANDLING

1 Chemicals most widely used in bleaching pulp are chlorine, caustic soda, lime, and calcium or sodium hypochlorite



2 Definite proportions of chlorine are used in bleaching. In- 3 Initial step in the bleaching process consists of chlorination

dicating and recording flow control unit showing vaporizer in a tower either continuously or in batch operation

4 After suitable retention for complete exhaustion of chlorine the pulp is washed and thickened

5 Stock can be thickened on the two deckers at the left from which it is discharged into the chest

6 Chlorine is mixed in bleach make-up tank with lime or caustie to form hypochlorite. A caustic soda tank car

7 Any one of several types of washers can be used for thickening and removal of excess chemicals

8 After final hypochlorite stage, pulp is again washed and the pH adjusted by means of sulphur dioxide or sulphuric acid

Big Times Coming... If You're Not Behind Them

There's a big time coming, if you clarity, dryer cake, with a standard save time producing.

There's going to be room for ex-pansion, if you know how to save space.

Perhaps we can help you do both. AT&M centrifugals have saved time and floor space in hundreds of processes.

In filtration, for instance, one manufacturer cut process time in half and saved 25 to 40 percent of an expensive chemical by installing compact AT&M centrifugals instead of a hard-to-clean, cumbersome system of filters.

In precipitation, another AT&M customer who used to wait for a particle-sized substance to settle in tanks now gets the benefits of immediate precipitation, finer degree of

AT&M centrifugal.

In impregnation, the story is the same. AT&M centrifugals require less room than kiers, tanks or autoclaves, and often do the job much more successfully. Centrifugal force presses liquids into semi-solids or solids faster, more uniformly-then may throw off the surplus in the same swift, space-saving operation.

Debydration? Coating? If you are not using centrifugals in these processes today, why not find out how much time and floor space they might be able to save you.

AT&M engineers are now available, as immediate national needs permit, to cooperate with you in planning installations of standard AT&M centrifugals . . . or special

centrifugals engineered to solve your particular production problem. Strict confidence will be preserved. Write American Tool & Machine Co., 1415 Hyde Park Avenue, Boston, or 30A Church St., New York, N.Y.

One high standard of quality throughout . . . One source of supply . . . One responsibility for all materials

COR these advantages you can thank the unusual C completeness of the Crane line of piping materials, shown by the installation at left. Every part, from pipe and pipe hangers to valves and fittings, comes from Crane. And from end to end, the performance of every part is assured by Crane superior quality.

Take a look at Crane quality through the iron body wedge gate valves in this hook-up. The body is strengthened to resist line strains. Port openings are straight through, giving streamline flow. A deeper stuffing box lengthens packing life. The stem has adequate power for positive seating, and extra long guides keep disc travel true.

With such refinements marking every item in the world's largest line of piping equipment, Crane is your magic word for better fluid handling service whether you need a single pipe fitting or an entire system. Crane Co.'s 89-year leadership in its field sees to that.

CRANE CO., General Offices: 836 S. Michigan Ave. Chicago 5, Illinois.

CHEMICAL & METALLURGICAL ENGINEERING MARCH 1944 .

VALVES · FITTINGS · PIPE PLUMBING · HEATING · PUMPS GIRDLER PROCESSES for manufacture, Jehydration . . Girdler on your rejinery gases, liquid hydro-Originators of the Girbotol Process

When confronted with a problem requiring a more efficient and economical gas process, call on Girdler! Time-tested, practical processes are already available for most purposes. An unprecedented problem? Then, remember this. Girdler has a complete staff — splendid research facilities — and a backlog of expe-

Hose 400 of 100 Set 10040-10240 MDBLEM? PROCESSING PROBLEM? Jot down Girdler

5=12000 × 1030 = 53 50 / 1030

The GIRDLER CORPORATION ENGINEERS

Gas Processes Division Louisville, Ky. CONSTRUCTORS

MEMO

rience gained by solving many engineering and construction problems in connection with gas processing.

Inquiries involving gases, gas n eous mixtures or liquid hydrocarbons receive action-attention from a pioneer-minded, foresighted organization. So - next al time, jot down Girdlerl

138

NEW PRODUCTS AND MATERIALS-

JAMES A. LEE, Managing Editor

SOLVENT EMULSION CLEANER

A solvent emulsion cleaner, Pennsalt E. C. No. 10, developed by Pennsylvania Salt Manufacturing Co., Philadelphia, Pa., combines soap emulsifying action with solvent penetration. Composed of emulsifying agents and suitable solvents, it is of the self-emulsifying, non-phenolic type. Suggested uses are for removing grease, oil, smut, and drawing and buffing compositions from metals and painted surfaces. Undiluted material may be applied cold or warm by dipping, spraying or brushing. It is applicable to power washer and soap type operations in water emulsion form or to increase effectiveness of alkaline cleaners. Packed in 55 gal. drums, it is available in commercial quantitics.

CERAMIC COMPOSITION

A ceramic type composition which produces electrically conductive coatings that may be applied to a wide variety of nonconductors including glass, plastics, porcelain, soapstone, wood, cloth and paper is being manufactured by E. I. du Pont de Nemours & Co., Wilmington, Dcl.

These coatings can be applied by spraying, dipping or brushing, followed by air drying and, in some cases, baking. Containing silver powder, the composition produces a surface of low electrical resistance and high conductivity, and is valuable for use in electrical condensers and other units employed in electrical circuits. Aging, or exposure to sulphides has only a slight effect upon the conductivity.

Several different formulations of the material are being produced, each designed to meet the varying requirements of different base materials and degrees of adherence and film toughness. The coatings are dull, metallic gray in appearance. A thermoplastic conductive cement is one form. Others include a conductive coated cloth and a flexible conductive film. Four types are being produced but other formulations are available for evaluation purposes.

INSECTICIDE DUSTS

Two chemical dusts that give the grower a combination insecticide and fungicide against a wide range of insects and diseases have been announced by E. I. du Pont de Nemours & Co., Wilmington 98, Del. These materials, designed especially for growers of potatoes and of farm garden crops, are Du Pont Potato Dust and Du Pont Garden Dust. Both have been tested under field conditions. These products contain no lime or any other harmful diluents, are easy to mix and apply, and can be dusted or sprayed at any time of day.

Du Pont Potato Dust contains calcium

CONTENTS

Solvent Emulsion Cleaner	139
Ceramic Composition	139
Insecticide Dusts	139
Emulsion Cleaner	139
Metal Cellulose Glycollate	139
Sodium Cellulose Glycollate	139
Synthetic Rubber	140
All-Purpose Insectifuge	140
High Impact Phenolic Resin	140
Insulating Firebrick	140
Protective Packaging	140
Shoe Coating	140
Furniture Finish	140
Flame-Proof Cotton	140
Bacteria Repellent	140
Alkali Fluoborates	142
Three-In-One Glue	142
Trivalent Chromium	142
Mildew Proofing Compound	142
Aluminum Yarn	143
Insecticide For Typhus	143
Resin Chemical	143

arsenate insecticide and Copper-A Compound fungicide. It is recommended for control of Colorado potato beetles, flea and blister beetles, hornworms, leaf hoppers, early and late blight and other leafspot diseases. The potato dust may be used on tomatoes, eggplants, and peppers, but in that case the fruits should be washed thoroughly before using, to remove any possible poisonous residue.

Du Pont Garden Dust contains synthetic cryolite insecticide, a material specially manufactured for fineness and uniformity, and the Copper-A Compound fungicide. It is recommended for Mexican bean beetles, flea beetles and blister beetles, striped and twelve-spotted cucumber beetles, leaf hoppers, various caterpillars, "worms" and "slugs" and other chewing insects, as well as various leaf spots, mildews, and "blights" of vegetables and flowers. For sucking insects such as black or green aphis, a nicotine dust or spray should be used.

EMULSION CLEANER

A concentrate type emulsion cleaner, Pennsalt E. C. No. 2, comprising soaps, blending agents, and co-solvents for industrial grease cleaning applications, and soluble in water and in hydrocarbon solvents has been announced by the Special Chemicals Division of Pennsylvania Salt Mfg. Co., Philadelphia, Pa. It may be diluted with from 5 to 20 parts of suitable solvents such as low-cost kerosene, Stoddard solvent, or light fuel oil distillate. Uses suggested by the manufacturers are as an emulsifying solvent in removing carbonized oils, grease, smut, and drawing and buffing compositions. It finds use as a precleaner, prior to electroplating, yielding a physically clean surface, and is also applicable to power washer and soak tank operations in water emulsion form or to increase the effectiveness of alkaline cleaners. The material also acts to inhibit rust formation. Packed in 55 gal. drums, it is available in commercial quantities.

METAL CELLULOSE GLYCOLLATE

The aluminum salt of cellulose glycollic acid in which carboxy methyl (CH,COOH) radical comprises the substituent group is known as Collocel A by the manufacturers, the Dow Chemical Co., Midland, Mich. It is unlike sodium cellulose glycollate, Collocel S, in that it is insoluble in water. Solution of Collocel A can be effected through the use of inorganic or organic bases. It is produced as a cream to light brown powder passing a 18 in. mesh screen. The apparent density of this product is 0.9 or approximately 56 lb. cu.ft. Collocel A has been successfully used to improve the transparency of a glassine sheet. It can be used to produce grease and oil proof papers. The wet strength of the paper can be increased by sizing with this material but the water absorbing property of the paper will be markedly reduced. The extensive com-patibility of the material with direct and acid dyestuffs coupled with its inherent usefulness as a thickener has led to the successful development and application of Collocel A as a print paste thickener in the textile industry. Its solubility in aque-ous solutions of amino alcohols indicates that this derivative should find application as a thickener or stabilizer since many of these alcohols are now used in cosmetic formulations. Films cast from ammoniacal solutions are transparent, hard, and possess excellent tensile strength. They are stable to light and heat. They are resistant to turpentine, vegetable and mineral oils and greases, and can be made water insoluble by incorporation of reactive materials such as water soluble urea and melamine resins and polycarboxylic acids which possess functional groups capable of reacting with the Collocel A molecule.

SODIUM CELLULOSE CLYCOLLATE

The neutral sodium salt of cellulose glycollic acid or carboxyemethyl cellulose is known as Collocel S by the manufacturer, the Dow Chemical Co., Midland, Mich. It is an interesting addition to the group of commercially available water

soluble cellulose esters because besides being a tough film forming material and possessing other useful properties characteristic of cellulose esters, it has special characteristics by virtue of its salt character. It is produced in the form of a dry powder which is soluble in water but insoluble in all organic solvents. It is unaffected by oilv or greasy materials of animal, vegetable or mineral origin. It is odorless and nontoxic. Collocel S is stable to heat without discoloration at temperatures up to 175 deg. C. Although it will burn when once ignited, if offers no greater fire hazard than cellulose in the same physical form. Collocel S is stable to light and does not discolor on long exposure to ultra-violet light. It is available in two viscosity types, low and high.

The properties of the material recommend it for use wherever natural gums such as locust bean, karaya and tragacanth are employed. It can be used in formulations requiring a thickener, stabilizer, adhesive compound, emulsifying agent or protective colloid. It is suitable for application as a pigment disperser, print paste thickener, warp sizing agent and assistant or base for water soluble inks. Collocel S is easily removed from textiles by mild washing and does not form precipitates with hard water. Films are grease and oil resistant and should be useful in coatings requiring this property.

SYNTHETIC RUBBER

A new product which may result in better automobile tires than can be made from GR-S (Buna S) rubber, because of greater energy resilience and higher resistance to cut and tear tendencies has been announced by Goodyear Tire & Rubber Co., Akron, Ohio. Butadiene is an ingredient but another chemical has been substituted for styrene in the new synthetic.

ALL-PURPOSE INSECTIFUGE

As a result of research by government agencies, the U. S. Industrial Chemicals, inc., New York, N. Y. has announced an insect repellent which performs with high effectiveness in all parts of the world, against all types of insects including mosquitoes, biting flies and chiggers. Although the complete composition of the material cannot be revealed at present, it can be stated that one vital ingredient is the company's Indalone. It owes its unusual repellency to its bitter taste and its effect on the nerve endings in the feet of the insects.

HIGH IMPACT PHENOLIC RESIN

The development of a high impactresistant molding material, BM-16468, has been announced by Bakelite Corp., unit of Union Carbide and Carbon Corp., New York, N. Y. The material is a black

	Physical 1999	
Compressive strength, lb. per sq.in.		
Tensile strength, lb. per sq.in. Flexural strength, lb. per sq.in.		
Maximum deflection-in.		
Impact strength, Izod		

INSULATING FIREBRICK

In order to make possible speedier, more economical installations of insulating re fractory linings, Johns-Mauville, New York, N. Y. has developed insulating Fireblok. It is available in four different grades, each suitable for a different range of temperature conditions.

One Fireblok is said to cover more surface than is covered by five full-size brick. This large size, compared to the standard firebrick unit makes installation faster and materially reduces the number of joints, thus requiring a minimum of mortar for bonding. It can be used wherever insulating firebrick are recommended, but is particularly suitable for the lining of doors. for suspended arches, and, when tapered. for sprung arches of exceptional stability. It can be cut with a saw and shaped with a rasp. Most special shapes can be either shop or field cut from standard slabs, thus reducing the inventory of special shapes that need be kept in stock.

PROTECTIVE PACKAGING

It is said that Hercules' Ethyl Cellulose Plastic Peel has reduced rust proofing to a simple procedure and slashed man-hours by as much as 90 percent. Metal parts are quick dipped in a hot liquid mixture of ethyl cellulose, synthetic resins, and oil. In seconds they are coated, the plastic hardens, and the protective oil is sealed in. The plastic is permanently tough but easily peels off.

While ethyl cellulose hot-dipped plastics were developed to handle the war emergency, they are expected to have a number of industrial applications such as the protection of finely finished parts for aircraft and automotive engines during shipment, protection of machine tools from corrosion and similar applications. Also there will be a large number of plant installations put up for war purposes, which will need protection from corrosion. These plastics may be applied to large stationary pieces to protect them indefinitely. Such coatings, of course, can be readily removed by stripping and will be much tougher and more durable than oil, wax or grease coatings now in use. In addition to the transparent formulations, a translucent formulation has been approved by Army Ordnance because some parts must be in-dividually boxed or tagged with part numbers for identification and in those cases transparency is not necessary. These materials are products of Hercules Powder Co., Wilmington, Dcl.

phenolic plastic having a strong filler rather than chopped fabric which is employed for other types of shock-resistant materials. Impact strength of BM-16468 is about 20 to 25 times greater than general purpose phenolics.

Physics	al Properties	
	Direction	of stress
r sq.in.	Parallel	27,500-32,700
- 1 - 1 - 1 - 1	Transverse	15,600-18,000
in.	Transverse	7.500- 8.500
.in.	Parallel	12,000-12,900
	Transverse	10,200-14,200
	Parallel	.086122
	Transverse	.095118
	Parallel	3.49-4.84

• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

SHOE COATING

A solution of a vinvl resin, said to be "impervious to sulphur-base cutting oils, kerosene, paint, lacquer, cleaning and degreasing compounds and other organic solvents" has been announced by the Resistoflex Corp., Belleville, N. J. Shoes are merely dipped in Compar shoe coating and allowed to dry. The wearer will be protected against allergy, dermatitis and folliculitis caused by oils and solvents. The coating resists the destructive action of the solvent and yet leaves the leather flexible. It will protect and greatly extend the life of the shoe, according to the report of the manufacturer.

FURNITURE FINISH

A better finish for home, school and office furniture, much tougher than present varnishes or lacquers, is promised after the war by the Finishes Division of E. I. du Pont de Nemours & Co., Wilmington 98, Del. A formulation described as "unique" has been developed at the company's laboratories for use as a base or prime coat. Its value lies in the extraordinary adhesion it provides for the top coat. The new socalled penetrating primer, by affording improved anchorage, permits the use of higher scratch-resistant finishing lacquers. Such super-tough pyroxylin lacquers have long been available but were impractical because a sufficiently strong adhesive bond with a wood surface could not be obtained.

FLAME-PROOF COTTON

Efforts of the Department of Agriculture, the National Bureau of Standards and the Surplus Commodities Corp. have resulted in the development of a flame-proof cotton which is being placed on the market. The new cotton insulation, marketed under the trade name of Revn-o cell, is now being manufactured in six mills in the country and distributed through the General Electric Supply Corp.

The material is a 3-in. blanket of flameproofed and heat-resisting cotton protected on one side by a moisture-vapor-proof paper. It weighs only about 4 oz. a square foot, and is the lightest insulation yet produced. Tests show the material saves up to 30 percent of fuel. Instead of settling the material fluffs up from vibration to greater thickness and becomes more effective.

BACTERIA REPELLENT

Textiles, if treated in the finishing bath with a new chemical developed by Gallor hur & Co., New York, N. Y., are said to be resistant to bacteria and fungi growth. Its developers have given the treatment the name the Puratized process. It will prob ably not be generally available for application to textile for civilian use until after the war. At the present time it is being used for the treatment of textiles for military purposes. Puratized process formulations N5-X, N5-D, and N5, may be introduced phase, or by an oil-in-water type of enulsion, and then insolubilized in situ in the fabric at a temperature as high as 200 de F. During the operation the active F gredient combines in part with cellulos

HB-40 A Clear, Mobile High-Boiling Hydrocarbon

With its unique combination of chemical and physical properties, HB-40 should find many uses in a wide variety of industries. A few of the possible applications of this high-boiling, stable hydro-carbon oil, with its unusual spread between freezing and boiling points, are listed below.

SUGGESTED USES:

- 1. As a hydraulic fluid in thermal controls.
- 2. As a plasticizer for vinyl, polystyrene, methacrylate resins and for asphalt or gilsonite base paints.
- 3. As a textile lubricant and softener, in particular for rayon and woolen goods.
- 4. As a constituent of leather dressings, particularly those formulations used for softening leathers.
- 5. As a solvent for various types of oils, resins and waxes.
- 6. As a solvent for industrial processing. (Such as extraction of organic materials from waste liquors.)
- 7. As an absorber to remove volatile organic compounds from gases. (Such as removal of naphthalene from by-product gas.)
- As a solvent where low volatility and low flammability are essential or desirable.

PHYSICAL PROPERTIES:

Appearance: Almost colorless, mobile, oily liquid, with faint pleasant odor.

Color: Less than 500 APHA (Darkens on exposure to sunlight.)

Specific Gravity: $1.005 \pm 0.010 @ 25/15.6^{\circ}C. - (8.37 pounds/gallon, average).$

Refractive Index: 1.5540 - 1.5740 @ 25°C.

Coefficient of Expansion: 0.000741 cc/cc/°C.

Carbon Residue: (Conradson) 0.02%.

Ash: (10-gram sample) Nil.

Neutralization Number: 0.03.

Steam Emulsion Value: 45.

Stability to Heat: Appears to be relatively stable at the boiling point (at least in glass), and does not readily oxidize. However, it does decompose at 300°C. under pressure, in iron.

Stability to Acids and Alkalies: Appears to be rela-

tively stable, and undergoes no significant changes in composition when kept in contact with boiling 10% aqueous solutions of H₂SO₄ or NaOH at atmospheric pressure.

r apor i ressure co	111114 # # # 5				
150	2				
165	4				
175	6				
190	10				
205	16				
225	28				
245	50				
250	71				
300	235 (est)				
325	25 410 (est) 57 760				
357					
	Deg. C.				
Distillation Range: S	tart 345 (corr.)*				
1	0% 353 "				
5	0% 359 "				
9	0% 393 "				
5	5% 420 "				

*Corrected for stein exposure

Flash Point: 345°F. ASTM D92-24.

Flame Point: 385°F. ASTM D92-24.

Pour Point: Minus 28°C.

Mons 1700 Witho Mons Name Comp. Street

City

Solubility: Not soluble in water, but is miscible in all proportions at room temperature with a number of solvents and oils.

Compatibility: Compatible in varying proportions with polystyrene, ethyl cellulose and methacrylate resins. Viscosity – SUS. 136.5 @ 100°F. 38.4 @ 210°F.

ELECTRICAL PROPERTIES: (Typical Data)

Dielectric Constant: 2.53 at 25°C. 2.35 at 100°C. Dielectric Strength: 30 kv., average, at 25°C. Resistivity: 5000 x 10° ohms/cm³ at 100°C. Above 17,000 x 10° ohms/cm³ at 25°C. Power Factor: 0.12% at 100°C. at 1,000 cycles.

MA	IL COUP	ON	FOR	2 5/	AMPLE		
anto Chemical South Second	Company, Pho Street, St. Louis	osphate s 4, Mis	Divisi ssouri	on,			
out cost nor anto HB-40.	obligation to	me, pl	lease	send	experimental	sample	of
any	3132.33						

Zone

State

These two illustrations of R-S Butterfly Valves exemplify the wide pressure range (15 to 900 psi) handled by this type valve as well as the simplicity of design.

When completely assembled, the heavy duty power operated valve, No. 610, will be equipped with a dual stuffing box, hand wheel declutching unit, hand jack and mercury switch. Shaft supported on ball or sleeve bearings enclosed in grease packed journals—pressure lubrication.

The manually operated three-way valve, No. 611, is utilized for quick interchange and mixing service. It is adapted to power operation as well as high pressures and elevated temperatures.

This visual presentation of R-S Engineering speaks for itself. If you are interested in simplified control and shut-off of volume and pressure, write for the complete story contained in the new R-S Catalog No. 14-B.

molecules in the fabric to become an integral part. Several types have been developed for various uses.

ALKALI FLUOBORATES

Three alkaline fluoborate salts, ammonium, potassium, and sodium, arc available in experimental quantities from Pennsylvania Salt Manufacturing Co., Philadelphia, Pa. Ammonium fluoborate (NH₄BF₄) has a sp.gr. of 1.85 and is freely soluble in water and alcohol, giving a slight acid reaction in aqueous solution. It sublimes at 230 deg. to 240 deg. C. Potassium fluoborate (K BF_4) has a sp.gr. of 2.5 and is only very slightly soluble in hot or cold water or alcohol. It has a melting point of approximately 500 deg. C. and at elevated temperatures decomposes to KF and BF_a . Sodium fluoborate (Na BF_4) is readily soluble in water but only sparingly soluble in alcohol, the aqueous solution giving a slightly acid reaction. It fuses below red heat and is slowly decomposed to NaF and BF_a. These materials, which are also known as borofluorides, find uses in welding fluxes, as oxidation inhibitors in sand casting of aluminum and magnesium, and in heat treatment of aluminum alloys.

THREE-IN-ONE GLUE

One glue that can be used in three different ways, cutting costs, inventory and production time, has been formulated by I. F. Laucks, Inc., Scattle, Wash. This glue, Lauxite Hot Press Urea Resin ("8-9XC-U"), can be used straight, with a fortifier (to meet standard three-hour boil test), or with wheat flour of any gluten strength.

Formerly it was necessary to have different glues for these three different type jobs. Special importance is attached to the fact that this new formulation can be used with any wheat flour regardless of gluten strength and still obtain a free spreading, uniform viscosity glue.

TRIVALENT CHROMIUM

Trivalent chromium is now available for chromium plating according to the Warner Laboratories, Chicago, Ill. The Warner process with its Skalite chromium salt, is said to provide substantially greater plating efficiency. Procedure for both hard and decorative chromium has been simplified. Plant investment is immeasurably less. The need for special chrome plating equipment has been eliminated according to the company. Time, electrical energy and salts required are only 20 percent of the old process. Due to the bath's non-gassing characteristics and substantially increased throwing power there is no longer need for special contour anodes on intricate objects. The bath is also non-corrosive. The new bath is non-poisonous, chromium plating is removed from the hazardous occupation classification with attendant savings in liability insurance.

MILDEW PROOFING COMPOUND

Mildew proofing and water repellency are said to be combined in Ceral TGI, announced by the Sandoz Chemical Works, New York, N. Y. The product, an emulsion containing dihydroxy-dichloro-di-

phenyl methane, possesses high stability both in its concentrated form and when diluted to working strength. Fabrics treated with this compound are said to be nontoxic and garments so treated may be worn in contact with the skin.

ALUMINUM YARN

There has been an announcement by Reynolds Metal Co., Richmond, Va., that it has developed an aluminum yarn which is made by cutting fine strips from large rolled sheets. One pound of aluminum has made six miles of this type of strip. Sheets coated with cellulose acetate have greater tensile strength. During the coating process any color may be imparted to the metal. After cutting the yarn may be used in its pure state or twisted around cotton or rayon to make aluminum coated yarns. The yarn is washable and may be dry cleaned. It does not tarnish.

INSECTICIDE FOR TYPHUS

The production of DDT, the new and powerful chemical weapon protecting the armed forces from typhus, will be multi-plied by the construction of a plant by the E. I. du Pont de Nemours & Co., Wil-mington, Del. A difficult compound to make, DDT, or dichloro-diphenyl-trichloroethane, is such an effective insecticide that the Army recently flew the first 500-lb. the Army recently new the first 500-lb. cargo produced at a du Pont pilot plant to an overseas front. Tonnage manufacture at the new half-million dollar plant to be built at government request will be entirely devoted to Army and Navy use. Work is expected to start almost immediately. Some conception of DDT's potency may

be had from the fact that a single application dusted on clothing gives protection from disease-carrying vermin for one month.

The chemical was first synthesized 70 years ago by a German chemist, but its use as an insecticide was patented by a Swiss firm, Geigy, Inc., in 1939. Previously employed largely as a moth repellent and a plant lice control, the U.S. Department of Agriculture revealed last May that its scientists had successfully tested its utility against body lice. The Army soon recommended its adoption as standard equipment, replacing the louse powder then in use.

RESIN CHEMICAL

A plastic covering that removes all the hairs from a pig when it is peeled off has given the housewife more high-grade pork cuts, ham, bacon, lard and other pork products, Hercules Powder Co., Wilmington, Del., reports.

The chemical shaving method, which has been adopted by meat packers, also saves processing time and reduces dehairing costs. Coating the pork carcass with Brisgo, a resin chemical made by Hercules, packers now get rid of the toughest whiskers and stubble in a simple stripping operation. The pig is dipped in a tank, and carried on the dressing conveyor to an operator who slits the warm plastic suit and unrolls it. In another method, the chemical is brushed on and scraped off. The removed plastic goes back to a remelting tank and is used over and over again.

monorail hoists

YOU SHOULD KNOW MORE ABOUT SHEPARD NILES CAB-OPERATED MONORAILS

HOIST MOUNTING -- The HOIST MOUNTING — The hoisting unit is mounted paral-lel to the runway, if side pulling at right angles to the runway is like-ly to occur—or, where the load hook must operate close to the end of the runway, the hoist can be mounted at right angles to the runway.

3 FULLY ENCLOSED OPER-ERATING PARTS—All op-erating parts of the hoisting unit are fully enclosed and complete-ly protected from moisture and dust.

BALANCED DRIVE-Stres-4. SALANCED DRIVE-Stres-ses are evenly distributed in the hoisting unit through the use of the Shepard "Balanced Drive".

5. LUBRICATION-Entire gear train operates in a bath of oil.

BEARINGS — Antifriction bearings used throughout. 6.

OPERATOR'S CAB supplied 7. either open or completely en-closed and weatherproofed

COMPLETE

LINE OF

for outdoor service.

deliver the goods . . . quickly, economically . . . day after day

Up, out of the way of important production, Shepard Niles Cab-operated Monorail Hoists go places-and get things done.

They are especially recommended for long runways, where rapid travel speeds are required.

When operated on the single beam of a Transfer Crane, complete areas are covered quickly, completely and continuously.

When operated in conjunction with a transfer crane, which permits the hoist to serve adjacent bays through a system of overhead switches and spurs, a Cab-operated Monorail achieves its greatest efficiency. No spot, indoors or out is so inaccessible that it cannot readily be serviced with a Monorail.

Qualified Shepard Niles sales engineers are located in all war-production centers to consult with you in determining the exact type of equipment you will need to obtain maximum efficiency in your materials-handling operations.

FREE. 106 pages, amply illustrated by line and sectional drawings.

THE

PROCESS EQUIPMENT DIVISION Agitators, Mixers, Blenders, Autodaves, Kettles, Pressure Vessels, Driers, Boll and Pebble Mills. Diesel, Diesel-Electric, Electric, Steam, and Fireless Steam Locomotives. GUIMAN PUMP DIVISION: Screw, Rolex, Centrifugol, Chemical, Pumps. ORDNANCE DIVISION : Projectiles, Heavy Forgings, Breech Blocks

Side-Entering N = W - Externally-Accessible Stuffing Box Can be repacked from the outside without draining tank.

Patent Fending

Sepackit in

- **5** W _ Self-Sealing Shaft Prevents loss of liquid while repacking stuffing box. NEW - Weather-Proof Motor Cover
 - Assures all-weather motor protection.

EW _ Adjustable Motor Support Adapts itself to mounting conditions.

Descriptive folder on request

H. K. PORTER COMPANY, Inc.

PITTSBURGH, PENNSYLVANIA FACTORIES: PITTSBURGH, PA. BLAIRSVILLE, PA.

NEWARK, N. J. NEW BRUNSWICK, N. J.

Mixer

in the second

CHEMICAL ENGINEERING NEWS_

SULPHURIC ACID CAPACITIES WILL BE INCREASED

SULPHURIC ACID production has reached a new high with total capacity now estimated at approximately 9,300,000 tons a year, the War Production Board announced on Feb. 28. In addition, new facilities with an estimated capacity of 800,000 tons yearly are under construction. These figures refer to 100 percent acid.

Total present capacity for private production (i.e., production by the user) is estimated by WPB officials to be approximately 706,000 tons per month, or 8,475. 000 tons per year. Plants in this category now under construction and expected to be completed by the fourth quarter of 1944, are expected to increase these figures by 66,500 tons per month, or 798,000 tons per year, excluding ordnance acid. Reports from commercial plants (i.e., those producing sulphuric acid for sale) indicate operation at over 100 percent rated capacity.

Definite requirements figures are still unavailable for 1944 but indications are that the following additional tonnage will be needed per month:

Superphosphate program, 26,300 tons; ammonium sulphate, 3,700 tons; rayon and cellulose film, 8,300 tons; petroleum re fineries, 24,000 tons; titanium dioxide and other pigments, 2,300 tons; chemicals, 3,000 tons; iron and steel, 13,400 tons; other metallurgical, 1,000 tons.

WPB officials said that present indications were that all but 14,500 tons per month of the anticipated increase can be met.

RESEARCH LITERATURE FROM DOCUMENTATION INSTITUTE

UNPUBLISHED manuscripts, inaccessible periodicals, and important translations are now available for research workers through new services offered by American Documentation Institute and certain important libraries. This group of agencies has arranged convenient facilities for making available at a nominal cost both unpublished and rare printed material.

Microfilms of published periodical articles are now available from about a dozen of the largest libraries at a flat fee of 50 cents per article. This service was originally rendered only by the Bibliofilm Service at the Library of the U. S. Department of Agriculture, Washington, D. C.

When ordering reproductions of articles the fee of 50 cents should be sent with the order. If the library first addressed does not have the original available, it will forward the order and fee to one of the others of the group believed to have the material for photographing.

Unpublished manuscripts of important nature are also received by A.D.I. from responsible cooperating editors of scientific journals. These journals must publish an abstract or a notice of the existence of the manuscript. The manuscript itself is then available from A.D.I. at a nominal charge in microfilm or photoprint form. A similar service is being arranged for microfilm reproduction of manuscript translations of important foreign articles.

PACKAGING CONFERENCE AND EXPOSITION AT CHICAGO

EXILIBITS of wartime packaging, packing, and shipping, together with developments which will be available after the war, will be on view at the 14th Annual Packaging Exposition sponsored by the American Management Association, to be held at the Palmer House, Chicago, March 28–31. Packaging machinery and equipment and packaging, packing, and shipping supplies for wartime and postwar uses will be on display. Featured, will be a clinic for packagers supplying the armed forces.

Concurrent with the exposition, the Association's Annual Packaging. Conference will be held, with speakers from government and industry. Changes in government specifications for overseas packing, postwar uses of wartime substitutes, trends in merchandising that will affect packaging in the postwar period, the re-use of containers and paper conservation will be among the topics. There will also be a technical session devoted to package testing, and bulk packing versus individual prekaging will be considered. In addition, there will be an address on the organization and operation of a packaging department.

PLASTICS ENGINEERS PLAN CHAPTER FOR TOLEDO

MOVING over to Toledo, Feb. 18, Detroit Chapter of the Society of the Plastics Engineers, Inc. met their Toledo members with plans for setting up a separate chapter in that city. Chairman of the Toledo organizing committee is G. W. Clarke of Owens-Illinois Glass which also provided the guest speaker, Oscar Burch. His subject was "Glass, A Thermoplastic Material." W. B. Hoev, national vice-president of S.P.F. followed the speaker with a talk on the aims and purposes of the Society. Over 100 men, including a generous representation from Toledo's many research laboratories, attended the dinner. Earlier in the day the national S.P.E. Board, under President Charles C. Henry. met the officers of Detroit and Cleveland Chapters and the National Affiliate Coun-cil. Because of George C. Gress's resigna-tion due to ill health. John H. Deer, gen-eral manager of Sinko Tool and Manufacturing Co., Chicago was elected secretarytreasurer of the Board to fill out the un-expired term. A. H. Voss, Western Electric Co., Cicero, was appointed chairman of the general committee of technical activities and J. F. Calef, Automatic Electric Co., Chicago, accepted the vice-chairmanship of this group.

ELECTROCHEMISTS WILL MEET IN MILWAUKEE

THE ANNUAL meeting of The Electrochemical Society, Inc., will be held in Milwaukee, April 12-15 with headquarters in the Pfister Hotel. Registration will open on the evening of April 12 and the annual business meeting, including tellers report on the clection of new officers, will take place on the following morning. The annual banquet will be held in the evening when Dr. R. M. Burns will deliver the presidential address. There also will be the bestowal of honorary memberships and the presentation of the young author's cash prize and, the young author's book prize. On the evening of April 14 there will be an informal reception to the new officers followed by a complimentary buffet supper and entertainment with Pabst Brewing Co. as host. The luncheon on April 15 will be in honor of the newly elected president of the Society.

Following the business meeting, the technical sessions will get under way with electrolytic cells as the first topic of discussion. In the afternoon the talks will center on powder metallurgy and on the morning of April 14, the program calls for discussion on miscellaneous electrochemical topics. Sessions on corrosion will open on the afternoon of April 14 and will continue throughout the following day.

SOCIETY FOR METALS SPONSORS RESEARCH ON CORROSION

PLANS HAVE been completed whereby the American Society for Metals will provide an annual fund of \$1,000 for the support of fundamental research in the field of corrosion. A committee has been formed under the chairmanship of Dr. R. M. Burns, assistant chemical director, Bell Telephone Laboratories, New York, and including T. S. Fuller, General Electric Co., Dr. F. W. Adams, Pittsburgh Plate Glass Co., and Dr. H. L. Maxwell, E. I. du Pont de Nemours Experimental Station. This committee will select such research projects as appear worthy of support. approve the qualifications of applicants for grants-in-aid, and certify to the Society the names of successful applicants.

VANCE T. EDWARDS CHOSEN TO HEAD TAPPI

THE Technical Association of the Pulp and Paper Industry held its 29th annualmeeting in New York Feb. 14–17. Vance T. Edwards was elected president to succeed Ralph A. Hayward who had served during the past two years. Mr. Edwards is with the International Paper Co. at Palmer, N. Y. The newly elected vicepresident is C. W. E. Nicholson of Union Bag & Paper Corp., Savannah, Ga.

Allen Abrams, past president of the association, presented the TAPPI medal to D. C. Everest, president of Marathon Paper Co.

It's an engineering fact . . .

This 9" MULTICLONE TUBE has <u>8 times</u> the dust separating power of a 6 ft. cyclone chamber!

N RECOVERING dusts, fly ash and other suspended particles from gases, it is a basic engineering law that the separating efficiency of a cyclonic collector tube *increases* as the tube diameter *decreases*. For example, with the same power expenditure per cubic foot of gas treated, the separating force acting upon a given-sized particle is 8 *times greater* in a 9 in. MULTICLONE tube than in a standard 6 ft. cyclone chamber ... 8 *times greater cleansing power to throw out extremely fine as well as coarse particles*. This is why the MULTI-CLONE is so highly efficient in recovering ALL types of suspensions, even those of low micron size!

The MULTICLONE provides the high recovery efficiencies of *small* diameter tubes because this construction is made practical by the simplified inlet of the *vane* tube design—an exclusive MULTICLONE development. Yet this is just one of *many* advanced features incorporated in the MULTICLONE. It has no filters or screens to clean or replace, no high speed moving parts to repair or maintain, nothing inflammable to burn or char. It is extremely compact, is easier to install, and is ruggedly built for years of heavy-duty service!

VG MULTICLONE TUBE Cross section shows patented vane which guides gases.

WHY SMALL TUBES ARE MORE EFFICIENT!

Every automobile driver knows that a car will safely negaliate a wide turn ... yet will turn over if forced around a sharp turn at the same speed. Why? Because centrifugal forces rapidly increase as the turning radius decreases. This same principle explains why the small MULTICLONE tube is a far more efficient dust separator than the conventional large cyclonic tube. The sharp radius of the small diameter MULTICLONE tubes sets up much higher action—than has the large radius of conventional cyclone tubes. This is why the MULTICLONE separates extremely fine as well as coarse particles with high efficiency!

36 years of specialization in recovering suspensions-starting with the first commercial application of COTTRELL Electrical Precipitation-is behind the MULTICLONE. Let this experience assist you in the efficient solution of your particular recovery problem!

Send for MULTICLONE Bulletin!

SUPERPHOSPHATE PRODUCTION MOVES UPWARD

THE War Production Board has announced that superphosphate requirements for 1944-45 have not been definitely established. The 1943-44 program provided for production of 7,000,000 tons of the fertilizer. It is estimated that by the first of the 1944-45 season, operations will be at the rate of 8,000,000 tons of superphosphate a year, estimated minimum requirements for the year are 9,000,000 tons, however.

A report on WPB-authorized acidulating plants which are under construction has been given to WPB's Inorganic Acids Industry Advisory Committee. The plant at Searsport, Maine, is expected to be in operation by June, while the acid portion of the project at Pocatello, Idaho. has been suspended until certain facts in re spect to another plant are clarified. If sulphuric acid production capacity is increased at Garfield, Utah, which is a waste gas operation, the acid unit at Pocatello may be eliminated.

Members of the committee also were told that the triple superphosphate project originally planned for Beaumont, Texas, has been shifted to Houston. Of the 170,-000 tons of superphosphate to be produced annually by this unit, only about 100.000 tons will be standard. The remainder will be triplephosphate. This plant is designed to operate on spent alkylation acid. Another acid plant which is expected to be in operation about April 1 is that of the American Agricultural Chemical Co. at St. Bernard, Ohio.

Distribution of ordnance acid to southeastern manufacturers in January was 25, 000 tons equivalent to 19,000 tons on a 100 percent basis, while February distribution in the same area will be 26,500 tons. The program for the north is still somewhat indefinite. San Francisco superphosphate plants are now operating at only 50 percent capacity because of lack of manpower.

ACS WILL DISCUSS POSTWAR OUTLOOK FOR CHEMICALS

THE POSTWAR outlook for the chemical industry will be surveyed at a symposium to be held in connection with the 107th meeting of the American Chemical Society in Cleveland April 3 to 7. The chairman will be Dr. L. W. Bass, director of the New England Industrial Research Foundation.

Ralph E. Flanders, president of Jones and Lamson Machine Co., Springfield, Vt., and chairman of the research committee of the committee for economic development, will deliver an address on "Technology and Industrial Management." D. M. Sheehan, comptroller of the Monsanto Chemical Co., St. Louis, will analyze the accounting and financial problems which will confront the industry in the transition period. Dr. W. L. Badger of Ann Arbor, Mich., manager of the consulting engineering division of the Dow Chemical Co., will outline the needs for practical engincering to effect rapid commercial-scale development of new products. John B. Glenn, president of the Pan American Trust Co., New York, and vice-president of the New York Board of Trade and chairman of the Latin American Section, will outline the policies necessary to maintain our international leadership.

Raymond Stevens, vice-president of Arthur D. Little, Inc., Boston, will discuss the more extensive and effective use, of fundamental and applied research which he foresees in the postwar period. Dr. H. S. Rogers, president of the Polytechnic Institute of Brooklyn, will interpret the trends in technical education, with special reference to chemists and chemical engineers.

FAT AND OIL SUPPLY WILL INCREASE IN 1944

TOTAL production of fats and oils from domestic materials in the calendar year 1944 may be about 11.2 billion pounds compared with 10.8 billion pounds in 1943. Stocks on January 1, 1944 were moderately higher than a year carlier and imports are expected to increase in 1944. Hence, the total supply of fats and oils in the United States will be substantially larger this year. Little change is likely, however, in supplies available for civilian consumption. With an increased number of men in the armed forces, military takings will expand. Exports of fats and oils under lend-lease are expected to increase.

CONVENTION CALENDAR

American Gas Association, war conference on industrial and commercial gas, Hotel Seneca, Rochester, N. Y., March 30-31.

American Society of Mechanical Engineers, spring meeting, Birmingham, Ala. April 1-3.

The American Ceramic Society, Inc., second war conference, Hotel William Penn. Pittsburgh, Pa., April 2-5.

American Chemical Society, 107th meeting, Cleveland, Ohio, April 3-7.

The Electrochemical Society, spring meeting, Milwaukee, Wis., April 12-15.

American Institute of Chemical Engineers, semi-annual meeting, Hotel Cleveland, Cleveland, Ohio, May 14-16.

American Association of Cereal Chemists, annual meeting, Nicollet Hotel, Minneapolis. Minn., May 23-25.

American Society for Testing Materials, annual meeting, Waldorf-Astoria, New York, N. Y., June 26-30.

1943 1942 1940

1944

1920 1910

1900

1930

PEERLESS PUMP DIVISION, Food Machinery Corp. 301 W. Ave. 26, Los Angeles 31, Callf. 1250 W. Camden Ave., S. W., Canton 6, Ohie OTHER FACTORIES: San Jose S, and Fresno 16, Calif.

Assembling this 4000-lb. track would be a tough job without Stearns Lifting Magnets. This is only one of many applications for Stearns magnets that help speed production in busy war plants.

Moving large quantities of material in fast time at low cost—guarding hand labor on difficult and dangerous operations, conveniently, safely and economically.

Increasing storage capacities, loading and unloading are a few of the advantages of using Stearns Lifting Magnets.

Let Stearns magnets give you a lift. We make 'em in many sizes and shapes. Why not consult Stearns Magnetic Milwaukee with your problem.

Write for our Bulletin 35.

PRICE ADJUSTMENT BOARD FOR WAR CONTRACTS

At its first meeting, held February 26, the new War Contracts Price Adjustment Board, created by the renegotiation section of the Revenue Act of 1943, which became law on February 25, 1944, established its organization.

The personnel of the new board, appointed by the heads of the agencies involved, is as follows: Joseph M. Dodge, chairman of the War Department Price Adjustment Board, chairman; Laird Bell, chairman of the Navy Price Adjustment Board, vice chairman; Commander Arthur G. Rydstrom, Maritime Commission Price Adjustment Board, who is also representing the War Shipping Administration Price Adjustment Board; Captain Harry C. Maull, Jr., chairman of the Treasury Department Price Adjustment Board; Charles T. Fisher, Jr., chairman of the Reconstruction Finance Corporation Price Adjustment Board, and Carman G. Blough, War Production Board representative. W. James MacIntosh has been appointed general counsel to the War Contracts Board.

The authority of the board applies to renegotiation for war contractors' fiscal years ended after June 30, 1943, while authority of the Joint Price Adjustment Board—established last October by voluntary action of the various individual departmental boards—applies to war contractors' fiscal years ended before July 1, 1943.

RECORD OUTPUT OF PRIMARY ALUMINUM LAST YEAR

THE War Production Board revealed last month that primary aluminum output in 1943 exceeded 1942 production by over 75 percent and amounted to over 1,800,-000,000 lb. Peak production for the year, and probably for the duration of the war, was reached in the last quarter when production averaged more than 185,000,000 lb. a month. Aluminum recovered from secondary sources exceeded 500,000,000 lb. for 1943 and reached a peak of 55,000,000 lb. in December.

December primary and secondary production was almost three times as much as in January 1942, the first month after Pearl Harbor. In addition to domestic production, the United States had available from Canada 262.800,000 lb. of primary aluminum in 1942 and 428.700,000 lb. in 1943.

POWER CONFERENCE WILL DISCUSS WAR PROBLEMS

TWENTY-FOUR speakers are scheduled to address this year's Midwest Power Conference, according to the preliminary program for the 1944 meeting which has just been announced by Illinois Institute of Technology. The third wartime meeting of the conference—and the seventh annual under its present sponsorship—the 1944 session will be held April 13 and 14 at the Palmer House in Chicago. Co-operating with Illi nois Tech in arranging the event are eight other colleges and eight engineering soci eties.

The conference will emphasize both war and postwar power problems.

• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

SIGMA XI HONORS ESSO RESEARCH CLUB

THE Society of the Sigma Xi, national scientific honor society, founded at Cornell University in 1886, with local members organized as chapters or clubs in about 125 American universities and colleges, is extending the fulfillment of its organic purpose of the "Encouragement of Original Investigation in Science, Pure and Applied" by encouraging member group activity in non-academic research institutions which qualify because of their participation in, and encouragement of, original research in science.

The first industrial research group to qualify and be granted affiliation with Sigma Xi is the Esso Research Club, of Elizabeth, N. J., whose membership is drawn from the chemists. physicists, engineers, and other technical research and development personnel of the companies associated with Standard Oil Company (N. J.). Arrangements are being made for the installation of the Esso Research Club by the national officers of Sigma Xi on April 26.

CHATTANOOGA MAY BE SITE FOR NYLON PLANT

ANNOUNCEMENT has been made by E. K. Gladding, manager of the nylon division of E. I. du Pont de Nemours & Co., Inc., that a site near Chattanooga, Tenn., is being considered by his company as a site for a postwar nylon plant. He said that options had been obtained on tracts of land on the north side of the Tennessee River northeast of Chattanooga, below the TVA power project. The proposed plant would be comparable in size to the Martinsville plant. Mr. Gladding further said that the plants at Seaford, Del., and at Martinsville, Va., would be materially expanded.

REICHHOLD RESEARCH WORK CENTERED AT DETROIT

RESEARCH activities of Reichhold Chemicals, Inc., recently have been greatly expanded and reorganized. Personnel in the company's laboratories has been enlarged about 25 percent in the last few months and all research has been centralized at the main plant in Detroit. John J. Bradley, Jr., is director in charge of research. The work has been divided into seven distinct units with A. G. Hovev in charge of research on coating resins; Harry Kline on phenol plastics; Arthur C. Lansing on chemicals; Harold E. Weisberg on chem ical pigments; A. G. Hovey on patents; J. Frank Maguire on market research; and Dr. E. F. Siegel on special compounds.

NEW DU PONT PLANT TO MAKE LUMINESCENT CHEMICALS

CONSTRUCTION started on March 1 at Towanda, Pa., on a new plant for the Patterson screen division of E. I. Du Pont de Nemours & Co., Inc. The Patterson Screen Co., acquired by du Pont last July, has pioneered the manufacture of fluoroscopic and x-ray intensifying screens and will use the new facilities for the production of luminescent chemicals.

CO-RES-CO IS WIDELY USED. It is an accepted method of corrosion control in many industries and official government departments.

WRITE for further data, giving details of your corrosion and maintenance problems for specific analysis.

CORDO CHEMICAL CORP., Norwalk, Conn. (Formerly: Corrosion Control Corp.)

CO-RES-CO

THE PLASTIC CORROSION RESISTANT COATING

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •

Roasting Recovers Valuable Materials

FILTER AIDS—Bethlehem Roasters are used to burn off the impurities in wet diatomaceous muds and fuller's earths, and return them to process with high filtering efficiencies.

CALCIUM OXIDES recovered by roasting from waste lime muds. No interruption of operations. Recoveries of 95% in terms of CaO.

CHEMICAL WASTES and sludges treated for uniform recovery of a premium-priced by-product.

A HIGH GRADE PIGMENT continuously produced in a Bethlehem Roaster, with a Bethlehem Experimental Roaster operating as a processing guide.

Since it first went to work burning pyrites for an acid plant in 1907, the Bethlehem Wedge Roaster has wrought many production benefits in chemical industries, as well as in the treatment of ores and concentrates.

Continuous operation, complete control of temperature and time factors, control of gaseous and solid products of reaction, ease of operation, low maintenance costs, and other desirable operating features, account for this diversity of successful applications.

How Bethlehem Wedge Roasters save process milerials for RE-USE and recover valuable BY-PRODUCTS.

Write for Catalog CM-34 for more facts about the Bethlehem Wedge Roaster. The catalog also describes Bethlehem Thermocoil kettles, nitrators, reducers, sulphonators, vacuum stills, autoclaves, and other processing equipment.

QUALITY OF PAINTS PRAISED BY WPB OFFICIAL

LAST MONTH, at the meeting of the New England Paint, Varnish and Lacquer Association, B. M. Belcher, chief of the paint, varnish and lacquer unit of the War Production Board, vigorously denied that the uality of trade sales paints had been degraded as a result of the enforced use of substitute materials. He admitted that the changing raw material situation which started prior to the war has forced the puint manufacturer to make changes in the formulation of his various products. He referred to the lack of certain resins and oils as a factor in changing the charcteristics of paints and said the present non-availability of colors will further affect the situation.

Mr. Belcher expressed the opinion that paints supplied by manufacturers today are perfectly adequate for the job at hand, which is the protection of property. He further said no evidence was at hand to substantiate the charge that paints have been degraded as a result of Order M-332 while evidence based on laboratory and field tests indicates that paints made under the order are equal to, and in some cases superior to those made under formulating methods prior to the war.

CHEMURGIC CONFERENCE WILL BE HELD AT ST. LOUIS

THE TENTH annual chemurgic conference, held under the auspices of the National Farm Chemurgic Council, Inc., will convene at St. Louis on March 29 for a three-day session. Included on the program for the opening day is a plastics session at which the speakers will be W. E. Parsons, Keyes Fibre Co., Waterville, Maine; Robert Haines, The Dow Chemical Co., St. Louis; P. W. Griffith, American Cyanamid & Chemical Corp., Axusa, Calif.; J. H. DuBois, General Electric Co., Pittsfield, Mass.; and Thomas D. Perry, Resinous Products & Chemical Co., Philadelphia.

The morning session on March 30 will be given over largely to discussions on fibers with papers to be presented by Dr. W. E. Coughlin, Celanese Corp. of America, New York; R. Boyer, The Drackett Co., Cincinnati; and Theodore Marvin, Hercules Powder Co., Wilmington. Among the speakers listed for the closing day is Philip A. Singleton, New England Alcohol Co., Boston, who will discuss the importance of Caribbean molasses in the alcohol program.

WESTERN NEW YORK SECTION AICHE ELECTS OFFICERS

CLARK B. SHEPHERD, assistant manager of new-process development for the electrochemicals department of E. I. du Pont de Nemours & Co., Inc., Niagara Falls. was installed as chairman of the western New York Section of the American Institute of Chemical Engineers in Buffalo, on Feb. 24. Other officers are: vice-chairman, Guy N. Harcourt of Buffalo; secretarytreasurer, Allan G. Hamilton of Niagara Falls. L. J. Murphy of the Westinghouse Electric & Mfg. Co., addressed the meeting.

BETHLEHEM FOUNDRY & MACHINE COMPANY Bethlehem, Pa,

5.

150

BARITE SHORTAGE AFFECTS BARIUM CHEMICALS

PRODUCTION of barite has declined markedly in the face of recent increases in requirements. Stimulation of its production is one of the most pressing problems confronting the War Production Board. The short position of the barite stockpile adversely affects production of barium chemicals, lithopone, glass, and ground barite used in well drilling.

At the beginning of the war there were many small producers in operation and there was a large stockpile of imported material on hand. The situation apparently being well in hand, producers of barite were placed below coal and solid metals when it came to priorities for both equip ment and manpower. Most barite mines are in low wage areas with the prevailing scale for common labor about 40 cents an hour with rates ranging up to 80 cents an hour for truck and tractor drivers and gig men. Barite mines soon lost their men to higher paying war industries.

Late last fall requirements for barite increased rapidly. It will be recalled that in 1942 government policy was to curtail drilling for oil. In the last half of 1943 that policy was abandoned and a tremendouamount of drilling was undertaken at the request of the Petroleum Administrator. It was the unusual demand for drilling mud that brought the barite supply situation to light.

Efforts to increase production followed. New mines in Arkansas came into prominence because of their proximity to the oil fields. In many other sections of the country deposits of barite in commercial quantities have been found. The Arkansas deposits are displaced shale which is separated by fine grinding and flotation. Ceiling prices were set on the Arkansas production to assist in channeling its movement to the oil fields. Ground barite for drilling mud was given a higher ceiling than chemical grades and producers found themselves selling material from the same bin for different prices depending upon the end use. The price differential was effective in getting producers to sell their barite for drilling mud but a further distortion of the supply followed and but little improvement is expected until fall.

DU PONT RENEWS FELLOWSHIPS FOR CHEMISTRY RESEARCH

AWARD of 22 postgraduate fellowships for research in the field of chemistry for the academic year 1944-45 has been announced by E. I. du Pont de Nemours & Co., Inc. Appointments of these fellowships, which amount to \$750 each, will be made later in the year by the heads of the chemistry departments of the several colleges and universities to which grants have been made.

Fellowships for advanced work in chemistry were established by the du Pont company in 1918, when there was a scarcity of well trained chemists. Through the Fellowship plan the company seeks to encourage promising students to follow a career in chemical research. Women are admitted to candidacy on the same basis as men.

... controlling the flow of material saves man-hours and makes certain that delivery schedules will be met

On the playing fields of sport and on the field of battle — sucsess depends on *timing*, rhythm of motion. Timing is a vital element in production, too.

Having the right material at the right place at the right time just enough of it and not too much — is a characteristic of efficient production.

Keeping production synchronized — timed — involves planning all along the line, to relieve congestion at one point, speed up movement at another, to the end that goods will be produced with precision and speed, and at an economical cost.

Conveyor engineering, applied like Standard does it, accomplishes all these things. If you feel that *timing* could be improved in your plant — check with Standard.

"Conveyors by Standard" — Catalog No. CM-3 is yours for the asking. Why not write today?

IT CAN BE DONE IN MOST IN STANCES. But it means better and mor. EXACT DESIGN and perhaps HIGHER TEMPERATURES.

FOR CHEMICAL PRODUCTS

embodying the use of ROSS Air Heaters, direct or indirect, oil or gas fired, will give you the needed EXTRA heat, the required EXACTING control—the greater SPEED with absolute SAFETY. Four major essentials in a single system.

Modern Testing Laboratory

The ROSS Laboratory is one of the finest in equipment and facilities for determining correct conditions for treatment of your product.

CHICAGO 201 N. Wells St. DETROIT 12953 Greeley Ave. ROSS ENGINEERING OF CANADA Ltd., Montreal

NEWS FROM ABROAD

POSTWAR DEMANDS OF BRITISH AGRICULTURE MAY INCREASE USE OF FERTILIZER CHEMICALS

Special Correspondence

THIS THE RIGHT PUMP

FOR THE PROCESS ?

PROBLEMS OF fertilizer production have attracted special interest in British chemical quarters, partly because the wartime needs of increased food production in the country have accentuated the importance of regular replacement of fertilizer clements withdrawn from the soil, and partly because the postwar demands of British agriculture promise to open an outlet for chemical trades which are now concentrating on the production of ex-plosives and other means of warfare. Apart from this, it is realized that after the war many overseas countries, especially in the colonial territories, will require larger supplies of chemical fertilizers to make up for shortages during the war and to make possible more intensive methods of agriculture.

Unfortunately Great Britain is not favorably placed with regard to chemical fertilizers. There are no deposits of potash or phosphates in the country, and the sources of hydroelectric power for the production of synthetic nitrogen compounds are limited and not yet fully developed. As far as potash is concerned, wartime supplies are mostly of United States, Spanish and Russian origin, but the Russian product often arrives in a rather damp condition, with consequent trouble in operations, so that manufacturers prefer United States potash salts. Russia also supplies England with apatite concentrates, and another im portant source of phosphates has been opened up with the occupation of North Africa. As far as sulphur is concerned, all supplies for England are still reported to come under lend-lease arrangements from the United States, while Spain is covering British requirements of pyrites. No information is yet available with regard to Sicilian sulphur. But since the Mediter ranean is now open to Allied shipping, it may be expected that Sicilian sulphur, Palestinian potash and other chemical raw materials from that region will play a more important part in meeting British needs.

While the importance of potassium and phosphorous for fertilizing is not underrated, the authorities have been compelled to concentrate on the provision of increased tomages of other fertilizer materials. Vast quantities of lime have been supplied to farmers, and the consumption of ammonium sulphate and other nitrogen compounds reached an all-time record in 1943. Since supplies are smaller than demands, it has been necessary to restrict their use to applications where they give best re-

—the right size, type, material, drive?...if not,

IS

we're sure to have the right one. We've been making pumps for over a quarter of a century, and can supply pumps for every process need. Available in stainless steels, acldresistant bronzes, nickel, lead or any required alloy; in horizontal or vertical types and in any combination of single or double

THE

ght one. We've been a quarter of a cennps for every process inless steels, acidit, lead or any retal or vertical types of single or double The formula is a suction and single or multi-stage; in direct connected, belted, chain or geared drives. Of rugged construction---guaranteed to meet the conditions for which they are sold. Call on us next time you need pumps for process work. TRON & STEEL CO. Frederick Meet

sults. Balanced fertilizers have been introduced, and certain compounds are supplied only for use on certain crops. Such wartime measures are however temporary, and there is no doubt that British farmers have become fertilizer-conscious, while systematic wartime tests have shown the vast scale of the need for chemical fertilizers to obtain optimum results.

For postwar days continued progress on wartime lines is anticipated. More attention than ever will be devoted to the way in which chemical fertilizers are to be applied. Granulation has made great advances, and may indeed be required on a large scale to overcome the farmers' prejudices based on the unattractive form in which fertilizers usually reach them. Another feature which is likely to attain in-creased importance is the standardization of chemical fertilizers, especially of compounds. Both developments-granulation and standardization-help to reduce the storage problem which has caused some difficulties in British fertilizer manufacture and application.

INTERNATIONAL CONTROL

While a steady expansion of fertilizer consumption in overseas countries is ex-pected after the war. British fertilizer in-terests believe that international market control will be necessary to avoid the evils of overproducion and excessive compe-tition. In the case of potash the export markets were before the war controlled by the German-French-Polish cartel, and a limitation and regulation of potash exports from Continental Europe also may be necessary after the war. In the case of phosphates the supply position will of course depend to a large extent on the position in the Pacific and shipments from Nauru and Christmas Islands, etc. As far as nitrogenous fertilizers are concerned, some control was exercised by the European cartel, which cooperated with the Chilean export organization, but in future this arrangement is unlikely to prove sufficient unless agreement is reached with the United States and Canadian producers. Yct, systematic market development should permit a vast expansion of sales. For In-dia, for instance, it is estimated that the prewar consumption, which has fallen to less than one-third during the war, could be trebled or quadrupled. Present production of sulphuric acid in

Great Britain is estimated by P. Parrish at over 2,000,000 long tons a year. The output of spent oxide has reached about 220,-000 tons (equal to about 100,000 tons of sulphur), and something like 120,000 tons of 70 percent acid is being made from anhydrite. These figures reveal a considerable increase over prewar tonnages. No further information has been re-

ceived about the synthetic rubber project of British Celanese Ltd. At the annual meeting of the company's shareholders the chairman confined himself to the remark that "we have been active in this field for many years, and all the known synthetic rubber products, and many up till now unknown, will be produced by us". The company has usually preferred its own counsels, and reports substantial progress also in the field of synthetic fibers. It states that it is now able to produce fibers with a strength of 11 grammes per

A TOLEDO CONTROL INSTRUMENT

• Toledo Scales weigh-count-measure-control both fluids and solids. So doing, they monitor production and accumulate Control Facts which are vital to the maintenance of quality and the accurate determination of costs. They are the Silent Sentinels of Production.

Behind their quiet efficiency stands TOLEDO RESEARCH -the coordinated activity of the largest engineering-research group in the scale industry.

Toledo Research, prewar, had up its sleeve many developments in the fields of applied electronics and optics, which have helped to make War Things better, and faster.

Toledo Research, postwar, will help build a better world through the more accurate and rapid measurement and control of materials ... Toledo Scale Company, Toledo, Ohio.

dustry, postwar. Hundreds of war plants are using them. We are at liberty to send you complete information por

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •
MOLDED PLASTIC HAVEG AGITATORS

HAVEG itself is acid-

and alkali-resistant throughout its entire mass. It may be molded to shape on metal shafts without involving expensive molds. Four standard types of agitators are illustrated. These are typical of the almost infinite variety of designs and types of agitators which can be molded from HAVEG.

Figure 104: This integrally molded pitched blade agitator for relatively high shaft speeds is usually supplied in diameters up to 2' 6'.

Figure 103: A plain, slow-speed, integrally molded, single - bladed agitator which is satisfactorily used for agitating free-flowing liquids and thin sludges. The blades can be supplied pitched or vertical. Figure 105: HAVEG Agitator with

demountable blades. A highly desirable design where abrasive conditions may make it necessary to replace blades. This type of blade may also be used to add blades to an agitator already in service.

Figure 106: A heavy-duty HAVEG Agitator. Has vertical double blades, thoroughly braced. They are also demountable. This type agitator has been made up to 6' in diameter.

METAL SHAFTS-HAVEG COVERED

In all or of HAVEG AGIANOTS the shaft itself is made of metal-and overed with HAVEG. This HAVEG covering is free to expand and construct. The positive method of attaching the HAVEG at the boxom is clearly shown in the illustrations. The hidesthemselves are always solidHAVEG. HAVEG Ballenn gives compared MAVEG-SARAN

HAVEG Balleon rins, design and appiration data on all pipes of HAVEG equip-ment. Tanks, Towers, Pipe En-mass. Doct and many others. Send for a corr.

abong Pipe & ittings: and wets are avail-HAVEG-SARAN - B. enin F.s. al for a coirs



FIG.

104



denier, compared with previous values of 6 to 7 grammes and 4 to 6 for nylon. The company is "busy on many other completely synthetic products, including those made from coal and hydrogen, with or without nitrogen" which may also be used in the textile industry for certain specific purposes. British Celanese thinks that it will be in a position to produce them as the need arises on the basis of its own processes. In this connection the company is arranging to produce all the intermediate chemicals needed for such final textile or other products, independent of any agreements of international character.

The field of synthetic resins is attracting increased attention also from the paint industry. One of the leading paint manufacturers, Lewis Berger and Sons Ltd., has formed a subsidiary, Berger Plastic Developments Ltd., to concentrate on this field of activities which "taking a long view, will provide additional carning capacity" The company reports that it has increased its production capacity in the paint field by attention to new methods and improved technique. As a result the production in factories of the parent company reached a volume greater than the previous high level established last year. Successful special investigations were carried out last year for , certain government departments.

The leading British producers of zinc pigments have formed the Zinc Pigments Development Association to encourage and develop the uses, actual and potential. of their product, particularly by making their properties and applications more widely known and appreciated. The asso ciation is non-commercial in character and stresses that it has no interest in pricefixing or similar matters. It will work in cooperation with the Zinc Development Association. The list of founders contains the names of eight firms.

PENICILLIN SUPPLIES

Supplies of penicillin in Great Britain are still so small that "it is a sort of corpse-raising drug at present", as Prof. Dr. H. W. Florey of Oxford University told the Royal Institution. Arrangements have been made by the Ministry of Supply to produce as much penicillin as possible, but for some considerable time to come the total supply will be insufficient even to meet the requirements of the Services so that none can as yet be released for civilian 1150

Alksthene, the I. C. I. polythene pro duced by subjecting ediviene to entreme conditions, is now used in the manufacture of cables and accessories, especially for high-frequency and high-voltage work. where its resistance to water and chemical strack added to its electrical properties have proved very vibable. Small case times or polytheme added to wares mise their making point and reduce any bandency to emcking or niking. Its good water resistance is recommended in connection with its one for wripping material especially for hot and humid atmospheres. Polyischardene mer be used as a past ciner in connections with polytheme.

The large number of moth moning agents accurate out during the past twen was has caused the Wool Incusting Research Association to can't out a sestemation

investigation into their merits. Triphenyldichloro-benzyl phosphonium oxide and similar products are believed to be the active constituents of certain agents which combine good moth-proofing qualities with fastness to washing. Many patented mothproofers are substituted ureas in which the substituents are aromatic groups, e.g. diphenyl ether, containing chlorine and a sulphonic group to confer solubility. Since many of the recognized moth proofing agents are aromatic compounds of high chlorine content, pentachlorophenol has been studied and found to give satisfactory results when suitably applied, although, like fluorides, it is substantially removed by washing. Material moth-proofed with formaldehyde, with hydrochloric or sul-phuric acid to give the requisite pH, washed with cold water, and neutralized with dilute sodium carbonate, also showed good resistance to larva attack. While fluorine products in general suffer from the drawback of insufficient fastness to washing, improved results in this respect have been obtained with chromium fluoride with or without antimony fluoride, adjusted to leave the equivalent of 0.65 percent of chromium fluoride in the dried material. Claims for fastness to washing for fluosilicic acid used in conjunction with triethanolamine and aluminum sulphate and for impregnation with a solution of a fluosilicate of a polymeric nitrogen-contain ing substance seem not to have been examined.

The Ministry of Supply has advised motor vehicle users that there are now six brands of commercial anti-freeze mixture available which may be bought without restriction. The solutions must however be regarded as wartime substitutes and give reduced protection (down to 20 deg. F. only). Moreover, they have slightly cor-rosive action on solder, mild steel, aluminum and aluminum alloys which need not however affect the efficient running if manufacturers' instructions are followed. Tetrahydronaphthalene is now being

used in Great Britain largely as a substitute for turpentine and it is thought likely that it will remain a serious rival to natural turpentine after the war because of its greater solvent power and high flash point. Very large quantities of naphthalene are said to be converted into the tetrahydro derivative, according to the president of the Midland Section of the Coke Oven Manufacturers' Association.

OUTLOOK FOR BABASSU AND CASTOR OILS IN BRAZIL

NO APPRECIABLE quantities of babassu oil are expected to be available for export from Brazil in 1944, according to semiofficial sources. During recent years babassu oil production in Brazil has not exceeded 7,000 metric tons, and stocks have been reserved almost entirely for domestic consumption. Moreover, relatively high prices for other oils have increased the use of babassu oil by the soap industry.

The Federal Council of Foreign Commerce recently publicized a proposed project for the increase of babassu oil production by using oil-crushing plants. If the 1943-44 castor bean crop in

Brazil is similar in volume to that of the



OUR ENGINEERS will recommend the type of flexible tubing most adaptable to these uses-

- 1. For conducting liquids from a vibrating to a stationary medium.
- 2. For high fatigue resistance under constant vibration.
- 3. For handling searching liquids without seepage.
- 4. For extreme temperature conditions.
- 5. For use where corrosion resistance is a factor.
- 6. For conducting liquids and gases to reciprocating parts.
- 7. For maximum flexibility with a minimum of length.
- 8. For dampening noise between two units that must have pipe connections.
- 9. For correcting misalignment.

Flexible Metal Hose CONTROLS IT

Chicago Metal Hose Corporation's **REX-WELD** is highly resistant to fatigue even when subjected to constant vibration over long periods of time. It is extremely flexible and remains airtight and leakproof after years of hard usage. It stands up under high temperature and prolonged flexing. REX-WELD is fabricated from strip metal and is precision autogenous welded to form a weld stronger than the tube itself. Write, giving complete information and we will be glad to furnish engineering recommendations for any design problem.

Flexible Metal Hose for Every Industrial Use



155



TOMORROW'S NEWSPAPERS via MORRIS Pumps

These stacks of pulpwood . . . and many, many others all over the country . . . will soon be converted into newsprint and other kinds of paper in mills equipped with MORRIS Centrifugal Pumps.

Today ... as for two generations ... MORRIS Pumps have made records of economy and efficiency in handling heavy pulp, liquors, chemicals, and clear water. Mills and chemical plants that have tried MORRIS Pumps quickly standardize on them . . . because of the authoritative recommendations of the long-experienced MORRIS engineers, the large line of MORRIS Pumps for every type of service, and the 80-year record of MORRIS Centrifugal Pumps for trouble-free service and low operating costs.

Write for Bulletin



ST-P Non-clogging Pump - Guaranteed Non-binding for Pulpy Mixtures

MORRIS MACHINE WORKS Baldwinsville, N. Y.



Double Suction Horizontally Split Pump for Clear Liquids



1942-43 season, there will probably be from 70,000 to 80,000 metric tons of castor oil or oil equivalent, available for export.

The 1942-43 castor bean crop estimate was 250,000 metric tons, which would make it the largest recorded in Brazil. Present indications are that the current crop will be comparable.

CARBIDE LIGHTING USED IN SWEDISH RURAL DISTRICTS

CARBIDE lamps are being used exten-sively in Sweden in isolated communities and rural districts which are not supplied with electricity and which formerly depended largely upon kerosene lamps and wax candles for lighting. The war has curtailed the importation of kcrosene (the last significant shipment reached Sweden in 1940) and also the raw materials used in making candles.

To solve the lighting problem, approxi-mately 400,000 carbide lamps are re-ported to have been manufactured in recent years. Ten factories are engaged in their production, and it is understood that practically all the carbide being used is obtained locally.

SWITZERLAND REGULATES SOAP PRODUCTION

THE Swiss government's regulations concerning soap production provide that laundry soap must be composed of 60 percent fats and can be manufactured only in pieces weighing 100 grams. Scrubbing soap and hand soap, whether in tins or in cake form, cannot contain more than 30 percent insoluble matter. Rationed soaps and substitutes, the specifications continue, must bear the producer's name either on the package or the soap itself, and, in the case of the latter, the word "Substitute" must be printed on the wrapping or con-tainer. Certain standards have been set up, also, as to the ingerdients in substitute soaps.

VEGETABLE OIL PLANT UNDER CONSTRUCTION IN TORONTO

A \$2,500,000 plant for the extraction and processing of soybean, linseed, and other vegetable oils is under construction in Toronto, Canada, according to the Canadian press. Immediate construction will include a \$400,000 storage plant, with a capacity of 450,000 bu., and a screw-press process section. It is believed that produc-tion will begin by the middle of 1944.

The first operating section, the screwpress process, will use approximately 3,000 bu. of soybeans daily, and the second section, a solvent-extraction process, approximately 4,000 bu.

BRAZIL PLANT TO PRODUCE DEHYDRATED CASTOR OIL

A MONTHLY capacity of 60,000 lb. of dehydrated castor oil is the expected production of a plant to be erected in Brazil. The process, evolved in Brazil, require heating the oil in an atmosphere of inert gas and in the presence of an acid catalyst About 4.7 percent of the combined water is removed in this manner.

ACETANIL_DE MANU JACTURE IN SWEDEN

MANUFACTURE of acetanilide was started by the Swedish chemical concern, Bofors, several years ago. Production has been increased from 30 to 40 tons annually to about five times that amount. This development is expected to be important in the manufacture of sulfanilamide preparations.

Acetanilide is not a wartime product in the usual sense. Its manufacture is the result of long-range planning intended to convert production facilities of the Bofors Co. to more diversified peacetime civilian requirements.

NEW ZEALAND MAY PRODUCE WAX FROM PEAT

A wax, similar to montan wax, obtainable from peat in the Chatham Islands, New Zealand, has been investigated by the British Imperial Institute. Among the conclusions reached after a chemical examination were that it melts at 10 deg. C. lower than montan wax; that peat wax could be used as boot polishes; and that consideration should be given to extracting the asphaltic content by a petrol process.

Previous tests of New Zealand peat as a wax were undertaken by the Institute in 1926. Shortages of wax as a result of wartime conditions have resulted in renewed interest in this development.

FIVE RAYON PLANTS OPERATE IN STATE OF SAO PAULO

BRAZIL's rayon production is said to be centered in five plants in the State of Sao Paulo. In 1942, these mills had a combined output of 8,092,244 kg. of yarn. comprising 5,746,753 kg. of viscose yarn. 1,701,533 kg. of acetate, 32,375 kg. of cuprammonium and 611,800 kg. of staple fiber. The entire production reportedly is used within the country—25 percent for hosiery and knitted goods, and most of the remainder for dress goods, hat bands, and ribbons.

JAMAICA EXPANDS PLANS FOR MAKING ALCOHOL

CONSTRUCTION is expected to commence soon in Jamaica, British West Indies, on the proposed pilot plant to manufacture ethyl alcohol from rejected bananas. Erection of five other factories will follow, and it is anticipated that these plants will absorb about 3,000,000 stems of bananas annually, or whatever surplus remains above local and export requirements.

GLYCERINE FROM MOLASSES PROVES UNECONOMIC

THE manufacture of glycerine from molasses by a fermentation process has been abandoned by National Chemical Products, Ltd., of South Africa, states the company's annual report. Whereas glycerine of high quality, suitable for making dynamite, was produced, the process proved meconomic, it is stated. The yield was ower than had been estimated and filtraion offered a difficult technical problem.

Presenting the New WILLSON MONO *Goggle*

The latest development in plastic eye-protection . . . combining safety, unobstructed vision and the highest degree of comfort.

NOTE THESE ADVANTAGES

himmer best

 Weighs only 1¼ oz., lightest goggle of its type
 Crystal-clear plastic lens

3. Lens is non-shatterable

4. Lens is replaceable

5. Eye-nose shield an integral unit, leaving no open danger spots

6. High impact-resistance

7. Comfortable over glasses

 Rolled edge makes smooth contact with face
 Scientifically ventilated

10. Easily adjusted



REASONS WHY ... ACME Patented MULTI-JET BAROMETRIC CONDENSERS OPERATE WITH MAXIMUM ECONOMY/



CONDENSER FOR EVAPORATORS



VACUUM COOLING SYSTEM



Designed for vacuum processes where the condensate is not retained, the Acme Patented Multi-Jet Barometric Condenser combines the economies of both wet and dry operation. This patented unit offers the following exclusive features:

- COUNTER-CURRENT FLOW that produces higher vacua (hitherto feasible only with dry operation).
- 2 CONVERGING JETS that expel the incondensible gases from the top of the condenser without the use of vacuum pump or ejector (the principal advantage of wet operation).
- 3 A PATENTED SEAL that prevents the escape of vapors until they reach the top of the condenser, thus making it possible to combine advantages (1) and (2) in one piece of equipment.
- 4 POSITIVE CONTROL of both involute and converging jets that attains maximum condensation at a minimum expenditure of water, even under fluctuating loads.
- 5 LOW INITIAL COST of equipment and installation.
- 6 SIMPLE DESIGN includes no moving parts, will not clog, and requires virtually no maintenance cost.

7 CONVENIENT OPENINGS for quick, easy inspection.

Bulletin MJ-44 "Acme Patented Multi-Jet Barometric Condensers" sent upon request

Where vacua over 27" Hg. are to be attained, we recommend the use of an Acme Counter-Current Barometric Condenser with suitable vacuum pump or ejector. The complete Acme line embraces every important type of condenser and ejector. Our engineers are prepared to study the requirements of any process and to make suitable recommendations for the most efficient operation.



FROM THE LOG OF EXPERIENCE-

DAN GUTLEBEN, Engineer

A VISITING "SOOP" remarked that a few days ago he had discovered in his refinery a long 6 in. copper pipe that had been installed by his predecessor to test out a proposed process short-cut. The theory and the practice did not harmonize and so the valves were shut off and the pipe was forgotten. The pipe fitter was cautioned "Don't take it down, we might need it some day." The predecessor retired 30 years ago. Brainstorms come The predecessor and go and sometimes they strike a bonanza. However, when some piece of apparatus becomes obsolete, it should be removed on the basis of "pro bono publico" which, being liberally translated, means that a little vacant space in a plant that is continually developing and changing is better than a space cluttered up with idle equipment. The house, like an unpruned tree, eventually becomes overwhelmed with dead branches and growth is hampered thereby.

IN FOOD AND SHIRTS the popular color is white. To attain whiteness in sugar, the syrup was formerly blown up with ox blood furnished from neighborhood slaughter houses. Emil Claus, Chief Engineer of the Edgewater Refinery (Ret.) entered the refining industry by way of the blow-up station at the Dick plant in New York in 1885. Blood was still used as a coagulant of impurities. The operators of the refinery had walked out without notice and left the blood and syrup to revert to basic elements, accompanied by the evolution of an impressive stench. The use of bone char and decolorizing carbons was a great improvement both technologically and psychologically. For sugar refining, bone char still possesses the preference over activated carbons. It has the ability not only to decolorize, but also to absorb ccrtain salts and acrid aromas. This latter property is employed when medical practitioners prescribe charcoal tablets for a sour stomach. Bone char adds a heavy financial burden on the refinery. At present prices the char in process in an ordinary refinery may reach \$400,000 in cost and the equipment investment runs to about a million.

The mystery under which bone char performs its work has not yet been subjected to a clear-cut elucidation comprehensible to a run-of-mine engineer. For at least a half century the mechanical procedure has remained stationary. The only spectacular improvement was the thin stainless steel retort tubes contributed by Paul DeVries of Revere. Everybody is kicking about the awkwardness of the process. The chronicler sat in on a symposium wherein a group of chemists, with special emphasis, prefaced the discussion with the admission that they knew nothing about char. Then they read a verbose paper on the subject and followed with a two-hour debate! Q.E.D.

AT THE LABORATORY of the Drexcl Evening School, Lab apprentice Carter was conducting a test that required the use of H_2SO_4 . His eyes were intent upon the reaction while holding the test tube of acid in his hand. Under these circumstances he

Here is the balance of the setting-up routine followed by your chronicler. See Chem. & Met., Feb. 1944, p. 201 for first ten exercises



suddenly sensed that a mosquito was exploring about his neck, in scarch of a promising spot to set up operations. Carter reflexively obeyed the impulse to strike first and unwittingly dumped the test tube down his back. While he was at the hospital growing a new slab of skin on his back, he was bemoaning the destruction of his new silk shirt. The mending of this did not proceed by nature's munificence. It required the cash of the realm. On the other hand, his dad discharged the hospital bill.

WISDOM TEETH, crowded in the amen corner, get little exercise. They are the last to come and the first to go. Our electrical Wizard shared the common experience and when distress appeared, he had the upper ones removed. Later the lower ones suffered as a result of "innocuous desuetude." A youthful practitioner, appreciating the value of building up a backlog of custom, maintained the teeth by various treatments and an occasional filling. After enduring 10 years of expense, the Wizard at "long last" perceived the purposelessness of a pair of tongs with one jaw missing and so he got himself a new dentist and had the lower wisdom teeth removed.

CHEMICAL MANUFACTURERS accompany their products with the privilege of the free advice of their staffs to guide the users. The customer accepts this as his perquisite and calls on the manufacturer's "Doc" whenever some problem perplexes him. The respect which the proffered assistance inspires can be enhanced by special technique. The customer propounds a problem puzzling to himself but it is elementary to Doc by reason of his 30 years or more of effort and experience. Does Doc spit out the answer spontaneously? He does not. His pearls of experience are not thus lightly to be cast away. He knits his brows professionally and hesitates; then he announces gravely that the problem will require thought and research. He reckons that he may be able to evolve a solution in a couple of weeks. Accordingly he marks his calendar and proceeds to forget all about the matter till the memo pops up a fortnight later. Then he calls up the customer and delivers himself extemporancously of the answer. The customer values the answer, knowing the time and study that it called forth. And Doc's hokus-pokus gains the desired compensation in the way of good-will for his House.



"You may be interested to know," wrote an official of a West Coast manufacturer, "that our Deming Water Lubricated Deep Well Turbine Pump has been operating continuously, 24 hours per day for the past 27 months without interruption, delivering about 220 gallons per minute to our plant.

"We have not spent one cent for repairs and the pump is running as smoothly and efficiently as the day it was installed. We are convinced that the Rubber Bearings with water lubrication are largely responsible for this outstanding performance and freedom from interruption of service."



Ask for Catalog No. 4700-8

This special catalog on Deming Deep Well Turbine Pumps is available from the Deming Distributor in your locality, or from The Deming Company, Salem, Ohio.

Deming Turbine Pumps are designed to deliver capacities from 15 to 3000 gallons per minute. Vertical hollow shaft motors are standard construction. Where required, other types of heads can be furnished such as: belted drive heads; gear increaser heads; steam turbine heads; flexible coupling heads; or combination type heads.



BAG FILTERS constituted the common device for filtering sugar liquors up to about 1919. One of the 12-hour shifts was conducted under the profanity of Sergeant Jack McGahan. He was in command of an assortment of foreigners who mand of an assortment of foreigners who had only a few years carlier escaped slavery in Europe. By comparison, their new job was an improvement. Jack's profanity was about equal in volume and differed only in that it contained fewer sneezes. The filters did an excellent job but the bird operating costs were endured but the high operating costs were endured only because there was nothing better to When Sweetland filters and be had. eventually Vallez' replaced the old bags. Srgt. Jack joined the pipe fitters' gang. He resembled more or less any conventional style of pipe fitter except that, having been a top sergeant in the regular army, he was crankier than the rest. He became the trouble shooter and under this classification his task demanded jumping from hither to yon on emergency repairs. Every time he was called for a hurry-up job. he exploded. Never-the-less, in spite of all his cussing and obstreperations, he always dispatched the job. Occasionally, he celebrated too hilariously at the club and skipped work the next day to nurse the hangover. One day the master fitter decided to reduce his gang and his cycs fell upon "Uscless", an inefficient attache who suffered from synthetic hookworm. However, when the fitter counted noses, he found that Useless was present and Jack was not. The ax therefore decended upon Jack. A few days later, by special request of the Chronicler, Jack was returned to the gang. His Irish humor was an asset to the House. He was the counterpart of the stubborn one in the parable of the two sons. The first one "answered and said, I will not: but afterward repented and went." It was agreed that he possessed qualities superior to those of the second who curried favor by answering "I go, sir: and went not."

TANKERS have been delivering molasses from the Tropics to our tank farms for the past twenty years. The No. 2 farm is located on a dark alley a quarter mile from tidewater, being connected by means of a 15 inch pipe under Delaware Ave. The tanks are 60 feet deep and the aggregate capacity of the four is 12,500,000 gallons. There has never been an overflow of these tanks even when the Cubans were pumping molasses into the cubans were pumping monasses into the tankers at one-eighth cent per gallon and sometimes letting gravity feed it to the sharks; that is, never except once, and that was when the war price had gone to 18 cents. On that occasion, 40,000 gallons oozed out of the vent in the roof and collected within the dykc. Most of it was later recovered. The superintendent made search for the cause. The tank man had the answer. When he awoke he announced that there was more room outside of the tank than inside! C'est la guerre.

EARLY MONDAY MORNING when the No. 5, 1000-K.W. generator went on the line, there was a suspicion of burning rubber in the air. Everybody in the Power Plant went about sniffing for the origin. There were some short rubber wires on the generators but the switchboard instruments indicated no distress. Nevertheless, the boys feared the worst and so they sensed increased concentration of odor near the big generator. The Wizard stationed an electrician at the board prepared for quick action. The attaches became jittery. After 8 hours, when the next shift came on, the oiler pointed out a new rubber gasket that had been installed during his shift in the hot discharge pipe of the air compressor during the Sunday shut-down. The compresser was started at 7 A.M. and by 7:30 the pipe had reached vulcanizing temperature thus emitting the extremely distressing odor.

COPPERSMITH Joe Dvornvich fashioned a wondrous device of copper, and the photograph in the log shows Joe standing beside his handiwork. The device was a steam sparger which the boys dubbed "pretzel" when they installed it in the bottom of the "beer" still where it thereafter made possible the substitution of surplus exhaust steam for live steam from the boilers. ("Kernal Kirk" thought well enough of it to present it to the readers of Chen. & Met. January. 1938, p. 78). Joe was given a copy of the log. When the subsidized war plants began to exaggerate wages so as to draw out the men developed by the little plants, Joe took his copy of the log and picture to a large shipyard employment officer, and was hired instanter as a Class A artificer in copper. Our house thus lost Joe for the duration.

THE CHEMISTS ARE CONVERTING sow's cars into silk purces, wherein they exhibit superiority over the employment manager. Mentalitics not technologically inclined have to be developed to function in mechanical arts. The girls taken from the household have to learn to leave their knitting and their favorite movie magazine at home. A "bo" rejected as military material replaces an experienced oiler who has gone forth. Among the new oiler's assignments is the re-filling of four gear cases on rotary pumps that deliver molasses and wort in the distillery. Nearby is the molasses weigh tank with a convenient sample cock and bucket at the bottom. Black strap molasses resembles 600-W oil in appearance and viscosity and so the oiler saw no reason for going to the store room 200 feet away when a substitute was right at hand. He therefore filled the four gear reducers with blackstrap. After four motor starters had burned out the electricians discovered the cause.

SIMILAR EXPERIENCES were lived through in the last war. A crew had to be broken in for the new beet sugar house at Hooper. Utah in 1919. For the engine room job a farmer was selected who claimed proficiency as hostler to a threshing machine engine. On the second day of plant operation, the main bearing burned out. The farmer was flabergasted. He had oiled every bearing but that one. He could not understand why the principle that he had learned as an average adjuster among the neighbors failed to apply.

EVERLASTING VALVES

STRAIGHT THROUGH BLOW

TYPICAL SERVICES WHERE EVERLASTING VALVES

EXCEL . . .

Outlets of storage and measuring tanks Throttles of hammers and hoists

Presses for plastics

Washers for laundries, cleaners and dyers.

Spray lines to rolls

Blow-offs of condensers, economizers, vulcanizers, purifiers, compressed air tanks

Suitable for acids, alkalies, caustics, cellulose, coal tar, emulsions, syrups, and other liquids; also gases and vapors The many important advantages of the Everlasting Valve . . . its drop-tight seal, its self-grinding action at each motion, its provisions against damage to disc and seat, and its "everlasting" wearing qualities . . . make these valves literally unequalled for many services on process lines, emergency shut-offs, equipment outlets, boiler blow-off, etc.

NOTE THESE FEATURES

Straight-through blow Does not stick Maintains initial tightness Meets all State Boiler Laws and all requirements of A.S.M.E. Code Proven by over 30 years of service FULLY GUARANTEED

Write for Bulletin

EVERLASTING VALVE COMPANY 49 FISK STREET JERSEY CITY 5, N. J.



The Quality of DICALITE FILTERAIDS

A view from one of the Dicc lite deposits, showing th exceptional purity of th diatomaceous silica from which Dicalite filteraids ar processed.

started here some 4,000,000 years ago

The quality of Dicalite filteraids began with the original diatom structure—"tailored" by Nature in form and purity most suitable for a filtration material. This natural advantage is enhanced by modern methods of processing, continuously controlled and improved by laboratory research. Because they give desired clarity at higher flowrates, Dicalite filteraids increase the total throughput of liquor per unit of time. Maximum output with thorough removal of impurities, insures high quality production at lower cost.



NINE GRADES of Dicalite filteraids, shown on the chart above, give desired clarity and a range of flowrates to insure maximum production at lower cost.



FILTERAIDS . FILLERS . INSULATION . ABSORBENTS . ADMIXTURES

THE DICALITE COMPANY

520 No. Michigan Ave., CHICAGO • 120 Wall St., NEW YORK • 756 So. Broadway, LOS ANGELES

JOBBERS AND OFFICES IN PRINCIPAL CITIES OF U.S.A. AND REPRESENTATIVES IN FOREIGN COUNTRIES

NAMES IN THE NEWS_



G. E. Barton

George Barton has retired after nearly 48 years of service with the Whitall-Tatum Co. and its successor, the Armstrong Cork Co. Mr. Barton is a charter member of the American Institute of Chemical Engineers and one of the oldest living members of the American Chemical Society.

A. H. Reu, acting plant manager of Hercules Powder Co.'s Brunswick, Ga., naval stores plant, has been named manager. He became acting plant manager of the plant in 1940 when R. Rockwell, plant manager, went to Chattanooga, Tenn., as Hercules plant manager of Volunteer Ordnance Works.

D. A. Hurst, formerly of the Research Division of the Barrett Division, Philadelphia, is now with Rohm & Haas Co. as a technical assistant. Mr. Hurst took his graduate work in chemistry at the George Washington University and his undergraduate work at Albion College, Albion, Mich.

Selwyn G. Blaylock, president and managing director of the Consolidated Mining and Smelting Co. of Canada, Ltd. of Trail, B. C., has been elected an honorary member of the American Institute of Mining and Metallurgical Engineers.

Roger C. Bascom has joined the technical service staff of Hycar Chemical Co. and will serve New England, eastern New York State and northern New Jersey. Mr. Bascom, who came to Hycar from Standard Products Co., where he was chief chemist, will make his headquarters and residence in Milford, Conn.

N. M. Barnett has been named manager of the Chicago branch office of Bailey Meter Co. to succeed M. Greenberg who resigned Feb. 1.

Charles P. Blinn, Jr., has been appointed vice president in charge of finance for the Publicker Commercial Alcohol Co. of Philadelphia.



F. A. Abbiati

F. A. Abbiati, who has held the position of assistant general manager of sales for the Plastics Division of Monsanto Chemical Co., Springfield, Mass. has been named director of sales for the division.

William E. Harrison has been appointed assistant fuel engineer for Lukens Steel Co. and subsidiarics, By-Products Steel Corp. and Lukenweld, Inc. A graduate of the University of Pennsylvania, Mr. Harrison joined Lukens in 1934.

Thomas H. Flaherty has been appointed head of the construction and engineering department for the five American-Marietta Co. plants. He will direct the paint company's building expansion program. Mr. Flaherty was formerly with the Austin and Koreschell Engineering Cos.

Henry M. Richardson, formerly with General Electric Co., has established himself as a consulting engineer on plastic products with headquarters at Pittsfield, Mass.

W. B. Rose, has been made division chief of the Charleston Research Division, Westvaco Chlorine Products Corp. W. T. Nichols, formerly Research Division Chief at Charleston has become technical assistant to the executive vice president. A. G. Aitchison, formerly assistant technical director, has been appointed technical director.

H. W. Catt has been appointed manager of the chemicals and pigments department of the purchasing division of The B. F. Goodrich Co. Mr. Catt, a graduate of the University of Illinois with a degree in chemical engineering joined B. F. Goodrich in 1929. He succeeds Dr. V. E. Wellman who becomes director of purchases in the company's newly created chemical division.

L. P. McAllister, who has been metallurgical engineer for Lukens Steel Co. since 1936, has been appointed assistant to the general superintendent with specific duties of quality control.



Dwight R. Means

Dwight R. Means, who has been associated with the Columbia Chemical Division of the Pittsburgh Plate Class Co. for 21 years, has been named assistant to the vice president. Prior to his new appointment he was technical director and had previously served as research director and assistant superintendent.

Lucien F. Craig has resigned from his position with the Supply and Transportation Division of Petroleum Administration for War.

Charles H. Briggs has joined the research staff of Truesdail Laboratories, Inc. Mr. Briggs holds a Bachelor of Science degree from Cornell University. For the past 35 years he has owned and directed the Howard Laboratory.

Edmund A. Georgi has been named manager of technical development in the Paper Makers Chemical Department of Hercules Powder Co. Mr. Georgi has been with Hercules since 1918 when he graduated from Cornell University.

Thomas A. Guerin, Jr., has won the 1944 Electrochemical Society Membership prize at Pratt Institute. The award is made annually to the most promising senior in electrochemistry.

Dene B. Hodges of the Shell Oil Co., has been appointed associate director of the Petroleum Administration for War's newly combined Supply and Transportation Division.

D. S. McAfec, vice president and director of the Dorr Co. has arranged to terminate his association with the company. He has for several years specialized in equipment and methods for the process industries. In addition to the North American Continent this work has included South America and parts of the Far East and Europe.

Karl E. Luger is now head of K. E. Luger Co., Houston, Tex., metallurgical

A Tough Fire Hazard ...



A Tougher FIRE FIGHTER!

This is just another spot where DUGAS Fire Extinguishers are on the job. Ready for action!

Applied from the DUGAS pressure-type extinguishers, PLUS-FIFTY DUGAS Dry Chemical makes short work of dangerous flammable liquid or gas fires. Knocks them out with tremendous speed! Less hazardous for the operator, too, because PLUS-FIFTY DUGAS Dry Chemical does its work from safe distances. Non-toxic, non-corrosive, it hurts nothing except fire.

Write for complete information regarding DUGAS PLUS-FIFTY Dry Chemical—and for priority facts about DUGAS Fire Extinguishing Equipment.



engineers specializing in stainless steel applications.

Max A. Bradshaw recently returned to this country from England. Major Bradshaw, formerly with the Eastern Regional Research Laboratory in Philadelphia has been in the armed forces for some time.

Carl S. Miner, president, The Miner Laboratories, Chicago, has been elected as one of the councilors of the Purdue Research Foundation. Mr. Miner is representing the American Chemical Society.

OBITUARIES

Graham L. Montgomery, associate editor of Food Industries, died on Mar. 4 at his home on Long Island. Mr. Montgomery, a mechanical engineering graduate of Columbia University, joined the McGraw-Hill Publishing Co. in 1922 as an assistant editor of Chem. & Met. From 1927 until 1930 he was on the editorial staff of Power which he left to become managing editor of Food Industries. He was active in the affairs of the Institute of Food Technologists and the American Society of Mechanical Engineers.

Charles Copeland, formerly secretary and director of the E. I. du Pont de Nemours & Co., died Feb. 3 after a long illness. He was 76 years old.

James H. MacMahon, 83, pioneer in introducing the use of American-made bleaching powder and later liquid chlorine in paper pulp bleaching, died at his home in Buffalo, N. Y., on Feb. 7. He was intimately connected with the early development of chemical manufacturing in the United States, was widely known in the paper and other chemical-consuming industries and for nearly 40 years was connected with the Mathieson Alkali Works.

George L. Dumbauld, vice president treasurer of the Blaw-Knox Co., died suddenly Feb. 3 after an illness of several days. He was 61. Mr. Dumbauld had been identified with the growth and development of the Blaw-Knox Co. for 24 years in an official capacity.

Bevis Longstreth, president of the Thiokol Corp., of Trenton, N. J. died Mar. 1 following an operation. He would have been 51 years old this month.

Fred W. Shibley, vice president of the Bankers Trust Co. for 18 years until he retired in 1939, died Mar. 1 at his home in New York after a brief illness. He was 80 years old. He was a director of a number of companies including St. Joseph Lead Co. and Manville Jenckes Corp.

Charles Randolph Borland, 74, for 26 years consulting chemist for the American Powder Co., Acton, Mass., until his retirement in 1950, died at Cambridge, Mass., on Feb. 16. He was born in Lonion, England,

Jesse Jav Ricks, chairman of the board of Union Carbide and Carbon Corp., died at his home in Plandome, N. Y., on Feb. 20 after a brief illness. He was 64 years of



Here's a moistureproof, fireproof insulating material with high crushing strength



Just how strong is Foamglas? This has been answered by tests made in Armstrong's Laboratories on this sensitive, accurate Baldwin-Southwark Universal Tester.

When tested on all faces, Foamglas blocks have an average compressive strength of 150 pounds per sq. in. Thus, this new, low-temperature insulation can be erected without framing members to form self-sustaining walls and partitions in cold-room construction.

Proof against moisture is a second important feature of Armstrong's

Foamglas. The material is composed of thousands of tiny cells —and each cell is completely isolated from adjoining cells by thin glass walls. Hence, neither moisture nor vapor can



penetrate Foamglas—so it's just as efficient years later as the day it is erected.

Proof against fire. Since Foamglas is pure glass, it is absolutely fireproof. In many types of refrigerated construction—par-

ticularly in marine work—this is an extremely important requirement of the insulation.

Add them up moistureproof, fireproof, and high structural strength, plus insulating efficiency and easy handling—and you have good reason for investigating this new, low-temperature insulation. Write today for your free copy of the folder, "Armstrong's Foamglas," which gives complete physical data. Address Armstrong Cork Company, Building Materials Division, 4203 Concord St., Lancaster, Pennsylvania.

PHYSICAL PROPERTIES
Average crushing strength,
150 lbs. per sq. in.
Modulus of rupture90 lbs. per sq. in.
Modulus of elasticity,
163,000 lbs. per sq. in.
Impact resistance
Absorption (24 hr. immersion in water),
0.4% by volume, 2% by weight
(all at surfaces)
Permeability0
Capillarity0
Volume change with moisture0
Conductivity (K at 70° F.),
0.45 B.T.U. per hr. per sq. ft.
per "F, per m.
Specific heat 1619 per lb. per "F.
Coefficient of expansion
9

* Trade-mark, Pittsburgh-Corning Corp.



CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •

Pyroflex "Baby" Tower a Big HCl Producer!

T WAS dubbed a baby tower by the Knight organization because it was so small. Actually, it will do a lot of work for its size. It is designed to make 500 lbs. of 36% HCl per hour from 50% gas.

Pyroflex construction is not a pile of bricks or a lining. It is a completely designed functional unit. Each unit has the strength of steel and the corrosion resistance of ceramics.

Knight engineers have created many types and kinds of Pyroflex functional units to do specific jobs. Many of them provided the first satisfactory solution to tough problems.

Knight engineers' wide experience in this field is always available to help you solve your own special problems. In writing, please give us complete details.

MAURICE A. KNIGHT 103 Kelly Ave., Akron 9, Ohio



age. Mr. Ricks became chairman of the board of Union Carbide and Carbon Corp. in 1941. He had been president from October 1925 to May 1941. Nearly twenty years ago he instituted a liberal policy of research that has been in a large measure responsible for the growth of the numerous interests of the corporation which he headed.

Harry Fletcher Brown, a vice president and director of E. I. du Pont de Nemours & Co., died in Wilmington Feb. 28 after a long illness. He was 76 years of age. In 1900 he joined the International Smokeless Powder & Chemical Co., a subsidiary of the Marsden Co. When the latter company was acquired by Du Pont in 1904, Mr. Brown was given technical direction of smokeless powder manufacture at four Du Pont plants. In 1911 he became head of the Smokcless Powder Department, in 1914 he was elected a director and member of the Executive Conmittee, and in 1916 he became a vice president of the company.

Perley J. Buchanan, research chemist and director of chemical control of American Agricultural Chemical Co., died in Montclair, N. J. on Feb. 23 after 35 years service with this company.

James E. McDonald, 53, General Sales Manager of the Edward Valve & Mfg. Co. died Feb. 25 after an illness of several months.



L. H. Baekeland

Leo Hendrik Backeland, one of the most widely-known American chemical engineers, died in Beacon, N. Y., Feb. 23 at the age of 80. Dr. Backeland was born in Ghent, Belgium, Nov. 14, 1863, and came to this country in 1889. Here he engaged in chemical research and the first fruit of his efforts was Velox photographic paper. After effecting certain improvements in the equipment used in the production of caustic soda and chlorine, he turned his attention to synthetic resins. Bakelite, as is well known, was the result of these investigations.

During his lifetime Dr. Baekeland was the recipient of numerous honorary degrees, medals and awards given in recognition of his contributions to the industry and the world. He was a past president of the Electrochemical Society, the American Chemical Society and the American Institute of Chemical Engineers.



Operated from any 110 volt A.C. outlet, CAMBRIDGE self-contained and portable pH meters are always "ready-to-go." These instruments may be turned on continuously so that they are available without the necessity of a warm-up period to obtain stability. The electron-ray null indicator, immune to danger from mismanipulation, replaces the conventional, delicate pointergalvanometer.

LABORATORY MODEL Accuracy .02 pH. Sensitivity .005 pH, Readings Reproduci-ble to .01 pH, Range 0 to 14 pH and 0 to 1200 mv.

INDUSTRIAL MODEL Accuracy .05 pH, Sensitivity .01 pH, Readings Reproduci-ble to .02 pH, Range 0 to 14 pH and 0 to 1000 mv.

CAMBRI D GE PH METERS CAMBRIDGE INSTRUMENT CO., INC.

3732 Grand Central Terminal, New York, N. Y. SEND FOR BULLETIN 910E



DUAL SCREENS



AND DRUMS DUA

The dual screens of the Prater Gradual Reduction Grinder (4) definitely increases screening area from the usual 45% of the ordinary mill to 70% of grinding area. Also, the screens can be more efficiently designed. There is no need for reinforcing the Prater Screens against the shocks of material in the breaking (1) and crushing (2) stages. That is all done in the primary drum, where the materials bounce against tough steel castings.

Then the crushed material is fed around the entire periphery of the rotor to the final sizing blades (3) of the main grinding drum. The particle size is such that the greater part of the area can be devoted to

screening. Because the dual screens are away from preliminary breaking and crushing they can be designed for true screening efficiency, as there are no large and heavy particles hammering the dual screens. This hammering in the usual mill distorts the screens and lowers screening efficiency still further.

The immediate value of the 70% screening area is immediately apparent to the grinding engineer-but there are many other factors in this principle of dual screens and dual drums, that are worthy of the study by the man interested in production control and low power cost.

Write for information.

Address:



BROWN & SITES COMPANY

50 CHURCH STREET

NEW YORK, NEW YORK

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •



YOUR WATER SYSTEM Might Be Called for Extra Duty Tonight

FIRE—that killer of man and destroyer of property strikes suddenly and without warning! Standing guard, after performing its daily duty, is your water system. If it bears the name of LAYNE, be assured that it has a great stand-by reserve of power and productivity ready to be unleashed when the emergency call comes.

In many, many cases Layne Well Water Systems, due to their extra reserve of power and productivity, have saved untold thousands of dollars worth of property in cases of sudden emergency.

Layne Well Water Systems are specifically built to give their owners much more than normal daily operational service. They are built to give protection to property and lives.

If your city or manufacturing plant needs more water, please remember that Layne Well Water Systems produce great quantities at exceptionally low cost and at the same time provide an extra reserve of power and productivity that stand guard in cases of emergency.

For fully illustrated literature on Layne Well Water Systems, address Layne & Bowler, Inc., General Offices, Memphis 8, Tenn.



WELL WATER SYSTEMS DEEP WELL PUMPS

BUILDERS OF WELL WATER SYSTEMS FOR INDUSTRIES AND MUNICIPALITIES

INDUSTRIAL NOTES

ELLIOTT Co., Jeannette, Pa., has selected R. W. Owens to be assistant to the president. Mr. Owens formerly was with Westinghouse as section engineer, manager of the industrial motor engineering department, general manager of industrial engineering, and manager of the motor division in charge of engineering, manufacturing and sales.

WISHNICK-TUMPEER, INC., New York, has changed its name to Witco Chemical Co. The change does not effect the corporate structure, management, or personnel.

LEBANON STEEL FOUNDRY, Lebanon, Pa., has opened a new office in the Commerce Bldg., Houston, Texas. Herschel J. Wood has been appointed southwestern representative and will be in charge of the new office.

ROHM & HAAS Co., Philadelphia, has inaugurated a pension plan for its employees which includes a monthly retirement income plus increased life insurance during active years. The entire cost of the plan will be underwritten by the company.

UNITED STATES RUBBER CO., New York, through investment in capital stock, has become associated with Compania Croydon del Pacifico, S. A., leading rubber manufacturer of Columbia, South America. The sales office which United States Rubber Export Co. has maintained at Bogota will be merged with the sales organization of Croydon.

FRITZCHE BROS., INC., New York, has appointed Stanley B. Schuster office manager of its Chicago branch. The Chicago office is under the general management of Joseph A. Gauer.

PAUL W. STEWART & ASSOCIATES, New York, has changed its name to Stewart. Brown & Associates. Dr. Lyndon O. Brown, professor of marketing at Northwestern University on leave, has been admitted as a partner.

WALTER KIDDE & Co., Belleville, N. J., has appointed C. E. Gischel director of product development in charge of postwar planning. He is succeeded as advertising manager by Gordon F. Ives who had been connected with the production department.

KEROTEST MFG. Co., Pittsburgh, has moved its New York office to the Lincoln Bldg., 60 East 42d St.

WESTINGHOUSE ELECTRIC & MFG. Co., East Pittsburgh, has placed William J. Massey in charge of lamp sales with headquarters at Bloomfield, N. J. In his new position, Mr. Massey will direct all lamp sales activities of the lamp division, the



FLETCHER WORKS Glenwood Ave. & Second St., Phila. 40, Pa. illuminating engineering, commercial engineering and advertising departments.

LINCOLN ELECTRIC Co., Cleveland, is now represented in Detroit by B. J. Brugge as welding engineer. Mr. Brugge had represented the company in Los Angeles and Houston and prior to his removal to Detroit was located in Washington, D. C.

GENERAL ELECTRIC Co., Schenectady, N. Y., has named E. A. Green as general assistant to the manager of the motor division. He joined the company as a student engineer in 1924 and recently had been working on special assignments under the supervisor of apparatus production.

THE TIMKEN ROLLER BEARING CO., Canton, Ohio, has appointed Donald S. Klippert to the position of assistant general manager of sales of the steel and tube division. He has been succeeded as manager of the Cleveland office by Robert P. Donnell.

DEVOE & REYNOLDS Co., New York. who recently announced the advancement of Arthur H. Mohrhusen to the newly created post of general merchandise manager, now report that Mr. Mohrhusen has been succeeded as manager of the brush division by George P. Gray who will be located in Princeton, Ind. Kenneth Wood succeeds Mr. Gray as field manager of the western division with headquarters at Chicago.

MACHLETT LABORATORIES, INC., Norwalk, Conn., announces the appointment of Henry J. Hoffman as sales manager of the power tube division as well as administrative assistant to Miles Pennybacker, vice-president.

JOSHUA HENDY IRON WORKS, Ampere, N. J., has appointed Lyman D. Warner, sales manager and assistant vice-president of the Crocker-Wheeler division to succeed C. F. Poirier. Mr. Warner has been associated with the sales department since 1937.

THE GIRDLER CORP., Louisville, has added Boyd R. Hopkins to the sales department of the Thermex division. Mr. Hopkins will represent the company on the West Coast. He spend several years with Waugh Laboratories and with Magnaflux Corp. in their western offices.

BLAW-KNOX Co., Pittsburgh, has advanced N. I. Mekeel, Jr., to the position of manager of the grating department to succeed Elmer E. Brodhead who has formed a business connection on the west coast.

THE DAVISON CHEMICAL CORP., Baltimore, has formed a process division with E. B. Dunkak as manager. The new division offers a complete design and equipment service for the process industries.

THE C. M. KEMP MFG. Co., Baltimore, is now represented in the New York territory by F. H. Yocum and A. H. Goode with headquarters at 420 Lexington Ave.

ALLEGHENY LUDLUM STEEL CORP., Brackenridge, Pa., has named P. E. Floyd



TWIN SPECIAL DUST COLLECTORS

• If you are pressed for room—yet need more dust protection in your plant—Pangborn Dust Control Engineers are prepared to give you recommendations that will take advantage of unused or waste plant space. Like the imposing installation above—your system will be satisfactory from every point of view—engineering, erection, operation and maintenance.

"COME TO PANGBORN"



Semtile Tank and a cross section of the famous Semtile block construction which permits the use of both horizontal and vertical reinforcing. The cores are solidly filled with concrete forming a reinforced concrete wall faced on both sides with Stebbins glazed tile.

> If your tanks and chests are showing wear due to wartime strain...let Stebbins handle your relining problems.

> For sixty years, we have successfully lined practically every known type of process reaction vessel or treating tank. Process plants of many types have utilized our experience again and again—a fitting testimony to the quality and durability of our linings.

> We can furnish linings of brick, tile, porcelain and carbon materials for both acid and alkali conditions. For certain specific requirements, our resin membranes, resistant coatings and rubber films, in combination with brickwork, are most effective.

> Reline the "Stebbins Way" and take advantage of our complete service: Every job is covered by a lump sum contract. We supply all labor and material and turn the completed lining over to you ready for use.



assistant general manager of sales. Mr. Floyd recently returned to the company from Washington where he served as chief of the steel division of WPB. Before going to Washington, he was manager of the corporation's office in Chicago.

AMERICAN CHAIN & CABLE Co., INC., Bridgeport, Conn., has appointed Alton Parker Hall assistant manager of sales. He assumed his new post on March 1 with headquarters at 230 Park Ave., New York. Mr. Hall had been associated with Bethlehem Steel Co. since 1922.

ALLIS-CHALMERS, Milwaukec, has set up a new basic industries department which will correlate the activities of the crushing, cement and mining machinery division, flour milling and oil extraction division, and saw and pulp mill division. Walter Maxson will manage the department. The company also has established a separate Texrope division with T. C. Knudsen in charge.

THE PENNSYLVANIA SALT MFC. Co., Philadelphia, has moved its New York office to 40 West 40th St. This office is headquarters for two of the company's sales districts, one headed by F. G. Rodenburgh and the other by C. A. McCloskey.

MANHEIM MFG. Co., Manheim, Pa., has advanced Vincent K. Alexander to the position of sales manager. For some months, Mr. Alexander had served as acting sales manager and prior to that was in charge of the Chicago office of the company.

WYANDOTTE CHEMICALS CORP., Wyandotte, Mich., has selected C. T. Robinson to manage its Cincinnati office to replace C. D. Morris who left the company to enter the merchant marine service. Mr. Robinson joined the company in 1927 and for several years was central regional supervisor for the J. B. Ford division.

KAYDON ENCINEERING CORP., Muskegon, Mich., has appointed B. M. Staley factory manager. For the last 12 years Mr. Staley had been with the rotary pump division of National Transit Pump & Machinery Co. at Oil City, serving successively as chief engineer, superintendent, and general manager.

HOOKER ELECTROCHEMICAL Co., Niagara Falls, has assigned Thomas H. Trimble as its sales representative in the eastern Middle Atlantic territory with headquarters at 60 East 42d St., New York. Ralph E. Davis, Jr., has been appointed sales representative in upper New York and western Pennsylvania with headquarters at Niagara Falls. He will continue his special service for the leather industry.

SKF INDUSTRIES, INC., Philadelphia, has placed Walter C. Ahlers in charge of its office in Detroit to succeed Robert H. Hirsch, resigned.

HERCULES POWDER Co., Wilmington, has appointed George A. Paine district manager of the synthetics department for the New York territory and Paul L. Lefebvre as district manager for Chicago.

Disposal of Government Inventories

How to dispose of government surpluses when the war ends need not be an insuperable problem – if we face it promptly and intelligently. But if we do not, peacetime markets may be disrupted, government funds wasted, production discouraged, and reconversion of the whole economy to peace seriously hampered.

What we need most in order to attack the problem is estimates of how much surplus there will be, in what types of goods, and where.

At the war's end, government inventory of war goods is likely to total around 60 billion dollars. Most of this will consist of aircraft, ships, and other ordnance. Only some 15 billion dollars or less will be in food, clothing, trucks, tools, chemicals, medical supplies, transportation, engineering and communication equipment, and other goods for which there is a civilian market.

In addition, war contractors will have about 10 billion dollars of inventories, the bulk in specialized raw materials, goods in process, and finished products. Only about one-fifth of the total, or some 2 billion dollars, will be marketable or usable for civilian purposes. While the government takes over the usable inventory, the exwar-contractors will have to build up their stocks for peacetime production, so that on balance, they will not be disposing of usable inventories in large volume.

Not even all of the usable war-end inventory will be "surplus" for sale to civilians in competition with new production. Some of it will be needed by the sizable peacetime Army and Navy we are likely to maintain, and such additional items as can be stored without serious deterioration or obsolescence will be held against possible future war emergencies. Some of it will be disposed of abroad. And up to half of it will be abroad and may be sold there or used for relief.

After allowing for these factors, the war supplies to be disposed of in our own markets probably will be less than 10 billion dollars (cost basis). While the total is not overwhelming—the equivalent of two months' retail sales—in certain lines the surplus will be several years', instead of a few months', normal supply. In particular, the volume of scrap metals available from otherwise unusable munitions will present a problem.

A great deal can be done now to reduce the size of the postwar surpluses by achieving a better balance between military needs and supplies and avoiding excessive inventories of particular raw materials or finished goods. This work needs to be pressed, not only to simplify our transition to peace but also to prevent wasting productive energies during the war. Furthermore, when the war ends on one front, inventories of war materiel should be worked down to the reduced scale of remaining military activity.

We cannot develop programs of action until we know approximately how much of each type of item is to be sold, and where and when it will be available. Wide margins of error are inevitable as long as large-scale procurement and large-scale consumption are still taking place; yet such information is essential and must be developed. Indeed, improved inventory records and estimates are badly needed for the conduct of the war as well as for managing the surpluses after hostilities cease.

In decisions on the disposal of war-goods inventories, the public interest must be the prime consideration. Proposals that none of these goods should be sold domestically because of competition with new production obviously are untenable. Everything that is not needed by the Armed Services or for other special purposes should be disposed of ultimately. The real problem is not whether surpluses should be sold, but rather to whom, at what price, and at what time the sale should be effected.

In the distribution of such large quantities of goods, we believe that established trade channels should be used wherever possible. Otherwise, we shall witness widespread speculation in war goods and the mushroom growth of inefficient and disruptive fly-by-night distributors. This will benefit only a few speculators and will discourage legitimate producers and distributors from making their normal commitments.

All war contractors should have the privilege of retaining those inventories for which they are willing to pay actual cost or a fair price negotiated with the government procurement agency. The balance of the inventories in the hands of war producers should be assembled by the government and sold in an organized manner. It is of great importance that the plants be cleared of these inventories at once so that the process of conversion to peacetime operation can proceed without further delay. To accomplish this, preparations must be made before the end of the war for speedy determination of the inventories to be moved and for a huge volume of storage space to accommodate them.

The price which can be realized and the timing of sale are closely related. Certainly the best prices will not be secured if the government attempts to dispose of large supplies of material and products suddenly without regard to market conditions. Most businessmen rightly favor an early transfer of surplus inventories from government to private ownership. But, they also realize that if all the surpluses are dumped indiscriminately as they become available, many markets will be badly depressed, and the resulting low prices will bring lower production. If this depression effect becomes general, as it easily can, it will be costly to the nation in terms of jobs, income, and goods.

In industries in which production is inadequate to meet postwar demands, an immediate sale of government inventories can prevent inflated prices and preserve balanced market conditions. In cases in which the surpluses are large in relation to annual production, the disposition can be scheduled over a period of years. Generally, however, it will be best to clear the surpluses as quickly as orderly sale can be accomplished rather than to leave them as a continuing threat overhanging the market. Most industries can, and should, take the disposal process in their stride without special dispensations from the government. In this connection, it should be noted that the tax provisions for carry-back of losses and excess profit credits after the war greatly increase the possibilities for speedy disposal of surpluses without serious injury to producers.

There will be some industries, however, in which the postwar surplus is so large that it would practically saturate the market for years to come. The problem of these industries is further complicated by their wartime expansion of capacity many fold in excess of peacetime requirements. These lines of production are, moreover, crucial for our national defense. Aircraft and shipbuild-

ing are cases in point. Each of these situations calls f careful study and discussion by all concerned to devimeans to keep alive the necessary production organiz tions, the research effort, and the spirit of enterpris Insofar as possible, the individual manufacturers shoul work out their own salvation in the conversion to peac time markets. They can do this by taking on new line by increasing their production efficiency, and by d veloping technical improvements which make the e: isting inventories obsolete. But they still will need som kind of government protection or assistance while th huge surpluses are being worked off. It is most in portant, however, that such protection or subsidy b limited to a period of three to five years. It must no become permanent unless it is really essential for ou national security.

The disposal of surplus inventories is part of th whole process of demobilization of the war effort an conversion to peace. If this process is to be accomplishe with minimum dislocation and injury to our economy it will have to be directed by a central agency which has developed adequate information service and is in position to coordinate the policies of the Armed Serv ices and the other interested executive branches of the government. This agency should draw freely on the knowledge of businessmen in the specialized problem of marketing surpluses in each industry. It should for mulate definite programs of inventory disposal for al industries in which the problem is acute; and it should make these programs public as soon as possible, so that business can plan for the future with confidence. In large measure, the success with which we make the economic transition to peace will depend on the quality of gov ernment administration in the process of industrial de mobilization. We shall need better organization for the transition to peace than we had in mobilization for war if we are to avoid needless unemployment, loss of pro duction, and frustration of business enterprise.

Mules H. W. haw

President, McGraw-Hill Publishing Company, Inc.

CONVENTION PAPER ABSTRACTS

PAPER COLORING

NAPHITHANILS belong in the class of colors known as azoic colors. This means forming an azo dyestuff directly on the fiber. The naphthanil process may be used to color paper either in the beater or by surface application. A water soluble naphthanil "prepare" is formed by treating the naphthanil with caustic soda. These prepares have a certain degree of affinity for cellulose and will exhaust on the fiber. The addition of a diazotized amine causes a rapid coupling reaction to take place forming a bright color directly on the fiber. Almost a complete range of shades is possible by using naphthanils, but the orange, red, and yellow shades form the bright shades for which these dyes are famous. These colors are suited for dyeing twisted papers used in auto seat covers, paper rugs and woven paper sacks.

Sulphur colors may be beater applied to paper from a solution of the color reduced with sodium sulphide. Formerly the liberation of hydrogen sulphide vapors when the beater was neutralized limited the use of these colors. Today the use of certain heavy metal salts such as zinc chloride and copper sulphate eliminates the odor and neutralizes the excess alkalinity in one operation. Sulphur colors are ideal colors for granite fibers and for dyeing all types of heavy black and brown shades.

Vat colors have the best all around fastness of any group of textile colors. They are usually bright, with outstanding light fastness and are water insoluble. In general they are fast to chlorine, acids, and alkalies. They may be beater applied to paper from an alkaline hydrosulphite reduced solution of the color. This "leuco" exhausts on the cellulose fiber and may be air oxidized to give bright shades of every desired hue.

H. A. Lips before 20th TAPPI Annual Meeting, New York, N. Y., Feb. 14, 1944.

DISTILLATION AND RECTIFICATION

DISTILLATION implies more than setting up a flask, condenser, and receiver. Even in the laboratory efficient fractionating columns are employed for analysis of mixtures and purification of compounds; and to the chemical engineer distillation may imply a series of heat exchangers and of columns, maybe as large as 20 ft. in diameter and 200 ft. high, as employed in the precise separation of hydrocarbon gases.

The requirements of a problem involving the separation of a binary mixture by distillation involve two prime considerations: the number of theoretical stages of equilibrium contact and the reflux ratio. These can be determined graphically by means of the McCabe-Thicle diagram, on which is plotted the equilibrium composition of the vapor, y^* against the liquid composition, x, and the relation between the composition of the liquid flowing down the column, x_{n+i} , and the composition of the vapor rising to the same point, y_n ,



The casting of alloy steels is an art. Atlas metallurgists having pioneered the casting of stainless alloy steels, are thoroughly familiar with the intricacies involved. All stainless steel castings must be designed for the particular job. Therefore when a casting is in the blueprint stage, Atlas metallurgists can save much redesigning if consulted at once. There is no obligation for this valuable service. Your inquiries are invited.

Write for Illustrated Bulletin





Division Atlas Foundry Co. 540 LYONS AVE. IRVINGTON, N.J.



TO END ALL PROBLEMS OF CORROSION

Saram is a tough thermoplastic originally made to replace such strategic war materials as aluminum, stainless steel, nickel, copper, brass, tin and rubber. Now found adaptable to a wide range of uses in product designing, food processing and wherever non-corrosive materials are necessary. Its insulating qualities, flexibility and ease of handling make it extremely valuable in installations dealing with oils, gases, air, water and corrosive chemicals. It is available in tube, pipe, sheet, rod and molded fittings. Technical Bulletin P-8 will be sent on request. Address Dept. A.







CHEMICAL & METALLURGICAL ENGINEERING . MARCH 1944 .



in terms of the ratio of reflux L, and the vapor, V, and the moles of distillate removed, D:

$$y_n = \left(\frac{L}{V}\right) x_{n+1} + \left(\frac{D}{V}\right) x$$

If the relative volatility, a, defined by the equation

 $\frac{y^*}{1-y^*} = \alpha\left(\frac{x}{1-x}\right)$

is taken as approximately constant, the limiting critical values can be calculated analytically. The minimum reflux ratio, requiring an infinite number of plates, is given by

 $\left(\frac{L}{V}\right)_{\min} = \frac{y_D - y^*_I}{x_D - x_I}$

while the minimum number of plates, n, at total reflux, requiring a column of infi-nite capacity, is given by the Underwood-Fenske equation:

$$n = \frac{\log\left[\left(\frac{x_n}{1-x_n}\right) / \left(\frac{x_1}{1-x_1}\right)\right]}{\log \alpha}$$

Results of calculations by these methods illustrate the relative difficulty of separation of mixtures with different values of α . With $\alpha = 1.1$, for example, (correspond-ing to 3 or 4 deg. C. difference in boiling points) it would require 96 plates at total reflux and a minimum reflux ratio (L/D) of 990:1 to give a distillate of 99 percent low-boiler at the same time as the still composition was 99 percent of the high-boiler. With $\alpha = 3.7$ (perhaps 40 to 50 deg. C. difference) only 6 plates are required at total reflux and a reflux ratio of only 37:1 for the same degree of sepa-ration. Practical reflux ratios only 10 to 50 percent above the theoretical minimum value of (L/D) were shown to give the optimum column volume, with a number of plates of 2 to 3 times the minimum number required at total reflux.

These methods imply continuous operation. The requirements of a batch operation, the method generally employed in the laboratory, and often in the chemical plant, are somewhat more difficult to estimate. They can be handled analytically, however, by the extension of the Rayleigh equation

$$\frac{dS}{S} = \frac{dx}{x_{1} - x}$$

to relate the composition of the product withdrawn, xp, to the relative volatility in terms of the reflux ratio, assuming an infinite column, or step-wise by graphical means. The results of such calculations are curves showing the predicted course of batch distillations for various reflux ratios and values of a. Both a highly effi-cient column and a high reflux ratio are required for the effective separation of close-boiling fractions. It is possible to employ "batch stripping," or "inverted batch distillation," where it is desired to take off the high-boiling component in a high degree of purity.

Data on experimental tests on typical columns of both bubble-cap and packed types were obtained in terms of the allowable vapor velocity and, for bubble-cap columns, the plate efficiency, and, for packed columns, the height of equivalent theoretical plate (H.E.T.P.), or height of a transfer unit (H.T.U.). In the range

of sizes on which comparative data were available (approximately 2-ft. in dia.) it was concluded that bubble-cap columns were competitive with packed and there is not much advantage of one commercial packing over another; in larger sizes bubblecap columns would be found relatively cheaper, and in smaller sizes packed columns.

T. H. Chilton, E. I. du Pont de Nemours & Co., Wilmington, Del., before Northeastern and Rhode Island sections of American Chemical Society, Jan. 14, 1944.

PETROLEUM ADVANCES

TECHNOLOGISTS have bridged the spread from laboratory to use in every department of living. Nylon and rayon fabrics are products of the last quarter century. Vinylite and lucite plastics are ever so recent. The miracle life savers and methods called to mind by such terms as blood plasma, sulfamilamid, penicillin---all these stem from research. Yet, experienced engineers are very humble in their estimate of what has been done these last 25 years. They believe we are just beginning to realize how much there is to learn and do. Progress has been wonderful, but it is not to be compared with what will be seen in the coming 25 years.

The petroleum refining industry makes a good case history because its advancement has been super-great, yet the men in it know that much greater attainment lies ahead.

In 1919, the refining of crude petroleum to gasoline and lubricants was done by pot still distillation. The standard of efficiency was no greater than that achieved by the maker of moonshine in the Kentucky hills, maybe not as good. A million barrels of crude then yielded

A million barrels of crude then yielded about 200,000 bbl. of gas. Today the yield is about 500,000; and crude production is up about 4½ times. But such figures tell an incomplete story. Because the power value also has gone way up. A petroleum engineer is a sort of fuel bartender. He mixes a power cocktail, and measures its potency by octanes. The old Model "T" Ford, the early

The old Model "T" Ford, the early single engine flying crate—they knocked along on a 50 octane gasoline. Improved methods brought the rating up to 70. Then in 1927, the discovery of the efficiency addition of tetraethyl added another 15 points. In the 1930's, the process of catalytic cracking served to open a way to make high octane gas in large volume.

The engines were hungry for it, and like any greedy thing, be it animal or machine, responded gratefully to those who provided what was wanted. In the Battle of Britain in 1940, the British airplanes were powered with 100 octane gasoline supplied by the United States. The Germans used an 87 octane gas. The resultant advantage in British maneuverability, rate of climb and altitude possibility had much to do with the result.

Gasoline supplies were and still are a war factor of major importance. From the war's beginning, our war leaders knew that however much everything else would be needed, aviation gasoline would be required in hitherto undreamed of quantities. Today it is easy to form a mental picture of such requirements. Two thousand WILLIAMS HEAVY DUTY HAMMERMILLS FOR INDUSTRIAL USE . . . Grind Chemicals . . . Crush 4 feet Cubes of Rock . . . Shred Steel Turnings



ANIMAL ... MINERAL VEGETABLE MATTER

Capacity from 50 lbs. to 300 tons per hour

• Williams is the world's largest organization of crushing, grinding and shredding specialists and have developed standard machines for the reduction of practically every material whether animal, mineral or vegetable. Capacities range from 50 pounds to 300 tons per hour permitting selection of exactly the proper size for your work. Whether you wish to grind chemicals to 400 mesh, crush 4 feet cubes of rock or shred steel turnings, you can profit by Williams' experience.



...at Port Neches, too!

Here is your complete chemical engineering library



Chemical Engineers' Handbook

2nd Edition, 3029 pages 1300 illustrations, 1,000 tables, \$10.00

CONSULT Perry's Handbook for data needed in routine problems of design and practice, or in investigation of special problems or branches of work. Check your methods against best accepted practice, as reflected in its 29 big sections of carefully selected and authoritative facts.

You'll find concise descriptions and working fundamentals of processes and equipment, supplemented by a profusion of comprehensive formulas and equations, charts, tables, data, schematic diagrams, etc.—you'll find everything carefully selected for its practical application, arranged for quick reference to the essentials required by men in practical contact with chemical engineering problems of all types—the information you want, in the form in which you can use it.

10 days' examination — Easy monthly payments

McGRAW-HILL EXAMINATION COUPON
McGRAW-HILL BOOK CO., INC. 330 West 42nd Street, New York 18, N. Y. Send me Perry's Chemical Engineers' Handbook for 10 days' examination on approval. In 10 days I will send \$1.00, plus few cents postage, and \$3.00 monthly for three months thereafter, or re- turn book postpaid. (Postage paid on orders accompanied by remittance.)
Name
Address
City and State
Position
Company

WORLD'S LARGEST BUTADIENE PLANT USES WESTON all-metal thermometers

Deep in the heart of Texas is this new giant plant whose production dwarfs all others in the processing of Butadiene. And in this plant, too, WESTON all-metal temperature gauges are used at checking points because of their legible, gauge-type scales . . . their 1% full-scale accuracy . . . and their simplified all-metal construction which assures *long-term* accuracy, and safeguards against damage from vibration, over-ranging or mechanical abuse.

Literature describing WESTON temperature gauges, which employ no gases, liquids or fragile elements, gladly sent on request. Weston Electrical Instrument Corporation, 679 Frelinghuysen Ave, Newark 5, N. J.

WESTON TEMPERATURE GAUGES

174

of 1%.

WESTON All-Metal

Temperature Gauges

are available in sizes and

types for a most .. industrial

needs . . . as well as in laboratory models with full scale accuracy within ½ bombers raiding Berlin from bases in England use 100,000 bbl. of 100-octane aviation fuel. This is equivalent to six months' production in 1937.

It isn't only in gasoline requirements that petroleum engineers have been called on to meet war's need. They found a way to make toluol for TNT. No longer is there a threat of a shortage so far as this war is concerned.

And rubber? That might have been like an Achilles heel for the United Nations. The chemical and oil technologists met this gravest of challenges. When some future word wizard tells the story of industry in this war, the recital of synthetic rubber manufacture will be among his most fascinating tales.

What the oil industry has been doing in this war, every other industry has done in its own field. The accomplishment of American producers has been so great that it will take years for us to realize its full import. We need perspective to really grasp what has been done. But we require no lapse of time to know that this wonderful achievement came not only from nature's bounty in material wealth. Rather, it came from the minds of men, particularly America's engineers.

Our country will emerge from this war as the strongest national entity that ever has existed. With such power goes great responsibility. If our engineers help to exercise that responsibility in matters of international decision, perhaps they can determine that the work of their minds and hands will be peacefully directed to the good of mankind.

Of all classes of men, classifying them by the nature of the work they do, none is more important than the engineer. Few are as important. It is the engineer who eases the physical load of life, improving contact, making living brighter, more healthful, more enjoyable, more useful. There is an immeasurable amount of all this which needs doing.

E. R. Smoley, the Lummus Co., at Class Day Exercises, the Massachusetts Institute of Technology, Feb. 26, 1944.

LUMINESCENT PIGMENTS

LUMINESCENCE, the phenomenon of absorption of ultraviolet light and reemission of this energy as visible light is finding practical applications today in the paper and printing arts. Two types of luminescent pigments are defined as fluorescent pigments which glow while excited, and phosphorescent pigments which have a useful afterglow.

Light sources providing satisfactory excitation of luminescent pigments in the long ultraviolet spectral range include daylight, incandescent filament lamps, argon glow lamps, mercury vapor lamps, and fluorescent lamps.

Fluorescent pigments are classified as either organic or inorganic. Organic pigments are usually dyes, lakes made from such dyes and metallic salts of dyes, and dye intermediates. They possess high fluorescent brightness and brilliant color but are subject to fading and loss of fluorescence on exposure to sunlight. Inorganic pigments most used are zinc sulphide and zinc and cadmium sulphide. These are crystalline pigments having white or yellow



How Norblo Helped America Out of Grave Shortage of Zinc

In May, 1942 zinc stocks were down to 18,447 tons. The situation was critical. Today stocks are about 160,000 tons, two months' supply. We are out of danger.

Increased production was obtained by re-opening old mines and by re-working old slag piles. But salvage of zinc formerly lost in brass foundry smelting and in the reclaiming of scrap brass has saved thousands of tons of zinc annually, thus stretching new production.

For the past two years Norblo fume collecting equipment has gone mainly into the smelting field. Norblo systems are incorporated in the several outstanding Eagle-Picher and Bunker Hill slag fuming installations. In the brass foundry of the largest cartridge factory in America, Norblo is saving zinc at the rate of 3,000 tons a year. In a new plant, The Samuel Greenfield Co., Buffalo, N. Y., for reclaiming copper from brass scrap Norblo has made it possible to salvage most of the zinc formerly lost.

In all of these and many other installations the high efficiency of Norblo Automatic Bag Type Fume Collectors combined with Norblo Centrifugals solved the engineering and metallurgical conditions required and made possible technological advances which will continue after the war and be applicable in many other fields. Whatever your fume or dust collection problems may be Norblo engineers welcome your inquiries.



AMERICAN ROLLING RING CRUSHERS Low Power Requirements ... only one outstanding feature

AMERICAN Rolling Ring Crushers are the right choice for grinding chemical raw materials. As the program of war continues, existing equipment becomes more valuable and AMERICAN equipment stands up under today's extra de-

mands. Each unit is arranged to meet the particular requirement of each application — each unit more than fulfills all expectations for quality, quantity, endurance, and economy. Let us suggest the equipment to do your job best.

OTHER ADVANTAGES

- Simplicity of operation
- Great range of reduction
- External adjustment easy accessibility
- Compactness
- Exceptional power

1718

AMERICAN PULVERIZER CO.

1219 MACKLIND AVE. ST. LOUIS 10, MO.



WASHING DRYING OF SOLIDS for

CLARIFICATION DECOLORIZING DEODORIZING PURIFYING HYDROGENATING WINTERIZING

> for THICKENING EXTRACTION



The advantages of Shriver Filter Presses for your processes are based on

- 1. Their extensive practical applications.
- 2. Their low investment and operating cost.

3. Materials of construction of any metal, wood, rubber, plastics, plating or coating on metal.

- 4. Operation at any temperature or pressure.
- 5. Their use of any type of filter media.

6. Availability in any size, capacity, type and handling method.

Write for the Shriver Filtration Book

T. SHRIVER & COMPANY, Inc. 802 HAMILTON ST. HARRISON, N. J. daylight color, and blue to red fluorescent color.

Phosphorescent pigments are classified as either short afterglow or long afterglow. Zinc sulphide and zinc and cadmium sulphide are the materials having short afterglow. Calcium sulphide and strontium sulphide are the materials having long afterglow. The latter are particularly unstable in the presence of water. All are very coarse, unsuitable for printing inks, and not generally used in paper or printing inks.

The luminescent properties of the fluorescent type of zinc and cadmium sulphides are a function of their crystal structure, thus accounting for their coarse size. They are chemically stable and resist exposure to weather. Vehicles giving best luminescent properties include methacrylates, polystyrene, and vinyls. Fluorescent colors range from blue and green zinc sulphides to yellow, orange and red zinc and cadmium sulphides. The green and yellow pigments have highest fluorescent brightness. In general, they are used at low levels of brightness, 1 to 40 microlamberts. There is a slight afterglow present in all fluorescent pigments and some applications require that this be kept to a minimum.

G. F. A. Stutz, New Jersey Zinc Co., before 29th TAPPI Annual Meeting, New York, N. Y., Feb. 15, 1944.

NITROUS OXIDE AS REFRIGERANT

STANDARD texts and handbooks on the subject of refrigeration include listings of the various compounds that have found use at some time or other as refrigerating agents. Occasionally the engineer in his search for a material that will meet the demands of a specific application will find some reference to the possible use of nitrous oxide as a refrigerant. Further inquiry into the literature will disclose contradictory statements as to what are thought to be the characteristics of this gas together with an almost complete dearth of information on some of its physical properties.

Since nitrous oxide in many of its physical and thermodynamic properties is quite similar to carbon dioxide it would be expected that its field of use would closely parallel that of the latter. Distinct differences do exist between the two gases. Most important is the location of the triple point. For carbon dioxide this occurs at a temperature of about -70 deg. F. and a corresponding pressure of about 75 lb. per sq.in. absolute. On the other hand, nitrous oxide has its triple point at about -131.5 deg. F. with a corresponding pressure of 12.75 lb. per sq.in. absolute corresponding to a 4-in. vacuum. Significance of this is that carbon dioxide will solidify at temperatures lower than -70 deg. F. and is not usually employed for temperatures any lower than about -60 deg. F. for fear of freezing up in the valves, lines, etc., of the refrigerating system. On the other hand, nitrous oxide can be used to attain temperatures as low as about -125 deg. F., at which temperature the suction pressure is still slightly above atmospheric.

In the production of low temperatures of the order of -60 to -125 deg. F., it would, therefore, seem that nitrous oxide presents defineite promise. Although it is

possible to obtain temperatures within this range with a number of other refrigerants, this generally entails operation at subatmospheric pressure with the accompanying necessity of handling large volumes of vapor in large sized equipment. Operation above atmospheric pressure also avoids the possibility of leaks into the system and makes the detection of any leakage much easier. In some instances, the use of duplex compressors or of the cascade system employing more than one kind of refrigerant has been resorted to in the production of temperatures that would be easily obtainable with nitrous oxide in a simple cycle. Vapor pressures are so similar that the mixture will function as a one-component fluid and differential leakage will be negligible. Therefore, whatever advantages a combination of these two gases offers can be effectively utilized.

Freezing points of the mixtures will be lower than that of carbon dioxide so that they will prove useful for applications where temperatures lower than -60 or -70 deg. F. are needed and where the carbon dioxide can modify the fact that nitrous oxide is an oxidizing agent.

Experiments have shown that about 65 percent carbon dioxide is required in a mixture with nitrous oxide to eliminate entirely the tendency of the latter to support combustion. Such a mixture actually tends to extinguish flame and therefore would be suitable where complete absence of any fire hazard whatsoever is required. Also, it would seem to be reasonably safe to use such a mixture in an oil-lubricated compressor. The minimum temperature that would be obtainable without freeze-ups with this composition would be about -90 deg. F.

From experimental observations it is indicated that a whole series of true solid solutions can be produced from mixtures of nitrous oxide and carbon dioxide. This is so because the crystal forms and the space lattices of the two gases are of the same type and allow mixed crystals to be formed. Such crystals or solid solutions constitute only one phase and, since the liquid state of the mixture also acts as a one-component fluid, the system exhibits true triple points such as either one of the constituent gases. The exact location of the triple point of the solid mixture will depend, of course, on the percentage composition of the mixture.

In other words, it is possible to produce solid mixtures of nitrous oxide and carbon dioxide that will be stable at atmospheric pressure, subject only to sublimation, and can therefore be handled similarly to solid carbon dioxide or dry ice. By varying the relative proportions of the two gases the specific preperties of the solid can be varied to suit the demands of any particular application. For instance, a 65 percent carbon dioxide and 35 percent nitrous oxide solid mixture will produce vapors while subliming that are free from any tendency to support combustion for use where such property may be desirable. This mixture would have a triple point of about 48 lb. per sq.in. and the temperature of sublimation at ordinary pressures would be about -115 deg. F.

Although there have been no commercial applications for these solid mixtures up to the present time, such demands may



Whatever your drying problem... KEMP HAS SOLVED IT BEFORE

K. S. G. silica gel adsorptive dryers are speeding forced draft production in every war industry^{*} that faces problems in drying gases, liquids or solids.

Kemp Silica Gel Dryers are available on prompt notice in a wide variety of standard types and sizes, while specially engineered units to meet special requirements are furnished as quickly as war conditions permit. To summarize, standard units are made in capacities from ten to 100,000 c. f. m., from atmospheric pressure to very high pressures. Activation is by gas, electricity or steam as desired, with single tower units for intermittent operation or twinned towers for continuous production.

To paraphrase a famous (and living) U.S. General, standard units may be had RIGHT NOW, special designs will take a little longer. C.M. Kemp Mfg. Co., 405 East Oliver Street, Baltimore-2, Maryland.



*Except the dehydration of foods. which is a different problem altogether.



Unsurpassed Sensitivity and Dependability

Write for Catalog 52

VALVE



Readily removed orifice cartridges eliminates

necessity for stocking several sizes for low tonnage installations.

· Carefully lapped hard faced ball insures positive tight shut-off

Thoroughly field tested.

Handles freon, methylchloride, sulphur dioxide.

GENERAL

801 ALLEN AVENUE . GLENDALE 1, CALIF. SRANCHES: Boston, New York, Philadelphia, Cleveland, Detroit, Denver, Chicago, Dalias and San Francisco





Properly Alloyed . . . Correctly Poured and Heat-Treated



Specialists in high alloy castings are here at Scottdale . . . with twenty odd years experience in the selection of the alloying elements and production of sound castings . . . and modern facilities to produce chromeiron and chrome-nickel castings.

If your equipment is operating under difficult conditions of corrosion. high temperatures and abrasion, investigate the use of chrome-iron or chrome-nickel castings to meet these conditions. For tubular products requiring a denser, stronger, more uniform metal, consider the use of DURASPUN CENTRIFUGAL CASTINGS.





We can produce castings in any size from a pound or so up to four tons in weight, with the correct proportion of alloying elements. Consult us on your requirements. Our metallurgists may be able to render valuable advice that will help to solve your problem.

DURALOY COMPANY Office and Plant: Scottdale, Pa.

Eastern Office: 12 East 41st St., New York 17, N. Y.

Los Angeles: Kilsby & Graham Chicago & Detroit F. B. Cornell & Associates

Scranton, Pa. Coffin & Smith

Metal Goods Corp.: St. Louis, Houston, Dallas, Tulsa, New Orleans, Kansas City

3-DU-8

arise as a result of new developments. Experimental work has indicated that nitrous oxide has bactericidal and bacteriostatic actions under certain conditions and its use for the preservation of foods has been suggested because of this action combined with its lack of toxic effects.

William Strobach, The S. S. White Dental Mfg. Co., Staten Island, N. Y., before the 31st annual meeting of the Compressed Gas Manufacturers' Association, New York. N. Y., Jan. 25, 1944.

PORT NECHES SYNTHETIC RUBBER

Six thousand men have been sweating at Port Neches in the face of all kinds of obstacles, and a few brickbats, to create and put "on stream" the first half of the largest single petroleum plant in the synthetic rubber program.

Prior to the war, during the war within the limits of the controls which we have had to impose for the greater good, and after the war the five companies—Atlantic, Gulf, Magnolia, Pure and Texas—have been, are, and will be competitors in the oil business. They first met to aid the synthetic rubber program at the invitation of government. Under special blessing of government they have acted cooperatively to build an efficient machine for butadiene production.

They organized a non-profit corporation to operate a joint enterprise for government and staffed the program with the best technologists who surveyed, according to their best judgment, all the information available. Such data as were in the possession of other competitors were turned over by them promptly and fully. Technical committees selected processes and process steps which were in no case those sponsored by any particular company. A small part of the normal butylene

A small part of the normal butylene which is produced in the five refineries in the Neches area is the raw material from which butadiene is made in this government-owned industry-operated plant. The price which each is to be paid for this raw material was separately negotiated with Rubber Reserve Co. The cost methods used in determining each of these separate prices were the same as those developed by the Petroleum Administration in its 100 octane program. Rubber Reserve used the Petroleum Administration as a technical advisor for this purpose.

It should be noted for the record that even with the vast new equipment investments and operating costs necessarily incurred, the contract prices for the butylene which is supplied to the Neches plant are only a few pennies more per gallon than the current wholesale price of premium motor gasoline at refineries in this area. Incidentally, the total volume to be supplied—about 4,500 barrels per day—is less than 1 percent of the total output of refined petroleum products of the five participating petroleum refiners.

It is true that this volume is a considerable though minor portion of the total butylene and butylene equivalents (iso butylene and amylenes) to be used by the five Neches refiners in producing 100 octane gasoline and butadiene. But in addition it must be borne in mind by those who have feared a shortage of butylene for the rubber program that for every refinery



• The valuables recovered by DRACCO Dust Control amounts to thousands of dollars each day. In many installations elimination of a serious dust hazard was the primary object but a profitable by-product was the recovery of valuables which often paid for the entire installation. The elimination of dust, even in small and what appears to be inconsequential quantities, should be given serious consideration because dust is destructive in so many ways. DRACCO Dust Control improves working conditions and increases plant efficiency. It will lower maintenance cost and prolong the useful life of equipment. Why not consult DRACCO Engineers? For over 30 years they have corrected dust conditions of every description.

• For Further Information write •

DRACCO CORPORATION

4071 E. 116th St., Cleveland 5, Ohio • New York Office, 130 W. 42nd St.

PNEUMATIC CONVEYORS . DUST COLLECTORS

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •

Safety Protection for Pressure Systems



THE LONERGAN "WTN" SERIES SAFETY AND RELIEF VALVES

Top-guided-high capacity-thoroughly engineered throughout-Lonergan "WTN" provides dependable protection for your boilers and other pressure systems. The "WTN" is more than just one valve-it is a whole series of related designs and constructions for steam, air, gases or liquid service. Vital pressure systems must be guarded—use dependable LONERGAN valves. Write for Bulletin 501A.

Medel "WTN"-EL Steel Safety Valve

J. E. LONERGAN COMPANY, 2nd & RACE STS., PHILA. 6, PA.

onergai

SAFETY VALVES . RELIEF VALVES . PRESSURE GAUGES . SPECIALTIES



making 100 octane gasoline in the United States which is called upon to make any butylene contribution for butadiene production, there will be five other 100 octane producers whose butylenes are not needed at all in the rubber program as well as a host of other refineries which are supplying butylenes, either as such or as "codimer", which flow into the 100 octane program.

Bruce E. Brown, Assistant Deputy Ad-ministrator, Petroleum Administrator for War, at dedication of Neches Butane Prod-ucts Co. plant, Port Neches, Texas, Feb. 23. 1944.

RESEARCH OF TALL OIL AND SULPHATE TURPENTINE

DURING the present emergency, tall oil and sulphate turpentine enjoy a market in excess of normal times. Tall oil is chiefly employed to compensate more expensive fatty acids primarily in the manufacture of various kinds of soaps and as a drying oil for cheap paints. It is noted that this commercial demand follows a similar pattern as in the Scandinavian countries dur-

ing the last war. Tall oil resin acids are more uniform in composition than those of rosin, and hence, produce high yields of dehydroabietic acid on disproportionation of hydro-gen in the highly unstable abietic acid molecule. Tall oil is not only an excellent raw material for making of this stable resin acid, but it may also serve as a chemical raw material for making of products now manufactured from coal tar. Crude sul-phate turpentine renders itself easily to processes for producing of high grade pine oil and other derivatives of terpenes.

It may be to the advantage of the sulphate pulp industry to develop their by-products along cooperative lines in the commercial utilization of tall oil and crude sulphate turpentine as chemical raw materials. The establishment of central plants would apparently best permit the industry to capitalize on the potentialities of their byproducts.

T. K. Hasselstrom, G. & A. Laboratories, before 29th TAPPI Annual Meeting, New York, N. Y., Feb. 15, 1944.

SYNTHETIC RESINS IN PAPER

THE PART played by synthetic resins in paper manufacturing, while now signifi-cant, gives every indication of assuming greater importance in the post war period. However such a development depends upon a proper evaluation of resin film properties when incorporated into paper making as against its behavior in other fields.

They must, first, be water soluble or water dispersible; second, lend themselves to specific application in the usual paper making operation; third, be odorless, colorless and, for many purposes, tasteless and non-toxic and, finally, they must not ex-cessively increase the cost of the finished paper. Other factors are probability of excessive machine time, broke recovery, variations in wet strength and grease-proof-ness, corrosion of equipment and aging characteristics of the finished product. Certain resin types have had limited

or no application in the paper manufacturing process. Among these are the phenolic resins which tend to yellow upon aging, require long curing periods and are not satisfactorily soluble; the alkyd resins

2 new books on ferrous metallurgy

By ERNEST J. TEICHERT

Supervisor of Metallurgy Extension, The Pennsylvania State College, currently Metallurgist, E. G. Budd Mfg. Co.



Here are the first two books of a new 3-volume publication in the Pennsylvania State College Mineral Industries Series. Each book is complete in itself and presents a sound and practical approach to important phases of ferrous metallurgy, based on material successfully developed and used in Pennsylvania State College extension courses.

INTRODUCTION TO FERROUS METALLURGY

Vol. I of Ferrous Metallurgy

This book presents the sciences upon which metallurgical research and practice are based, and gives a complete introduction to iron-making. It reviews the chemistry and chemical applications, physics, electricity, pyrometry, and combustion necessary to an understanding of the mechanism, effects, and calculations of metallurgical processes. It covers refractories, fluxes, and slags with information on their nature and use. The primary processing of iron ore in the blast furnace, and the methods and equipment used in the manufacture and production of cast iron, wrought iron, and crucible steel are fully described. Second edition, 484 pages, 82 illustrations, 74 tables, \$4.00.

THE MANUFACTURE AND FABRICATION OF STEEL

Vol. II of Ferrous Metallurgy

A book that tells you how to prepare, process, and fabricate steel for best production results. It gives all the important steelmaking processes, describes the materials and equipment used and most successful methods, and explains the chemical changes that take place. It covers the fabrication of steel from casting into ingot molds, through finishing and coating operations, and deals with such topics as rolling operations, welding methods, forging practice, and many others. Methods from tested plant practice are described, and many tables, curves, and diagrams give you practical, usable working data. An indispensable book for reference or study. Second edition, 487 pages, 152 illustrations, \$4.00.

10 days' free examination

McGRAW-HILL BOOK CO., INC. 330 West 42nd Street, New York 18, N. Y.	
Send me the books checked below for 10 days on approval. In 10 days I will pay for books, plus few cents postage, or return them postpaid. (We pay postage on orders accompanied by remittance.)	
Teichert-Vol. I-Introduction to Ferrous Metal- lurgy Teichert-Vol. II-The Manufacture and Fabri-	
cation of Steel	
Address	
City and State Position	
Company	

NS E M O think of the TROY-ENGBERG STEAM ENGINE not as just a drive but as a means for using steam twice and thus cutting costs.



Troy-Engberg Engines driving pumps in an oil refluery

Do you use steam in your plants for heating or processing? Do you use live steam from the boiler? Reduced to what pressure?

• The simplest way to look upon a modern Troy Engberg Steam Engine is as a combination pressure reducing valve and drive for a pump, compressor, fan, cooler, blower, dryer, or other processing equipment. It takes steam at the highest pressure, capitalizes on its inherent power and delivers in its exhaust at a lower pressure nearly all the heat units that were there originally. What could be simpler?

There are many places where the use of a modern steam engine can produce this power — it's called By-Product Power — at a lower cost than of any other equipment. So many places, in fact, that every process plant should investigate its use.

TROY ENGINE & MACHINE CO. Established 1870

1319 Railroad Avenue

Troy, Pennsylvania

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •

181





which, with certain exceptions, do not possess satisfactory solubility and permanence; and the vinyl and acrylic resins, most of which have not been adequately investigated. Those resins which have demonstrated varying degrees of usefulness in paper making may be classified in the urea and melamine formaldehyde group.

It was not until fairly recently that the resins were used in commercial quantities as tub sizes. Previous attempts failed largely because the urea-formaldehyde resins were not sufficiently substantive to the fiber and did not precipitate well enough in the beater to have satisfactory retention. Minor improvements followed with the result that appreciable amounts were used for various applications.

The use of melamine-formaldehyde resins in paper making resulted in the retention of wet tensile and wet burst of an order of 50-60 percent of dry tensile, and a large increase in wet rub as well as a 15 percent increase in dry bursting and dry tensile. A urea-formaldehyde resin known as Uformite 466 permits the use of a resin of this type as a beater size. This material meets the three principal requirements: it is water soluble, combines chemically or is physically absorbed by the pulp, and converts to an insoluble form in a limited time on the machine. In actual practice, wet strength of the finished product is proportional to resin concentration and at the higher resin concentrations, the increment per added unit of resin is less. Most cases do not require a resin concentration higher than 3 percent based on the pulp.

Experience indicates the desirability of adding this type of resin as early in the paper making process as possible, preferably in the beater rather than in the headbox or fan pump. The use of other ingredients normally used in paper making, such as rosin and starch, have no appreciable effect on resin application. At the present time, Uformite 466 is finding commercial application in the production of toweling, blue print, tag stocks, map and chart papers, bag and wrapping papers, glassine and greaseproof papers, tissue papers, manual and book papers and other miscellaneous types.

Louis Klein, The Resinous Products and Chemical Co., before Lake State Section. TAPPI, Feb. 11, 1944.

MELAMINE RESINS

CHEMICAL industry introduces new products, not always at the time they are initially developed, but more frequently as the need for them arises. The new plastic products that have been introduced during the last ten or fifteen years, have made major contributions to the better performance and serviceability of innumerable products. The raw materials and the resins produced from them were developed in the chemical laboratory, with little thought as to what might be their ultimate commercial application.

The rapid growth in the use of the resins produced from melamine is an outstanding example of how the science of chemistry and the chemical industry have contributed to the spectacular progress of the plastics industry.

Some years ago it was found that melamine reacts with formaldehyde to produce a soluble and fusible resin. This resin is colorless and water clear when produced from pure materials. It is hygroscopic and miscible with water and water-alcohol mixtures. When subjected to heat, or under the influence of certain chemicals, it becomes insoluble, infusible, and, as compared to its unconverted form, relatively tough. This change can occur over a wide range of acidity and basicity, in contrast to other thermosetting resins. The unconverted resin is capable of reacting with alcohols to form resins soluble in a wide variety of organic solvents. Melamine resin can be used in combination with either mineral or cellulosic fillers for molding compositions and laminated articles.

It was found that melamine resins will cure in contact with the heat resistant inorganic fillers such as asbestos, glass and silica. Asbestos filled molding compounds were consequently developed, and have extensively replaced hard rubber and other plastics in aircraft ignition systems.

In many of these applications, large parts weighing several pounds and containing numerous metal inserts are involved. Were it not for the advent of transfer molding, it would have been feasible to produce such intricate parts. Melamine laminated products which

Melamine laminated products which possess these added advantages of arc and heat resistance are now commercially available for use in electric insulation. It is to be noted that even the fabric base material is self extinguishing. The glass cloth and asbestos base products are, of course, more highly heat and fire resistant.

In addition to these war essential applications of melamine, which are based on electrical insulating properties, there are many other applications contributing to the war effort which are based on other properties imparted by melamine resins.

properties imparted by melamine resins. Prior to the war, melamine resins were used quite extensively in paper laminates to impart hardness, scratch-resistance, color stability, heatproofness, and protection against the action of cleaning agents.

Similar technique has been utilized during the war, in the production of name plates to replace those hitherto made of critical metals, translucent instrument panels and permanently mounted instructions and diagrams for servicing military equipment.

equipment. The improved heat resistance of melamine laminates, particularly in translucent form, will undoubtedly expand the use of such products in the field of lighting, and the improved weathering resistance imparted by melamine will permit, after the war, the use of laminates for exterior applications.

¹There are other examples of prewar applications which are contributing to the war effort. In combination with alpha cellulose, molding compositions were developed before the war in pearl and a limited range of bright stable colors. These were used for the holding of wash buttons which, after repeated laundering, preserved their original gloss and general appearance. The alpha cellulose molding material was also found well suited for use in molding tableware where its hardness and stain resistance were its principal advantages. During the war the military services have utilized melamine buttons for wash garments. Due to its light weight,



Carried in stock for all standard pipe sizes up to 12" in size-to-size and reducing sizes—up to 24" on special order. Stock fittings are drop forged steel, but to meet unusual conditions can be supplied in Monel, Everdur, Toncan Iron, wrought iron, etc.

Bulletin WT31 gives detailed information about all the advantages of WeldOlets, ThredOlets and Socket-End WeldOlets. Write for a copy today.



crystal gazing with PQ silicates

PLANNERS of postwar products and processes, look into our "crystal" this *soluble* glass. You'll see a variety of useful arts now being practiced in vital industries with the silicates, colloidal and crystalline. Also you'll find others still fresh from the patent office, like the ones listed below.

Some uses are still in the research stage, for the fifty different soluble silicates available from PQ offer properties of colloids, adhesives, detergents, binders at very low cost. Their efficiency and economy are worth investigating. Write for a copy of Bul. 17-4, which describes PQ publications on silicates of soda and their applications. *Vulcanizing neoprene:* Three parts by weight of sodium silicate prevents premature vulcanizing during milling but does not check vulcanization at the point where it is properly carried out.

Fire-Protecting Paint: Sodium silicate, combined with pyroantimonic acid in a colloid mill and subsequently with such pigments, oils, and resins as desired, furnishes a paint suitable for external application.

PHILADELPHIA QUARTZ CO. Dept. A, 119 South Third Street, Phila. 6, Pa. Chicago Sales Office: 205 West Wacker Drive Distributors in over 65 cities • 9 PQ Plants



combined with relative lack of fragility, molded tableware has been utilized by the Navy for overseas stations, light vessels, and aircraft use. More recently, a number of the molders in the States have been producing compartment mess trays with a medium impact, fabric-filled melamine molding composition.

A more recent application for melamine resin has been in hot set waterproof glues for plywood, and laminated wood. Its outstanding characteristic is the strength of the glue line when under tension and in shear; combined with water resistance far surpassing the requirements for aircraft plywood.

The use of melamine in glues provides an excellent example of an unique property of melamine. It has been found that the addition of relatively small proportions of melamine resins to urea resins produces glues of bonding quality very much superior to that of the urea glues themselves.

Numerous applications, other than in plastics, demonstrate the ability of melamine when used in small proportions, to impart special properties to other products without modifying their fundamental characteristics-texture, form, etc.

Untreated paper scarcely holds together when wet, but paper containing about 3 percent melamine resin is over 60 percent as strong when wet as when dry. In addition to imparting wet strength, the incorporation of melamine resin has greatly im-proved the wet rub resistance. Contrary to what one might expect, the addition of this resin does not embrittle the paper, but actually improves the dry tensile strength and increases the capacity of this paper to be repeatedly folded without frac-ture. These improvements are retained even on prolonged storage of the paper under high humidity and temperature conditions. Paper so treated has been used for such applications as toweling, blueprints, maps, heavy duty paper pack-aging, and currency, and numerous other applications. The utilization of melamine resins in the manufacture of paper is making possible the entry of paper into appli-cations from which this material has been excluded by reason of its great loss of strength upon becoming wet.

Another example of the use of melamine resins in relatively small proportions to impart specific properties is in the treatment of textiles. These resins, in water solutions, have been used to render fabrics creaseproof, in the shrink-proofing of cotton, rayon and woolen fabrics, as stiffening agents in mosquito and camouflage netting, and as hardening agents to modify polyvinyl butyral and other elastomers, in impermeable coatings.

The alkylated melamine resins produced by reaction with alcohols have been used extensively, particularly before the war, as components of baking enamels. It is anticipated in the postwar period that this application will increase in volume. In these enamels, melamine resins contribute, not only extreme hardness, but curing speed, color retention, resistance to heat and weather, and the action of many chemicals and solvents.

Melamine resins are used in many strictly plastic applications, as well as in products that are in no way directly related to plastics. In all instances melamine

Water for the folks of China

and Chemical Mixtures for the Processing Industries

> Water supply and sanitation are postwar projects to improve health, economies and contentment of backward peoples.

5

WILSON Pulsafeeders will play their part because Government agencies and leading technicians have specified thousands of them for use all over the world and their performance has been uniformly gratifying. They operate with positive displacement, without packing glands or breakable diaphragms; without contact between working parts and the chemicals being handled.

Flows or one or more liquids are constant at any manually adjusted rate from one cubic centimeter to four hundred gallons per hour; and accuracy does not change with viscosity or feed against pressure.

WILSON Pulsafeeders fill all requirements in chemical proportioning, food and other processing industries, research and ampoule-filling laboratories, in water and sewage treatments... wherever difficult problems are met.

> Let us have your inquiry in form that will permit us to give specific information; and remember that we also supply Automatic Liquid Filling Machines.







REEVES Reducer - Type TRANSMISSION

• This new REEVES unit consists of the famous REEVES Variable Speed Transmission with built-in, helical-type speed reducer. Provides accurate speed adjustability and speed reduction without use of other auxiliary speed reducing equipment. Compact, space-saving. Easily installed on any driven machine. In horizontal or vertical designs for mounting in any desired position. Each design offered in many different horse power capacities and ranges of speed variation. Either design may be equipped for individual motor drive by use of REEVES motor base, adjustable to accommodate any standard make motor. Get full details of this efficient new REEVES drive. Write for 128-page Catalog CM-435.

REEVES PULLEY COMPANY . COLUMBUS, INDIANA Recognized Leader in the Specialized Field of Speed Control Engineering







VARIABLE SPEED TRANSMISSION for providing infinite, accurate speed flexibility over wide range.

VARI-SPEED MOTOR PULLEY converts any standard constant speed motor to a variable speed drive.

MOTOORIVE combines motor, speed varying mechanism a duction gears in single unit.



CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •



PURITY: Ninety-five per cent minimum.

DISTILLATION RANGE: Ninety-five per cent shall distill within a range of 2°C. including the temperature of 243°C.

FREEZING POINT:23°C. minimum. SOLUBILITY: Sparingly soluble in cold water. Soluble in dilute mineral acids and in most common organic solvents, including alcohols, ethers, esters, ketones, aliphatic and aromatic hydrocarbons.

USES: Manufacture of pharmaceuticals, dyes, insecticides, rubber accelerators, and in organic syntheses.

APPROXIMATE WEIGHT PER GALLON: 9.15-lbs.

SHIPPING CONTAINERS: 450-lb. drums; 45-lb. cans.

A Dependable Source of Supply For All Coal Tar Products

• With unusual production and delivery facilities, plants in 17 strategic locations, and offices in major cities, Reilly offers a complete line of coal tar bases, acids, oils, chemicals and intermediates. Booklet describing all of these products will be mailed on request.

REILLY TAR & CHEMICAL CORPORATION Executive Offices: Merchants Bank Building, Indianapalis, Indiana 2513 S. DAMEN AVE., CHICAGO, ILL. ST. LOUIS PARK, MINNEAPOLIS, MINN.



has imparted a high degree of resistance to the effect of water and moisture vapor. The versatility of the applications of melamine is demonstrated by its ability to be used in conjunction with a wide variety of materials.

In its use in plastics, melamine imparts heat and fire risistance, arc and cracking resistance, hardness, and general inertness to the effects of humidity and the other influences of weather.

C. J. Romleux, American Cyanamid Co., before Canadian Section, Society of the Plastics Industry, Jan. 25th, 1944.

ELECTROLYTIC TUNGSTEN

TUNGSTEN ore today occupies a major position among strategic minerals. Few minerals have increased so rapidly in importance within the last twenty years. In the case of tungsten this has been mainly due to an increase in the use of hard alloy steels rather than to the introduction of new applications of tungsten metal.

On account of the metal's several unique properties, tungsten is being used as pure metal, as alloy constituent, and in chemical compounds. Its use as pure metal is especially due to its high melting point of 3,370 deg. C., the highest of any metal. It is practically the only metal now used for incandescent lamp filaments. A com-bination of physical properties—tensile strength, hardness, melting point, ductility, corrosion and erosion resistances-of this metal accounts for its efficient service as the major and essential constituent in making high speed steel which plays a most important role in the tool industry. Tungsten is also used for electrodes for atomic hydrogen welding, in tungsten arc lamps, and for electrical contacts in automobile engines. Pure tungsten is employed as a heating element in electric resistor furnaces, in the form of wire and ribbon; in gas-discharge lamps, and in radio tubes. For leading-in wires through special borosilicate glass, its low thermal expansion is of importance. The fact that the tensile strength and modulus of elasticity of fine tungsten wire are the highest of any metal invite its use in measuring instruments. Tungsten compounds are used in the arts as mordants, pigments and fireproof ma-terials. Finally, tungsten carbide tools are used in machine shops on account of the carbide's extreme hardness.

Only two tungsten minerals are of commercial importance, namely, wolframite (Fe,Mn)WO₄, and scheelite, CaWO₄. Wolframite with high iron content is termed ferberite; and with high manganese content, huebnerite. The largest and richest tungsten deposits are in Asia. China has been dominating the tungsten market since 1916. Despite the war, China's 1941 production outstripped that of any other country and China remained the world's largest producer of tungsten ore.

largest producer of tungsten ore. As a result of a large number of tests, it was invariably found that the WO, content of tungsten ores will dissolve in fused alkali borates and alkali phosphates. Furthermore, these baths are good conductors of electricity and produce pure tungsten metal at the cathode at relatively high current efficiencies. Different types of ores which included wolframite, ferberite, kuebnerite and scheelite were tried and proven to be satisfactory. The tungsten in the ore used does not require preliminary transformation into alkali tungstate as in the older processes. The process can be applied not only to high grade ore concentrates but also to low grade ores and concentrates.

For the fused borax bath using wolframite as the source of tungsten, the results were: (1) best composition of electrolyte, $1\frac{1}{2}$ parts, Na₂B₂O₇ per 1.0 part of dre concentrate; (2) operating temperature, 1,050 to 1,300 deg. C.; (3) optimum current density, 50 amp. per sq.dm.; (4) best current efficiency obtained, 78.23 percent; (5) best yield, 417.5 g. per kwh.; and (6). best quality of tungsten produced, 99.57 percent W.

The

THIS IS THE

of a series

explaining why

G-T PACKINGS

give better

service.

8 REASONS for the Superiority

of G-T Packings

1. SIMPLE LINE . . . makes correct selection easy

2. COMPLETE LINE . . . an

3. SELF LUBRICATING .

exactly suitable type for every service.

each individual strand saturated with lubricant

4. SPECIAL LUBRICANTS ... lubricant for each service specially compounded in our own plant

5. SELECTED YARNS . . . provide tensile strength and resist high tempera-

6. CONSTRUCTION . . . assures maximum endurance, longest life, lowest

7. EXPERIENCE 80 years of manufacturing experi-

8. PERFORMANCE . . . proven in thousands of plants of every type

ture

friction

ence

For the fused phosphate bath using wolframite as the source of tungsten, the results were: (1) best composition of electrolyte, 1.75 parts phosphate mixture (7 mols Na,P₂O₇ + 3 mols NaPO₂) per 1.0 part of ore concentrate; (2) operating temperature, 1,050 to 1,300 deg. C.; (3) optimum current density, 50 amp. per sq.dm.; (4) best current efficiency obtained, 80.96 percent; (5) best yield, 505.1 g. per kwh.; and (6) best quality of tungsten produced, 99.7 percent W.

tungsten produced, 99.7 percent W. The tungsten metal produced from either the fused borate or the fused phosphate bath is free from impurities, present in the tungsten ores, such as phosphorus and arsenic, which must be absent according to rigorous specifications laid down by the tungsten steel producers.

Colin G. Fink, Columbia University, and Chuk Ching Ma, Westinghouse Lamp Co., Bloomfield, N. J., before the 84th general meeting of the Electrochemical Society, New York, N. Y., Oct. 14, 1943.

INHIBITORS

CERTAIN chemicals, when they are added to a corroding solution in small amounts, have the property of reducing the total amount of corrosion of metals. Such chemicals are called corrosion inhibitors. Thus the chemical is termed an inhibitor if the following expression has a positive value but an accelerator if it has a negative value.

$$P = \frac{W_1 - W_2}{W_1} \times 100$$

where W_1 is the weight loss of a metal specimen after some definite period of exposure in a corroding solution and W_2 is the weight loss of an identical specimen exposed for the same length of time in a similar solution to which a small amount of some of the chemical in question has been added. The chemical would be an effective inhibitor if P had a high value, say +80 or +90 and a weak inhibitor if the value were only +10 or +20.

Further classifications of inhibitors are also useful. If the attacked area of the specimen exposed to the inhibited solution is larger than the attacked area of a similar specimen exposed to the uninhibited solution, the inhibitor is classed as "expansive." If the attacked area is smaller for the specimen exposed to the inhibited liquid, the inhibitor is "contractive." Similarly, if the depth of attack at those areas of the specimen exposed to the inhibited solution than for the specimen exposed to the uninhibited solution, the inhibitor

G-T PACKINGS service-resistant and long wearing

that make

Unly the finest obtainable and most suitable materials are used in G-T Packings.

For PALMETTO and other G-T Packings, high quality, long-fibre, heat-resistant, Canadian asbestos is carefully selected and processed in one of our own large plants. For SUPER-CUTNO acid-resistant Packing, only genuine South-African Blue Asbestos is used because it does not contain water. PALCO Packing, for cold water, is made of selected long-line cotton spun into a soft, lubricant-absorbing roving which is superior to flax and other materials.

These are instances of how each G-T Packing is specially prepared for long life in the precise range of services for

which it is designed. To assure lowest year-round packing costs and best service, insist on G-T Packings . . . obtainable from your dealer.



GREENE, TWEED & CO. Bronx Blvd. at 238 St., New York 66, N.Y.




It would be difficult to find a "pumpable" material, in the handling of which LAWRENCE CENTRIFUGAL PUMPS have not found wide-spread and successful applications. Especially in the pumping of corrosive acids and clemical solutions, both hot and cold, have LAWRENCE CENTRIFUGALS made notable records for economy, low maintenance cost, and long life. Starting with designs that are fundamentally right, LAWRENCE construction is developed in various resistant metals and alloys specially selected to withstand the action of the fluid, or semi-fluid, pumped. Fre-

AWRENCE CENTRIFUGALS

quently, abrasive as well as corrosive effects must be guarded against. Our experience of over 80 years is at your service-without o':ligation. Tell us your problems; let us work with you.

LAWRENCE MACHINE & PUMP CORP. 369 Market Street LAWRENCE, MASS.



Acid Pump in Lead



Vertical Acid Pump Inside Tank

would be classed as "safe," whereas if the reverse were true, it would be classed as "dangerous."

Thus the following classifications of effective inhibitors are possible: expansive, safe inhibitors; contractive, safe inhibitors; contractive, dangerous inhibitors. The class, expansive, dangerous inhibitors does not exist because such a chemical would be an accelerator.

It is of value to attempt to explain why a given chemical falls into one or the other of these classes. In all cases where corrosion is an electrochemical phenomenon, the rate of attack will be proportional to the current flow between the local anodes and cathodes. Thus,

D = kI

where D = rate of attack, and I = current flow. The magnitude of the current at any instant is determined by the open circuit potential difference between the local anodes and cathodes, the anode and cathode polarization and the electrical resistance of the liquid path between the anodes and cathodes. Otherwise expressed

 $I = \frac{E - (E_{\bullet} - E_{\epsilon})}{R}$

Where E = open circuit potential between the local anodes and cathodes, $E_s =$ anode polarization, $E_c =$ cathode polarization, and R = resistance of the liquid path. Thus, from the electrochemical standpoint, in order for an inhibitor to be effective it must do one or more of the following: (1) Increase the resistance (R) of the electrolytic path between the local anodes and the local cathodes. (2) Increase the polarization (E_s) of the local anodes. (3) Increase the polarization of the local cathodes (E_c). (4) Decrease the open circuit potential difference (E) between the local anodes and the local cathodes.

If an inhibitor functioned solely by increasing the resistance of the electrolytic path and did not affect the area of the local anodes, it would be a safe inhibitor. If the anodic area were decreased, as long as the decrease in anode area did not exceed the rate of decrease in local current flow, it would still be a safe inhibitor.

If the inhibitor increased the polarization of the local anodes but did not affect other factors, especially the anode area, the inhibitor would be classed as safe. However, if it reduced the anode_area faster than it increased anodic polarization, it might be dangerous.

Actually, inhibitors very seldom have only one of the four effects. Generally, the addition of an inhibitor will cause simultaneous alterations in anode and cathode polarization, in resistance of the electrolytic path, and in open circuit potential difference between the local anodes and the local cathodes. Thus the mechanism of inhibitor action in any specific case is likely to be exceedingly complicated. It is much easier to state how an inhibitor behaves than to account for the way of its behavior. Because of the difficulty, relatively few tests have been made to evaluate reasons for inhibitor action.

R. B. Mears and G. G. Eldredge, Aluminum Research Laboratories, New Kensington, Pa., before the 33rd general meeting of the Electrochemical Society, Pittsburgh, Pa., April 8-10, 1943.

DES. MOINES BUILDINGS FOR FIGHTING JOBS

and for Service Stripes, too !

Pittsburgh-Des Moines' many years of service to industry in peace developed the wealth of building experience serving our wartime construction assignments today.

Since Pearl Harbor, the demands for speed have been doubled and redoubled—and met, with the skill and craftsmanship which have marked the work of this company as building contractors in the industrial field, on commercial projects of specialized types throughout the country.

Handling the job complete from foundations to roof, including all service facilities, Pittsburgh-Des Moines is ready to meet your "priority" building needs under one contract, one responsibility—with satisfaction assured over many future years of useful life.



PITTSBURGH · DES MOINES STEEL CO.

PITTSBURGH, PA. 3417 NEVILLE ISLAND—DES MOINES, IOWA, 916 TUTTLE STREET NEW YORK, ROOM 990, 270 BROADWAY · CHICAGO, 1207 FIRST NATIONAL BANK BUILDING DALLAS, 1216 PRAETOFIAN BUILDING · SAN FRANCISCO, 606 HIALTO BUILDING

SPRAY TROUBLE? CONSULT NOZZLE HEADQUARTERS

Fig. F-80

Are all of your processes using Spray Nozzles as efficient as you think they could be? Do the Sprays produce even distribution? Break up the liquid into as fine particles as you would like? Resist the corrosion or wear conditions satisfactorily?

Send Monarch an outline of your spray problem—if your liquid can be sprayed with direct pressure at all—Monarch can furnish the nozzles.

NOZZLES FOR:

- · OIL ATOMIZING
- HUMIDIFYING
- · AIR WASHING
- DESUPERHEATING
- SPRAY PONDS
- . MILK POWDERING
- · EGG DRYING
- ACID CHAMBERS
- · CONCRETE CURING

WRITE—While you think of it!

MONARCH MFG. WKS, INC. 2730 E. WESTMORELAND ST. PHILADELPHIA 34, PA.

Ab No. 5415

FOREIGN LITERATURE ABSTRACTS

LITHIUM IN ALUMINUM ALLOYS

CONSIDERABLE interest in light and nonferrous metal alloys containing lithium has developed within the last ten years. The addition of several hundredths of one percent of lithium to copper, for example, improves the mechanical properties to a surprising degree. Alloys of aluminum with zinc and lithium show properties comparable to those of soft steels.

Original work was conducted in the metallurgical laboratory of the Institute of General and Inorganic Chemistry of the Academy of Science (USSR) on the properties of various alloys of aluminum, zinc and lithium. The accompanying table shows the compositions used and the type of treatment to which the alloys were subjected. Aluminum-zinc alloys containing 6-24 percent zinc were also investigated.

Aluminum alloy containing 11.89 percent zinc and 0.11 percent lithium, for example, has the following properties after being annealed: elongation of 33.5 percent, temporary resistance to rupture of 20 kg. per sq.mm., Vickers hardness of 70, and an Ericksen index of 8-9 units for a sheet 1 mm. thick. The alloy with 5.6 percent zinc and 0.4 percent lithium had the following properties: elongation of 25.7 percent, temporary resistance to rupture of 10 kg. per sq.mm., hardness of 31, an Ericksen index of 9 units. After hardening and natural aging, the second alloy has a temporary resistance to rupture of 22 kg. per sq.mm. and a hardness value of 57. Resistance of these alloys to corrosion in sea water decreases with an increase in lithium content up to composition IV (see table) after which it increases again.

Digest from "Mechanical Properties of Alloys of Aluminum with Zinc and Lithium," by T. A. Badaev and F. I. Shamrey, Zhurnal Prikladnoi Khimii XVI, No. 5-6, 161-172, 1943. (Published in Russia.)

BORON IN CERAMICS

BORATES and boric acid are used in producing glazes on all types of ceramic ware, from porcelain dishes to earthenware pipes. Boric oxide improves the appearance and color of enamelled hardware. It also tends to decrease the coefficient of expansion so

Thermal Treatment of Aluminum-Zinc and Aluminum-Zinc-Lithium Alloys

		Hardenin Natural	ng and Aging	Ha	rdening an tificial Agin	ld ng
	Annealing Temp.,	Hardening Temp., der C	Aging Time, deve	Hardening Temp., deg. C	Aging Temp., deg C	Aging Time,
Cross-Sections	ueg. 0.	ucg. 0.	any s	ace. o.	acg. 0.	
Al-Zn Alloys	350	350	10	350	75	42
I Zn:Li = 104:1	350	350	10	350	75	42
II Zn:Li = 37.5:1	350	350	10	350	75	42
III Zn:Li = 13.9:1	450	450	10	450	125	48
IV Zn:Li = 4:1	450	550	10	550	125	46
VII Zn:Li = 1:1.3	450	580	10	580	150	42



• Taber "General-Use" Pumps for the Processing and Chemical industries are not subjected to costly "onepurpose" pump waste. Merely changing Impeller and Casing fits Taber Pumps for various services.

Helpful Bulletin CLVS-339 on request.



that objects finished with such a frit are more resistant to considerable changes in temperature and have greater elasticity. Glazed finishes containing boron oxide are resistant to solutions of alkalis and salts such as caustic soda, ammonia, carbonates, phosphates, chlorides, sulphides and even to acid solutions if the proportion of boron oxide to silicon dioxide is proper. Boron products, especially borax, can largely supplant lead compounds in ceramics which is advantageous both in that the quality of the glaze is improved and that the boron is not toxic.

A mixture of 90 percent salt and 10 percent borax gives best results for earthenware pipes. A refractory material with optimum chemical resistance is made with 0.3 percent borax and 1.3 percent boric acid added to the refractory mass. Refractory bricks for furnaces are finished by impregnation with 200 parts borax, 225 parts litharge and 120 parts fine sand. This mixture is applied in the form of a paste and baked on at 900-1000 deg. C.

Digest from "Boron Products in the In-dustries," by E. F. Gobel, Revista de Química Industrial XII, No. 137, 16-21, 1943. (Published in Brazil.)

KETONE MOTOR FUELS

THE FIRST ketone motor fuel, known as "Ketol," to be introduced into industry is obtained by dry distillation of the calcium salt of organic acids from the butyric acid fermentation of sugar solutions. This product, a clear liquid of unpleasant odor with a heat value of 9,200 cal., is a mixture of acetone, propyl ketone and other ke-tones with varying amounts of isobutyl

and amyl alcohols and aldehydes. Fischer's "Synthal" contains ketones, including acetone. Recent investigations have shown that acetone is suitable for motor fuel. It has an octane number of 98, latent heat of vaporization of 526 joules per gram and a heat value of 6,959 cal. Also suitable are certain of the higher homologs of acetone, including methyl ethyl ketone, which has an octane number of 99. Lower ketones are especially suitof 99. Lower ketones are especially sur-able as blending agents for aviation fuel. A mixture of 30 parts of ketone, 70 parts of gasoline and 0.6 parts of tetraethyl lead has an octane number of 100. Italian patent 350,427 describes a proc-

ess for making acetone oil by fermentation of molasses to lower fatty acids and then catalytically ketonizing the acids in the vapor phase at 300 to 500 deg. C. with steam.

Digest from "Ketone Motor Fuels." Oel und Kholc in Gemeinschaft mit Brenn-stoff-Chemie 39, Sch. 138, 1943. (Published in Germany.)

GAS PURIFICATION

WHILE the ferric hydrate content of natural iron oxide is the most important factor in removal of hydrogen sulphide from coal gas, much exact information is missing from most discussions on this essential phase of the gas industry. Until recently, it was assumed that the ferric oxide content roughly indicated the reactivity of an oxide. Then it was realized that the water of hydration exerted a definite influence, and so it has been the practice of the Australian gas industry to use, for hydrogen sulphide removal, oxide from Port Macquarie containing 6 percent or

This Brochure Will GUIDE YOU In Buying Stainless Steel Processing Equipment

With war orders reducing the speed of delivery-with all emphasis on getting equipment that will stand up in the emergency-with all efforts directed toward conserving metals and alloysengineers will make frequent use of this ready reference covering all the facts about what to look for when specifying stainless steel processing equipment:

- 1. What grade will you order?
- 2. What finish will serve you best?
- 3. How will you design for economy and for conservation of steel?
- 4. How can you be sure of sound welds?

These and other questions, important to your production, are answered in the new informative brochure issued by S. Blickman, Inc.

> SEND NOW FOR THIS BOOK

What to look for STAINLESS STEEL PROCESSING EQUIPMENT

S. BLICKMAN, INC. 601 GREGORY AVE., WEEHAWKEN, N. J.

What to look for

when you specify STAINLESS STEEL

PROCESSING EQUIPMENT

TANKS . KETTLES - CONDENSERS - AGITATORS EVAPORATORS . PANS . VATS - CYLINDERS

No dangerous spark from this tool—



Latest model open-end wrench, specially engineered for greater strength with less weight. One of over 400 standard tools available.

...it's an Ampco Non-Sparking Safety Tool for use in hazardous situations

Explosive fumes and gases, a fortune in plant equipment, and men at work...that's a combination that calls for your utmost vigilance. From the aviation mechanic opening a gasoline drum on some distant battlefront, to factory processing of chemicals, such men need the protection of these well-known safety tools. • Tested and approved

by Factory Mutual Laboratories and other insurance authorities frequently required to earn lowest insurance rates. • Standardize on Ampco Safety Tools. Special types available when needed.

Write for catalog.





more water of hydration and a total iron content of over 70 percent.

In natural iron oxide from Port Macquarie, the active portion for hydrogen sulphide absorption is the hydrated oxide, comprising approximately 50 percent by weight of the total oxide. Optimum conditions for hydrogen sulphide absorption by this oxide are 6.5 to 7 percent moisture and 29–32 deg. C. Acidity in the purifiers lessens the activity of Port Macquarie oxide. The optimum hydrogen ion concentration is within the range 6 to 8. By heating the oxide above 500 deg. C., no stable hydrate is re-formed when the oxide so treated is brought into contact with water, and the reactivity of the oxide is substantially reduced. On heating through a temperaure range of 500 to 700 deg. C., an irreversible change occurs with a corresponding loss in activity for hydrogen sulphide absorption.

It has been found possible to convert chemically the inactive rhombohedral form of oxide into the active cubic form. In addition, it has been shown that the chemically converted oxide has a greater activity for hydrogen sulphide absorption than the original oxide. An inert filler of the nature of granulated refractory insulating brick was found to give the desired porosity to minimize back pressure without development of caking in service or decomposition during roasting. The use of ferric hydrate chemically prepared from natural iron oxide is considered to have definite advantages for plant conditions.

War conditions emphasize the need for additional experimental work on the suggested method of sulphur removal in order to conserve oxide stocks and to make available for Australia a large tonnage of sulphur, a commodity which will become more valuable as imports become more difficult.

Digest from "The Fundamentals of Dry Purification of Towns Gas" by E. McLelsh, Journal and Proceedings of the Australian Chemical Institute 10, No. 8, 198–218, 1948. (Published in Australia.)

BARIUM PEROXIDE

COMMERCIAL grade barium peroxide always contains a small proportion of barium oxide which is not the result of secondary dissociation, since at the temperature of the oxidation no dissociation pressure can be measured. It appears to be caused by some slight lack of porosity of the initial oxide and to the presence of certain impurities, such as iron oxides, which catalyze the decomposition of the barium peroxide. As a result, commercial material may contain some 10 percent of the lower oxide. Attempts to oxidize this by after-treatment have been unsuccessful. It was thought at first that washing the product with water would bring about hydration and that on subsequent drying considerable decomposition would occur.

If barium peroxide hydrate is dried at a temperature of over 200 deg. C., decomposition occurs, but the speed of hydration is very slow. If temperatures under 40 deg. C. are maintained during the period of contact with water, the proportion of hydrate formed after 15-20 minutes is negligible. Experiments were carried out to find out what volume of water and method of washing were most appropriate to the purification of this material. This involved repeated washings with fresh or previously used water. In this way the peroxide content of impure material can be raised some 5 percent without appreciable loss.

Digest from "Barlum Peroxide," by E. V. Drathen and H. Walther, Chem. Z., 119, March 1942. (Published in Germany.)

ALIPHATIC HYDROCARBONS

METHANE can be oxidized with air to form a certain amount of formaldehyde, but the process still awaits large-scale development in Germany. Methane can also be converted to a mixture of carbon monoxide and water, and plants for making motor fuels could probably be operated alongside natural gas fields. Ethane oxidation, which has not been carried out on a commercial scale, yields formaldehyde, formic acid and some acetic acid. The oxidation of propane and butane with air has been given considerable attention but no feasible process has yet been developed. It is undoubtedly possible to produce certain alcohols or aliphatic acids, although the yields are poor. Low temperatures and high pressures promote the oxidation process.

Oxidation of elefines produces olefine oxides. Although many suggestions have been made for the preparation of ethylene oxide from ethylene and air with the aid of silver catalyst, it still has not yet been proved that such process would be feasible on a large scale.

Olefines can be dimerized or trimerized with the help of catalysts or inorganic acids to yield gasoline-like materials. They can also be polymerized with catalysts such as benzoyl peroxide or boron fluoride to substances having molecular weights up to 500,000. Ethylene and propylene can be made to yield lubricating oil or wax-like materials by polymerizing with phosphoric acid, phosphorus pentoxide or aluminum chloride under pressures of several thousand atmospheres and at temperatures of 200-300 deg. C. Purity of the olefines, especially from hydrogen, is very important for the polymerization. Isobutylene can be polymerized at temperatures as low as --80 deg. C., with boron fluoride catalyst, into gum-like synthetics. These are known in industry as "Oppanol" and are used for lining chemical apparatus.

Digest from "The Utilization of Lower Aliphatic Hydrocarbons," by C. T. Kautter, Die Ohenie 56, 225, 1943. (Published in Germany.)

CELLULOSE ESTERS

By USING phosphoric instead of sulphuric acid in the nitration acid mixture, degradation of the cellulose is avoided; the degree of polymerization as the other essential viscosity-influencing factor is thus eliminated. It was found that under such conditions—confirming the results reported by previous investigators—the viscosity increases with increasing degree of substitution, probably as a result of increasing solvation (increasing particle volume) in the solvent.

Digest from "The Influence of the Degree of Substitution Upon the Viscosity of Cellulose Nitrates," by H. A. Wannow, Kolloid-Z. 102, No. 1, 29-34, Jan. 1943. (Published in Germany.) [From Bulletin of the Institute of Paper Chemistry, 13, No. 11, 429, July 1943.]

For Lower Costs and Dependable Results in Cooling LIQUID CHEMICALS



• Wherever there is a need for the use of cooling water or the cooling of any liquid to exact temperatures, the NIAGARA AERO HEAT EXCHANGER provides a more accurate control and lower costs for cooling. Refrigeration is not needed.

These results are advantageous in all types of water-jacketted and water-cooled equipment; for example, they have solved for many the troubles coming from excess water and oil in air compressor lines. Other uses include the cooling of diesel engines and hydraulic equipment; also chemicals and intermediates requiring cooling or controlling temperatures in chemical processes.

In addition, wherever used, it saves practically all the expense of cooling water and the cost of piping, pumping and extra equipment. Users have cut such costs as much as 95%.

Write for complete information



WHEN YOU PLAD YOUR FILTER STATION

...that's the time to decide on your FILTER AID

Filtration engineers and progressive makers of filter equipment agree that there should be a definite relationship between filter equipment and filter aid. This means the filter aid best suited to your needs must be determined before your filter station can be properly designed.

Whether you are planning a new filter station or want to increase the capacity of present equipment, Johns-Manville's 30 years' experience in working with filter equipment manufacturers and filter-aid applications may prove of valuable assistance to you. We will be glad to co-operate with you and your equipment maker in carrying out the test work necessary to assure the proper balance between filtration equipment and filter aid for greatest efficiency.

Nine standardized grades of J-M Celite Filter Aids are available providing a wide range of porosities and screening properties. If you are already using Celite, certain minor changes in equipment and procedure may further increase capacity, reduce cost. If not, it will pay you to investigate these high flow-rate filter aids immediately. Write Johns-Manville, 22 E. 40th St., New York 16, N. Y.

Celite is available for prompt shipment



CHEMICAL ENGINEER'S BOOKSHELF-

LESTER B. POPE, Assistant Editor

PLASTICS ANNUAL

PLASTICS CATALOG, 1944 edition. Pub-lished by Plastics Catalogue Corp., New York, N. Y. 990 pages. Price \$6.

THIS is the usual fine annual issue of the catalog which contains much of the material of interest to everyone in the plastics industry or concerned with these products and their raw materials. All sections of the volume have been revised and brought up to date. Some rearrangements have been made. Many of the data have been put on large fold-in charts. The only adverse comment has to do with the large charts. So many interfere with ease in referring to material in the book and in addition these large charts are awkward to handle and if folded and unfolded many times are soon destroyed. The catalog includes not only solid plastics but coating materials, laminates, synthetic fibers and synthetic rubbers.

MODERN CONCEPTS

ELECTRONIC INTERPRETATIONS OF OR-CANIC CHEMISTRY. By A. Edward Remick. Published by John Wiley & Sons, Inc., New York, N. Y. 474 pages. Price \$4.50.

Reviewed by F. C. Nachod THERE are a number of books dealing with the physical chemistry of organic compounds, such as Hueckel's "Theocompounds, such as Prucckers Theo-retische Grundlagen der Organischen Chemie," Waston's "Modern Theories of Organic Chemistry," and Hammett's "Physical Organic Chemistry." Your re-viewer was therefore surprised and somewhat doubtful with respect to duplication of effort when he was asked to review this treatise. He is now very enthusiastic and pleased to recommend this text by Dr. Remick wholeheartedly to anyone who wishes to obtain quickly a good understanding of modern organic chemistry con-

cepts. The reason for this enthusiasm was substantiated by a discussion with an organic chemist friend who pointed out that most other treatises approach the field from the view point of the physical chemist. This book however is written with the organic chemist's viewpoint and carefully builds up from it. The mathematical treatment which, of course, is necessary in certain parts of such a subject is nevertheless strict and definite.

The introduction is based on the historical development of various concepts. Following chapters are on the Lewis theory, on the contributions of the English School (Ingold, Sidgwick, Watson and others). Electron- pairing and sharing reactions as well as solvent roles are adequately treated.

The purpose of the book is a dual one, "a review and an advanced textbook." Your

reviewer feels that Dr. Remick certainly has accomplished both goals. Especially good are the appendixes which cover such topics as Refractivity and Chemical Constitution, Dipole Moments, and so forth. A table of Basic Principles is found at the end of the book and reference is made to

RECENT BOOKS RECEIVED

Basic Mathematics for War and Industry. By P. H. Daus, J. M. Gleason & W. M. Whyburn. Macmillan. \$2.

The Chemistry of Synthetic Substances. By E. Dreher. Philosophical Library. \$3.

- The Constituents of Wheat and Wheat Frod-ucts. By C. H. Balley. Reinhold. \$6.50. Ferrous Metallurgy. Vols. I & II. 2nd ed. By E. J. Telchert. McGraw-Hill. \$4 per vol.
- The Physical Chemistry of Electrolytic Solu-tions. By H. S. Harned & B. B. Owen. Reinhold. \$10.
- Protective and Decorative Contings, Vol. IV. By J. Mattiello. Wiley. \$5. Quantitative Analysis. 2nd ed. By H. S. Booth & V. R. Damerell. McGraw-Hill. \$2.50.

A Survey of General and Applied Rheology. By G. W. Scott Blair. Pitman. \$4.

this table throughout the text. The author has achieved a truly remarkable correlation not found in any other text on this subject.

The absence of an author index and 18 typographical errors noted (the name Sidgwick is consistently misspelled) are the only criticism The book will probably soon see its second edition and it is hoped that these two comments will have been helpful.

In conclusion your reviewer would like to say that he has read a very fine book and that he believes that it will rank with the foremost texts of the field.

EMULSION REPRINTS

EMULSION TECHNOLOGY, THEORETICAL AND APPLIED, INCLUDING A SYMPOSIUM ON TECHNICAL ASPECTS OF EMULSIONS. Published by Chemical Publishing Co., Brooklyn, N. Y. 290 pages. Price \$5.

Reviewed by Jerome Alexander A BRIEF "Preface" by H. Bennett states: "The symposium on emulsions, held by the Leather Trades Chemists, brought together some of the foremost European colloid chemists. The papers, presented at this symposium, were published under the title of Technical Aspects of Emulsions. This useful book ran to three editions and is now out of print. Because of the numerous requests for it and because of new developments in emulsion technology, it was decided to bring out a new edition with certain revisions and additions-the latter by American specialists."

The bulk of the book (pp. 228) con-sists of the reprinted articles. The original date of publication is not stated, but since none of these articles have references later than 1934, the date seems to be 1934 or

1935. The reprinted "Foreword" (pp. 2) by Prof. F. G. Donnan, states: "This by Prof. F. G. Donnan, states: volume contains the papers read at the second Symposium held by the British Section of the International Society of Leather Trades' Chemists." Dr. William Clayton's reprinted paper (pp. 27) on "Emulsions in the Patent Literature" includes a few 1934 patents, and the fourth edition of Clayton's well known "Theory of Emulsions" has an Appendix, "Summary of Important Patents Since 1934." And in his "Preface" to his fourth edition Clayton states: "The British Section of the International Society of Leather Trades' Chemists held a symposium in London in 1937, the papers with my Forword being published later in a volume entitled 'Wet-ting and Detergency,' Its relation to emulsions is obvious."

Relative to the new articles: "The Fundamental Principles of Practical Emulsion Manufacture," (pp. 26) by R. M. K. Cobb states (p. 8): "It is the object of this chapter to outline the principles of practical emulsion manufacture in a very general way. The actual formulation and production of industrial emulsions is covered elsewhere in this volume by Hofmann. q.v." Miss Cobb's paper contains many q.v." practical suggestions; e.g., (p. 27): "A successful trial of an emulsion in a five gallon can, before going on to more ambitious commercial batches, is highly advisable. Problems of procedure, which cannot be suspected in a 500 cc. beaker formulation, show up in the five gallon batch." The paper by M. P. Hofmann. "Industrial Emulsion Formulation" (pp. 21) states (p. 66): "Only practical applications of colloidal principles and practical working emulsion formulae will be discussed in this section... As the list of chemicals, com-pounds, by-products, and other materials, having potentialities as dispersants and protective colloids, is very long and is being daily augmented, only the best known of these materials will be discussed in this section." The sixteen typical formulations include furniture polish, mineral oil emulsions. and mayonnaise, and the procedure is well outlined. [Hydration appears confused with hydrolysis in the statements: "...hydrolyze the glue in part of the water" (p. 82), and "Soak gums until they are well hydrolyzed..." (p. 83).]

"Emulsion Paints," by S. Werthan (pp. 15) states (p. 213): "Several years ago, the casein paint manufacturer, in order to improve his product, incorporated a small percentage of an oxidizing oil into his pastepaint. This may be considered the start of the present-day oleoresinous emulsion paste-paints... It is with the thought that through the publication of the results of practical tests, the increase in the technical knowledge on the subject will be expedited, that this brief discussion of some of the

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •



Here's an unusual storage bin designed and constructed for an eastern processing plant . . . and incidentally, it was constructed by our "sliding form" method. Because of the heavy top section, the conventional bin construction could not be used. Special trusses and strengthening ribs are used throughout.

Nicholson is staffed to handle any type of concrete storage bin or tank . . . conventional or unusual. Nicholson's experience goes back to 1914, a pioneering date for this country.



tests made will be presented."..."Special machines, colloid mills, homogenizers and emulsifying machines, are frequently used in the manufacture of emulsions. The equipment of the average American paint plant does not include any of these machines. However, it did not take long for the paint manufacturer to learn how to prepare his paint emulsions with his available equipment."

The statements of the three new contributors do no appear to justify the claims on the jacket that the book "discusses the new developments in emulsions," and contains a "comprehensive list of commercial emulsifying agents." It is a pity that the ten-year-old papers were not brought up to date before being reprinted, for this would have greatly increased the value of the book.

PHYSICAL CHEMISTRY TEXTBOOK

OUTLINES OF PHYSICAL CHEMISTRY. Seventh edition. By Frederick H. Getman, revised by Farrington Daniels. Published by John Wiley & Sons, New York, N. Y. 691 pages. Price \$3.75.

THE ORIGINAL Getman "Outlines" appeared more than 30 years ago and since that time, in various editions, has become a standard textbook of physical chemistry. The present revision by Dr. Daniels involves rearrangement, addition of more advanced material and, of course, inclusion of new developments. There is also "a somewhat different approach to thermodynamics and the phase rule." Practical applications are emphasized with the help of frequent examples.

Recent Books &

Pamphlets

Industrial Alcohol. Special Report of the U. S. Tariff Commission prepared for the Ways and Means Committee of the House of Representatives. 67 pages. A statistical review of the present interest in raw materials, plant locations, output and postwar prospects. Primary purpose of the report is to give facts and figures bearing on the probability on start standards of the United States industrial alcohol industry.

Wage Incentives in Wartime. Published by Consolidated Management Consultants, 521 Fifth Ave., New York 18, N. Y. A guide to increased production without extra manpower.

Vladimir M. Ipatieff, testimonial in honor of three milestones in his career. Published by Universal Oil Products Co., Chicago 4, 111.

A Yearbook of Railroad Information. 1943 edition. Published by the Committee on Public Relations, Eastern Railroad Presidents Conference, 143 Liberty St., New York 6, N. Y. 96 pages. Gratis. Facts regarding the railroads of the United States giving statistics (1921-1942) regarding the railroad plants and its operations.

Modern pH and Chlorine Control. Published by W. H. Taylor & Co., 7300 York Road, Baltimore 4, Md. 83 pages. Sixth edition. Theory and applications of pH control together with description of all Taylor equipment for pH, chlorine and phosphate control and for water analyses.

Bibliography of North American Geology, 1919-1928. By J. M. Nickles. Geological Survey, Bulletin 823. Price \$1.25.

New World. Published by United States Testing Co., Inc., Hoboken, N. J., 24 pages. Gratis. An attempt to give industry a brief over-all answer to this question, "What can a scientist do for us?"

Channel Blacks in Butyl Rubber. Published by Continental Carbon Co., 295 Madison Ave., New York, N. Y. 10 pages. Gratis. Test procedure and results on a GR-I test formula containing 50 parts channel black.

Practical Design of Welded Steel Structures.

• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

196



BULK DENSITIES ... **Air Tables** Solve Another Problem



CUTTON, Steele & Steele Air Tables can control the apparent bulk density or weight per cubic foot.

IN many industries Control Engi-neers desire specified weights per cubic foot of their material. Air Tables can separate flat and spikey particles from round or cubical ones of the same material-thus changing the weight per cubic foot as much as 10%.

T'HIS can be done in tonnage per hour, for a few cents per ton.

ONSULT us about the use of Air Tables either as concentrators of different materials, or as Graders of homogeneous materials, or as Con-- trollers of bulk density.

We will gladly run samples.



By H. M. Priest. Published by American Welding Society, 33 W. 39th St., New York, N. Y. 153 pages. Price \$1. Concise essentials of welding and welded construction.

of welding and welded construction. Blends of Standard Channel and Semi-Rein-forcing Furnace Blacks to Match Processing Channel Blacks. Report SRF No. 1, Published by Continental Carbon Co., 295 Madison Ave., New York, N. Y. 16 pages. Gratis. Properties of blends of medium processing channel black and semi-reinforcing turnace black compared with easy processing channel black in a typical rubber GR-S tread compound. Scientific Research and War Effort of USSR. By J. E. Tolpin, Universay Oil Products Co., Chicago, Ill. 3 pages. A reprint from Science.

Synthetic Liquid Fuels. Available from Government Printing Office, Washington, D. C. 470 pages. Price 70 cents. Report of the hearing before the Public Lands Committee of

GOVERNMENT PUBLICATIONS

The following recently issued documents are available at prices indicated from Superintendent of Documents, Government Printing Office, Washington, D. C. In ordering any publications noted in this list always give the complete title and the issuing office. Remittances should be made by postal money order, coupons, or check. Do not send postage stamps. All publications are in paper covers unless otherwise specified. When no price is indicated, the pamphlet is free and should be ordered from the Bureau responsible for its issue.

Statistics of Natural Gas Companies, 1942. FPC S-33. For sale only by Federal Power Commission, Washington 25, D. C. Price 50 cents.

United States Consumption of Food in Terms of Fats, Protein, Carbohydrates, and Calories, 1939-1943. Available from U. S. Tariff Commission, Washington 25, D. C. United States Government Manual Winter 1943-44. Office of War Information. Price \$1.00.

Reconstruction Finance Corporation Act as Amended and Other Laws Pertaining to Re-construction Finance Corporation. Revised to September 1943. Price 20 cents.

United States Production, Consumption and Stocks of Chemicals 1941-1943. "Facts for

the Senate on S-1243. A volume giving ex-pert opinion from well-informed American sources on the prospects of liquefaction of solid fuels to make synthetic petroleum and petroleum products.

petroleum products. The Smiths and Their Wartime Budgets. By-Maxwell S. Stewart. Pamphlet No. 88 pub-lished by Public Affairs Committee, 30 Rocke-feller Plaza, New York 20, N. Y. 32 pages. Price 10 cents. Abbreviated history of ration-ing with comparisons to the inflation of World War I.

As We Win. CIO Publication No. 98, available from Congress of Industrial Organiza-tions, 718 Jackson Place, Washington 6, D. C. Price 5 cents. Report No. 1 of the CIO Post-war Planning Committee.

Felt Facts. Published by the Felt Associa-tion, 366 Madison Ave., New York 17, N. Y. 22 pages. History, manufacture and uses of felt.

Industry" Series 6-1-1. Obtainable from Bureau of the Census, Washington 25, D. C. Monthly Production of Softwood Plywood, and Consumption and Stocks of Materials, 1941-1943. "Facts for Industry" Series 16-1-1. Obtainable from Bureau of the Census, Wash-ington 25, D. C.

ington 25, D. C. Census of Pulp Mills and of Paper and Paperboard Mills, 1942. "Facts for Industry" Series 24-1-1. Obtainable from Bureau of the Census, Washington 25, D. C. Statistical Abstract of the United States, 1942. Census Bureau. Price \$1.75. Buckram. Topographic Maps. Geological Survey. Sale of the standard topographic maps of the Geo-logical Survey for areas within the continental United States (excluding Alaska) and Puerto



Rico has been resumed. Therefore, beginning with the list of "Publications issued in Janu-ary 1944," the maps issued each month will be announced in the monthly lists. A con-solidated list of the maps published between March 1, 1942, and Dec. 31, 1943, inclusive, is being prepared and will be printed as soon as possible. A copy of that list will be sent automatically to all those who receive the monthly announcements of new publications, and those persons should not submit special requests for it. Others who desire copies of the consolidated list may submit requests, which will be honored when the list is printed.

printed. Coatings That Prevent End Checks. Tcch-nical Note No. 186. Available from Forest Products Laboratory, Madison, Wisconsin. Wood and Paper-Base Plastics. By Alfred I. Stamm. Mimeo No. R1438. Available from Forest Products Laboratory, Madison, Wisconsin.

consin. Suitability of Birch, Aspen, and Sugarberry for Rayon Pulp: Results of Certain Sulfite Pulping and Bleaching Experiments. By Hugo Nihlen and J. N. McGovern. Mimeo No. R1441. Available from Forest Products Labora-tory. Madison, Wisconsin. Fire-Retarding Coatings. By Arthur Van Kleeck. Mimeo No. R1280. Available from Forest Products Laboratory. Madison, Wis-consin.

consin.

Suggestions and Instructions for Kiln Op-erators Drying Aircraft Lumber. By Glenn Voorhies and W. Karl Loughborough. Mineo No. 1362. Available from Forest Products Laboratory, Madison, Wisconsin.

Increasing the Durability of Casein Glu, Joints with Preservatives. By F. H. Kaufert. Mimeo No. 1332. Available from Fores Products Laboratory, Madison, Wisconsin. Glue Forest

Wood's Technological Coming-of-Age. By F. J. Champion. Mimeo No. 1442. Available from Forest Products Laboratory, Madison, Wisconsin.

Marketing Vermiculite. By G. Richards Gwinn. Bureau of Mines, Information Circular I. C, 7270. Mimeographed. Use and Misuse of Flame Safety Lamps. By W. H. Tomlinson. Bureau of Mines. Information Circular I. C. 7271. Mimeo-marked graphed.

Analyses of Crude Oils from Some West Texas Fields. By Boyd Guthrie, Burcau of Mines, Report of Investigation R. I. 3744. Minneographed.

Mimeographed. Report of the Administrator of Agricultural Research 1943. Agricultural Research Admin-istration. Includes the annual reports of the subsidiary agencies, which are: The Bureaus of Agricultural and Industrial Chemistry; Animal Industry: Entomology and Plant Quarantine; Human Nutrition and Home Economics; Plant Industry, Soils, and Agricultural Engineering; and the Office of Experiment Stations. Price 25 cents.

The Explosion and Fire Hazard in Handling Ammonium Nitrate as a Fertilizer. By R. O. E. Davis. Agricultural Research Administra-tion. Available from Bureau of Plant Indu-try. Soils and Agricultural Engineering, Belts-ville, Maryland. Mimeographed.

Cotton Quality Statistics United States 1942-43. War Food Administration. CS-5. Price 15 cents.

Dairy and Poultry Market Statistics Var Food Administration. CS-4. Pr 1942 Price 15 War cents.

cents. Commercial Standards. National Bureau of Standards. Price 5 cents each. Items as follows: Structural Fiber Insulating Board, CS42-43. Homogeneous Fiber Wallboard. CS12-43. Earthenware (Vitreous-Glazed) Plumbing Fixtures, CS114-43. Bituminized-Fibre Drain and Sewer Pipe, CS116-44. Tire Repairs-Vulcanized (Passenger, Truck and Bus Tires), CS110-43. Textiles-Testing and Re-porting, CS59-44. Service Tests of Some Oil-Treated Sole

Service Tests of Some Oil-Treated Sole Leathers. By Robert B. Hobbs and Howard E. Bussey. Bureau of Standards. Letter Cir-cular LC-739. Mimeographed. Cooking Dehydrated Foods. War Depart-ment. Technical Manual TM 10-406. Price 15 cents.

Oleomargarine. Hearings on H. R. 2400. 78th Congress, 1st Session. House Committee on Agriculture. Price 55 cents. Claims for Damage or Personal Injury, Incident to Noncombat Activities of the War Department or Army. War Department. Army Regulations No. 25-25. Price 5 cents.

Army Regulations No. 25-25. Price 5 cents. Federal Specifications. New or revised specifications which make up Federal Stand-ard Stock Catalog on the following items: Paper Shipping Sacks, UU-S-48. Motor-Fuels, VV-M.567. Oil, Tung (China-Wood), Raw, JJJ-O.353. Oil, Peanut, Z-O.358. Asphalt, (for use in) Road and Pavement-Construction, SS-A.706b. Leather, packing, chrome-vegetable-retauned, KK-L-231, Var-nish; spar, water-resisting, TT-V-121b. Price 5 cents each.



No. 3 Reason for

Buell's High Efficiency, Low Maintenance, Long Life

To stand up under the severest conditions of continuous usage, cyclone bodies and cones in Buell Dust Recovery Systems are fabricated of extra-thick steel, completely seal-welded inside and out and ground flush to form a smooth, homogeneous surface. Hoppers are braced and stiffened with 3" channels to resist vibration.

This extra-sturdy type of construction is possible only with large-diameter cyclones and is one of the plus values that have made Buell Dust Recovery Systems famous throughout industry for long life and low maintenance. Due to their sturdy

construction Buell installations have been in service three, four, five or more years without the replacement of a part.

How the patented "shave-off" of the van Tongeren cyclone (found only in Buell Dust Recovery Systems) makes it possible to use large diameters and, at the same time, obtain high collection efficiencies is fully described in a 28page book: "The van Tongeren System of Industrial Dust Recovery." To secure a copy, simply write us for Bulletin G-842. BUELL ENGINEERING COMPANY, INC.

18 Cedar Street, New York 5, N.Y. Sales Representatives in Principal Cities



DESIGNED TO DO A JOB, NOT JUST TO MEET A "SPEC."



Use NEWARK Press-Crimped Space Cloth

Note the crimping. It's strong; lock-crimp; vise-like. Heavy pieces falling on to the screen will not push the woof wires ahead or spread the warp wires. Spacing is maintained ... and with it screening accuracy.

Our ability to make accurate wire cloth is due to these factors: Nearly 70 years experience in making cloth and in designing machinery for making it; making use of the most modern machinery possible; skilled workmen.

NEWARK FOR ACCURACY is not an empty phrase.







Equipped with Wheatley Synthetic Seal —a synthetic rubber ring dovetailed and fitted into a removable bronze seat also dovetailed to accept this rubber ring. When the bronze clapper falls against this rubber, a perfect seal is formed regardless of what irregularities have deposited on the seat or in the fluid, such as sand, scale and cuttings which under pressure ordinarily would completely cut out a hard-surfaced seat.

Preferred by the United States Engineers on projects handling high octane gasoline.

Sizes 2" to 24" Pressures 125 lbs. to 2000 lbs. Series 15-30-40-60 and Ludlow FBE - SBE - SOE & FOE Steel-Iron-Bronze

- The rubber ring conforms to all deposits and obstacles and makes it possible for this valve to seal under the worst conditions.
- Seals regardless of viscosity.
- Operates equally well on kerosene or crude.
- Absolutely silent in operation. Ideal for refineries and pumping stations where the slapping of metal check valve clappers is annoying.
- No lapping or grinding of seats necessary.
- Renewable bronze seat ring, into which the rubber ring is inserted, can be replaced by the standard metal to metal seat, if desired.
 Write for Bulletin No. CM-1

WHEATLEY PUMP and VALVE MFR. Hale Station, Sand Springs Road TULSA, OKLAHOMA

3-NWC-3

MANUFACTURERS' LATEST PUBLICATIONS

Publications listed here are available from the manufacturers themselves, without cost unless a price is specifically mentioned. To limit the circulation of their literature to responsible engineers, production men and industrial executives, manufacturers usually specify that requests be made on business letterhead.

Protective Coatings. Hercules Powder Co., Wilmington, Del. 14-page technical booklet describing the use of the company's Lewisol Maleates in protective coatings.

Safety Glasses. American Optical Co., Southbridge, Mass.—A 16-page booklet entitled "Right on the Nose" explains in detail, quick, easy methods of adjusting non-prescription industrial safety goggles for worker's comfort.

Plastics. The Richardson Co., Melrose Park, 111.-22-page illustrated booklet describing the industrial and consumer applications for plastics. A description of the company's custom service for molded and laminated plastics is included.

Packaging Machinery. Triangle Package Machinery Co., 906-920 North Spaulding Ave., Chicago 51, Ill.—20 page illustrated bulletin describing weighing, filling, measuring and carton-sealing equipment. Details on production rates of the packaging machines, methods of handling goods, and other data included.

Carbon Seal Rings. Pure Carbon Co., Inc., Saint Marys, Pa.—8-page illustrated folder dealing with carbon seal rings and their application to the bellows type shaft seals. Includes similar information on steam turbine seals, air seals, seal noses and others.

Fire Clay Brick. McLoed & Henry Co., Inc., Troy, N. Y.—4-page bulletin to introduce three fire clay brick products, Hyex, Super-Hyex, and Superam. Contains information regarding available sizes and specific applications.

Heat Treatment of Steel. Leeds & Northrup Co., 4934 Steuton Ave., Philda. 44, Pa.-36-page catalog entitled "Vapocarb-Hump Method for Heat-Treatment of Steel". A revised edition of 1940 catalog. Should be of interest to heat-treating departments and production executives of war plants.

Synthetic Rubber Glossary. Hycar Chemical Co., 335 S. Main St., Akron, Ohio-8-page pamphlet to meet demands for a glossary giving pronunciations and meanings of synthetic rubber words. Not a highly scientific treatise, it is designed to help business, industrial, and sales executives in discussion of this subject, and, thus, includes only the more common chemical terms and well-established trade names.

Flow-Meters. Cochrane Corp., 17th & Allegheny Ave., Philadelphia 32, Pa.—16-page reprint of "Flow Meter Engineering" telling why, when and where flow meters and instruments are needed in the modern plant, and how they can be made to further the war effort.

Pouring Buckets. The B. F. Goodrich Co., Akron, Uhio.—4-page catalog section (9425) on Flexite rubber pouring buckets, for the safe and economical handling of acids, corrosives, and liquid high explosives. This section also describes Flexite rubber dippers, hand rubber funnels, and anode acid rubber gloves.

Hydraulic Elevators. Revolvator Co., North Bergen, N. J.—4-page bulletin (96-J) illustrating and describing the company's line of hydraulic freight elevators. The folder includes illustrations of interesting installations, and a diagram for obtaining a particular installation quotation.

Tubing Identification. Formed Steel Tube Institute, 1621 Euclid Ave., Cleveland, Ohio.— A chart showing the symbols of all companies who manuiacture welded steel tubing for heat transfer apparatus and who are reported to

Do you need MULTI-WALL BAGS in a hurry?

• If you do—specify TARENTUM. 80 years of experience is evidence of quality and accuracy of manufacturing year after year.

Tarentum Multi-Wall Bags will be made to your specifications — in any quantity — damp proof or water resistant — printed in any color, on one or both sides.

Send us a sample or give us specifications and quantity required — we will quote by return mail.

Quality and Accuracy



TEMPERATURE and HUMIDITY 0 When you want accurate and dependable automatic temperature or humidity control for Industrial Processes, Heating or Air Conditioning Systems, call in a Powers engineer. With over 50 years of experience and a very complete line of self-operating and air operated controls we are well equipped to fill your requirements. Write for Circular 2520 2727 Greenview Ave., Chicago Offices in 47 Citles-See your phone directory. THE POWERS REGULATOR CO.



When you need Swivel Joints, you certainly want maximum flexibility with <u>minimum</u> torque.

Specify CHIKSAN Ball-Bearing Swivel Joints and you specify the only joint built to the formula for perfect flexibility:

66,= Double rows of ball bearings.

BB2+EP=

EP = Effective Packing Element – self-adjusting for:

V/P= Pressure or Vacuum Service LT = Resulting Low Torque.

CHIKSAN Ball-Bearing Swivel Joints are supplied in over 500 different Types, Styles and Sizes. Manufactured in steel, malleable iron, bronze and aluminum. Sizes from 3/8" to 12"; larger sizes to order for pressures to 300 lbs. and to 3,000 lbs. at 225° F. and for pressures to 500 lbs. at 700° F. End connections optional. Write for latest Chiksan Catalog and Engineering Data.





have adopted the method of symbol identification on each length of welded tubing.

Refrigeration. Air Conditioning and Refrigeration Machinery Assoc., Inc., Southern Bldg., Washington 5, D. C.—32-page booklet entitled "Refrigeration and Air Conditioning in War . . . in Peace" recording briefly the vital services performed by refrigeration and air conditioning in World War II . . . their essentiality to the morale and health of civilians and fighting men . . . and their use in the advancement of new industrial, nutritional and research techniques.

Radiant Heat. Westinghouse Lamp Div., Westinghouse Electric and Mfg. Co., Bloomfield, N. J.—12-page illustrated booklet telling what radiant heat is, and discussing its advantages. Takes up the design and performance of the drying lamp, design of radiant heat installations, the arrangement of equipment, and electrical circuit design. Booklet A-3817.

Materials Handling Machinery. The Yale & Towne Míg. Co., Philadelphia 24, Pa.-124-page illustrated book entitled "Modern Materials Handling Machinery Applied to American Industry". Describes the handling of goods from time of receipt, through production, processing, storage and shipping.

Rubber Machinery. National Eric Corp., Eric, Pa.—32-page booklet describing with illustrations the company's machinery and equipment for processing rubber and plastics.

Sheaves. Allis-Chalmers Mfg. Co., Milwaukee 1, Wis.-4-page illustrated bulletin on the Magic-Grip sheave. Six photographs demonstrate the put on-take off operation.

Manganese Steel. Amsco, American Manganese Steel Div., Chicago Heights, Iil.—30page pamphlet on manganese steel for the clay products industry. Describes its application for excavating, hauling, crushing, mixing, and manufacturing equipment. Bulletin 1243-CP.

Pulverizer. The Babcock & Wilcox Co., 85 Liberty St., New York, N. Y.—4-page bulletin (G30-A) describing the company's Type E ball bearing pulverizer.

Machining of Steel. Haynes Stellite Co., Kokomo, Ind.—8-page illustrated booklet entitled "Operating Information on Stellite 98M2 Cobalt-Chromium-Tungsten Turning and Boring Tools and Milling Cutters". Intended to help users obtain the hest results with this cast cobalt-base alloy which was developed for faster machining of steel. Form 5350.

Handling Equipment. Rose Mfg. Co., 12400 Strathmoor, Detroit, Mich.—6-page edition (second section) of an industrial Handling Equipment catalog providing a comprehensive file on factory trucks and trailors.

Recharging Extinguishers. C-O-Two Fire Equipment Co. U. S. Highway No. 1, Newark, N. J.--A pocket size booklet entitled "Recharging Instructions for Carbon Dioxide Extinguishers". Illustrated with drawings of the equipment required for and the procedure followed in recharging both system cylinders and portable extinguishers made by the company.

Chemical Catalog. Glyco Products Co., Inc., 26 Court St., Brooklyn 2, N. Y.—144-page catalog entitled "Chemicals by Glyco". Additions include a number of plasticizers for synthetic rubber, synthetic resins, etc., and further information on the esters manufactured by the company. Usual features have been retained, including formulas, suggestions and tables of useful chemical and physical data.

Ball Bearings. New Departure Division of General Motors, Bristol, Conn.-1944 edition of "Interchangeable Ball Bearings for Replacement", a booklet containing numerically arranged lists of ten competitive makes of ball bearings together with corresponding New Departure numbers, as well as a section explaining prefixes and suffices used with each make of bearing, and one on comparative bearing type and series numbering systems.

Paint Ordering Catalog. American-Marietta Co., 43 E. Ohio St., Chicago 11, Ill.—A fully illustrated catalog providing application suggestions, product descriptions, and technical data concerning heavy duty industrial maintenance paints of the Valdura line.

Pipe and Tube Bending. Copper & Brass Research Assoc. 420 Lexington Ave., New York 17, N. Y.—80-page treatise showing methods and devices for bending pipes and tubes of copper and its alloys. Contains 113 figures and illustrations, as well as pertinent information on the chemical and physical properties of such pipe material.

Metallizing Process. Metallizing Co. of America, 1330 W. Congress St., Chicago, Ill.— 40-page catalog dealing with all phases of the metalizing process in which all information is classified according to industry. A section is devoted to the history, development, use and technique of metalizing. The equipment section deals with the Mongul Electric Bonder, Mogul Link, etc. Another section gives guestions and answers pertaining to metallizing.

Vibration Study. The Cooper-Bessemer Corp., 2511 Terminal Tower, Cleveland, Ohio. -S-page reprint of a techical paper entitled "The Vibration Characteristics of 'Free-Free' Circularly Curved Bars' reporting the outcome of an extensive study, the results of which furnish data that make it possible to calculate with reasonable accuracy, the frequency of vibration, parallel or transverse, of any incomplete, free-free, circularly curved har of uniform cross section where its mechanical constants are known. Illustrated.

Electronic Tubes. Electronics Dept., General Electric Co., Schenectady, N. Y.-4-page bulletin (ET-12) containing a quick-selection chart of electronic tubes for industry.

Gyratory Sifter. Allis-Chalmers Mfg. Co., Milwaukee J. Wisconsin.—16-page bulletin (B-6124A) including perspective drawings of low-head sifter sieves, showing what takes place in a sifter box. What the sifter user should know of the material is listed in 10 points. Specification tables. illustrations, and questions and answers are also given.

Silent Chain Drives. Morse Chain Co., Ithaca, N. Y. -80-page illustrated bulletin includes, in addition to the usual specifications and price lists, new material covering the advances and developments made in the high-speed chain drives and other fields. Bulletin 43.

Water Softener. Cochrane Corp., 17th & Allegheny Ave., Philadelphia 32, Pa.--8-page illustrated reprint of "Improvements in the Hot Process Water Softener" covering a brief history of the development of this method of feed water conditioning. Chemical reagents and new improvements are discussed.

Powdered Metal Parts. Keystone Carhon Co., Inc., Saint Marys, Pa.--32-page booklet "Powder Metallurgy" covering the advantages and latest applications of powdered metal parts. Designers aid section and table on engineering properties are included. Second section of the booklet is devoted to Selfuble porous bronze bearings, Selfube porous iron bearings and D-10 graphite impregnated brass bearings.

Coal Tar Chemicals. Reilly Tar & Chemical Corp., Merchants Bank Bldg., Indianapolis, Ind.-56-page booklet describing the various coal tar products of this company. This second edition includes new by-products of coal tar recently made available.

Wire Cloth. C. O. Jelliff Míg. Corp., Southport, Conn.--96-page technical reference book listing data and price lists for Jelliff industrial wire cloth.

Band Filing. Continental Machines Inc., 1301 Washington Ave. South, Minneapolis, Minn.--4-page bulletin on the DoALL Band Filing machine including information on file broaching operations on metals, wood and plastics.

Acid Addition Agent. The Euthone Co., Dept., CME, 442 Elm St., New Haven, Conn. -4-page bulletin describing the company's product "Acid Addition Agent", its advantages and applications.

Emulsion Waxes. The Euthone Co., Dept. CME, 442 Elm St., New Haven, Conn.—4page bulletin describing hard drying rust-inhibiting waxes available to the metal treating industry.

Motorized Valves. Automatic Temperature Control Co., Inc., 34 East Logan St., Philadelphia 44, Pa.—4-page illustrated bulletin A3 including detailed engineering and application data concerning high-speed motorized valves for "On-Off" control of steam, air, oil, gas or chemical solutions.

Stuffing-Box Problems. Ingersoll-Rand Co., 11 Broadway, New York 4, N. Y.—8-Dage illustrated bulletin describing the Shaft-Seal which is intended for services in which unusual stuffing-box conditions are encountered. Bulletin 7018 describes advantages, construction, installation and operation of the Shaft-Seal.

Leaf Filter, Niagara Filter Corp., 1432 Niagara St., Buffalo, N. Y.--16-page booklet to acquaint food and chemical processing technicians with the features of the Niagara filters, their construction, uses and advantages. Illustrated.

Pressure Guage. Manning, Maxwell & Moore, Inc., Bridgeport 2, Conn.-12 page illustrated bulletin on the phenol turret case Duraguage.



DE BOTHEZAT DIVISION OF AMERICAN MACHINE AND METALS, INC., EAST MOLINE, ILLINOIS

CHEMICAL & METALLURGICAL ENGINEERING . MARCH 1944 .

Why is Lead Called the Everlasting Metal?



Lincoln Cathedral-England-construction begun in the twelfth century-showing lead roofs, parapets, gutters and pinnacles.



Lead pipe systems, as above, are extensively used in flumes where acid is carried through welded lead pipe for great distances.

Studying the properties of lead, one is immediately impressed with its ability to resist corrosion. We have seen lead pipe in excellent condition, that was put in service in Rome over 1800 years ago.

Plumbers are continually digging up lead pipe that has lain in muck and mud and damp earth for fifty years or more, that is still in perfect condition.

Some of the most famous buildings in England have lead gutters and leaders which have been used for centuries. The use of lead as a roofing material has enabled many historic edifices to withstand the ravages of time and the elements.

Old cast lead monuments seem to last forever.

Lead's resistance to the corrosive action of chemicals is known throughout the industry. Great quantities of sheet lead and lead pipe are used in the construction and operation of chemical and industrial plants. Steel has been protected by a tin-lead alloy called Terne metal, and during the present tin shortage, by lead with extremely small quantities of tin. Lead paints get their lasting quality from the durability of the metal.

If you want it to last, make it of lead.

ST. JOSEPH LEAD COMPANY

250 PARK AVENUE • NEW YORK 17 • ELdorado 5-3200 Lead Zinc Oxide Antimony Zinc Antimonial Lead Cadmium THE LABGEST PRODUCED OF LEAD

THE LARGEST PRODUCER OF LEAD IN THE UNITED STATES

CHEMICAL ECONOMICS-

H. M. BATTERS, Market Editor

PRODUCTION OF CHEMICALS HAS SHOWN PROGRESSIVE DECLINE IN LAST THREE MONTHS

As a result of cutbacks in the military program and the closing of some ordnance plants, the output of chemical products has been at a declining rate since last October. The unadjusted index of the Federal Reserve Board stood at 401 in October, dropped to 392 in November, 367 in December, and the preliminary figure for January is 358. In this compilation the Board uses the term chemicals in an inclusive sense with paints, soap, rayon, industrial chemicals, and explosives and ammunition as the components. While all these branches have contributed somewhat to the declining trend, it is fair to assume that the major influence came from curtailment in outputs of explosives and ammunition. As the current output of ammunition is reported to be sufficient for requirements and for holding stocks at the desired level it is probable that peak production of chemicals has been passed.

A separate index for industrial chemicals is prepared by the Federal Reserve Board. This is confined to the "chemicals not elsewhere classified" as reported by the Burcau of the Census and charts the monthly progress of chemicals without the inclusion of allied products. This index advanced from 396 in October to 398 in November but declined to 394 in December and the preliminary figure for January is 392. While many of these chemicals tic in closely with the war program and hence would be affected by cutbacks, they also get the benefit of the newer developments, such as manufacture of synthetic rubber, and if requirements for civilian goods hold up, it is probable that total needs will force production schedules to heights not yet attained. Hence in following the monthly progress of chemicals, a distinction must be drawn between an index which includes many related products and one which is chemical in a literal sense.

In addition to steadily rising outputs of such products as butadiene and styrene, the outlook for enlarged production of chemicals is brightened by plans for in-creasing supplies of alcohol, sulphuric acid, and phthalic anhydride. Requirements for alcohol were revised upwards in March and ways are being sought to bring production and demand in balance. Productive capacity of sulphuric acid plants, not including ordnance acid, is expected to exceed 14,900,000 tons in terms of 50 deg. acid by the latter part of this year but some of the new capacity will not come into operation until late in the year. The scarcity of phthalic anhydride has more recently forced recognition and plans are being studied either to add to existing plants or to increase the number of plants.

Essential requirements for plastics, which use phthalic anhydride in their manufacture, are not being met and some action is necessary to relieve this condition.

The Chem. & Met. index for industrial consumption of chemicals stands at 179.28 for January compared with a revised figure of 176.96 for December. The number for January, 1943 was 173.20. Comparison with earlier months indicates that all consuming industries are not moving in unison as some of them have increased their raw material requirements while others have reduced their rates of operation. The situation promises to remain mixed for some time to come but the rates of increase in heavily weighted industries point to a moderate uplift in the composite index number.

Data for production, consumption at producing plants and stocks, which are now issued monthly for specified chemicals by the Chemicals Bureau of WPB, comprise a fair cross-section of the industry and the figures are valuable inasmuch as they are authoritative. The production data for December show that most of the

Chem. & Mct. Index for Industrial Consumption of Chemicals 1935 = 100

	D

	A7 C C .	
	revised	Jan.
Fertilizer	42.52	42.50
Pulp and paper	17.95	19.40
Petroleum refining	17.24	17.38
llass	18.50	18.75
Paint and varnish	13.25	14.00
ron and steel	13.67	13.75
layon	16.12	16.41
Cextiles	11.00	10.70
Coal products	9.85	9.90
Leather	4.30	4.25
ndustrial explosives	5.35	5.19
lubber	3,00	3.00
Plastics	5.30	5.40
I I I I I I I I I I I I I I I I I I I		
	178.45	180.63

tonnage chemicals gained over the totals reported for the preceding month. Gains over November are noted in the case of such important chemicals as sulphuric acid, soda ash, caustic soda, chlorine, acetylene, anhydrous ammonia, bleaching powder, and sodium silicate. Bichromate of soda, however, which reached a record production of 7,450 tons in November dropped to 6,688 tons in December and manufacturers are finding it difficult to secure competent workers.

The status of industries which make use of fats and oils as raw materials may be inferred from the allocations of these materials. For edible use, it is estimated that per capita consumption of fats and oils in 1944 will be 43.9 lb. as against 46.5 lb. in 1943. For inedible use, the allocations refer only to the first quarter of the year and are as follows; the figures referring to millions of pounds: soap, 518.2; paint and varnish, 124.3; coated fabrics, 25.2; printing ink, 6.4; lubricating oils, 70.7; textiles and leather, 44.8; rubber, 39.8; core oils, 21.7; vitamin carriers, 7.5; pharmaceutical, 5.7; putty and other caulking compounds, 8.3; other industrial uses, 73.5.

While the output of plate glass may move up this year, the outlook for the glass industry as a whole seems to be much in line with what it was last year. The use of white arsenic will be lowered as the industry has been allocated 3,000 tons for the year as compared with a consumption of 5,000 tons in 1941. The container branch has been informed that the supply of soda ash will be adequate provided the rate of consumption does not exceed that for 1943. However, possible shortages of newsboard, pulpboard and kraft for closure liners may have an adverse effect on production of glass containers as about 70 percent of ths year's estimated production will require paper liners.



PRODUCTION AND CONSUMPTION TRENDS



Jan Feb Mar Ape May June July Aug Sept Oct. Nov. Dec

As THE YEAR advances, the position of some of the chemical-consuming industries becomes clearer. Among the outlets which give promise of an expanded demand for raw materials is the rubber industry. While some improvement may be found in the volume of imports of natural product, the emphasis is placed on production of synthetic. Production of synthetic rubber in January was reported as about 50,000 long tons. In addition about 35,000 tons of scrap is being reclaimed each month. With larger outputs of synthetic in prospect as the program progresses toward completion, it is evident that the over-all supply will show a gain over that for last year, even though this may help civilian consumers but little.

Reports about activities at petroleum refineries also are encouraging for the year to date. Daily runs to stills in January were close to record highs and an even higher rate was maintained throughout February. Incidentally an encouraging outlook for the industry in postwar years was presented last month by a representative of one of the largest producing companies. He fore-cast that by 1949, demand for petroleum would hit an average of 5,000,000 bbl. a day which would be about 600,000 bbl. per day over the current rate. He further stated that this total would be reached despite a gradual decline in export shipments. This increase, however, was to be preceded by a temporary drop of not more than 15 percent from current rates.

Textile mills are confronted with a situation where they will be called upon to fill military needs in about the same volume as last year which combined with regular demands would mean full operation of plants. The industry did not get off to a very good start as labor troubles slowed production at some mills in New England. There was a drop in total consumption of cotton in January with southern mills down 8.5 percent from January 1943, while New England mills were down 26.6 percent. The outlook for textile production is clouded by difficulty in securing needed new equipment and by the steady drain on skilled manpower. Scarcity of certain dyestuffs also is a handicap in dyeing and printing branches.

Production in lines which use animal glues are affected by the supply of which grows worse instead of better. Actions taken late in January to relieve the tight situation that had been growing have not been able to relieve the shortage of labor or the shortage of raw materials, the basic troubles. Since the orders controlling the distribution and uses of animal glue were written, production has not been sufficient to meet allocations. Under these circumstances a downward revision of the amounts permitted for various end uses may be expected unless there is an immediate marked improvement in available supplies.

The raw material supply is not expected to improve for some months. The drag between the time cattle are killed in the packing plants and the time the hide trimmings and fleshings reach the glue factory amounts to three months or more.

206

• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

WITH

70U can buy this new postwar L designed Fairbanks-Morse motor now-knowing that it will be just as modern-just as efficient-just as up to the minute in years to come as it is today.

It is indeed a challenge to the future -in efficient motor design.

• It is a 40°C, motor.

opperspun ROTOR

- It is a protected motor!
- It has the most adaptable, convenient, and handiest conduit box you ever laid your eyes on!
- It has the famous Fairbanks-Morse **COPPER-SPUN** Rotor!

FAIRBANKS-MORSE WATER SYSTEMS **DIESEL ENGINES** Motors PUMPS . SCALES MOTORS STOKERS FARM EQUIPMENT GENERATORS RAILROAD EQUIPMENT

TOMORROW'S MOTOR

IS HERE TODAY !

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •



Never before has there been more stamina - more protection-more versatility built into a motor housing. A demonstration is necessary to fully appreciate how much this motor can really offer you. See it and judge for yourself.

Write Fairbanks, Morse & Co., 204 Fairbanks-Morse Bldg., Chicago 5, III.







Imitated but never duplicated, the France ring is manufactured in three sections. The contacting faces form the lines of an equilateral triangle. As the ring is expanded or contracted, the sections must move in or out radially equal distances from the center of the rod to which the ring is fitted.

This fundamental mechanical principle accounts for the efficiency, trouble-free performance and extra-long life of France Metal Packing,

After years of service, when the rings have become worn to such an extent that the sections nearly butt together, further years of additional service can be obtained by cutting off the narrow points of the three sections where they form a part of the inner circumference of the ring.

The spring then requires adjustment so that the sections are held to the rod with a slight tension.

For installation in engines, pumps and compressors — under all conditions of service. France Full-floating Metal Packing means true economy in the long run. Permit France Engineers

to analyze your packing re-

quirements. Write for Cata-

Solid on approval Solidiantion Guarantied

THE FRANCE PACKING COMPANY Tacony, Philadelphia 35, Penna. Branch Offices in Principal Cities



Item	19411	1942 -	1943
Acetanilide (tech. and U. S. P.): Production	2,937,318	7.651.883	13.822.780
Consumption		2,571,147	4,574,346
Acetic acid (synthetic): ²		180,114	009,475
Consumption	225,671,063	264,898,632	196,592,316
Stocks.		11,637,350	7,419,886
Production	4	430,363,880	460,237,021
Stocks.		10,463,495	11,408,754
Acetyl salicylic acid: Production	8.084.003	8,650,113	8,577,173
Consumption		914 185	4
n-Butyl acetate:		011,100	04 150 044
Consumption.	93,226,698	67,024,658	04,100,894
Creosote oil (gallons):	•••••	2,110,814	2,228,084
Production	103,170,750	133,076,971	130,650,601
Stocks.		8,995,673	16,743,032
Creosols, meta-para: Production	3	7,041,626	8,861,250
Consumption		1,279,021 231,068	1,296,620 192,784
Cresols, ortho-meta-para:6	17 047 022	10 940 901	0.260.014
Consumption.	17,045,033	10,840,891	4
Stocks Cresylic acid. crude:		1 security	Sec. Sec.
Production	3. 4	20,389,956	25,245,555
Stocks.	V	4	1,008,748
P-oduction	26,595,853	36,113,811	39,109,301
Consumption,		3,629,963	6,273,444 2,115,270
Diethyl ether (all grades):	99 645 591	55 017 600	64 069 517
Consumption		4	0 005 507
Ethyl acetate (85%):		1,990,971	2,200,021
Production	94,689,878	86,542,085 12,615,727	102,472,494 17,297,565
Stocks		6,671,365	3,432,681
Production	2,334,058	3,124,439	4,456,284
Stocks.		269,159	327,405
Production	2,646,210	2,931,106	3,197,535
Stocks.		142,655 170,848	162,287
Methyl chloride (all grades): Production	4,911,360	4.1.3	13,026,129
Consumption		4 1 441 644	1.012.127
Naphthalene, crude:7	112 220 004	175 212 005	104 400 745
Consumption	113,732,224	65,976,135	0 140 000
Naphthalene. refined:8		0,527,542	8,149,220
Production	70,801,554	81,583,820 38,541,162	83,551,952 46,486,796
Stocks.		4,939,056	3,487,313
Production	21,111	70,257	160,087
Stocks		10,184	37,382
Oxalic acid (technical): Production	15,851,200	15,110,276	17,101,580
ConsumptionStocks		307.956	680,250
Phenobarbital and sodium salts:	901 100	240 399	318, 127
Consumption.	201,108	42,033	41,764
Phthalic anhydride:		74,930	01,210
Consumption	and-entraits Rts	94,807,180 - 44,504,625	113,067,286 33,847,958
Stocks Riboflavin (for human use):		3,922,218	1,642,083
Production.	2,777	16.381	75,640
Stocks.		3,167	23,179
Production.	inter a start stre	5,434,427	9,860,330
Consumption		1,091,515 259,513	2,260,345

U. S. Production, Consumption and Stocks Synthetic Organic Chemicals*

• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

log M-4.



Injurious DUSTS

Whether dusts are fatal or merely irritating, maximum protection is a safety requirement. The first step is to disperse dusts if possible. Then ...

call for CESCO



Make sure all workers in danger areas are equipped with CESCO Healthguard Respirators. These provide a plus margin of safety, with low-cost replaceable filters held securely in molded rubber facepieces. Snug facial fit guards against leakage. Breathing is safe and easy. For comfort the new style facepiece rests easily over the nose and mouth; it will not interfere with splash or safety goggles.



RECENT WILEY BOOKS in CHEMICAL ENGINEERING



Post-war plans in your field are being made now. This, then, is the time to "dig in" and study the latest, most authoritative works on important subjects, such as those listed below. Make your selection now. Be ready for new demands. Order today from the coupon below.

THE ORGANIC CHEMISTRY OF SULFUR

Tetracovalent Sulfur Compounds

By Chester M. Suter

\$10.00

Considers the practical values of compounds as well as their chemical properties. Describes many compounds of biological or medicinal interest, including saccharin, sulfonamides, sulfonephthaleins and aminosulfonic acids. This is the first book of its type in print.

THE CHEMISTRY OF ORGANIC MEDIC-INAL PRODUCTS-Second Edition

By Glenn L. Jenkins and Walter H. Hartung

858 Pages

675 Pages

\$6.50 Organizes the large number of organic medicinal compounds according to the accepted scheme of chemical classification.

THE CHEMISTRY OF CELLULOSE

By Emil Heuser

660 Pages

\$7.50 A study of the scientific aspects of the subject, useful to the practicing chemist in industrial and other research lahoratories. Gives consideration to the microscopic and submicroscopic structure of the cellulose fibre.

CHEMICAL PROCESS PRINCIPLES

-Part 1 By O. A. Hougen and K. M. Watson 452 Pages \$4.50

Part I deals with material and energy balances. It covers the application of physical chemistry, thermophysics, thermochemistry, and the first law of thermodynamics

STATISTICAL ADJUSTMENT OF DATA By W. Edwards Deming

261 Pages \$3.50 Unifies under one general principle and solution such problems as statistical procedures associated with curve fitting and other adjustments to least squares

GENERAL CHEMISTRY—Fifth Edition

By Horace G. Deming 706 Pages

\$3.75 A clear presentation of principles and an inter-esting and accurate summary of the chief chemi-cal industries and outstanding industrial materials

QUANTUM CHEMISTRY

By Henry Eyring, John Walter and George E. Kimball

394 Pages

\$5.00 Includes treatments of the theory of reaction rates, optical activity, molecular structure, spe-troscopy, and group theory, in addition to the material usually offered in introductory books in the subject.

JOHN WILEY & SONS, Inc. 440 Fourth Avenue, New York 16, N. Y.

Please send me on ten days approval the books I have checked in this advertisement (or I am attaching to this coupon a separate list of the books desired). At the end of that time, if I decide to keep the books, I will remit indicated price plus postage; otherwise I will return the books postpaid.

ENGINEERS' DICTIONARY

Spanish-English and English-Spanish

Compiled by Louis A. Robb 423 Pages Flexible Binding

A practical, up-to-the-minute dictionary of engineering terms, expressly prepared for Pan-American use. Uses the Spanish of Central and South America.

PRINCIPLES AND APPLICATIONS OF ELECTROCHEMISTRY

Principles—Fourth Edition

By H. Jermain Creighton 477 Pages

Applications—Second Edition

By Walter A. Koehler 573 Pages

296 Pages

\$5.00

\$5.00

\$6.00

A comprehensive work of real value to chemical engineers. Fundamental material has been re-stated and amplified, and new material, both theoretical and practical, has been added. Timely, authoritative, clearly presented.

SYNTHETIC RESINS AND RUBBERS

By Paul O. Powers

.\$3.00

Covers theories of polymer formation and con-densation, vinyl polymers, synthetic rubbers, resins from natural products and the application of synthetic resins.

PROTECTIVE AND DECORATIVE COATINGS

Edited by Joseph Mattiello

Vol.	I	819	Pages	\$6.00
Vol.	11	658	Pages	\$6.00
Vol.	ш	830	Pages	\$7.50
Vol.	IV	419	Pages	\$5.00

Volume I covers raw materials. Volume II deals with the chemistry and classification of pigments. Volume III covers the manufacture and use of various types of coatings. Volume IV presents special studies on emulsions, wetting and grinding, microscopy, etc. Volume V is in variant time. Volume II raw materials. preparation.

ON APPRO	OVAL COUPON	i
HN WILEY & SONS, Inc. Fourth Avenue, New York 16, N. Y.	Name	
se send me on ten days approval the books we checked in this advertisement (or 1 am	Address	
ching to this coupon a separate list of the is desired). At the end of that time, if I de to keep the books. I will remit indicated	City and State	
e plus postage; otherwise I will return the is postpaid.	Employed by C&ME-3:44	2

United States Production, Consumption and Stocks of Chemicals: December 1943

December statistics on the chemicals shown in this	table supplem	Dec	ember 1943-	(ace chem, a	Nov	ember 1943-	0.1.)
			Made and		5-18-19 . W.C.	Made and	NOL YOU
Chemical and Basis	Units*	Production	Consumed	Stocks	Production	Consumed	Stocks
Acetylene: For use in chemical synthesis	M cu.ft.	324,253]	00.000	10.000	2 309.026 1	01 000	12 1
For commercial purposes	M cu.ft.	2149.224	80,820		* 150,672	81,082	SAULA
Synthetic anhydrous ammonia (100% NHa)	Tons	48.657	2 39.663	6.580	46,318	38,301	4,911
Bleaching nowder (35%-37% avail Cla)	M lb.	5.591	1,459	651	2 5, 134	11,754	2 692
Calcium acetate (80% Ca (CaHaOa)a)	M lb.	1.356	2	342	1.416	1	413
Calcium arsenate (100 % Cas (AsQ ₄)*)	M lb.	5.855	50	9,413	1,518	72	8,349
Calcium carbide (100% CaC)	Tons	55,985	6	2 11.786	52,457	4 10 10	11,571
Calcium hypochlorite (true) (70% available Cly)	M lb.	971		979	985	3	950
Calcium phosphate - monobasic (100% CaH ₄ (PO ₄) ₂)	M lb.	5.147	1	4.361	5,872	3	4,784
Carbon dioxide: Liquid and gas (100% CO1)	M lb.	26,444	2,627	4,829	23,819	2,253	1,858
Solid (dry ice) (100% CO ₂)	M lb.	39.237	2,026	2,501	40,150	770	3,514
Chlorine	Tons	2 111, 584	2 60, 664	28,242	106,420	2 60,545	26,398
Chrome green (C.P.)	M lb.	627	65	2788	665	35	840
Hydrochloric acid (100% HCl)	Tons	30,912	17,532	22,092	² 29,690	17,323	2,395
Hydrogen	llions of cu.ft.	21,771	1,449	4	1,680	1,372	4
Lead arsenate (acid and basic)	M lb.	6,970	22	8,039	7,572	73	8,464
Lead oxide - red (100% Pb ₃ O ₄)	M lb.	9,406	495	4,944	8,192	2 723.	4,723
Methanol: Natural (80% CH2OH)	Gal.	379,498	adder a	244,261	366,620	1011014	261,344
Synthetic (100% CH1OH)	M gal.	5,069		4,723	5,210	3	5,143
Molybdate orange (C.P.)	Lb.	96,148	3,361	106.624	131,474	3,070	119,549
Nitric acid (100% HNO1)	Tons	39,571	36,511	7,563	42,404	37,917	8,556
Oxygen	M cu.ft	21,443,379	34,828	1	1,460,271	37,180	1
Phosphoric acid (50% H ₃ PO ₄)	Tons	2 53,705	² 47,548	2,12,043	52,790	51,107	12,551
Potassium bichromate and chromate (100%)	M lb.	647		656	² 708	CHARLES THE	² 733
Potassium chloride (100% KCl)	Tons	99,588		17,867	91,974	3.	41,414
Potassium hydroxide (caustic potash) (100% KOH)	Tons	3,533	811	2,079	3,619	809	2,242
Boda ash — Ammonia soda process:	When I wan I !!	Trent C	L.D.B.A.		CALCERCE OF L		
Total wet and dry ⁵ (98%-100% Na ₂ CO ₃)	Tons	2 392,633		21111112	379,015		
Finished light (98%-100% Na ₂ CO ₂)	Tons	\$ 205,637	235,910	* 18,471	6 207,553	39,490	16,288
Finished dense (98%-100% Na ₂ CO ₄)	Tons	124,515	3,116	26,826	110,902	2,682	8,172
Natural	Tons	13,763	129	1,911	15,337		2,205
Sodium bicarbonate (refined) (100% NaHCO ₂)	Tons	14,192		4,933	15,185	5 11 m at	4,802
Sodium bichromate and chromate (100%)	Tons	6,688	LOF FIN	043	7,450	01 040	00 645
Lime code process (100% NaOH).	Tons	105,482	125,517	137,410	97,588	21,042	33,043
Sodium phoenkater Marcharis (100% NaUH)	Tons	* 30,037	0.4311-0.313	* 13,130	0,871	The Try Park 1	12,010
Dibasia (10007 No. HDO.)	MI ID.	2,090	and the second se	328	2,002		041
Tribasic (100% Na PO)	Tons	0,940	0.0	971	0,144	150	1 205
Sodium silicato (water claus): Liquid (409 Down())	Tons	09 728		000,1	0,099	100	1 106 090
Solid (all forms combined)	Tons	10 159	9.055	10,427	0 254	9 269	- 100,000
Sodium sulphoto: Claubor calt and crude calt cale 7	Tons	10,100	6 906	70 697	80 106	180 8	69 890
Anhydrous (refined) (10097 No.SO.)	Tone	5 702	0,000	6 524	5 402	2	5 435
Sulphur dioxide (100% SO.)	Mih	6 754	2 943	2 620	7 410	2.799	5 175
Sulphuric acid:7 Chamber process (100% H-SO)	Tons	2 294,067	21010	1000	(297, 215	1	100 010
Contact process & (100% H.SO.)	Tons	2 523 . 671		*244,301	1 493 . 864	}	190,942
Net contact process " (100% H-SOA)	Tons	2 459.856			423,314		
White lead	Tons	7,231	2,048	8,047	26,307	1,563	26,993
Zinc yellow (C.P.)	M lb.	2,229	² 206	867	2,428	198	811
		STATISTICS AND ADDRESS	all and all and and a	and the second second	112 - 212		1 - 11
" All ious are 2,000 lb. 1 Not yet available. 2 Revis	ed. ³ Data	cannot be pu	ublished.	Not availabl	e. ⁵ Total w	et and dry	production.

⁶ Not including quantities converted to unished dense soda ash. ⁹ Excludes spent acid.

[†] Data collected in cooperation with Bureau of Mines.

8 Includes oleum grades.



with Paul O. Abbé equipment results from better mechanical design, 64 years of exclusive concentration on grinding and mixing problems, and expert engineering service.

PAUL D. ABBE 375 CENTER AVE. LITTLE FALLS, NEW JERSEY The Typical machines shown are Rotary Cutter, Ball and Pebble Mill, Jar Mill and Mixer,



WANTED **MECHANICAL ENGINEER**

Graduate mechanical engineer with 7-10 years oil refinery engineering experience wanted for development work. Permanent position offered by a long-established AAAl company, manufacturing fractionating and pressure vessels, heat exchangers, cast-steel flanged fittings and other equipment for the petroleum and process industries. Knowledge of cast-steel header boxes desirable. Successful applicant will report directly to plant manager. Location in southwestern city where ample housing facilities exist. If you feel qualified for this key position in an expanding organization, apply giving full information and enclosing small photograph. Replies will be held strictly confidential. Maximum sclary-\$5000 per year.

P-789, Chemical & Metallurgical Engineering 520 N. Michigan Ave., Chicago 11, Ill.

ONVEYING SOME MATERIALS CONVEYED BY FULLER-KINYON SYSTEMS

С L E A N -

FULLER-KINYON SYSTEM

> S A F E . 0 W

> > C 0 S Т

> > > 0

Arsenic dust Asphalt filler dust Bag fume Baroid Barvtes Catalyst Cement (Portland) **Cement** raw materials Clays (dried) Colox Copper converter dust Dextrine Dolomite Fuller's earth Gypsum (raw) Lime (quick) Magnesite Manganese Dioxide Ore (pulverized) Rock dust Siliceous Powder Starch (Pearl) Starch (Powdered)

THROUGH PIPE LINES

The Fuller-Kinyon System is an outstanding example of simplicity of design, having many inherent advantages for the conveying of dry pulverized materials, some of which are:

CLEANLINESS-Materials conveyed through standard-size pipe lines, underground or overhead. No dust collectors necessary.

SAFETY-Explosion proof . . . air for conveying insufficient to support combustion. No mechanical or dust hazards.

LOW-OPERATING COST-No links, buckets or drags requiring frequent attention, replacement and repairs. Only one moving part ... the screw in the pump, which can be replaced with a minimum loss of time.

ELIMINATES STRAIGHT-LINE CONVEYING—Cuts corners to shorten conveying distances . . . anywhere a pipe line can be placed: horizontally, vertically, up or down hill.

Put your conveying problems up to us . . . we're here to help and suggest equipment best suited to your needs.

COMPAN CATASAUQUA-PENNSYLVANIA WASHINGTON, 5, D.C. SAN FRANCISCO, 4 CHICAGO, 3 Chancery Bldg. Colorado Bldg. Marquette Bldg.

P-67

CHEM. & MET. Weighted Index of Prices for

CHEMICALS

Base = 100 for 1937

This month	109 49
ast month	109.59
March, 1943	108.80
viaren, 1942	

CURRENT PRICES

The accompanying prices refer to round lots. Where it is trade custom to sell fob works, quotations are so designated. Prices are corrected to March 13.

INDUSTRIAL CHEMICALS

	Acctone, tanks, lb.	\$0.	.07		14		
	Acid. acetic, 28%, bbl., 100 lb	3	.38	-	\$3.	63	
l	Boric, bbl., ton	109	.00	-1	13	00	
l	Citrio, kegs, lb.		10	1		11	
	Formic, cDys. Ib.		08	-		081	
ļ	Testis 44% tech light bhl.lb.		07	3-		07!	
	Muriatic 18° tanks 100 lb.	1	.05				
	Nitric, 36°, carboys, lb.		.05	-		05]	
	Oleum, tanks, wks., ton	18	.50	-	20	. 00	
	Oxalie, erystals, bbl., lb		.11	Ł		. 123	1
	Phosphoric, tech., tanks, lb	10	.04		• •	•••	
	Sulphuric, our, tanks, ton	10	20	1-1		• • • •	1
	Alcohol amyl			-			
	From Pentane, tanks, lb.		.13	1			
	Alcohol, butyl, tanks, lb		,10	1-		.18	ł
	Alcohol, ethyl, denatured, 190)					
	proof						•
	No. 1 special, tanks, gal. wks.	•	- 00	1	• • •		•
	Aluminum sulphate com baga		.01	4	••••		•
	100 lb	. 1	.15	- 1	1	.40	
	Aqua ammonia, 26°, druma, lb		.02	1-		.03	
	tanks, lb		.02	-		,02	1
	Ammonia, anhydrous, cyl., lb	- 66	.16	-		• • •	•
	tanks, iD.	•	.04	- 1	• • •	• • •	•
	Animonium carbonate, powd.tech.		.00	1-		19	
	Sulphate wks top	2	8.2)-			
	Amylacetate tech., from pentane			1			ĺ
	tanks, lb		.14	5-			:
	Arsenio, white, powd., bbl., lb	•	.04	- 1		.04	;
	Barium carbonate, bbl., ton	, 60	0.00	- 1	65	. 00	
	Chloride, bbl., ton	. 71	1.00	-	81	.00	
	Nitrate, casks, ib	. 60	100	- I	70	100	
	Bleaching power fob whe			-			
	drums 100 lb	. :	2.50) –	3	.00	ĵ
	Borax, gran., bags, ton	. 4/	5.00	- 1			
	Calcium acetate, bags	. :	3.00) -			•
	Arsenate, dr., lb	•	.07	-		,08	
	Carbide drums. ton	- 54	1,00		05	00	
	Chloride, flake bags, del., ton.	. 12	5.00	2	20	051	
	Tetrachloride drums gal		73			80	
	Chlorine, liquid, tanka, wks., 100	њ	1.7	5 -	2	.00	
	Copperas, bgs., f.o.b., wks., ton.	. 17	.00) -	18	.00	
	Copper carbonate, bbl., lb		.19	1-14		.20	
	Sulphate, bbl., 100 lb	. :	5.00)	5	5.50	
	Cream of tartar, bbl., lb	•	. 57		• • •	15	ł
	Diethylene glycol, dr., 10	i	. 19			. 13	2
	Loo b		1.90	1 -	2	2.00	
	Ethyl acetate tanks lb		.11	14-			
	Formaldehyde, 40%, bbl. lb		.0	5-		-0	ł
	Furfural, tanks, lb		. 09) -	•••	• : :	
	Glaubers salt, bags, 100 lb		1.0	5 ~	1	.10	
	Glycerine, o.p., drums, extra, lb.	•	. 18	51-	•••	• • • •	•
	Lead:						
	neeks lb	3	. 01	83-			
	Red, dry, sck. lb.		.0	-16			ļ
	Lead acetate, white crys., bbl., lt).	.1	21-	5	.13	ł
	Lead arsenate, powd., bag, lb		.1	1	5	-12	l
	Lithopone, bags, lb	•	.0	al	3	-04	1
	Magnesium carb., tech., bags, iD.	•	.0			,00	'
	Supthetic tenks gal	•	2	8 -			1
	Phoenhorus vellow cases lb	110	.2	3 -		.2	5
	Potassium bichromate, casks, lb.	-	.0	9 -		.10)
	Chlorate, powd., lb	-	.0	91-	-	.12	2
	Hydroxide (c'atic potash) dr., ll	b.	.0	7 -	27	.07	I
	Muriate, 60% bags, unit	•	.5	21-	•••		a
	Nitrate, bbl., lb	•	.0	01		.00	n
	Prinaigenate, drums, 10		1	7 -	-	11	ŝ
	Sal ammoniac, white casks lb.	-	.0	51	5-	.00	ñ
	Salaoda, bbl., 100 lb.		1.0	0 -	-	1.0	5
	Salt cake, bulk, ton	1	5.0	0 -			•
	Soda ash, light, 58%, bags, con	n-		-			
	tract, ewt	••	1.0	5 -		• • •	•
	Sode caustic 7607 souid damage		1,1	9 -	•••		•
	ewt.	10,	2 3	0 -	-	3.0	c
	Acetate, del., bbl., lb.			5 -	5	.0	6
	Bicarbonate, bbl., cwt		1.7	0.	-	2.0	C
	Bichromate, casks, lb			171	-	- 0	8
	Bisulphate, bulk, ton	••• 3	16,0	10 -	- 1	7 0	5
	LIGUIDINC, UL, IU.,		. 1	10.			-

STURTEVANT eliminates "air-float"

YOU CAN'T

AIR FLOATING

MATERIALS

BLEND

"Air-float"—i.e. fine particles floating in the air in the mixing drum unmixed with heavier materials —can cause plenty trouble in batches of chemicals, pharmaceuticals, etc. But there's no chance for "airfloat" in the four-way cascading, side-to-side, (fromthe-outer-edge-inward) mixing motion of the Sturtevant Dustless Batch Blender. Nothing escapes. No dust is lost or wasted—the charging-and-dtscharging chute is close sealed during mixing. In other words, every batch perfectly blended, regardless of ingredients of various weights and densities, fineness, dust or granules.

the ordinary dry batch blender

If you want to know more about the Sturlevant Dustless Batch Blender, write today for Bulletin 080B. This is only one of many Sturlevant Products for Crushing, Grinding, Pulverizing, Separating, etc. Bulletins covering equipment promptly sent on request. Get a complete set and learn how to step up your production and lower costs. Write today.



Only

CHEM. & MET. Weighted Index of Prices for

OILS & FATS Base = 100 for 1937

This month		145.24
Last month March, 1943		145.24 145.37
March, 1942		141.32
Chlorate kegs lb	061-	100
Cyanide. oases. dom., lb	.141 -	.15
Hyposulphite, bbl., cwt	2.40 -	2.50
Metasilicate, bbl., owt Nitrate, bulk, owt	2.50 - 1.35	2.65
Nitrite, casks, lb	2.70 -	.07
Prussiste, yel. bags, lb	.91 -	10
Sulphide, bbl., lb.	.021	
Sulphur, crude at mine, long ton.	16.00	021
Dioxide. cyl., Ib Tin crystals, bbl., lb	.391-	.08
Linc, chloride, gran, bbl., lb	.051-	.06
5% leaded, bags, lb	.071	4 00
OUS AND FATS	0,00	1.00
Castor oil, No. 3 bbl., lb	\$0.131-	\$0.14]
Chinawood oil, bbl., lb Coconut oil, Ceylon, tank, N. Y.,	.38	
lb Corn oil crude, tanks (f.o.b. mill).	nom .	
lb. Cottonseed ail, orude (f.o.b. mill).	.121 .	
tanks, lb.	.121	
Palm casks, lb.	.09	
Peanut oil, crude, tanks (mill), lb. Rapeseed oil, refined, bbl., lb	.13 nom	
Soya bean, tank, lb	.111	
Crude, tanks (f.o.b. factory) lb.	.089	
Oleo stearine, lb	.091-	
Red oil, distilled, dp.p. bbl., lb	.111-	
Tallow extra, loose, ib	.081	
Alnha-nanthol. crude bbl., lb	\$0.52 -	\$0.55
Alpha-naphthylamine, bbl., lb	.32 -	.34
Aniline, salts, bbl., lb.	.22 -	.24
Benzidine base, bbl., lb	.70 -	.75
Benzyl chloride, tech, dr., lb	.23 -	.25
Benzol, 90%, tanks, works, gal Beta-naphthol, tech., drums, lb	.15	.24
Cresol, U.S.P., dr., lb	.11	.83
Diphenyl, bbl., lb	.15 -	45
Dinitrophenol	.23 -	.25
Dip oil, 15%, dr., gal	.23 -	.25
H-acid, bbl., lb	.60	. 50
Hydroquinone, bbl., lb Nanhthalene, flake, bbl., lb	.90 -	.071
Nitrobenzene, dr., lb	.08 -	.09
Para-nitraniline, bbl., lb	.47 -	.49
Pierie acid, DDL., ID	.35 -	.40
Resorcinol, tech., kegs, lb.	.75 -	.80
Salicylic acid, tech., DDI., ID Solvent naphtha, w.w., tanks, gal.	.33 -	.40
Tolidine, bbl., lb Toluol, drums, works, gal	.86 -	. 88
Xylol, com., tanks, gal	.26	
MISCELLANEOUS	5 \$0.21 -	\$0.24
Dry colors	0335-	30
Prussian blue, bbl., lb.	.36 -	.37
Chrome green, bbl., lb	.211-	.30
Pars toner, 1b	.75 -	.80
Vermilion, English, bbl., lb Chrome yellow, C.P., bbl., lb	2.75 -	2 80
Gum copal Congo, bags, lb	.09 -	30 15
Demar, Batavia, cases, lb.	.10 -	.22
Magnesite, cale, ton.	64.00 -	
Rosin, H., 100 lb	5.43 -	
Turpentine, gal	.39 -	
Bleached, bonedry, bags, lb	.39	

T. N. bags, lb....



MONO-BLOCK

A One-block Insulation, Effective Over the Full Temperature-Range

up to 170

Made from black rockwool, B-H Mono-block is high-temperature-resistant (up to 1700° F.) and has exceptionally low thermal conductivity. You'll find it lighter, and more efficient, too, because its long, straight fibres are interwoven in layers by an exclusive, patented process. In each block, millions of tiny air-cells hold back the heat, preventing its escape. Because it is a one-block insulation, Mono-block delivers substantial savings in installation costs, too. Send for sample and new bulletin.

Baldwin-Hill Co., 532 Klagg Ave., Trenton 2, New Jersey. Plants in Trenton, New Jersey; Kalamazoo, Michigan; and Huntington, Indiana.



NEW CONSTRUCTION_

PROPOSED WORK

- La., Gretna Gulf Distilling Corp., Gretna, plans the construction of ten 200,000 gal. steel fermenting tanks. L. S. Weil and W. B. Moses, Audubon Bldg., New Orleans, Engrs. Estimated cost \$125,000.
- Mich., Detroit—Cook Paint & Varnish Co., 3301 Bourke St., is having plans prepared by Harley & Ellington & Clarence E. Day, Archits., 1507 Stroh Bldg., for the construction of an addition to its paint factory. Estimated cost \$45,000.
- N. J., Elizabeth—Apex Chemical Corp., 200 First St., is having plans prepared by Robert L. Pryor, Archt., 196 Kent Pl. Blvd., Summit, for the construction of a 2 story laboratory. Estimated cost \$40,000.
- N. J., North Brunswick—E. R. Squibb & Sons, 745 Fifth Ave., New York, N. Y., will soon award the contract for the construction of a 1 story laboratory addition. Abbott & Merkt Co., 10 East 40th St., New York, N. Y., Archts. M. C. Chase, 25 Columbia Heights, Brooklyn, N. Y., Engr.
- Ore., Springfield Willamette Valley Wood Distillation Co., Yeon Bldg., Portland, is having plans prepared by Smith, Hinchman & Grylls, Archts., 800 Marquette Bldg., Detroit, Mich., for the construction of a wood alcohol plant here.
- Tenn., Chattanooga—Southern Chemical Cotton Co., M. D. Munson, Pres., plans the construction of a manufacturing plant. Estimated cost \$300,000.
- Tex., Amarillo—Consumers Cooperative Assn., Amarillo, plans improvements to its refinery. Estimated cost will exceed \$40,000.
- Tex., Austin—Defense Plant Corp., 811 Vermont Ave., N. W., Wash., D. C., plans to construct additional chemical plant facilities here to be operated by International Minerals & Chemical Corp., Old Georgetown Rd. Estimated cost \$175,000.
- Tex., Houston—Southern Acid & Sulphur Co., Inc., Rialto Bldg., St. Louis, Mo., plans to construct additional plant facilities here. Project will be financed by Defense Plant Corp., Wash., D. C. Estimated cost \$3,500,000.
- Tex., Longview—Danciger Oil & Refining Co., W. T. Waggoner Bldg., Fort Worth, plans to construct additional facilities at its refinery here. Estimated cost \$80,000.

	Proposed Work	Con
New England		
Middle Atlantic	\$80,000	
South	425,000	7
Middle West.	45.000	
West of Mississippi	4,070,000	
Far West	40,000	
Canada	80,000	1
Total	\$4,740,000	\$10

-Curre

- Tex., Seminole—Phillips Petroleum Co., Philtower Bldg., Tulsa, Okla., plans to construct plant in Seminole Field to have daily capacity of 20,000,000 cu.ft. Estimated cost will exceed \$150,000.
- Tex., Shamrock—Smith Bros. Refining Co., Shamrock, plans to construct a plant unit for utilizing sweet gas for manufacture of carbon black. Estimated cost will exceed \$40,000.
- Tex., Velasco—Dow Magnesium Corp., Velasco and Midland, Mich., plans to construct additional facilities at its magnesium plant here. Estimated cost \$185,000.
- Que, Isle Verte—Premier Peat Moss Corp., 635 Fifth Ave., New York, N. Y., plans the construction of a peat factory and warehouse here.
- Que., Lac a la Tortue—Shawinigan Chemicals, Ltd., Shawinigan Falls., Que., plans to reconstruct its plant here.

CONTRACTS AWARDED

- Calif., Richmond—General Chemical Co., Russ Bldg., San Francisco, has awarded the contract for the construction of a chemical plant to Bechtel-McCone & Parsons, 601 West 5th St., Los Angeles.
- Conn., Naugatuck—Naugatuck Chemical Div. of U. S. Rubber Co., Elm St., has awarded the contract for a 2 story storage building addition and 1 story brine purification plant to W. J. Megin, Inc., 51 Elm St. Estimated cost \$75,000.
- Conn., West Haven—Armstrong Rubber Co., M. Snyder, 475 Elm St., has awarded the contract for a 3 story, 115x274 ft. factory to Mahoney-Troast Construction Co., 657 Main Ave., Passaic, N. J. Estimated cost \$240,000.
- Fla., Clewiston-U. S. Sugar Corp., C. R. Bitting, Pres., Clewiston, will construct a starch plant here. Work will be donc by own forces. Estimated cost \$7,000, 000.
- O.. Cleveland—Industrial Rayon Corp., H. S. Rivitz, Pres., West 98th St. and Walford Rd., has awarded the contract for the construction of a 3 story, 68x82 ft. viscose manufacturing factory to George A. Rutherford Co., 2725 Prospect Ave. Estimated cost \$75,000.

nt P	rojecta	Cumulatin	ve 1944
	Contracts	Work	Contracts
	\$360,000	\$40,000	\$864,000
000	850,000	575,000	1,345,000
000	7,420,000	905,000	820,000
000	165,000	125.000	3,717,000
000		9.440.000	6,895,000
000	40.000	540,000	4,540,000
000	1,825,000	2,660,000	1,825,000
000	\$10,660,000	\$14,285,000	\$20,006,000

O., Columbus—M & R Dietetic Laboratory, Inc., 585 Cleveland St., has awarded the contract for a 4 story, 42x64 ft. factory addition and 1 story power plant, boilers, etc., to E. E. Elford & Son, 555 South Front St. Estimated cost \$50,000.

and with a start damped

- Pa., DuBois—B. F. Goodrich Co., 500 South Main St., Akron, O., has awarded the contract for altering 2 story, 100x120 ft. manufacturing plant to W. S. Johnson Bldg. Co., 2532 Hyde Park Bldg., Niagara Falls, N. Y. Estimated cost \$50,000.
- Pa., Glassmere—Aluminum Co. of America, R. O. Keefer, Purch. Agt., 801 Gulf Bldg., Pittsburgh, has awarded the contract for the construction of an atomized aluminum plant for Navy Dept., to Day & Zimmerman, Inc., Packard Bldg., Philadelphia. Estimated cost \$800,000.
- R. I., Woonsocket—Goodyear Fabric Corp., Orchard St., New Bedford, Mass., has awarded the contract for alterations and addition to its plant to Gilbane Building Co., Inc., 90 Calverly St., Providence. Estimated cost \$45,000.
- W. Va., New Martinsville—Columbia Chemical Div., Pittsburgh Plate Glass Co., Grant Bldg., Pittsburgh, Pa., has awarded the contract for chemical plant expansion, including new processing equipment, to H. K. Ferguson Co., 1422 Euclid Ave., Cleveland, O. Project will be financed by Defense Plant Corp., Washington, D. C. Estimated cost \$420,000.
- Wis., Wausau—Defense Plant Corp., 811 Vermont Ave., N. W., Washington, D. C., will construct a 1 story, 100x192 ft. addition to factory here to be operated by Marathon Battery Co., 840 Henrietta Ave. Work will be done by day labor.
- Out., Port Clairborne—Canada Cement Co., Ltd., Canada Cement Bldg., Montreal, Que., will construct six cement storage silos and office building. Work will be done by owner's forces. Estimated cost \$325,000.
- Ont., Peninsula-Marathan Paper Mills of Canada, Ltd., 320 Bay St., Toronto, Ont., has awarded the contract for the construction of a pulp and paper mill to Foundation Co. of Canada, Ltd., 1158 Bay St., Toronto. Estimated cost \$1,-500,000.

Putting B1 in America's Bread

How Synthetic Organic Chemicals Are Helping To Solve A Nutrition Problem

27,000,000 loaves of bread a day enriched with synthetic Vitamin $B_1^*...$ this is now the biggest use for this man-made vitamin first synthesized just a few years ago.

The commercial production of Vitamin B_1 requires adequate quantities of Ethylene Oxide and Ethyl Acetoacetate. Fifteen years ago these, too, were rare chemicals.

In 1929, we began commercial production of Ethylene Oxide. In 1932, we began synthesizing Ethyl Acetoacetate by a new and economical method. Now these chemicals are available in quantities and at prices which permit their use in large-scale vitamin production.

Other vitamin products have also benefited from the availability of low-cost, high-quality synthetic chemicals. Vitamins A and D are extracted from fish liver oils with Ethylene Dichloride. Propylene Glycol is a solvent for crystalline Vitamin D. Acetone is used in the synthesis of Vitamin C, and Acetic Anhydride for Vitamins B_2 and B_6 .

Vitamin production is one example of the many industries which have depended upon the broad group of synthetic organic chemicals we produce. If you have a problem involving these chemicals, call on us.

*Vitamin B2, niacin, and iron are added as well.

BUY UNITED STATES WAR BONDS AND STAMPS



UCE

30 East 42nd Street, New York 17, N. Y.

PRODUCERS OF SYNTHETIC ORGANIC CHEMICALS

Here is how the RCA ELECTRON

These sub-microscopic photos helped find the answer to a problem

in rosin size

tained

Good results were ed when the size

Making mountains of molehills improves papermaking chemicals

Newest in the Hercules equipment available for papermaking research, the electron microscope makes possible a new approach to papermaking problems. Submicroscopic phenomena can now be examined-for example: the penetration of pigments; the effect of cooking procedures on

wood fibers; the variations in particle size and shape of clays. fillers, sizes, binders, adhesives,

impregnants, inks. The objective: to find out what makes more economical and finer

chemicals for paper production -and then to supply these chemicals to you.



15

icus houne

this, trouble antif.

PAPERMAKERS CHEMICAL DEPARTMENT COMPANY Savonnah, Ga DELAWARE WILMINGTON Allania, Ge Chicago, III. Haw York, N. T. Milwaukee, Wis. Albeny, N.Y. Freeman, Oni. (Hercules Powder Co., Canada, Ud.) Helyghe Mast Detrall, Mich. ten Mass Hattere, Le San Francisco, Calif. Jacksonville, Fle. Partiand, Ors.

SOLTHERN PULP and PAPER JOURNAL

MICROSCOPE helps manufacturers

REPRODUCED at the left is an advertisement recently published by Hercules Powder Company.

This advertisement demonstrates that the RCA Electron Microscope is much more than a laboratory instrument; that with this instrument it is possible not only to discover the cause of many defects in materials and products, but to establish effective procedures for remedying such defects.

Used in this way—(1) as a means of finding out how to improve manufacturing results; then (2) as a means of checking results actually obtained in commercial processing—RCA Electron Microscopes are today paying large dividends on their cost in a number of America's most prominent and progressive industrial plants.

Please address inquiries to Electron Microscope Section, RADIO CORPORATION OF AMERICA, Camden, New Jersey.

RCA ELECTRON MICROSCOPE RADIO CORPORATION OF AMERICA

PALLADIUM on CARBON FOR LOW TEMPERATURE and LOW PRESSURE HYDROGENIATION

For many years our name has been identified with progressive research and the development of palladium catalysts.

Palladium is an active catalyst for the hydrogenation of nitrocompounds, ketones, aldehydes and unsaturated compounds in the liquid phase at room temperature. For instance:

Palladium on Activated Carbon Powder 5%

is used in the industrial hydrogenation of terpenes, alkaloids, therapeutic preparations, vitamins, dyestuffs and other organics.

We honestly believe you will benefit by conferring with us on any catalytic problem you may have.

BAKER & CO., INC. SMELTERS. REFINERS AND WORKERS OF PLATINUM, GOLD AND SILVER 113 Astor St., Newark 5, N. J. SAN FRANCISCO

NEW YORK

CHICAGO





Neches Butane Products Company, designed and built by The Lummus Company for the production of 100,000 tons of butadiene per year, is managed by Gulf Oil Corporation, The Texas Company, Socony-Vacuum Oil Company, Inc., The Pure Oil Company, and Atlantic Refining Company.

A technical committee, composed of members from eight major oil companies and Lummus, investigated all butadiene process developments and selected the process steps used. Difficult and new distillation problems due to the magnitude of the operation and the complexity and exacting nature of the process steps were solved in light hydro carbon separations and purification. A measure of the magnitude of the project is shown in the utilities system including a feed water treating system and boiler plant for 2,200,000 pounds per hour of high pressure steam and a cooling water system of 225,000 gallons per minute circulation. The fabrication and delivery of 72 large bubble towers, some of them 14 ft. diameter and 160 ft. high, were accomplished by construction of a shop on the site equipped with modern handling facilities and automatic welding and forming equipment.

The petroleum chemical industry in its growth will require a solution of many new difficult and complex problems similar to those encountered in the development of the synthetic rubber industry. Lummus by its performance in butadiene, styrene, phenol, toluol and explosives has proven itself the leader in this industry.

THE LUMMUS COMPANY

420 Lexington Avenue, New York 17, N. Y.

600 S. Michigan Ave., Chicago S, Illinois Mellie Esperson Building, Houston 2, Texas 634 S. Spring St., Los Angeles 14, California 70 Barn Hill, Wembley Park, Middlesex, England

PETROLEUM REFINING PLANTS

Yes—WE CAN DO SOMETHING ABOUT IT

No matter what you want handled-for any branch of industry you select . . . Jeffrey has probably developed and installed material handling equipment to do it. For over sixty-five years, Jeffrey has accumulated knowledge by doing . . . has increased efficiency and speeded production in thousands of plants.

We stand ready to place this experience at your disposal Some of the proved products offered by Jeffrey to speed processing are shown below.



Jeffrey-Traylor No. 5 standard pan feeder, [Patented] electric vibrating type, 42" wide and 60" lang with renewable liners



Jeffrey scraper conveyor flight single or double strand chain—co veys on incline or horizontal run.



Jeffrey belt conveyors furnished in troughing or flat belt types—widths from 14" to 50"—anti-friction idlers

Jeffrey steel apron section. Conveys on incline or horizon-tal — double-baaded flights makes conveyor practically leak-proof.

Jeffrey-Traylor FB-2 gravity type single deck electric vibrating screen (patented) equipped with Patented Heller plane wire cloth.

Bucket elevators to suit every need—vertical or in-clined.



SALES OFFICES: Baltimore 1 Birmingham 3 Boston 16

(ESTABLISHED IN 1877)

> Buffalo 2 Chicago 1 Cleveland 13 Cincinnati 2 Jeffrey Mfg. Co. Ltd. of Canada - Head Office and Works: Montreal

Detroit 13 Denver 2 Harlan — Houston 5 Huntington 19 Milwaukee 11 New York 7 Philadelphia 3 Pittsburgh 22 Scranton 3 St. Louis 3 Salt Lake City 1

RENNEDY BRONZE GATE VALVES

Figure 27 Standard, Screwed Ends

125

Simple Sturdy Durable

Assure easy operation, and lastingly trouble-free service. Available in nonrising and rising stem types; also outside screw and yoke. Built for steam pressures up to 300 lbs.

Buy From Our Distributor

THE KENNEDY VALVE MFG. CO. ELMIRA, N.Y.



Another Dempster Development For Industrial Materials Handling

Another typical example of how the Dempster-Dumpster is saving time, manpower, trucks, tires, and gas in leading industrial plants of almost every classification.

In this case, twenty standard Dempster-Dumpster drop-bottom bodies of 6 cu. yd. capacity each, equipped with special twin, self-balancing, spring hinged tops, are spotted throughout one of America's most vital war factories. A few are placed in convenient spots for receiving waste and rubbish. Others are placed at strategic points for recovering metal shavings. As each body is filled, forked truck conveys loaded body to convenient point where truck, equipped with the Dempster-Dumpster Hoisting unit, hoists load to carrying position, and dumps it at delivery point, all under full control from driver's seat. When empty body is returned, another loaded one, perhaps with a different type of material, is there for hauling and dumping . . . an uninterrupted cycle of materials handling using twenty badies but with only one truck.

In dozens of other plants, various types of badies are in use handling materials of almost every description from dust to liquid ... light to heavy up to $7\frac{1}{2}$ tons pay load ... finished and unfinished products ... hot



materials up to 1500 degrees F... and in every operation with one truck serving from 6 to 50 bodies.

The chances are that the advantages of the Dempster-Dumpster can and should be adapted to your plant. Let our engineers cooperate with you. Write for our complete operating manual No. 242 now.



Reservices on this page tell its sporeting starty of the Despater-Domester,

Tage states shown so bound bridg result for bounds. Shown share is able about in the special term, anti-both access apring bingers may an des particular

Center Phase shows broked body in carry-

games Plats ites para instant ar one trained, done pites maked of the Demoper Sempeter Sempperating type of hedge

Types of kindliks souldble use trive avera determine design. Comparation of our anglesters with their sourcement has been any the vestment has a subject to be design of the vestment has part of materials averaging probabilities average.

Dempster Brothers, Inc., 134 Shea Road, Knoxville 17, Tennessee

CHEMICAL & METALLURGICAL ENGINEERING • MARCH 1944 •
-a newspaper editorial, January 14, 1944 MILITARY SECRET

dk

th

The jet propulsion plane apparently is a rocket plane without the fire and smoke. The smalling is a daubt will be medified to medieve Tocket plane without the fire and smoke. The Invention, no doubt, will be credited to modern Invention, no doutor, will be created to modern day science and ingenuity, altho the greatest manufactor should date manufactor to should be greatest wonder about jet propulsion is that mankind has let the idea kick around for so long with.

It you want a picture of the first jet pro-If you want a picture of the first jet pro-pulsion motor, filp the pages of the dictionary to the word aeolipile. The aeolipile was the irret straam anging and it was int promuleion to the word acouplie. The acouplie was the first steam engine, and it was jet propulsion. Dura and simple. Hero of Alexandria, a Greek pure and simple, siero or Alexandria, a Greek mathematician and physicist, about whom little mathematician and physicist, about whom little /te is known except that he probably lived about /at and R. C. invented on gave the first account /at 13 Known except that he probably lived about 130 B. C. invented or gave the first account It is a metal basin with a cover, standing on

what e.

out putting it to use.

a tripod. Hollow tubes lead up from the basin

thing in jet propulsion. DANCADOTIC

EADI

a tripoa, fionow tubes lead up from the basin a boller to a metal sphere, which is mounted in the basin is a space of the tripost of the basin is a space of the tripost of the basin is a space of th or voner to a metal sphere, which is mounted so that it can revolve, Two jets protrade from so that it can revolve, two jets protride itom opposite sides of this sphere, with their tips itom scheme itom the scheme itom opposite sides of this sphere, with their tips turned at a tangent to the sphere, like the turned at a tangent to the sphere, like the arms of a swastika, Fut some water in the arms or a swastika. Fut some water in the basin, build a fire beneath it, and the steam whistles out of the jets, spinning the ball. Men have learned to do a lot of things with stean since Hero's time, but it took them more than 2,000 years to realize that Hero had some.





MANUFACTURERS OF READING CAST STEEL VALVES AND FITTINGS PRATT & CADY BRASS AND IRON VALVES D'ESTE VALVE AND ENGINEERING SPECIALTIES The announcement of the new jet-propelled mystery war plane-unspeakably fast and powerful-just gives more proof to those old-timers who stick to the idea that there is nothing new under the sun.

A Chicago newspaper in an editorial late in January traced the idea to Hero of Alexandria and dated its first use as 130 B.C.-in what is often called the. original steam engine.

READING-PRATT & CADY's research ran across the story about five years ago-and a very early drawing of the steam engine. We located an old-time woodcut craftsman and asked him to reproduce the ancient sketch.

The $5\frac{1}{4}$ " x $5\frac{1}{2}$ " prints were so interesting and rich in their early simplicity that we offered to send a copy, mounted on mat board ready for framing, to any who would like one.

Today, because of the nation-wide interest in jet propulsion, we are repeating the offer. Please make your request on the letterhead of your company and address our offices at Reading, Pennsylvania.



Reading, Pa., Atlanta, Boston, Chicago, Denver, Houston, Los Angeles, New York, Philadelphia, Pittsburgh, San Francisco A DIVISION OF AMERICAN CHAIN & CABLE COMPANY, Inc. BRIDGEPORT . CONNECTICUT

THESE machines fill a long felt need for double reduction units of the fully enclosed type to be used for agitators, mixers, ore roasters, bending rolls, etc., requiring a vertical shaft drive. Built in standard ratios in various types of assemblies ranging from 40 to 1 to 250 to 1 for all common motor

speeds and a wide range of horsepower ratings.

Jones Bulletin No. 75 covers complete details on these Worm-Helical Speed Reducers, with rating tables, dimension diagrams, torque charts and other application information. We shall be pleased to send you a copy.



. Jones Worm-Helical Speed Reducer on ore roaster with section of dust guard removed to show final gear reduction.



RM-HELICAL

REDUCERS

for Vertical Shaft Drives

• Jones Worm-Helical Speed Reducer driving a lacquer agitator. A simple design prevents leakage of oil along the vertical low speed shaft.

A. JONES FOUNDET & MACHINE CO., 4415 Reasevelt Road, Chicago 24, Illinois



• Jones Worm-Helical Speed Re-ducer on a paper mill agitator drive.

"Out of another world" comes an amazingly better Liquid Handling Pump

To look at it you wouldn't see much to "ah-h" about.

It's small. Weighs less than 4 pounds. But when you note its capacity ... its efficiency curve ... its performance record ... then you begin to take notice.

You see, we designed this pump for operation in another world, high in the heavens . . . in rarefied, subzero atmospheres...for planes demanding fuel to maintain speeds of five miles per minute and better.

Pesky things can, and did, happen to pumps up there. But no more ... since we perfected enginedriven pumps with relief and by-pass valves that maintain efficiency regardless of temperature ... since we perfected fuel pump refinements which

will be mailed promptly upon request.

handle "dry" high-octane aviation gasoline at close to 100 per cent volumetric efficiency...since we developed a motor-driven booster pump with a new impeller which is approximately 20 per cent more efficient on a power consumption basis than any other now in use on centrifugal pumps of equivalent size.

By mastering these and many other aircraft pumping problems, PESCO can give you fluid handling equipment of entirely new performance. Equally improved PESCO equipment is also adaptable for all types of pumping needs; hvdraulic, air, vacuum and liquid. May we tell you more about PESCO Pumps and PESCO Engineering Service?

SEND FOR THIS BOOK "Pressurized Power and Controlled Flow by PESCO". This book pictorially tells the story of PESCO equipment, manufacturing facilities and engineering service. A copy



WRITE TO. **PESCO** Products Co. Industry Service B 11610 Euclid Avenue Cleveland 6. Ohio

Division Borg-Warner

In Precision Hydroulics, Fuel Pumps, Air Pumps, Related Accessories PERFORMANCE POINTS TO



CALL IN THE BEMIS MULTIWALL PAPER BAG EXPERT

Bemis has a staff of Multiwall Paper Bag experts which are at your service whether you are a Bemis customer or not. Call upon us any time you have a troublesome packaging problem. You'll find the Bemis Man an expert on all phases of such problems, whether it be bag design, bag closing equipment, shipping or storing bags. Let him study your packaging operations. He may suggest ways to increase output, lower man power, cut costs or reduce waste. His call will cost you nothing and place you under no obligation.

Okla

BEMIS BRO. BAG CO.

Peoria, III. • East Pepperell, Mass. • Mobile, Ala. San Francisco, Calif. • Wilmington, Calif. • St. Helens, Ore

Balinave - Balinave - Balina - Bullalo - Charlone - Checago - Dener Datao - Hayron - Indianagoola - Kansas Crty - Lon Angeles - Lourville Menghin - Minnegoola - New Orleam - New York Crty - Nodali - Otla-ham Crty - Omaha - St. Law - Salina - Sali Lake Crty - Sardine - Wichshe

BETTER BAGS FOR 86 YEARS



BOILER SCALE NOSELITE SODALITE ANALCITE MAGNETITE

X-RAY DIFFRACTION AT WORK

A new boiler had been in operation at the Dow Chemical Company at Midland, Michigan for a short time when a number of tubes ruptured on the hot side. When the tubes were sectioned, a hard scale was found. An x-ray analysis of this scale gave a pattern which was identified as containing a mixture of noselite, sodalite, analcite, and magnetite.

From the results the boiler expert concluded (1) that the hard scale lowered heat transfer and caused excessive temperature and oxidation of the tube wall, and (2) that the cause of the hard scale was in the feed water system. The feed water used was that returned from other boilers and was given an oil treatmentthis introduced alumina and silica, which later reacted in the hotter areas to form the hard scale. A revision of the oil treatment system eliminated the scale.

Here again, is evidence of the unusual importance of x-ray diffraction investigation, and how a seemingly difficult problem

> was readily solved by a G-E XRD Diffraction Unit. You, too, may have problems which can best be solved by x-ray diffraction. If you wish full information about this unit and its application to your problems, write or wire, today, to Department N53. The services of our X-Ray Diffraction Laboratory are yours for the asking.



Today's Best Buy = 4. S. War Bonds

CHICAGO (12), ILL., U. S. A.





G-E XRD Powder Camera with specimen mount

• MARCH 1944 • CHEMICAL & METALLURGICAL ENGINEERING

CHIEF CHEMIST

PLANT ENGINEER

CHEMICAL CONSULTANT

PAPER TECHNICIAN



WILL THIS VACANT CHAIR COST YOU MONEY AND MARKETS ?

If the "paper technician's chair" remains vacant during your conferences on present or postwar production plans, you may be passing up economies and improvements vital to the future progress of your business.

Mosince Paper Technicians have met many of the demands of war service by developing "special analysis" industrial papers, with properties never before considered possible in paper. Today, industrial papers have broader utility... and will have still more in postwar use.

Paper specially engineered by The Mills of Mosinee to meet your exact needs, may speed up processing, assembly or packaging operations . . . replace critical materials, lower your costs, multiply your markets.

Call for a Mosinee Paper Technician to fill that "vacant chair." The broad experience and facilities of the Mills of Mosinee are ready now to go to work on problems of present or postwar product planning and production.

MOSINEE PAPER MILLS COMPANY WISCONSIN Essential Paper Makers

小震

Please address your letter Attention Dept. C"



LENGTHEN "ON STREAM" TIME OF TOWERS

with Bubble Caps of Enduro

When bubble caps made of Republic ENDURO Stainless Steel go into service, they hold back the day when the tower must be taken off stream for maintenance or replacement.

Hence, they increase production time-step up efficiency of operation-reduce costs.

Republic ENDURO Stainless Steel resists corrosion at high or low temperatures. It practically eliminates coking. Its high strength-toweight ratio provides light weight and insurance against breakage. Its uniform workability permits

fabrication of a wide variation of designs to obtain greatest efficiency.

You'll find this most noble of ferrous metals a long term cost-saver in many refinery applications. It has proved its desirability in bubble trays, tower liners, hot vapor lines, heater tubes, return bends, valves, pumps and other places.

Would you like to know more about

ENDURO and its relative corrosion-resistance in the presence of various substances? Write for descriptive literature containing the complete story.

REPUBLIC STEEL CORPORATION

Alloy Steel Division Sales Offices . Massillon, Ohio GENERAL OFFICES • CLEVELAND 1, OHIO GENERAL OFFICES • CLEVELAND 1, OHIO Berger Manufacturing Division • Culvert Division Niles Steel Products Division • Steel and Tubes Division Union Drawn Steel Division • Truecon Steel Company Export Department: Chrysler Building, New York 17, N.Y.



OVER THE HUMP with war-swollen freight

You are looking at the world's largest classification yard. Here, 8,000 cars a day, loaded with freight roll down the hump, are sorted and sent on their way to cities and hamlets across the breadth of the land.

These loaded cars rolling downgrade to the classification tracks would gain tremendous momentum were it not for the electrical retarders placed at intervals along the track. These retarders slow up the cars by gripping the wheel flanges with steel fingers.

Here is another job where Foote Bros. gears are working 24 hours a day helping get America's most important job—winning the war—done.

But the sturdy speed reducers—the compact actuators the extreme precision gears that Foote Bros. are today producing for the Army, the Navy and for industry hold promise to American manufacturers of new efficiencies in the transmission of power made possible by new engineering developments—new manufacturing "know hows" acquired in the stern laboratory of war.

FOOTE BROS. GEAR AND MACHINE CORPORATION 5225 South Western Boulevard • Chicago 9, Illinois



Better Power Transmission Through Better Bears

INDUSTRIAL AND PRECISION GEARS • SPEED REDUCERS • MOTORIZED REDUCERS • AIRCRAFT DEVICES

WOULD YOU CHOOSE THE NORIA?

Bowls of the De Laval Oil Purifiers are of the "constant efficiency" type — the degree of purification is not affected by the removed sediment, which accumulates outside of the zone of separation.

IT WORKED BU

YOU would not choose the old Asiatic wheel, the noria, to pump your water today — there is a better way. But some otherwise modern plants continue to employ equally obsolete gravity settling processes in attempting to solve problems of separating or clarifying various liquids.

Gravity settling in most cases is as out of step as the noria. Today, De Laval Separators and Clarifiers utilize centrifugal force, many thousands of times stronger than gravity, to separate instantaneously and continuously two liquids of different specific gravities or to remove solids.

The result of using De Laval Industrial Centrifugals is that processes can be simplified, costs cut, the product improved, and output increased. De Laval engineers have had many years of experience solving difficult problems of separation, clarification and concentration so that the solution to your "unusual" problem may be in our files — now.

Write for additional information.

THE DE LAVAL SEPARATOR COMPANY 165 Broadway, New York, 6 427 Randolph St., Chicago, 6 DE LAVAL PACIFIC CO., 61 Beale St., San Francisco, 19 THE DE LAVAL COMPANY, Limited MONTREAL PETERBOROUGH WINNIPEG VANCOUVER



NEED ANY HELP...

NEW PRODUCTS FOR FUTURE BUSINESS?

The Rustless Development Division — concentrating entirely on Stainless Steel Billet, Bar and Wire products knows how to engineer the correct grade of Stainless Steel into any product.

Trained through broad experience with thousands of diversified applications, this special service division of Rustless will be glad to render every possible aid to Designing Engineers now working on special future plans or products.

Any request for information with reference to the proper selection of Stainless Steel, what grade to use, best conditions under which to use it, or details concerning its fabrication will have our prompt and personal attention. If you have a specific problem, call our nearest District Office.

> If It's Urgent, Ask RUSTLESS By Phone Wolfe 5400, Baltimore 13, Maryland



Producing STAINLESS STEEL Exclusively

RUSTLESS IRON AND STEEL CORPORATION, BALTIMORE 13, MD.

SALES OFFICES: BUFFALO • CHICAGO • CINCINNATI • CLEVELAND • DETROIT LOS ANGELES • NEW YORK • PHILADELPHIA • DISTRIBUTORS IN PRINCIPAL CITIES

WHEN YOU WANT

TO KNOW ABOUT

STAINLESS

Ask RUSTLESS

Now available for additional wartime applications, STAINLESS STEELS provide means of improving the performance of our

RUSTLESS will be glad to help you select the

fighting equipment.

proper grade.

50 YEARS' EXPERIENCE ENABLES US TO BUILD DEPENDABLE VALVES

A large percentage of the men who build Fairbanks Valves have specialized in that work for from 20 to 40 years.

Isn't it only natural that this concentration should result in producing better, more reliable valves? And isn't it evident that there must be real merit in the products of a concern that can survive the business storms of more than half a century?

The long life, reliable performance and low maintenance cost of

Fairbanks Valves reflect the care and enduring quality built into them.

Write for our interesting Catalog No. 42, and name of our nearest distributor.

> THE FAIRBANKS COMPANY 393 LAFAYETTE ST., NEW YORK, 3, N. Y. BOSTON, MASS. PITTSBURGH, PA.

Fairbanks Standard And Renewable Valves