

be bright

Stock say

 Reproduction in miniature of the new Crompton Lamp Poster. The publicity campaign also includes National and Provincial newspapers, weekly and monthly periodicals, railway and arterial road signs.

1

1

ii

October 20, 1944

ENERGY FOR THE NATION'S FACTORIES, WORKS & PUBLIC SERVICES

Uninterrupted transmission of electrical energy by C.M.A. Cables in quantity greater than ever before in our history is playing a most vital part in Britain's supreme effort for victory.

CMA

ABLES



The Successful Colors of the Color C

Jahnson & Phillips

The India Rubber. Gutta-Perchal& Teletraph Works Co. Ltd. (The Silvertown Co.)

Cable Ce L(d The London Electric Wire Co. and Smithe

The Macontosh Cable Co Ltd

The Metropolitan Electric Cable & Construction Co.

Pscelli-General Cable Works Ltd (General Electric Co. Ltd.)

Si Halana Cable Aubbar Co Lui Sismens Brothers & Co Ltd (Siemens Electric Lamps and Supplies Ltd)

Standard Telephone & Cables Ltd Union Cable Co Ltd

Advt. of the Cable Makers' Association, High Holborn House, 52-54 High Holborn, W.C.I.

Phone: Holborn 7633

The Art of Knowing How



Centuries before Man realised the necessity for elasticity in his constructional work, the spider had proved the point—in practice. Subsequently Man copied the Spider's Web—the lightest and most tenuous construction in the World. Now, although Man still works with Metals that are inert and inelastic, there are no limits to the "elasticity" of the mind in producing new designs from Industrial metals. Thereby is measured the art of Progress.



LEADERS IN ELECTRIC WATER HEATING



PHONE : NORWICH 25131

FATRAI

GRAMS : HEATRAE, NORWICH









2

October 20, 1944

FOR ALL ESSENTIAL PURPOSES



WE are actively engaged in all the manufacture of V.I.R. and synthetic insulated cables to meet the urgent requirements of war. Our Research Laboratories have been associated with the development of synthetic materials as cable insulants for many years before the war, and the experience thus gained has been applied to the manufacture of our cable products.

> V.I.R. and synthetic insulated cables produced by this Company are being used for all essential war purposes.

Standard Telephones and Cables Limited

(Cable Sales Department)

NORTH WOOLWICH, LONDON, E.16 Telephone : Albert Dock 1401

Time flies – Backwards !

A man we know has worked out by means of a slide-rule and a bit of snooping that 351,429 man-hours were lost to industry on February 17th, 1944 by drilling holes with hand drills instead of Desoutter power drills. He says that the result of this immense loss of time was that when the workers came to work next day it was *really* February 18th, 1903. After a bit of a pause while our eyes stopped rolling, we said we thought there was a catch in it. We said wouldn't it be February 18th, 1985. Like British Summer Time, first you put it on and then you take it off. He said, no, it was 1903 like he said and what a terrible waste of time. He said the British were always getting ready for the previous war and this proved it. Well, we wouldn't stand for that so we slung him out and his slide-rule after him. But it's a shaking sort of a thought, isn't it? And nothing you can do about it because Desoutter Tools weren't invented in 1903.

DESOUTTER Specialists in Lightweight Pneumatic & Electric Portable Tools DESOUTTER BROS. LTD., DEPT. R, THE HYDE, HENDON, LONDON, N.W.9 PHONE: COLINDALE 6346-7-8-9

IGRANIC MAGNETIC DEVICES



Igranic Magnetic Specialities have been tried and proved in some of the largest industrial plants in this country. They are built to withstand years of arduous service.

Igranic Magnetic devices include : Magnetic Brakes Magnetic Clutches Lifting Magnets Magnetic Separators Magnetic Selenoids, etc.

Illustration above shows Igranic Lifting Magnet, Below, Igranic Type "M" Magnetic Brake.

Write for Detailed Leaflets



B T-H ELECTRIC MOTORS WITH APPROPRIATE CONTROL GEAR for any industrial application

Range includes:- General Industrial, Textile, Machine-tool, Steel Works, Rolling Mill, Crane, and Mining Motors

General Industrial A.C. Motor (Squirrel-cage Type)

BTH products include all kinds of electric plant and equipment; Mazda lamps and Mazdalux lighting equipment. In the coming period of general reconstruction SPECIFY BTH ELECTRICAL EQUIPMENT



THE BRITISH THOMSON-HOUSTON CO., LTD.



NOV. IL PLEASE GIVE GENEROUSLY REMEMBRANCE DAY

October 20, 1944

PARSONS TRANSFORMERS



The design, construction and reliability which characterise Parsons Transformers are a direct result of many years' experience in manufacture and operation



& COMPANY LTP NEWCASTLE - ON - TYNE 6 LONDON OFFICE : 56 VICTORIA STREET, LONDON, S.W.I



Large numbers of Sturtevant Industrial Vacuum Cleaners are successfully operating in factories and industrial works of all types engaged on essential war work.

They are giving continuous service and maintaining the highest efficiency under the most exacting conditions. Experience shows that the systematic and regular use of a Sturtevant Cleaner overcomes dust problems and increases the efficiency of all cleaning operations. Furthermore, it has been proved conclusively by a great many users that better and greater output can be produced as a result of the very clean conditions obtainable by using a Sturtevant Industrial Vacuum Cleaner.

Innumerable tests have proved that, due to the high mechanical and electrical efficiency, Sturtevant Cleaners clean more quickly and thoroughly than any others of equal power. May we send particulars and our publication U.1391 ?

STURTEVANT ENGINEERING CO. LTD. 25.WORCESTER ROAD, SUTTON, SURREY.

ECONOMY of FLOOR SPACE

NEWMAN Totally Enclosed Motors are proof against damage caused by dust, grit, swarf and coolants.

They can be safely mounted on any part of a machine close up to the work, thus saving valuable floor space and enhancing appearance.



Head Sales Office : 32 VICTORIA STREET, S.W.I

ABBey 2023



DAVIDSON & CO., LTD., SIROCCO ENGINEERING WORKS, BELFAST. LONDON LEEDS MANCHESTER GLASGOW BIRMINGHAM NEWCASTLE CARDIFF DUBLIN

HYDRO-ELECTRIC DEVELOPMENT for THE GALLOWAY WATER POWER CO.



The E.H.T. UNDERGROUND CABLES and OVERHEAD TRANSMISSION LINES WERE SUPPLIED and INSTALLED BY W. T. GLOVER & Co. LTD. TRAFFORD PARK MANCHESTER 17

11



October 20, 1944



Overhead

CERVICE ACCESSOFIES

range of HENLEY Overhead Service Accessories. May we send you further details ?

> HENLEY Aerial Service Fuse. The withdrawable fuse carrier can be sealed. Line wires interlock if porcelain is broken. (30 and 60 amp. working current).

HENLEY Aerial Service Fuse comblning duties of both line tap and fuse. Suitable for insulated or bare service wire. (30 amp. working current).

> HENLEY Nut type Service Tap specially designed to prevent trouble due to vibration. Four standard sizes. Insulating shroud effectively insulates service connections.

> > Outdoor Service Fuse. Fuse holder replaceable from ground level. No pole climbing. Suitable for mounting on exterior walls or overhead line poles. (30 amp. working current). 100 amp. model also available — this is suitable also for mounting with shackle insulator.

ELECTRICAL DISTRIBUTI

EQUIPMENT

Branches and Agents throughout the World.

W.T.HENLEY'S TELEGRAPH WORKS. CO. LTD. MILTON COURT. WESTCOTT. DORKING, SURREY

October 20, 1944



ELECTRO ZINCING

Canal G

by

THE GALVANAX PROCESS

is approved by the A.I.D. when a zinc coating is specified as a substitute for Cadmium plating owing to a shortage of the latter metal.

For fast deposits on wrought iron and steel it is unequalled in colour simple to operate, and has excellent throwing power besides providing efficient protection from rust.

GREAT HAMPTON STREET

8

BIRMINGHAM

2.14

SIEMENS-

CONTRACTORS FOR THE MANUFACTURE & LAYING OF ALL TYPES OF ELECTRIC CABLES

FOR POWER SUPPLY MAINS

We have a world - wide experience in the laying and jointing of all types of underground and underwater tables.



SIEMENS BROTHERS & Cº LTD WOOLWICH, LONDON, S.E.I8

• Other manufactures: V.I.R. Wires & Cables of all classes

ESTABLISHED 1858

Telephone : WOOLWICH 2020

15

October 20, 1944

FOR THE PRESENT AND THE FUTURE-

Consult the

G.E.C. on STREET LIGHTING

THE SECOND FOR WARTIME . . .

The adaptation of many peacetime installations to the improved wartime street lighting permitted in many areas is quite simple, and new equipment is only required in relatively few cases. May we assist you and submit our suggestions? Write for leaflet giving recommendations for converting G.E.C. lanterns to comply with the latest regulations.



Z.3130 G.E.C. Reflector for 0.02 f.c. illumination.

★ SCIENTIFIC PLANNING FOR POST - WAR STREET LIGHTING . . .

Peacetime lighting cannot be improvised. Safety on the road depends on scientific equipment and correct layout planning. The G.E.C. was a pioneer in modern street lighting. It led the way with the Osira electric discharge lamp, with "road brightness." planning, and with lanterns designed on engineering principles.

G.E.C. lighting engineers are glad to place their services at the disposal of lighting authorities who want to prepare for a brighter Britain.



Z.8128 Side entry Difractor lantern for "Road Brightness."

Adut. of The General Electric Co. Ltd., Magnet House, Kingsway, London, W.C.2

16

30.14

RE

17



Б

REHIND

October 20, 1944

LIGHTING

LIFE-TEST

IN order to keep continuous check on the "burn-out" life of Mazda Lamps, batches of lamps, taken at random from normal production, are tested to destruction in the BTH Lamp Testing Laboratory.

RESEARCH

In the equipment shown, the lamps under test are on the other side of the racks. Each lamp throws heat on to a highly ingenious thermal relay of BTH design. Each relay is connected to its own electric clock which automatically records the time of " burn-out."

LAMPS LAMPS

This is just one of a multitude of scientific devices

employed in the BTH Laboratories to maintain and improve the quality of Mazda Lamps.

BTH RESEARCH AIDS INDUSTRY BTH Research Laboratories have made an intensive study of both the physical and psychological aspects of lighting in wartime industry and their knowledge and experience are at the disposal of the principals of intensitial undertakings through the Mazna Lighting Advisory Service.





3. 14

19



0



YOU CAN 'BANK' ON CROMPTON V. D. R. CABLE





LIMITED, ELECTRA HOUSE, VICTORIA EMBANKMENT, LONDON, W.C.2 CROMPTON PARKINSON Telegrams : Crompark , Estrand, London Telephone : TEMple Bar 5911

21



四日

October 20, 1944





This remarkable number of Holgun Drills has been produced in record time, and the service demanded from them by war-time industries has far exceeded our claim for 1/4" lightweight drills The Holgun has proved the lightweight drill for all industries-now and in the future. . and here's the reason



B Deep-groove ball bearing on and accuracy

C Splined mounting of spindle gear increases strength, facilitates inspection, reduces noise friction wear

D Needle roller bearing on back end or spindle

E Full-size armature plnion, with 12 teeth, ensures smooth, quiet operation, less wear longer service

mounted inside the gear

G Generous size, double grease-sealed ball bearing on armature shaft

of the ventilating system

| Full-size fan mounted on armature

J Powerful Black & Decker Universal Motor, through-bolts hold field securely

K Famous Pistol Grip & Trigger Switch Instant release switch control convenient for right or left-Switch." hand use

E Switch-locking pin for optional use on continuous operations

MTwo-pole automatic release switch locking pin, cord protector and 3-wire cable are mounted in handle as one complete unit

Three screened air inless (on top mounted inside the gear G Generation of which provide ample ventilation

O Brush holders and springs mounted on moulded bakelite brush Ample air outlet slots prevent clogging ring, locked in place by the switch of the ventilating system

Black & Decker



BLACK & DECKER LTD · HARMONDSWORTH . MIDDX PHONE: WEST DRAYTON 2681/6. GRAMS : "BLACDECK," WEST DRAYTON BRANCH SERVICE STATIONS : LONDON + BIRMINGHAM + BRISTOL + GLASGOW LEEDS MANCHESTER + NOTTINGHAM

An explosion a very rapid chemical reaction, developing a sudden high pressure by the simultaneous formation of a large volume of gases and the liberation of great heat energy. If the energy developed by an explosive compound were released slowly, and not in the fraction of a second, there could be no explosion.

IT'S ABOUT TIME!

lime is the ruling factor

—and speaking of time, may we mention that for positive accuracy with dependability you could not offer anything better than the Ferranti Clock



ANGENT

October 20, 1944

SOUND SIGNALS LUMINOUS CALL SYSTEMS STAFF LOCATORS MINING SIGNALS FIRE, BURGLAR & BANK RAID ALARMS TELEPHONES RELAYS WATCHMAN'S CLOCKS ELECTRIC IMPULSE AND SYNCHRONOUS CLOCKS STRIKING, CHIMING

AND TOLLING MECHANISM

LIQUID-LEVEL INDICATING RECORDING 8 ALARM

APPARATUS

& OUTPUT RECORDERS

PROCESS TIMERS SPECIAL APPARATUS, ETC.

PIONEERS

in the Electrical Industry, the pre-war pre-eminence of GENTS' of Leicester will not be forgotten when Peace is once more proclaimed and Industry demands the products they manufacture.



GENT & CO. LTD., Faraday Works, LEICESTER ALSO LONDON . NEW CASTLE-ON-TYNE BELFAST DUBLIN

ELECTRICAL REVIEW

25

PRECISION TYPE

Illustration shows an example of an N.C.S. Frequency Meter of Precision type, complying with B.S.S. No. 89-1937 for short-range precision accuracy, being within 0.1% of the mean value of the frequencies shown on the scale.

These instruments are independent of voltage and temperature variations over wide limits and develop no selfheating errors. Low v.a. consumption.

Supplied with 90, 150, or 200 deg. scales.

INDUSTRIAL TYPE

Industrial Type Frequency Meters are also available in all sizes from 4" to 12" diameter dials with 90 deg. scales (approx.).

Nalder Lipman Patents

N.C.S. PRODUCTS include all types of Measuring Instruments, Indicating Recording, Switchboard or or Portable. Also Protective Relays, Synchronisers, Circuit Breakers, Earth Leakage Trips, etc. Every unit is designed for maximum operating efficiency, reliability and durability, prices being competitive without sacrifice of quality.

FREQUENCY METER

Quotations on request.

BROS. & THOMPSON NALDER Telephone : DALSTON LANE WORKS, LONDON, E.8. Telegrams : Clissold 2365 (3 lines) DALSTON LANE WORKS, LONDON, E.8.



27



THIS SORT OF THING CAN GO ON FOR EVER

A rabbit may be a dunce at some things, but he does know his multiplication. But don't be deceived. This is no family—it's the same rabbit every time. Study each one (through a magnifying glass if you like) and you'll find they're all exactly alike. You get the same thing among Tru-Wel electrically welded steel tubes. They are mass-produced at speed, million after million. Every length receives the same examination and tests for precision. Tru-Wel Tubes come to you ready for your job, all identical in dimension, strength, and concentricity,

ELECTRICALLY WELDER STEEL TUDES

T. 131

according to your orders, so that manipulation provides absolutely uniform results. Yes—this sort of thing will go on for ever.

MADE BY TUBE PRODUCTS LTD

A MEMBER OF THE TUBE INVESTMENTS GROUP

28







LEAFLET 126

This recent HIGGS publication has been received with enthusiasm and has provoked universal interest.

Its contents throw a revealing light on the many potential uses of electric motors on farms and illustrate what a valuable contribution they can make towards improving the pro-ductive efficiency of this vital industry.

W/Q 12 23 1RCA ETK

001

U. M

0

Bristol, Birmingham, Nottingham, Peterborough,

Dundee,

Glasgow,

London, Manchester, Sheffield, Wolverhampton.



6.6/11 kV METALCLAD SWITCHGEAR FOR SUPPLY AND DISTRIBUTION UNDER ALL SERVICE-CONDITIONS

CLASS-C 75/150 MVA 400, 800, or 1,200 amperes

SINGLE OR DUPLICATE BUSBARS DIRECT-HAND, SPRING, OR SOLENOID OPERATION





Designed and manufactured by Specialists with over 40 years' experience

PREMIER

still stands as the unequalled name for

Fine Qualit

domestic electric heating appliances Kettles, Fires, Irons, Toasters, Coffee Percolators, etc.

> ★ The present conditions naturally limit supplies, but our spares and repairs supplies, but our spares ervice to help department is still at your service to help you to the best of its ability.

PREMIER ELECTRIC HEATERS LTD., BIRMINGHAM, 9

The New Craftsmanship for



The millions of new houses which are and will be needed in this country--"prefabricated" and brick built alike—will call for ample supplies of standardised electrical products of good design, quality and durability.

The M.E.M. factory is fully equipped to turn out switches, fuseboards, and other electrical gear immediately the change over from war priorities to peacetime production becomes permissible. By full mechanisation and skilled planning M.E.M. engineers have created the New Craftsmanship which might be described as *quality in quantities*.

Quality depends upon good design, good materials and tested construction. Quantity production is the result of mechanisation and organisation. The M.E.M.

factory is self-contained and self-sufficient. It produces good electrical gear from start to finish-good all through.

MEM 8" All-Insulated Switch and Fuse

M, 1



SWITCHGEAR · MOTOR STARTERS FUSEGEAR · ELECTRIC FIRES

MIDLAND ELECTRIC MANUFACTURING COLTD., TYSELEY, BIRMINGHAM, 11 London Showrooms and Stores ; 21-22 Rathbone Place, London, W.1 • Manchester Showrooms and Stores ; 48-50 Chapel Street, Salford, 3



The wheels of Industry make the world go round

Industry relies on the electric motor, faithful robot servant of mankind, for the production of its goods.

British manufacturers of

Electric Motors

are proud of their vast contribution. WRITE TO E.C.C. FOR QUOTATION.


D

EDISWAN

VITREOUS OR STOVE ENAMELLED FINISH



THE EDISON SWAN ELECTRIC CO. LTD. 155 CHARING CROSS RD., LONDON, W.C.2 (L.B.53)



A TA Octob

October 20, 1944

and TRUNKING

SYSTEMS

INDUSTRIAL

SWITCHGEAR

Labour costs on site are

saved by using solid copper connections throughout.

ETI(

ESIN Lang

NISHES

Varnie

-

Vanis

.TD. R 17 DRAKE & GORHAM LTP STANDARD RD. · NORTH ACTON · N.W.10 Telephones : Willesden 6601-2 Telegrams : Tincomar "Harles London."

37

ALSO

Bus Bar

Tee

OVERHEAD DISTRIBUTION SYSTEMS

MAKERS OF THE ELECTRICAL REVIEW

October 20, 1944

FUSION WELDED DRUMS





Marine engineers are not slow in appreciating the advantages of Babcock Fusion Welded Drum construction. The upper illustration shows Babcock Marine Boilers all with welded drums in multiple production for the British Merchant Navy. The lower illustration shows one of the actual Drums, built for a working pressure of 450 lb./sq. inch.

LONDON, EC.4

BABCOCK & WILCOX LTD. BABCOCK

ELECTRIC	AL REVIEW
October 20, 1944 Contents :—	Managing Editor : Hugh S. Pocock, M.I.E.E. Technical Editor : Commercial Editor T C. O. Brettelle, M.I.E.E. J. H. Cosens
Page Editorial. —Mass Installation . 541 Compression Cable 544 Marine Electrical Work 548 Radio-Frequency Bridges 548 Transformer Operation. By C. H. Pike, Graduate I.E.E. 549 New Books Reviewed . 552 Post- War Installations 553 Thermal Insulation 554 Correspondence . 555	Contents continued :PageCommerce and Industry561Rectifiers for Battery Charging.By F. T. Bennell, Graduate I.E.E.565Forthcoming Events567Recent Introductions568Electricity Supply569Financial Section570New Patents575Contract Information576
Institute of Fuel 558 Personal and Social 559	Glassified Advertisements 69 Index to Advertisers 78

EDITORIAL, ADVERTISING & PUBLISHING OFFICES : Dorset House, Stamford St., London, S.E.I Telegraphic Address : "Ageekay, Sedist, London." Code: ABC. Telephone No.: Waterloo 3333 (35 lines). Registered at G.P.O. as a Newspaper and Canadian Magazine rate of postage. Entered as Second Class Matter at the New York, U.S.A., Post Office.

Annual Subscription, Post free : British Isles, £2 7s. 8d. ; Canada, £2 3s. 4d. ; Elsewhere, £2 5s. 6d. Cheques and Postal Orders (on Chief Office, London) to be made payable to ELECTRICAL REVIEW LTD., and crossed "Lloyds Bank."

> Our Glass Fabrics and Tapes are manufactured with special heat-resisting varnishes so that no loss in flexibility or dielectric and tensile properties result when heated in transformer oil for 2 hours at 200° C.

> > GLASGOW

(oco)-for a

Varnished GLASS Fabrics & Tapes

FOR HIGH TEMPERATURE INSULATION

.





IOCO LIMITED

6, 1941

OW I

Marine

15%

atti

show

行

ind

ELECTRICAL REVIEW

October 20, 1944

PORTABLE OIL TESTER

(MAINS OPERATED) FOR THE RAPID TESTING OF TRANSFORMER & SWITCH OILS



Entirely self-contained and arranged for direct connection to any low voltage A.C. Supply.

The test voltage is adjusted continuously and smoothly from zero to 40 kV.

The control gear is contained in a detachable lid which is placed well clear of the high tension circuits.

The form factor closely follows a sine wave at all voltages.

Can be adapted for high voltage insulation flash testing when required.

EVERETT EDGCUMBE

Manufacturers of all kinds of indicating and recording electrical instruments. Photometry experts





ELECTRICAL REVIEW



THE OLDEST ELECTRICAL PAPER - ESTABLISHED 1872

9d. WEEKLY

Vol. CXXXV. No. 3491.

OCTOBER 20, 1944

Mass Installation

Electrical Provisions for New Housing Schemes

N order that the many thousands of small houses and flats which are to be built in the near future may be homes in the fullest sense, the same order of priority will be required for their electrification as is given to their construction. Experience with existing properties indicates that, with appropriately organised productive methods and some modifications in installation technique, the occupants of the new dwellings, despite modest incomes, should be able economically to enjoy all the advantages that arise from the use of electricity for all purposes.

Encouraging Full Use

It will not be enough that the new installations should be carried out on sound engineering lines. They should be designed with the positive aim of encouraging the fullest use of electricity not only for the more ordinary domestic purposes, but also for the convenient working of various essentially electrical small appliances which may be expected to become available in greater numbers as time goes on. These requisites must be in conformity with the need for rapid manufacture at low cost, entailing a high degree of standardisation and the adoption of mass-production methods.

This rare opportunity of starting with a clean slate, but with the benefit of knowledge of what has gone before, has been seized by the Study Committee operating under the ægis of the Institution of Electrical Engineers in making the recommendations for pre-planned installations which are summarised on another page. Of great importance is the plea that provision should be made at the outset for all likely applications of electricity. Other proposals of a basic character are those for the standardisation of a new 60-A consumer's control; of a ring circuit for serving a liberal allowance of general utility sockets throughout the house (which would call for some modification of the I.E.E. Regulations); and of a new 3-kW all-purpose socket outlet with a fuse in the plug.

For meeting the demand for electric cookers which is expected to progress at a rate exceeding even that of the immediately pre-war years, the horizontal kind is advocated. This has proved popular in the Dominions and its manufacture for the home market should therefore possess advantages. That the value of constant hot-water supplies should be recognised goes without saying, but more effort will probably have to be expended in pressing the case for domestic refrigerators; no doubt, as the Committee suggests, present costs of these could be materially reduced through quantity production.

Standard Plugs and Sockets

As some millions of socket outlets will be needed, it is gratifying that the Committee was of one mind regarding a new standard. It was less fortunate in its failure to decide the round versus flat pin controversy; the considered opinion of manufacturers on the production aspects, which the Committee awaits, will, it is to be hoped, not be delayed. Finality cannot yet be reached, for causes outside the control of the industry, on the question of whether v.i.r. or p.v.c. insulated cables will

E *

Long-Term

Cable Test

be most readily available. Plastics do not otherwise make an appreciable showing in the Report; nor do all-insulated systems. The foregoing comments apply of course to new houses, and not to all of these. The greater number of buildings already in existence will, no doubt, absorb the output of more conventional production lines until they become obsolescent in the normal course. The present Report presents an imaginative and practical treatment of a subject of great urgency and can be commended to the careful study of those intending to take part in the projected Institution discussion on post-war installations.

RUNNING like a refrain An Absolute through the Installation Essential Study Committee's Report

is a plea for early consultation between the half-dozen interests which (apart from the owner and occupier) may be concerned in the construction of a building, in order to ensure the provision of adequate electrical facilities. It is to be hoped that what might superficially appear to be a Shakespearean "damnable iteration" will be effectual at last. It is an amplified echo of what has been urged so often and, in the first instance, so long Mr. G. O. Watson in his address ago. to the I.E.E. Installations Section (reported on p. 552) quoted a complaint made as far back as 1889 that the electrical installation is "usually the last thing considered by the designer of a ship; consequently the engine and dynamo have to be put in any corner that may be found for them."

Keeping in Touch Not the least of the services rendered by the four sections of the I.E.E. are the opportunities that

they offer for maintaining contacts among the members, which the war years have generally so sadly interrupted. The range of contacts possible in present circumstances has been greatly extended by the informal luncheons which the sections have organised. Twice as many members and guests (many from overseas) as the 250 or so who could be accommodated had. it was stated, wished to be present at the function of the Installations Section over which Mr. A. G. Ramsey presided last week, indicating that the bonds uniting electrical engineers are not only those due to common technical interests.

ONE of the most pleasing features to us of a recent visit to Yorkshire to see the installation which is near-

ing completion for the long-term testing of a new compression cable for operation at 132 kV (described in this issue) was the opportunity to appreciate first-hand how the Central Electricity Board is co-operating to make the experiment possible. It is extremely difficult or well nigh impossible for cable makers to arrange independently for adequate long-term testing at the highest transmission voltages, and in view of the widely differing schools of thought as to what form a very-high-voltage cable should take it is not too much to say that such healthy co-operation now must have an enormously beneficial effect on the future development of the transmission of electricity.

Quality and great a tendency in the past to consider that British goods will sell in

overseas markets because of their superior qualities. Although this belief is firmly based on fact it should not be considered true in all cases and in all places. Sometimes it has been used as an excuse for halfhearted salesmanship and while this has got away with it " for a time competitors have often stolen a march on British exporters by producing something quite as good as theirs at a better price. There is still a demand for good quality but there is a limit to the extra amount which will be paid for it. But some customers prefer cheapness to quality all the time. In this case it will be necessary to modify ideals if foreign competition is to be countered. Manufacturers are constantly being urged to study their markets; it is quite as important to acquire a thorough knowledge of competitors' products and methods.

WHEN the lighting re-Lighting Costs strictions were eased many local authorities decided that the expense involved in a half-way measure was not worth while. Their people, strongly hoping for an early return to normal lighting, have generally acquiesced—though not always—and in many places the matter is still being discussed. In our opinion the question is entirely one of cost. It is a good thing for the public to have as much light as possible and they should be given it unless the

1/12

250

四 十 日

TOIL

市山

14

1

15 000

tile-

a a b

int:

-

d'il

11

上封

the

「日日」

608

山田田田田田

N N N N

dit itt

REAL

5 1

expense is quite unreasonable, as it often will be, especially where the street-lighting equipment has been badly neglected. Authorities must take into consideration, however, that this equipment will have to be put in order before very long.

THERE is, of course, the fuel economy aspect. Last **Fuel Saving** week in the House of Commons, Major Lloyd George said that full lighting would require another million tons of coal a year. At present lighting was on a much more limited scale and he had arranged to find the additional supplies required. (He did not say how or how much.) On the other hand Mr. F. W. Purse in a letter to the Daily Telegraph shows that he is totally against partial lighting, considering it a waste of fuel, labour and materials. Although optimism may have been a little damped lately, surely it cannot be long before full lighting will be permissible and once it is the authorities will be unable to withstand the justifiable public demand for speedy restoration. They must be prepared.

Post-war ques Priorities elect

FACED with urgent requests for expansion of electricity supplies to rural areas, the Minister of Fuel

and Power has intimated that as soon as labour and materials are available after the war priority is to be given to the electrical needs of the bombed areas and of the people who are without homes or have to live in patched up premises. Few will dispute the justice of this decision, but if there is to be a considerable delay in meeting the demands of the country dwellers, those electricity undertakings responsible for catering for them should be exonerated from all blame, for they have already made a substantial start with their plans for rural electrification. If they are not allowed to proceed more opportunities will be given to those who clamour for "reorganisation" as a certain means of securing a supply of electricity for country districts.

Refrigerator Developments THE introduction of the new "larder-conditioner" referred to elsewhere in this

issue raises several interesting points in regard 'to the future of domestic refrigeration. The new development ensures a really adequate storage space, but will the housewife really think

she has a refrigerator if she has no icemaking facilities? The reason the latter are not provided is that the company making it considers it more economical in the circumstances to provide ice-making apparatus as a separate unit if required. Should experience show that the housewife, in the climatic conditions prevalent in this country, is contented to be without ice, why, it might be asked, should not the normal type of refrigerator also be constructed without ice-making facilities for the sake of cheapness? One further question : Is the slightly greater consumption than that of the normal refrigerator important in a working class house? At 2 kWh a day probably not.

IN our issue of April South 28th we commented on Australian Coal the technical difficulties likely to be experienced by

the Adelaide Electric Supply Company in complying with the request of the Government of South Australia that coal mined in the State from the sub-bituminous deposits at Leigh Creek, 380 miles north of Adelaide, should be burned at the company's Osborne power station. Since then analysis has shown coal from an adjacent field to contain only 5 per cent. of ash as against about 16 per cent. in the other deposits, but to have a higher moisture content of 35 to 40 per cent. as mined. Although the quality of this more recently discovered deposit is somewhat better, the cost of dealing with moisture is inevitably high and may consequently neutralise economic improvements due to higher calorific value.

Drying Low-Grade Fuel

THE South Australian Government is now investigating the merits of the Fleissner process, as developed in Canada and

the United States (though not, we believe, on any considerable commercial scale), for drying low-grade coal by high-pressure steam in enclosed vessels. By means of this process the moisture content is said to be more than halved and not to be thereafter appreciably increased through exposure to the air. At the moment, however, it is still an open question whether the expense incurred in drying (assuming this to be done at the pit-head) may not be greater than savings in transport of moisture between coalfield and power station.

ELECTRICAL REVIEW

October 20, 1944

Compression Cable

Experimental Installation

MOST interesting transmission-cable experiment is about to be launched at Osbaldwick, Yorkshire, where an installation is near the point of completion for the longterm testing under service conditions of a new type of cable. This represents part of a great collective effort that is being made by cable manufacturers and experts to find a fully acceptable medium for the underground transmission of electricity at very high voltages, and the experiment is being made possible by the co-operation of the Central Electricity Board which has permitted the insertion of a length of the new cable into one of its 132-kV grid lines, so that it can be loaded under normal service conditions, and has afforded the necessary site facilities. The cable manufacturers are, of course, providing the necessary means of switching in and out the test cable, with safeguards against possible unforeseen ill-behaviour of the cable.



Gas is applied at the base of the sealingend insulator through a twin chamber casting; complete insulator, oil- and gas-chamber castings shown separately at bottom

The manufacturers are the Enfield Cable Works, Ltd., and the cable is designed to overcome the difficulties associated with very-



The inner sheath is oval and the outer sheath circular, providing gas spaces between the sheaths to permit breathing

high-voltage underground transmission consequent on the formation of "voids" in the dielectric systems of cables because of the refusal of the lead sheathing to contract with the conductor and dielectric after they have been expanded as the result of load conditions.

Although the development has been broadly classified as in the field of gas-filled cables, as the gas is not contained within the dielectric system, i.e. inside the normal cable sheathing, we feel that gas-filled is hardly the right term. Actually the gas is applied externally to this sheathing which is thereby caused to "breathe" with the contraction and expansion of the conductor by the gas pressure of 200 lb. per sq. in. outside the sheath. This peculiarity puts the new cable proper, *i.e.* the simple formation of conductor, dielectric and inner sheath, constructionally largely in line with the long-standing and accepted "straight" cable associated with lower voltages. The new cable, which is intended to operate at 132 kV and is in consequence of the singlecore type on account of easier production and installation, is in principle the same as an earlier three-core development for 66-kV transmission which appears to have been operated successfully, but "secretly," for some years past.

The later development is, of course, intended for three-phase transmission, a line consisting of a cable group trenched in triangular formation with suitable protection. The cable is not limited to any one size, but

-

12 -

-

251

I LE DA

#0 511

E1s

-

1

21

P

下に

57

in giving the essential details of construction we refer specifically to the Osbaldwick cable which has a current rating of 394 A, representing 90 MVA. The expansion and contraction to which we have referred is facilitated by the slightly oval section of the "breathing" sheath : therefore the cable construction starts with a slightly oval 0.40-sq. in. conductor (61 0.093 in.) which is built up in a normal type of stranding machine. Under the precision control necessary for such very high voltage the core is lapped with layers of paper tape (later suitably impregnated) up to a radial thickness of 0.46 in. Over

the paper is lapped a single tape of metallised paper screen and over this is extruded the inner oval lead sheath, or diaphragm which is 0.08 in, thick. The diaphragm is lightly reinforced by two oiled papers and covered with an oiled cotton tape.

An outer circular lead sheath 0.12 in. thick is extruded over the reinforced oval sheath, with the result that there are two "new moon" spaces, one at each side of the oval between the reinforced inner sheath and the outer sheath. These spaces,

Oil and gas systems are connected to a compensator which balances the oil and gas pressures; compensator shown up-side-down for convenience, inner component raised to show bellows

which really constitute a continuous space of varying depth right round the reinforced inner sheath, are filled with nitrogen gas at 200 lb. per sq. in., so

that the outer sheath acts as a gas retainer. The retaining sheath has a double reinforcement, circumferentially and longitudinally.

The circumferential reinforcement consists of two brass tapes which are lapped over two oiled papers and followed by a bedding of bituminised paper to a radial thickness of 0.04 in., and by a compounded tape. The longitudinal reinforcement comprises narrow brass tapes applied overall. Finally there is the makers' overall sandwich cable protection of two layers of non-fibrous insulating material which is reinforced with compounded cotton tapes and, in turn, served with impregnated hessian tapes. This build-up results in an overall diameter of about 3 in.

The installation at Osbaldwick is not yet completed, as our photographs show, and the cables, which represent a line length of a few hundred yards round a field, rise out of the ground and up the concrete pedestals of the special switching structure where the cable ends are temporarily "bottled off." The cables will, however, terminate in special sealing-end

> insulators which constitute an important part of the cable in that the gas is applied to each cable at the base of the sealingend insulator. This base, which is a casting on which the insulator proper sits, has two chambers hermetically sealed from each other. The inner lead sheathing opens out in the top chamber which is filled with oil at 200 lb. per sq. in., while the outer sheathing opens out into the bottom chamber to which the nitrogen is applied at 200 lb. per sq. in. ; thus, through these two chambers the gas and oil systems are fed for the maintenance of stable working conditions, without any interference with, or interplay between, the gas and oil systems.

> The junction of the two chambers is sealed off externally by means of a "Victaulic" joint consisting of a ring with an inner trough containing a rubber gasket of similar construction, with its channel

communicating with the gas chamber. In this way the pressure of the gas forces the rubber against the inner walls of the exterior ring and effects a gas-tight joint. The base of the gas chamber is plumbed to the outer lead sheathing by a normal wiped joint, and by means of a casting, engaging flanges on the gas chamber and the exterior of the cable, the normal wipe is reinforced by an outer bismuth-alloy scaling joint.



The gas path is continued in the joint by the space between the reinforcing tube and the outer casing ; joint before insulating (bottom) and with reinforcing tube in position (top)



The gas is supplied to the cable from normal service gas cylinders housed in specially designed gas-reservoir cabinets with suitable anchoring arrangements. The equipment includes an automatic regulating valve, a shut-off valve, a needle valve in the



Above : The cables rise out of the ground and up the concrete pedestals of the special switching structure where the cable ends are bottled off.

Right : Means for switching cable in and out, with safeguards against possible unforeseen trouble

gas line to the cable, and various indicating pressure gauges. The gas-reservoir cabinet is connected by a pipe line directly to the

gas chamber at the end of the cable, *i.e.* at the bottom of the sealing-end insulator, but there are connections from the gas line and from the oil chamber at the end of the cable to a compensator which preserves a balance between the oil pressure in the dielectric system of the cable and the gas between the inner and outer sheaths on the bellows principle. The compensator, with the necessary valves and gauges, is mounted on the pedestal carrying the sealing-end chamber.

Of outstanding importance is the method of jointing the cable, which can be supplied in 300 to 400-yd. lengths for normal working conditions. In this joint the "breathing" sheath of the cable is represented by a fluted copper sleeve which is placed over the built-up dielectric after the precision hand taping has been applied.

This "breathing" sleeve is plumber-wiped to the lead sheath of the cable through a copper spinning at each end. Over the fluted sleeve is a brass reinforcing tube, and overall there is an outer casing which represents, and is plumb jointed to, the cable outer sheathing via a copper spinning. Thus the gas path between the "breathing" and outer sheaths of the cable is represented in the joint by the space between the reinforcing tube of the fluted sleeve and the outer casing. In a similar manner to the arrangement at the sealing-end insulators, the normal wiped joints are reinforcing moulds. The joint is about 5 ft. long overall, and it is enclosed by a concrete box supported on the concrete floor of the jointing pit and filled with sand.

The 132-kV sealing bells at Osbaldwick enderschierter bener hier in entirely new principle, as applied

embody an entirely new principle, as applied to sealing bells, in dealing with the problem of industrial pollution. The bells were supplied by Taylor Tunnicliff & Co., Ltd., in collaboration with the Enfield Cable Works, Ltd. This principle of "stabilisation" involves the coating of the porcelain with a new type of semi-conducting glaze. Its action may best be explained by considering the mechanism of insulator flash-over due to pollution and moisture.

In an unstabilised insulator a surface current flows from line to earth and, owing to the pollution being non-uniform, the $I^2 R$ loss varies from point to point, the greater

441

2

「「「「

A STATISTICS IN

1

10

「「「「「

の日本の

572

ing)

dissipation occurring on the higher-resistance parts. This dissipation causes more rapid drying out of the moisture at the high re-



Each joint in the compression cable is about 5 ft. long overall

sistance parts than on the lower resistance parts; consequently the potentials across the higher-resistance parts also increase, and eventually local arcs short-circuit the higherresistance paths and initiate leakage current surges which sometimes lead to complete flash-over.

In the stabilised insulator the control of voltage gradient over the surface is taken over by the semi-conducting glaze and local overstressing is avoided. The degree of stabilisation depends on the stabilising re-



Cables trenched in triangular formation about 3 ft. deep with concrete slab protection

sistance; the lower this is the greater is the stabilisation. In the Osbaldwick sealing ends the stabilising resistance is of the order of 150 megohms between line and earth at 20 deg. C.

Costs of Fuel Saving

ELECTRICAL REVIEW

THODS of striking a balance between fuel savings and expenditure of manpower and material required to produce them were discussed in a paper presented by MR. G. N. CRITCHLEY before the Institute of Fuel at Manchester on October 18th. On the initiative of the author, an interim national standard for fuel saving had been taken by which schemes which saved enough coal at £2 per ton to pay for themselves in 2½ years were approved. An improvement on this was suggested in the paper which entailed the design of certain equipment on an incremental rather than an overall basis. The aim was to balance the man-power expended in all stages of manufacturing, installing and maintaining a fuelsaving device against the mining man-power economies it produced.

On the assumption that a saving of 275 tons of coal reduced the mining labour required by one man-year, the time taken (RT_L) for this economy to defray the labour on the device gave

a stable relationship. An exploratory relationship between the financial repayment time, RT_F , and RT_L showed the present standard $RT_F = 2.5$ yr. to correspond to a labour repayment time of about one year, which was lower than necessary. During the war at least two years for the latter would be justifiable, corresponding to $RT_F =$ 4.5 yr. As an example of the effect of such a modification, it was shown that the appropriate thickness of heat-insulating brick for roofs of metallurgical furnaces could be increased from 6 to $7\frac{1}{2}$ in. While RT_L was relatively stable, RT_F varied, so the relationship between the two would have to be kept constantly under review. A shortcoming of the financial repayment-time concept was that it gave the same value to all grades of coal. A labour repayment of at least ten years would be extended, e.g. to balance savings in boiler-house labour against manpower used in manufacture, installation and maintenance.

Marine Electrical Work

Selection and Training of Engineers

THE theme of Mr. G. O. Watson's inaugural address to the I.E.E. Installations Section on October 12th, was the "Future of Electrical Engineering in the Merchant Navy," mainly in regard to the training and education of electrical engineers, which he looked upon as the most pressing aspect. The quality and reliability of electrical installations and apparatus in British ships was, he stated, higher to-day than ever before, as comparative freedom from fires and other troubles showed, but this had been used as an argument against improving the qualifications and responsibilities of electrical superintendents and electricians.

Responsibility for Development

One consequence of this was that the initiative in any new direction was taken by manufacturers, whereas it should come from those whose duty it was to study running results and capital charges in relation to economy if British ships were to maintain their competitive position. For instance, there was a tendency in some countries to adopt AC instead of DC; the advisability of departing from existing British practice and the problems which were associated with variable-speed drives should be studied in a scientific manner.

There were two problems in training, namely the running and maintenance of installations while at sea and the progressive planning for future development and organisation at headquarters. The two were inseparable because executives were promoted from the lower ranks. Men of the type educated in universities and technical colleges and drawn from manufacturers' works should be encouraged to become sea-going elec-The present electricians tricians. had generally adopted their calling by chance, having been perhaps wiremen or contractors' charge-hands who had remained with the ship but were without encouragement to improve their position by study.

Grades and Qualifications

Two types of men were required. The first should be professional engineers, ranking as officers with a status comparable with that of marine engineers and similarly graded. The junior ranks would be uncertified, but their sea service on electrical work should qualify them for promotion (which it does not now) after examination, coupled with prescribed workshop experience. Suitable qualifications would be the Higher National Certificate in Electrical Engineering or the A.M.I.E.E. examination. Youths should be allowed one free day a week to attend classes, while those at sea might have short intensive courses supplemented by postal tuition.

The second type of electrical man should have passed a suitably modified City and Guilds examination, the course including the I.E.E. Regulations for the Electrical Equipment of Ships instead of those for buildings. This would be combined with apprenticeship to a concern engaged in installation or maintenance of electrical installations of ships. The Institute of Marine Engineers had formulated proposals for the education and training of their members. Similar representations should now be made on behalf of marine electricians.

During the course of his address, Mr. Watson said that the first record of the use of electricity in the Merchant Service (the Royal Navy had adopted it earlier) was in 1879 when the saloon of the Pacific Steam Navigation Co.'s new s.s. Mendoza was lighted by means of a Gramme dynamo and arc lamps. In 1883 the Swan United Electric Light Co. recorded the names of twenty-five ocean-going steamers illuminated by incandescent lamps, the largest of which was the Cunarder s.s. America with 550 Swan lamps and four dynamos. In 1891 Lloyd's issued rules relating to the use of electric light in vessels, probably the first code for electrical installations ever drawn up.

Radio-Frequency Bridges

BEFORE coming to the more technical aspects of his address on October 11th as chairman of the I.E.E. Radio Section, Mr. H. L. Kirke gave an account of discussions he, together with Dr. Smith-Rose and F. S. Barton, has had with the Institute of Radio Engineers of America, which has led up to the formation of a Liaison Committee. As soon as sufficient paper becomes available, abstracts of the American Institute's papers are to appear in the *I.E.E.* Journal and vice versa.

Mr. Kirke then turned to a description of five types of radio-frequency bridge which have been developed and used during the last ten years, namely, a short-wave admittance bridge (1935), a medium- and long-wave admittance bridge, a medium- and long-wave motor-ratio admittance bridge (15 kc to 2 Mc per sec.), an ultra-short-wave high-admittance bridge (100 kc to 100 Mc per sec.), a medium- and long-wave series (low) impedance bridge (100 kc to 2 Mc per sec.), and in addition a low-frequency capacitance bridge—the forerunner of some of the radio-frequency bridges. He concluded by giving some particulars of associated apparatus, including an oscillator designed to cover the frequency range from 150 kc to 28 Mc per sec. in and a straight-tuned radio-frequency receiver with a beat oscillator and audio-frequency 341

in the set

FFF

the star

10

23:

ning .

Transformer Operation

Effect of Loading on Life Expectancy

By C. H. Pike,

Graduate I.E.E.

ORE economic operation of transformers may be achieved by more effective use of capacity as loads increase and by reducing running charges. The advantage of adopting the first course is, primarily, that capital expenditure can be postponed if desired and that new units will embody any technical improvements in the interim. Such improvements may in themselves lower running charges, which with existing units may be reduced by closer attention to such factors as energy losses

and maintenance expenditure. More effective utilisation implies increasing the load on individual transformers to an

extent which does not shorten the physical life unduly. The economic life of a transformer is usually reckoned more or less arbitrarily for accounting purposes at from twenty to thirty years, at the end of which period all the fixed charges will have been met and the depreciation allocations made will permit the replacement of the unit. The physical life may be considerably longer and whatever margin remains is subject only to running charges.

The existence of a margin of physical life indicates incomplete utilisation during the economic life. Financial policy may require under-utilisation with an economic life period less than the actual life-expectancy. Moreover, loading below rated capacity may These probably give a reasonably accurate indication of the useful life, since the insulation as a whole may retain adequate strength after complete deterioration at the hotspots.⁽²⁾ The values may in fact be conservative, since no attempt was made to keep the ambient oil perfectly dry; hence the insulation itself probably contained moisture. Now in 1942 F. M. Clark showed⁽³⁾ that the rate of mechanical deterioration of insulation increased with moisture content,

especially at higher temperatures. In recent years the effect of developed acidity on mechanical strength has also been demonstrated.^(4, 5, 0) As

in the Montsinger research these effects were not eliminated—no attempt being made to keep the oil dry or acid-free (though the quantities present were probably small)—the life values stated might reasonably be considered as applicable to insulation used in practice.

Temperature and Life

The starting point of a utilisation investigation is the life expectancy required. Assuming this is thirty-five years, the continuous maximum or hot-spot insulation temperature permissible is 80 deg. C. Hence a transformer can be loaded so as to produce a hot-spot temperature of 80 deg. C. continuously (the daily life consumption being

TABLE 1.-LIFE OF OIL-IMMERSED INSULATION

Temperature, deg. C. 40 50 60 65 70 75 80 85 90 95 100 Years 82 70 58 52 46 40 35 30 23 16 10.5

minimise the total energy loss and maintenance charges. Nevertheless, more effective utilisation of existing capacity may result in greater economic efficiency. The several factors which must be taken into account require each case to be considered individually.

Rate of Deterioration

The permissible loading of a transformer depends largely on the life expectancy required. Normally a transformer will continue to give satisfactory service until the mechanical strength of the insulation deteriorates to such an extent that it cannot safely withstand the stresses likely to arise in service. Rate of deterioration is determined largely by the heating to which the insulation is subjected and increases with temperature.

In Table 1 above insulation life values estimated by V. M. Montsinger⁽¹⁾ are shown.

0 0078 per cent.). With variations of ambient temperature and load a representative daily load cycle must be obtained. The percentage of life used up can be computed by summating the percentage consumption at the various temperatures prevailing for known periods. From the Montsinger data in Table 1 the percentage life consumption can be calculated for different temperatures and the daily total found.

As an approximate example, with a transformer operating on a daily load cycle made up of four periods of six hours at 80, 70, 60 and 50 deg. C., about 0 0056 per cent. of its life would be used up daily. Thus there is a margin for increased loading to an extent which might, for instance, produce temperatures of 90, 80, 70 and 60 deg. C. equivalent to a daily life consumption of 0 0076 per cent.

Unless a winding temperature indicator

is fitted, hot-spot temperatures must be estimated from the correspondence between hottest-oil temperature and load over a daily cycle, which entails a knowledge of the fullload gradient between hot spot and hottest oil together with its variation with load. In general, the gradient of an ON transformer at any load is given by $L^{1.6}$ G, where L is the actual load expressed as a multiple of rated full load and G is the full-load gradient. The calculated gradient added to the corresponding oil temperature gives the hot-spot temperature.

Calculation Based on Weekly Figures

Where the number of distribution transformers is large, calculation of temperature is impracticable for checking the daily rate of ageing at sufficiently frequent intervals to ensure that changes in seasonal conditions (ambient-air temperature, maximum load and load factor) do not produce excessive temperatures. Nevertheless, although the data may be inadequate to permit utilisation of all unused capacity, some increased loadings will generally be practicable. For instance, if values of maximum hottest-oil temperatures and load are available weekly, together with approximate load factors, increasing loads can be checked by applying elementary principles.

Consider, for example, a transformer operating with a load factor of 50 per cent., and a peak load equal to rated capacity. Assuming that the loading is such as causes maximum daily loss and heating, *i.e.*, the transformer is fully loaded for twelve hours and is off load but excited for the other twelve hours, with constant ambient temperature, the daily life percentage for a given expectancy will be consumed at two different rates. During the no-load period the percentage is determined by the corresponding temperature—approximately that of the hottest-oil. The no-load temperature or a light-load temperature is usually obtainable.

At 50 deg. C. with 0.00196 per cent. of the life consumption in each no-load period, for a life of thirty-five years, the permissible daily percentage is 0.0078, so that there is a balance of 0.00548 per cent. available for use in each twelve-hour full-load period, the equivalent daily percentage being. 0.01168. By simple calculation the temperature permissible continuously during the full-load period is approximately 90 deg. C. This value is the limiting temperature for all transformers operating at or below the specified load factor and no-load temperature.

In practice, if the permissible temperature is not being attained, the load on each unit can be allowed to grow, or can be transferred, until such time as it is reached and, perhaps, occasionally exceeded. In the latter circumstance the effect on life should be negligible as there is likely to be an appreciable margin to allow for contingencies because the load is spread over the day and the maximum temperature exists for only a part of the time. The hot-spot temperature, the essential quantity required, is obtained by the sum of the hottest-oil temperature and $L^{1.6}G$.

Provided the reference temperature is not exceeded consistently and the load factor remains at 50 per cent. the peak-load value is unimportant, though considerations other than thermal capacity may set a limit to this. A substantial increase in load factor may necessitate a new reference temperature. For instance, an increase from 50 to 70 per cent. implies that the peak load is carried for seven-tenths of the day and no load for the remainder. In this case the life consumption in the no-load period is 0.001176 per cent. leaving a balance of 0.006624 per cent. for the full-load period. The equivalent daily percentage is 0.00947, which will be consumed with a continuous temperature of approximately 85 deg. C. Again, the actual value of the peak is not important provided the hottest-oil temperature plus L1.5G does not exceed 85 deg. C.

The temperature value employed for the calculation of the no-load life consumption may be, for convenience, the highest probable during a particular period and considered constant, but in practice it will vary with ambient temperature. If an indication of maximum ambient temperature is available, more effective utilisation of transformer capacity will be practicable by adjusting the no-load temperature values to accord with any wide seasonal and local differences in ambient temperatures. In some locations, the lower ambient temperatures during certain periods should permit higher hot-spot limiting temperatures and, therefore, greater peak loads—for a given load factor.

Overload Charts

Overloading of transformers when ambient temperatures are below the standard reference values is permitted by B.S.S. 171. If the ambient temperature indication satisfies the requirements of the Specification it can be used, together with load factor, to establish permissible loadings. B.S.S. 171 does not, however, include sufficient data to cover the range of operating conditions usually encountered, but the American Standards Association has compiled charts for this purpose.^(7, 8) These charts are based on factors investigated by V. M. Montsinger⁽⁹⁾ and others.

In general, for self-cooled transformers, 1 per cent. increase of rated capacity is allowed for each 1 deg. C. that the ambient air temperature is below 30 deg. C., and an additional 3 per cent. increase is allowed for each 10 per cent. that the daily load factor

1341

A RASER

26

275

「「「「「」」

1

きた

e leta

12.20

「日日」

122

11 52

四十四日

dI

ġŞ.

「「「「「「」」

100

is below 100 per cent. By applying these allowances effective utilisation can be achieved by-reference to ambient temperature indications which, for a given load factor and transformer thermal characteristics, will determine the permissible peak loads (as percentages of rated capacity). For this purpose Table 2 should be used, This refers particularly to self-cooled transformers conforming to United States standards, but it should also apply to most British ON units.

Given the hot-spot rise above ambient at rated capacity and the life-expectancy required, the column containing the 100 per cent. value must correspond with that 100 per cent. load factor, 30 deg. C. ambient the permissible peak is 95 per cent. of rated capacity and *pro rata* with other values.

With load factors less than 100 per cent. the hot-spot temperature will, of course, exceed the value permissible continuously due to overload peaks, but the daily ageing of the insulation will not be greater than when the basic temperature is maintained continuously — it may, in fact, be less. In practice, once a table has been compiled for a particular type of transformer, the actual hot-spot temperatures are not required. A periodical observation of peak load and maximum ambient temperature—with an occasional check on load factor—will indicate

TABLE 2.—PERMISSIBLE	PEAK LOADS OF	SELF-COOLED	FRANSFORMERS	(PERCENTAGE OF)	RATED CAPACITY)

Per cent. load factor	0	5	Ambie 10	nt Tempe 15	erature D 20	eg C. 25	30	35	40
50	145	140	135	130	125	120	115	110	105
60	142	137	132	127	122	117	112	107	102
70	139	134	129	124	119	114	109	104	99
80	136	131	126	121	116	111	106	101	96
90	133	128	123	118	113	108	103	98	93
100	130	125	120	115	110	105	100	95	90

ambient-temperature value which, added to the hot-spot rise, gives the continuous temperature permissible to achieve the required life-expectancy. Table 2 refers to any ON transformer operating under conditions which will permit the required lifeexpectancy to be realised provided the appropriate hot-spot temperature obtains when full load is carried continuously, the ambient temperature being 30 deg. C. For example, for a life-expectancy of thirty years the hot-spot temperature for continuous operation is 85 deg. C. so that if this is the appropriate value for Table 2 the transformer concerned has a hot-spot rise above ambient (30 deg. C.) of 55 deg. C.

To adjust the table to particular requirements, given the continuous hot-spot temperature appropriate to the required life-expectancy, the difference between this hot-spot temperature and the full-load hot-spot rise is the ambient temperature value corresponding to the column containing the 100 per cent. load datum. For example, in a table applicable to a 60 deg. rise transformer with a life-expectancy of thirty years, since the continuous hot-spot temperature permissible is 85 deg., the 100 per cent. load datum will correspond to a 25 deg. ambient.

Thus continuous full load is permitted only when the ambient temperature does not exceed 25 deg. C. This means, in effect, that the peak loads permissible with a 55 deg. rise transformer in a 30 deg. ambient are allowed with a 60 deg. rise unit in a 25 deg. ambient. In the latter case, the peak loads permissible with any combination of ambient temperature and load factor are 5 per cent. less than those shown in Table 2; e.g., at

adherence to the tabulated conditions relevant to the required life-expectancy. Since the ambient temperature is likely to be below the maximum for periods, an adequate margin for contingencies is assured.

With moderate overloads, probably the only disadvantage is an increased rate of oil deterioration. In addition to this, with heavy overloads consideration may have to be given to the effect on oil expansion, load capacity of bushings, leads and soldered joints and associated equipment, such as tap-changing gear, voltage regulators and circuit-breakers. Overloading, may increase running charges due to more maintenance and higher energy loss due to operation at lower efficiency. Short-time overloads may result in an increased all-day efficiency due to fewer units being required. Poor regulation due to overloading may cause a loss of revenue and reduced efficiency of the apparatus supplied.

The extent of the greater utilisation permissible will depend on the past history of the unit concerned and the manufacturer's opinion regarding the durability of the insulation. The life of the transformer will depend ultimately on what percentage of the original mechanical strength of the insulation can be lost with safety. Unfortunately this cannot yet be stated accurately, but if precise information were available, transformer capacity utilisation could be effected scientifically. Recent investigations show that, while the first 50 per cent. of the mechanical life of cellulose insulation is lost at a comparatively rapid rate at the higher temperatures, thereafter the rate diminishes quickly. F. M. Clark showed⁽³⁾ (Continued at foot of next page)

NEW BOOKS REVIEWED

Plastics-Radio-Wiring

Plastics for Production. By Paul I. Smith. (180 pp.; illus.) Chapman & Hall, Ltd., 11, Henrietta Street, London, W.C.2. Price 12s. 6d.

Mr. Smith has started his book well, with an excellent well-balanced preface explaining what he endeavours to achieve. There is an interesting discussion of the possibilities for employment offered by plastics. It is noticeable that he has not included electrical engineering among the large potential employment channels in relation to plastics. It almost certainly is one of the chief employers of plastics technicians at present. His good intentions are to some extent thwarted by the intensive condensation. The book is far too small to allow for the satisfactory handling of such an enormous subject.

Mr. Smith has considered plastics from the functional point of view. He does not bestow unqualified praise on the materials, being care-ful to point out their limitations. He does not suggest that they will answer every problem. He has tried to assess objectively their performance in various conditions. In his first chapter he analyses the qualities involved in the selection of a plastic for a particular purpose.

He summarises the range of plastics very accinctly and rather too briefly. Naturally his succinctly and rather too briefly. consideration of the use of plastics for insulation was of the greatest interest to the reviewer. The electrical industry is one of the greatest outlets for plastics of every description. It is very difficult to do justice to such an enormous subject in the small space which Mr. Smith

Economic Transformer Operation

(Continued from preceding page)

that the tensile strength of manila paper in a sealed container under oil in contact with oxygen fell from 18×10^3 to 8×10^3 lb. in fifty weeks at 100 deg. C. and then appeared to diminish at a very slow rate.

Bibliography

(1) V. M. Montsinger, "Loading Transformers by Temperature," Trans. A.I.E.E. 1930, Vol. 49. (2) V. M. Montsinger, "Emergency Overload-ing of Air-Cooled Oil-Immersed Transformers by Hot-Spot Temperatures," Trans. A.I.E.E.

 (3) F. M. Clark, "Factors Affecting the Mechanical Deterioration of Cellulose Insulation,'

on," Trans. A.I.E.E. 1942, Vol. 61. M. A. Pollitt, "Mineral Oils for Trans-prmers and Switchgear," Journal, I.E.E. A. A. Politit, Mineral Olis for Transformers and Switchgear," Journal, I.E.E.
 Part II, Feb., 1943.
 ⁽⁵⁾ C. F. Hill, "Temperature Limits Set by Oil and Cellulose Insulation," Trans. A.I.E.E.

Off and Cellulose Insulation, Trans. A.I.E.E. 1939, Vol. 58.
(6) F. J. Vogel and T. K. Sloat, "Emergency Overloads for Oil-Insulated Transformers," Trans. A.I.E.E. 1942, Vol. 61.
(7) E. T. Norris, "Loading of Transformers," *Electrical Review*, February 5th, 1943.
(8) "Guides for Overloading," Trans. A.I.E.E., Vol. 61.

Vol. 61.

⁽⁹⁾ V. M. Montsinger, "Effect of Load Factor on Operation of Power Transformers by Temperature," Trans. A.I.E.E. 1940, Vol. 59.

could devote. The same applies to his sections on wire covering, the deposition of metals on plastics materials and the effects of temperature on plastics.

But in spite of its defects the book is a very useful addition to the plastics library. It is written for the practical technical man, steering clear of the scientific implications. It is full of the salient facts relating to plastics, brought together in a convenient form.—H.B.

Phermionic Valve Circuits. By Emrys Williams, Ph.D., B.Eng., A.M.I.E.E. Second edition. (Pp. 208; figs. 127.) Sir Isaac Pitman & Sons, Ltd., 39, Parker Street, London, W.C.2. Price 12s. 6d. The appearance of this second edition so soon after the first (published in 1942) is explained by the author as "having been bastened by the extensive consumption of the

hastened by the extensive consumption of the first edition by the enemy Luftwaffe." A good deal of new material has, however, been added including an original general theorem on valve oscillators and sections on frequency modula-tion, gas-filled valves, time-bases, the Kipp relay, the transitron, the cathode follower, earthing and screening, and valve voltmeters.

Although open to the criticism of incompleteness, the author does not attempt the impossible and try to include all valve circuits, but contents himself with covering the main types of circuits in such a way that the student should be in a position to understand, or even foresee, further developments.

First Course for Electricians. By T. C. Gilbert, A.M.I.E.E. (Pp. 62; figs. 36) Morgan, Laird & Co., Ltd., 54, Bloomsbury Street, Bedford Square, W.C.1. Price 3s. 6d. In so few pages it is surprising how much

information the author has been able to impart. This he has done in such a lucid fashion that the reader can absorb it with the minimum of effort and is put in the right frame of mind for continuing investigations on the subject. Originally appearing in the form of twelve articles, the book is intended particularly for men and women taking up electrical work in the contracting business, factories and the Forces. After a preliminary simple explanation of current, voltage, resistance and power, it passes on to series and parallel connections, cables, methods of wiring, safety precautions. fusing, earthing, switching and lighting, and bell circuits. Special attention has been paid to wartime practice and substitutes. Details are also given of the leading electrical associations.

Electric Wiring. By W. S. A.M.I.E.E., M.I.Mar.E. By W. S. Ibbetson, B.Sc., A.M.I.E.E., M.I.Mar.E. Eighth edition. (Pp. 264; figs. 136.) E. & F. N. Spon, Ltd., 57. Haymarket, London, S.W.I. Price 10s. In this new edition, the third issued during

the war, various additions and alterations have been made to bring the matter into conformity with certain recent B.S.S. and the 1943 alterations and additions to the eleventh edition of the I.E.F. Regulations. This has been done without altering the original numbering of the pages, an achievement of particular importance in view of the widespread use of the book for educational purposes.—W.R.C. A B.C.

Harry H

山大学にしたいのないの

「日本」

2

Post-War Installations

Study Committee's Report

THE report of the Committee set up under L the ægis of the Institution of Electrical Engineers (with Mr. J. R. Beard as its chairman) has been issued by the Ministry of Works as No. 11 in its series of Post-War Building Studies. (Stationery Office, 1s. 6d. net.) The terms of reference covered a review of existing practice concerning installations in buildings, including household appliances and telecommunications, and the making of recommendations for post-war practice. Different sections of the Report of 96 pages deal with houses and flats (with particular attention to the smaller type), multi-occupier buildings (including ownership and control of service cables), schools, hospitals and farm buildings. There is a useful bibliography, four new terms for the Standard Glossary and an eight-page index.

The first and longest section of the Report deals with small houses. Service arrangements, it is urged, should provide at the outset for the full use of electricity for all purposes. For underground services, the recommended standard is 0.0225 sq. in. twin paper-insulated lead-sheathed unarmoured cabled, made to BS 480-1942, and laid at not less than 18 in. below gardens and 12 in. below paths. Overhead services should be of the same crosssection, single or twin, rubber (or p.v.c.) insulated, taped, braided and weather-resisting. Under-eave construction is suitable for semi-detached or terrace houses and wayleave procedure should be amended where necessary to permit of its adoption.

Earthing Methods

Internal installations should be earthed to the water main, to the sheath of the service cable, to electrodes (subject to periodic inspections) or, where these methods are impracticable, through an earth-leakage circuitbreaker or multiple earthing. A provisional standard consumer's control unit for incorporating any existing designs of cable sealing box, main switch, four single-pole fuseways and meter is described; it measures 34 in. high by $13\frac{1}{2}$ in. wide by 71 in. deep, but the development of a more compact unit is urged. In the meantime the type of fitting which serves as cable sealing and main supply fuse box should be used. Existing designs of consumer's control equipment should be housed in a box with a door for building into a wall.

In small dwellings lighting fittings should be supplied complete with lamps. Wiring or conduit should be run to the cooker position in each kitchen. For water heating, a new multiple 20-gal unit is advocated. Refrigerators should be of 4 cu. ft. capacity.

Early consideration should be given to the thermal insulation of buildings. Recesses for electric fires and convectors should be provided during building and there should be accommodation in the kitchen for washboiler, washing machine and drying cupboard.

Socket-outlets should be installed, as a minimum, as follows : Living rooms, 3; double bedrooms, 3; single bedrooms, 2 kitchen, 3, in addition to connections for cooker and refrigerator; water heater, 1 laundering, as required. Lighting switches should be 4 ft. 6 in. above floor level. Socket outlets should be not less than 5 in. but preferably 9 in. above floor level, except in kitchens and washhouses where the height should be 4 ft. 6 in.



Mr. J. R. Beard

Three circuits should be provided : for lighting, for cooking and for socket outlets. The last should be supplied from a ring circuit fused for 30 A at the consumer's supply control or, alternatively, a circuit fused for 15 A could be run to each principal room. Enclosed cartridge fuses (Category 3, B.S.88) should supersede rewirable porcelain fuses.

A new flush- or semi-recessed type of 3-kW socket outlet and easily withdrawable fused plug should be adopted as the " all purpose ' domestic standard with the live contacts of the socket protected ; incorrect insertion of one pin of the plug into the live contact tube of the socket, thus exposing a live pin of the plug, should be made impossible. On AC circuits a separate switch is considered unnecessary. Socket terminals should accommodate a 7/.029 in cable looped in and out and also a spur connection if required ; solid pins should not be slotted. The plug should accommodate either a 13-A or a 3-A interchangeable and readily identified fuse and should take either 23/0076 or 70/0076 circular flexible cords.

For wiring, v.i.r. or p.v.c. cable run in screwed or lug-grip jointed light-gauge welded or brazed-steel conduit or else a continuous wall duct at skirting level is recommended. Central heating, if adopted, should furnish background heat only, small radiant electric fires being used to give higher local temperatures.

For larger houses, a consumer's control unit with eight fuse ways or two separate units (one containing the undertaking's cable entry and main fuse and the other centrally mounted fuses) are proposed. The use of quick-acting circuit-breakers instead of a main switch and possibly instead of circuit fuses should be considered.

In multi-occupied buildings the undertaking should own, control and maintain the service cables, which it would provide at its own cost; retailing by the landlord of supply purchased in bulk is to be discouraged. A three-phase four-wire AC service would be taken from the 400-230-V mains or from a transformer installed in the building. Rising mains should be run in accessible ducts (not lift shafts) at least 18 in. by 6 in., one duct to supply each floor or, in larger buildings, one duct measuring 36 in. by 9 in. perhaps for each 5,000 ft. of ground floor area ; bare conductors are recommended. Horizontal mains may be run in floor ducts or hollow ceilings in corridors. For flats, a vertical duct should enter a sealed distribution board on every storey, provided with single-pole fuses for each service, conduits being run to the consumer's control.

Farm Requirements

While installations in urban buildings possess many major features in common, there are many special features in farm buildings to be taken into account. In order to reduce power wiring costs appliances would generally be grouped together. Power requirements on a dairy farm would be : Milking machine, $\frac{1}{2}$ to 1 HP; steriliser, 4 to 9 kW for 20 to 40 cows; water heater, 1 to 3 kW; cooler, $\frac{3}{4}$ to 2 HP; water-pump, $\frac{1}{2}$ to

Thermal

N analysis of the properties and processes which control the flow of heat in continuous and intermittent heating operations was given by Dr. H. R. FEHLING in a paper he presented before the Institute of Fuel on October 4th. Every heat insulating material, he said, had two components, one solid and the other gaseous. Low thermal conductivity was due to the air or gas enclosed in pores and voids. This was not accounted for only by the conductivity of air being about one-tenth of that of the poorest solid conductor; an essential factor was the bottleneck produced by its being the highest resistance in a series.

A most important characteristic was the relative proportions of air and solids in the structure of a material. There was a broad relationship between the conductivity and bulk density of widely differing materials; for insulators, variations from the average did not exceed \pm 30 per cent. On the other hand heat capacity per unit volume, which was roughly 1,000 times greater for solids than for gases, was determined by the solid components and was proportional to bulk density, the deviation from the average being small.

The author suggested that the marked difference in variation with bulk density between conductivity and capacity had hitherto been 1 HP. In addition there may be : Hoist, $\frac{1}{2}$ to 1 HP ; mixing machine, 5 HP ; grinding mill (new type), 3 HP ; cake breaker, 2 HP. For mixed farming, the following would also be needed : Chaff and root cutting and cake breaking, 10 HP ; threshing, sawing and crop drying, 10 to 20 HP. On poultry farms from $\frac{1}{2}$ to 1 W will be required per egg incubated, $1\frac{1}{2}$ to 2 W per chick reared and 2 or 3 W per laying bird for light and warming water.

Electrical accessories would preferably be of the insulated type and more robust than is usual for domestic purposes. For wiring a general purpose t.r.s. cable, protected with cotton braid, vulcanised and compounded over and containing an earth conductor, is recommended. A high degree of mechanical protection is needed in a limited number of situations only, when insulating conduit may be used. Metal conduit is not recommended since for safety it would require to be separately earthed and, unless galvanised, would be liable to corrosion. In damp or corrosive conditions p.v.c. cable may be more suitable than t.r.s. cable.

Wiring should be installed well out of normal reach. In dairies cleat wiring may be used, as it can be cleaned by hosing down, with mechanical protection for down-drops to sockets and for leads to motor terminals. Appliance frames should invariably be earthed. The service line (usually overhead) would preferably terminate at the centre of the heavier loads. For supplying near-by outbuildings, t.r.s. or p.v.c. cable may be slung from a catenary. For more distant loads a light open line should be used.

Insulation

overlooked, though it was important in regard to intermittent heat flow. The diffusivity, or the ratio of conductivity and capacity, had a minimum value for a bulk density of 0.7 to 0.9 (about 50 lb. per cu. ft.). An insulating layer not only upset temperature gradients throughout the wall but also the thermal resistance at the surfaces. The possibility of reducing radiation losses by using surfaces of low emissivity was limited because the increase in surface temperature increased convection-loss. In steam transmission there was a secondary power loss in the engine, due to deterioration in steam quality, which could be of the same order as the heat loss.

With intermittent operation, heat capacity and duration of the heating cycle were equally important. For heating from cold, heat storage was the dominant factor and hot-face insulation the only means of preventing wall losses. For re-heating operations storage and surface losses might be balanced in certain cases. Heat stored in insulating bricks was only a fraction of that absorbed by ordinary refractory walls in the same time—the reduction being more than that owing to reduction in weight because the product of conductivity and capacity was the controlling factor. Insulating bricks in the hot face shortened heating-up time, lessening storage loss.

「日日日

(NOIN

414

-

20

-

200

2 Carto

120

1

EA

No. 2

the second

21

-

-

H H H H H H

CORRESPONDENCE

Letters should bear the writers' names and addresses, not necessarily for publication. Responsibility cannot be accepted for correspondents' opinions.

Domestic Plugs and Sockets

WAS interested in Mr. James Scott's letter in your issue of October 6th and heartily endorse his view that every plug circuit, regardless of purpose, should be wired with at least 7/-029 cable. The City of Edinburgh Electricity Department has recently made a similar recommendation to electrical contractors as follows :--

"In domestic premises, in view of the possibility of the introduction of, and to facilitate changing over later to, a new standard universal 13-A 3-pin socket outlet and plug to cover the functions of the existing three sizes of standard socket and plug, it is recommended that nothing less than 7 029 in. (0045 sq. in.) conductors be used for wiring to sockets no matter which size of socket may be installed initially. In the case of a room not exceeding 200 sq. ft. in area we propose that there should be no limit to the number of sockets (possibly in addition to a fixed electric fire) in the one room which may be connected to one final sub-circuit of this size. For rooms larger than 200 sq. ft. 7/-036 in. (-007 sq. in.) conductors (or 7/-029 in. conductors ringed, *i.e.*, fed at both ends) should be used if one fixed fire and one socket or more than one socket is connected to a single sub-circuit. Furthermore, all the sockets and fixed fires in a maximum of four rooms with an aggregate floor area of not more than 600 sq. ft. may be connected to a single sub-circuit provided that 7/036 in. conductors are used (or 7/-029 in. conductors These recommendations are to be ringed). regarded as additional exemptions under Clauses 201B and 202D but Clauses 202A and 116A shall still apply, which means that not more than 15-A fuses shall be fitted on for hole that 13-4 tasks and 30-A fuses on 7/029 in. sub-circuits and 30-A fuses on 7/036 in. (or 7/029 in. ringed on one fuse only) sub-circuits and that flexible cables with smaller than 70/0076 in. (-003 sq. in.) conductors must be fitted with fused plugs."

This recommendation goes even further than Mr. Scott's suggestions. The clause numbers refer to the I.E.E. Wiring Rules. *Edinburgh.* P. d'E. STOWELL.

THE difficulty of inserting three pins into three socket holes was mentioned by Mr. A. N. Bott in your issue of September 1st. This is true of the more usual brown socket but it is much easier to do so in the case of a white or cream socket, in which the three socket holes are more readily visible. If it is considered essential that sockets should match the skirting-board, shutter-type sockets having shutters of contrasting colour could be used.

A further improvement would be the provision of a rectangular finger grip on the plug cover, in the position occupied by the knob of the handshield type. When picked up by this grip between the thumb and forefinger the plug would be automatically rotated into the correct position for insertion in the socket. The grip would also be of assistance in withdrawing the plug and the additional space inside it could be utilised for a more efficient cord-grip than is usually provided.

The foregoing suggestions apply equally to all three-pin plugs and sockets, but I am convinced that the existing **B.S.** types will meet all post-war requirements. While the "tree" system may still be preferred for large houses. commercial, and industrial installations, a "fused room" scheme similar to that suggested by Mr. Newton Davey in the same issue would be adequate in the smaller houses at minimum cost. A self-contained unit could be produced incorporating one 15-A three-pin switch-socket, two 5-A three-pin shuttered sockets, and a cartridge fuse. One of these units would be installed in each room and would feed four or five additional 5-A three-pin shuttered sockets by means of a ring main passing right round the room.

The scheme would make for greater safety by limiting the use of electric fires to one position in the room while providing full flexibility for other portable appliances.

Southampton.

B. J. FRANCIS.

IN the recent controversy about ring mains and plugs and sockets for dwelling houses the majority of the suggestions seem to have emanated from advocates of cheap installations. The introduction of ring mains and one size of plug and socket would result in all kinds of abuses. The handyman or amateur electrician could not resist the temptation to tap the ring main in any old way and while the use of fused plugs in certain circumstances is quite good, that arrangement would certainly not be satisfactory if it was decided to use one size of plug only. In all probability no spare cartridges of the correct size would be available and the handyman would simply stick in anything available.

One correspondent suggests that nothing less than a 15-A plug should be used and then strangely enough he goes on to condemn chain stores and such places who sell a lot of electrical junk. Certain "installers" would never dream of connecting, say, two 5-HP motors to one pair of fuses but have no hesitation in connecting two or three 8/12-A radiators to one circuit.

Twenty years ago we had plugs of all sizes and shapes which could only be regarded as a nuisance until the British standards were adopted and as these standards have justified themselves, why not leave well alone? In these remarks I do not intend to deal with rules and regulations but feel that all radiators of 8/12 A should be connected to separate circuits on a distribution fuse-board and wherever possible I adopt that method.

So far as 5-A outlets are concerned, these should only be regarded as lighting or possibly iron points and therefore half a dozen of them can be connected to one circuit with safety. The 2-A outlet cannot be ignored; it is a very useful accessory for radio or bell circuits and, when the correct size of plugs are fitted on the ends of flexibles, it is impossible to plug "the wrong thing in the wrong place." Both 5-A and 15-A outlets should be fitted with interlocked switches and, although some of these have proved unsatisfactory, there are good ones on the market.

I hope the present arrangement of standards will remain and if someone can suggest a method of cheapening installation costs without sacrificing efficiency and safety, I shall support it. I am, however, definitely against ring mains and one size of plug for dwelling houses.

Glasgow.

ALEX. MILNE.

An Industrial Aspect

N regard to standardisation of plugs and sockets one very important industrial application has not received much attention, and it may well be that in the future the same problem will arise with domestic apparatus, *i.e.*, the use of plugs and sockets for lowvoltage portable apparatus.

voltage portable apparatus. In a large steel works there may be two supplies, viz., three-phase 400-V four-wire AC and 220-V, two-wire DC. In such a works there will be a number of portable tools, handlamps, soldering irons and the like, the majority of the universal type. It is most desirable that all portable tools should operate at either 25 or 50 V single-phase. Where there is an extensive distribution system an endeavour should be made to eliminate all 230-V and 220-V plugs and sockets. The risk of plugging in 25- or 50-V apparatus on to single-phase, 230-V or DC 220-V circuits will thus be removed. This course is sometimes very difficult and in certain cases impossible, and with such a mixed system it becomes essential to have available two- or three-pin 25-V or 50-V plugs and sockets which are quite non-standard, even perhaps to have square pins on the plugs and square holes in the sockets. It is quite inadequate to have two-pin or three-pin plugs with pins of the standard sizes but different centres for the two sets of voltage conditions.

The time has arrived when the question of plugs and sockets for low-voltage industrial as well as domestic portable apparatus should be given careful consideration, and regulations issued to ensure complete safety.

Sheffield. R. BENNETT, Chief Electrical Engineer, Thos. Firth & John Brown, Ltd.

Phase Indicator

THE correspondence columns of your issue of September 22nd, contain a reference to a phase indicator. This is a very useful instrument, but it has its limitations in phasing out an AC system for the purpose of paralleling. It will indicate the phases of a supply to give a clockwise or anti-clockwise rotation for a motor, regardless of colours, letters or numbers marked on cables.

There are no doubt instances of jointers connecting up the wrong colours and it is possible for a number of combinations of colours, etc., to give the same rotation. A voltmeter can be used to indicate the correct phases for paralleling, regardless of colours, letters or numbers on the cables and at the same time indicate whether the pressures are correct. T. R. EVANS,

Rhondda.

Electrical Engineer.

Post-War Houses

WITH reference to the Ministry of Works' sample houses erected at Northolt, I have only the information provided in your issue of October 6th, and from the photograph there it would appear a compromise structure in more ways than one.

The view of the front which you illustrate appears to have an abnormal window space for the size of the house. While this may be very pleasant with a southern aspect in the southern counties, they would certainly be chilly rooms in the North of England with a northern or easterly aspect. We have heard a great deal on the scientific design of houses with regard to the use of fuel, but it would appear that in these particular houses this has been sacrificed to cheap construction.

It would be interesting to have the views of the heating engineer who may have had access to the plans of the Ministry's houses; or has the Ministry other designs which take care of this point?

Ruislip.

R. N. PEGG.

Permanent Magnets

AY I thank Messrs. Hoselitz and Edwards for their criticism of my letter which they gave in your issue of October 6th. It has given information which all will be glad to have. Admitting that my idea was wrong, it is still true that the experiment suggested would have led to useful results and it would have shown that there was benefit in magnetising the metal while it was undergoing heat treatment.

Cases are common where the idea behind an experiment is wrong but the results have been good. The Michelson-Morley experiment, to find the speed with which the earth moved through the ether, was a failure but it led to the relativity theory. Faraday tried the effect of placing a magnet in a coil, which he 60

15

Ы

161

2

55

20

10

10

P

35

125

21

3

-

z

1

x.

-

1

2

di j

1

9

e

then connected to a galvanometer without result, as S.P. Thompson has related, but it led eventually to something worth while. As a student the late Dr. Thornton tried an experiment which failed and he told Lodge that it was absurd, but Lodge replied "An experiment is never absurd."

I think it was Clerk Maxwell who encouraged experiments because, he said, if the student did not find what he was looking for he might find something else. My letter may encourage some student to make experiments on his own from which he will learn something worth knowing. I heard from a chemist who had worked with Perkin that Perkin said that he discovered his aniline dyes by doing an experiment which seemed to be absurd but that also was worth while.

Tynemouth. C. TURNBULL.

Freedom of Choice

R. D. MURPHY, in his letter in your issue of October 13th, is not using the correct arguments for what he advocates. The general view of an engineer is that the resources of the country, in this case the energy in coal, should be used with the utmost efficiency so that there will be a sufficiency of exportable margin to pay for future imports. The cost and comfort to the user are of secondary importance, and can be adjusted to conform with the social policy of minimising the number of miners required to obtain the desired amount of coal.

The first deduction is that soft coal in the domestic hearth should be entirely abolished. This is conducive to reduction of costs in decorations and cleaning, diminution of the pollution in the atmosphere and a marked reduction in the cost of building construction because of the elimination of chimneys; also the ventilation can be more accurately designed and the absurd situation of heating air *after* it leaves a room completely eliminated.

Electric power, being very easily transmitted over great distances, demands also that the coal be efficiently used in the power station boilers. This means that the surplus heat which is available, because of the use of turbines, must be diverted and supplied to local factories and domestic premises. Experience abroad shows that this can be done economically and it is being seriously considered by Coventry, Bristol and Luton in this country.

An interim proposal before the traditional fireplaces are removed from use is that coke be substituted as a hard fuel. This immediately necessitates a supply of gas for its ignition. It can be shown that if a quantity of coke is required there is a minimum quantity of gas to be disposed of economically. A very large increase in the demand for coke can be made economical only if the consequent increases of gas are disposed of economically. The actual usage of gas is increasing very slowly, whereas electrical energy is being taken year by year at a rapidly increasing rate. It therefore follows that the electrical industry has nothing to lose in agreeing to a more logical use of products of coal than is advocated at the moment. The one way in which the surplus gas should be used is in water heating and central heating in domestic premises. The use of electricity for such "low-grade" utilisation should be deprecated.

The question of regulation also arises, in that the superior regulation of electricity supply makes it more suitable for those highgrade applications in which a constant voltage is essential, whereas the lower grade of regulation which is economically possible with gas makes the use of gas suitable only in such applications as can be thermostatically controlled.

Engineers should not hesitate to use their knowledge in advocating wider issues rather than in supporting sectional interests which they may individually be considered entitled to support.

London, N.W.8. L. E. C. HUGHES.

[CORRECTION.—In Mr. D. H. S. Sanderson's letter in our last issue the word "latter" in the fifth line should have been "former," *i.e.*, it is washboilers with immersion heaters which have to have sumps. This was obvious from the subsequent wording.—*Editors, Electrical Review.*]

Bonding and Earthing

N a lecture illustrated by lantern slides which he delivered to the Coventry Electric Club on October 3rd, Mr. P. W. CAVE dealt with bonding and earthing systems in relation to the generation or use of electricity and to protection against damage by lightning.

Among the types of earthing electrode described was the recently introduced sectional earth rod for deep driving. The effect of site conditions on the choice of a particular type of electrode was discussed and the methods of carrying out the necessary electrical survey before designing and installing an electrode system were described. Examples from practice given included the time taken to drive earth rods into soil of widely differing character to depths varying from 8 to 40 ft.

Advice was given as to the correct layout of bonding systems and formulæ were developed for the current carrying capacity of bonds under fault conditions of short duration.

E.A.W. London Branch

THE autumn programme of the London Branch of the Electrical Association for Women will be opened next Tuesday, by a talk by Miss Caroline Haslett, director of the E.A.W., on her second visit to Canada and the United States. The White Paper on Social Insurance, "Wool and the British Empire," and the Tennessee Valley Authority will form the topics for later meetings.

Institute of Fuel

Proceedings at Annual Function

THE principal guest at the annual luncheon of the Institute of Fuel, at the Connaught Rooms, London, W.C.2, on October 12th, was LORD WOOLTON, C.H., Minister of Reconstruction, who proposed the toast of the Institute. Lord Woolton said that Great Britain was never more in need of enlightenment in fuel utilisation than at the present day. There was a time when coal was cheap and plentiful and the griminess of our cities testified to the wasteful way in which we had used our greatest raw material. Nobody then dreamed that we should be so short of coal as we were to-day.

In wartime our people were willing to endure much from the various Ministries which controlled their lives but in the matter of coal we should not be any better off in peacetime unless we bestirred ourselves. Industry would have to continue to operate at as great a rate after the war; would it be able to get all the coal which it would need? Then there was the export trade; we should need to export much more if we were to be able to purchase what we needed from foreign countries.

Economic reconstruction plans depended for their success upon a healthy, competent industry; and industry and the economic future depended largely upon the efficient use of fuel, which meant research. We needed cheap coal but we also wanted cheaper means of using coal. Cheap coal did not mean lower wages for the miners but the scientific mining of coal combining maximum output with high wages.

The Ministry of Fuel and Power was investigating this matter and looking into the organisation of the gas and electricity industries. Its Fuel Efficiency Committee was doing invaluable work in making industry "fuel conscious." All these efforts should produce results: the matter was one of great urgency. In the past we had been slow to make use of the knowledge of our scientists and this would have to be remedied.

In his response the president, DR. E. W. SMITH, C.B.E., spoke of the great days of Manchester University when he and Lord Woolton were fellow students there. He mentioned that Lord Woolton was to be Chancellor of the University and referred to the many eminent fuel technologists which Manchester had produced.

LT.-COL. W. A. BRISTOW, in proposing the health of the guests, said that the development of power achieved during the war would have been considered impossible in 1935. The policy of the Institute had always been to co-operate with all branches of the light, heat and power industry without political or sectional bias. He referred especially to the presence, among many other distinguished guests, of representatives of the Ministry of Fuel and Power and of Mr. Harold Hobson, chairman of the C.E.B.

In seconding the toast, MR. P. C. POPE (secretary) said that before the end of the year the membership of the Institute would have reached 2,000. Industrial organisations had been asked to subscribe to a five-year guarantee fund. The Institution came between the research organisations and industry. The speaker asked if there were not an appropriate Government Department to give assistance to the Institute similar to that given to research associations and thus enable it to make a more substantial contribution to the fuel economy campaign. The toast was replied to by MR. R. W. FOOT. chairman of the Mining Association of Great Britain.

Presidential Address

After the luncheon Dr. Smith delivered his presidential address. In the course of this he spoke of three recent developments within the Institute. They were the reorganisation of the seven sections and their representation on the Council; the raising of the standard of candidates for admission; and the establishment of a \pm 5,000 guarantee fund, half of which had already been promised. He went on to say that there had been very real and almost revolutionary advances in the technical side of the gas industry and reviewed these at length.

Melchett Lecture

This year's Melchett Medallist is Dr. J. G. King whose Melchett Lecture followed Dr. Smith's address. The title of the lecture was "The Pattern of Fuel Research" and it surveyed developments in this field, mainly during the past twenty-five years. Much attention was devoted to the hydrogenation of coal and coal products and the speaker then passed to advances in the gasification of coal for the production of town gas and to the considerations governing further research on coal structure and properties.

Spanish Supply Restrictions

ADRID will be without electricity in the daytime for three days a week. The restriction is due to persistent drought in Spain which has considerably reduced power production. So that the cut shall not affect the entire population at the same time the city has been divided into areas in which the supply will be cut off on three different days. Towns and villages in the Madrid province will also be affected.—Reuter.

344

100

A STATE OF

2/10

10.00

10. 20

100 1

in a

The second

2 200

in su

attac

N.Fai

the se

123

22

t tim

山田山

Ler h

217

12

"zil

20

1

el

PERSONAL and SOCIAL

News of Men and Women of the Industry

THE staff of Barnstaple Corporation Electricity Department have presented an inscribed clock to Mr. F. C. Allen who has retired from the post of chief assistant engineer after being connected with the undertaking since 1902. Mr. Allen went to Barnstaple when the Corporation electricity undertaking was established, and before that was on the staff of the Lynton and Lynmouth undertaking.

Mr. Ernest Stroud, who has been elected president of the Illuminating Engineering Society for 1944-45, has



Society for 1944-45, has for many years been chief engineer of Holophane, Ltd., and for the last five years general sales manager. He has served on various committees of the British Standards Institution, including street lighting, portable photometers, light distribution, lighting fittings, and A.R.P. street and factory lighting. He is an associate member of the Association of Public Lighting Engineers, and chairman

Mr. Ernest Stroud

Engineers, and chairman of the Street Lighting Section of the Electric Light Fittings Association. He acted as treasurer of the 1.E.S. from 1936 to 1938.

The Hon. J. K. Weir has been appointed managing director of G. & J. Weir, Ltd. Mr. A. H. Laidlaw becomes director in charge of sales and contracts, while Mr. John Davidson has been appointed secretary in place of Mr. J. D. Imrie, who has resigned that office for health reasons after forty-five years' service. Mr. Imrie's services are being retained.

Hull Corporation Committee has presented a long-service certificate to Mr. D. Bellamy, the general manager, on the completion of twentyfive years' service.

The A.E.I. News announces the election to the board of the Cosmos Manufacturing Co., Ltd., of Messrs. A. S. Kettle, J. W. Ridgeway and E. Y. Robinson.

Mr. Kettle has been manager of the Cosmos company's works since 1941. He served his apprenticeship with the Bournemough & Poole Electricity Supply Co., Ltd., in its Bourne Valley and Christchurch power stations and in 1911 joined the British Thomson-Houston Co., Ltd., with whom he took a two-year testers' course. Afterwards he was for two years in charge of the DC testing section and was then appointed chief of the department responsible for the testing of all products made at the Rugby works. In 1928 he was appointed service engineer to the B.T.H. company, in which capacity he held a watching brief on the board's behalf in any complaints in respect of products, and he carried out special investigations on behalf of the directors.

Mr. Ridgeway, after a metallurgical training, joined Metro-Vick Supplies in 1924, and was attached to the radio department at Sheffield. In 1928 he was appointed assistant to the then chief engineer of Metropolitan-Vickers radio department and in 1929, on the amalgamation of the radio divisions of the B.T.H. Co., Metropolitan-Vickers and Edison Swan, he was appointed assistant manager of the radio division of Edison Swan and he became manager in 1940. He has been chairman of the British Radio Valve Manufacturers' Association for the past three years. Recently he was appointed industrial adviser on radio valves to the Radio Production Executive of the Ministry of Aircraft Production.

Mr. Robinson joined the research department of Metropolitan-Vickers Electrical Co., Ltd., in 1922, to establish a valve section having previously been a college apprentice at the Trafford Park works. For some time he worked on the development of large power valves, but later his interests were mainly directed to radio receiving valves. Arising out of this work a radio valve production department was established in 1925. In 1927 this manufacture and development were transferred to the Cosmos Manufacturing Co., with Mr. Robinson as chief engineer of the valve department. He was appointed chief engineer of the company in 1929, when its activities were directed solely to radio valves.

Engineer Vice-Admiral Sir George Preece, K.C.B., has accepted nomination by the Council of the Institute of Marine Engineers for reelection as president for the 1945-46 session.

Mr. J. W. Rodger, M.I.E.E., director and general manager of Bruce Peebles & Co., Ltd., has been appointed managing director of the company. Mr. Rodger

company. Mr. Rodger who was formerly the company's chief engineer became general manager at the beginning of last year. He joined Bruce Peebles in 1924 for the purpose of inaugurating and developing the production of power transformers. He built up the new department in an extensive factory and later, as chief engineer, became responsible for all the company's design and manufacturing de-



Mr. J. W. Rodger

partments. He has travelled much in Europe and Canada to study practice and requirements. Before joining Bruce Peebles he had been with several leading electrical manufacturers including Ferranti, Ltd., and the Hackbridge Electric Construction Co., Ltd.

Mr. R. M. S. Morrison has been appointed sales manager of Scottish Plastics, Ltd.

The two Brush Scholarships for 1944 have been awarded to Messrs. Derek Davis (Staveley Grammar School) and John T. Hayden (City of London School). These scholarships are of the value of £75 per annum, tenable for four years, the first year in the works at Loughborough and the remaining three at any British university. After taking their degree, scholarship holders return to Loughborough for a final year of apprenticeship.

The Metrovick Dramatic Society run by the staff of the Metropolitan-Vickers Electrical Co. has become so active as to require a set of studios.

Final scene in " Quiet Wedding " presented by the Metrovick Dramatic Society

In spite of wartime difficulties it has recently Wedding " at four evening and one matinee performances and achieved notable success.

Mr. C. E. Luxton, manager of the electric tool division of the Consolidated Pneumatic Tool Co., Ltd., has been granted indefinite leave of absence in order that he may take up an appointment as Technical Adviser on Portable Electric Tools to the Director of Industrial Electrical Equipment, Machine Tool Control.

Mr. C. W. Allbut has been appointed to succeed the late Mr. A. R. Edwards as commercial manager and secretary of the Electric Lamp Manufacturers' Association in Australia. He has for many years been associated with the Australian General Electric Pty., Ltd.

Mr. G. H. Oldroyd, borough electrical engineer. Stockport, who was due to retire on November 25th, has been reappointed for a further period of six months at his present salary.

Mr. Julius A. Krug has been appointed acting chairman of the United States War Production Board in the place of Mr. Charles E. Wilson who, as previously reported, has decided to return to the General Electric Co. of which he was president before joining the W.P.B.

Paisley Association of Electrical Engineers opened its new session on October 9th when Mr. Thomas Scott delivered his presidential address which dealt with "Modern Factory Installations.'

The Association of Supervising Electrical Engineers is inviting applications for the post of organising secretary at a commencing salary of £500 per annum.

Obituary

2nd Lieut. J. M. Dalton.-We extend our sympathy to Sir John Dalton, manager and secretary of the County of London Electric Supply Co., Ltd., and Regional Controller for London and the South-East District, Ministry of Fuel and Power, and to Lady Dalton for the loss of their only son, 2nd Lieut. John Michael Dalton, R.E.,

Parachute Regiment, aged twenty, who died as the result of an accident on October 7th.

Mr. E. W. Robey.—We regret to record the death of Mr. E. W. Robey, who was for many years on the staff of the Underfeed Stoker Co., Ltd., and subse-quently of International

Combustion, Ltd. Mr. Robey was responsible for the introduction and development of many new appliances connected with the com-bustion and boilermaking industries.

Mr. A. A. Cawkwell, who was also for some years associated with International Combustion. Ltd., died recently. He retired in 1936, after a lifetime spent in the boiler-manual field. In his earlier with the years he was with the Stirling Boiler Co., Ltd.,

which he left to join the Niclausse Boiler Co., I td

Mr. James Smith, former assistant superintendent of telegraphs, G.P.O., Edinburgh, has died at the age of eighty-one. For many years he taught telegraphy and telephony at the Heriot-Watt College.

Tanis.—The Electrical World Mr. H. E. reports the death, at the age of eighty, of Mr. Hulbert E. Tanis who was the last of the pioneers who went to Schenectady with Thomas Edison in 1886 when the Edison Machine Works was moved from New York.

Mr. T. F. May.—His many friends in the electrical industry will learn with regret of the death on October 1st of Mr. T. F. May, sales manager of the Leyton

works of the London Electric Wire Co., and Smiths, Ltd. Mr. May who would have been 53 this month, was educated at All Souls, was Langham Place, and after a brief period with the St. James' and Pall Mall Electricity Co., Ltd., joined the Sun Electrical Co., Ltd., which he left in 1914 to Ltd., take up an appointment



with W. T. Henley's The late Mr. T. F. May Telegraph Works Co., Ltd. In April, 1927, he joined the London Electric Wire Co. and Smiths, Ltd., as assistant sales manager and in 1929 was appointed to the a widow and one son who is serving with the R.A.F. in Italy. The funeral took place at Golders Green Crematorium, among those Golders Green Crematorium, among those present being Mr. G. E. Jewell representing Mr. W. J. Terry (chairman and managing director of the London Electric Wire Co. and Smiths, Ltd.), Mr. S. B. Klein (assistant general manager of the Leyton works) Mr. Ernest Leete (director), and many represen-tatives of other electrical companies. 134

the second

-

Ju:

「日本」

11 (11)

111

A

till

DET

tit un

日本の町町の湯川

ELECTRICAL REVIEW

COMMERCE and INDUSTRY

Factory Accommodation. Compact Service Units.

Disposal of Government Factories

NDUSTRIALISTS who will later require space of 10,000 sq. ft. or more in surplus Government factories or storage premises, which they are willing to use for peacetime industrial purposes, are invited to apply to the Registrar, Control of Factory and Storage Premises, Neville House, Page Street, London, S.W.1. Except in special circumstances, factories will not be sold outright but will be let for a period of ten years, at the end of which there will be an option for a further lease for a long term. The short lease

will commence from the date when the Government is able to release the factory from war work, unless the selected tenant is the present occupier, in which event the short lease can commence at once.

The factories will be allocated in accordance with certain criteria of national interest, such as the establishment of a balanced distribution of industry ; the re-establishment and expansion of the export trade; the maintenance of a war potential; the require-ments of town and country planning; the ability of individual applicants for factories to make efficient use of the factory premises with the minimum of

time would be of real assistance to them when they are demobilised.

At Luton, the Electricity Department has offered to use its organisation to give instruction in cookery, etc., to young women from local Service establishments and experimental classes have already been formed and tuition started. It was felt that small classes, with consequent individual attention, would be most suitable, so, as a beginning, two classes of eight girls each have been formed and each class will attend six sessions of about two hours' duration at weekly intervals.



A cooking class for Service women in progress at the Luton Electricity Department's showrooms

reconstruction ; and the claim, on grounds of equity, of firms whose factories have been damaged or destroyed by enemy action, or have been requisitioned by the State under concentration schemes or otherwise.

A.S.E.E. Branch Merit Competition

The examiners have now announced their decision on the first year's competition between branches of the Association of Supervising Electrical Engineers for the best all-round record for the period 1943-4. In their report, they speak highly of the interest and value of the educational and business activities of the winning branch, and of its development on a carefully constructed plan. A silver cup will be presented to representatives of Birmingham Branch at the opening meeting of the 1944-45 session on October 21st, at the Lighting Service Bureau, London.

Domestic Training for Service Girls

To those thousands of women stationed at gun sites and similar establishments the present state of activities has brought a good deal of increased leisure; many of these young women on returning to civil life will be setting up home for the first time. Therefore, some training in domestic subjects given at the present

Each session includes a period of instruction in the use and care of the cooker, followed by tuition in the basic principles of cookery and tuition in the basic principles of cookery and recipes, after which the girls themselves carry out some preparation and cooking. This last practical work occupies a good proportion of the time. It is proposed to use the final session for a general chat on the domestic use of electricity for water heating, laundry and so on. The girls are keen intelligent and really aprious The girls are keen, intelligent and really anxious to learn. The accompanying photograph is reproduced by courtesy of the *Luton News*.

Hundred Years of Ironmaking

An attractively produced illustrated brochure, issued in connection with the recent commemoraison of a century of ironmaking, tells the story of the Midland Iron Co., Ltd., of Rotherham, which commenced forging in 1844. The wrought iron trade reached its heyday in 1855-65 when the concern was converted into a limited company. Further expansion raised the quantity of iron manufactured to 12,000 tons in 1880, occasionally amounting to 1,600 tons per month, at which time the whole of the plant was steam driven. Modernisation took place in 1904, when the old 16-inch beam engine was dismantled and the rolling of steel commenced, although the main product of the works remained wrought iron.

A start was made with electrification in 1928 when the rolling mills were converted, but trading became difficult subsequent to the 1926 coal strike which rendered the works idle for some months. After reconstruction in 1930, Thos. W. Ward, Ltd., of Sheffield, took control and introduced such improvements as an overhead electric gantry for the stock yard, a 5-ton overhead crane with a 46-in. diameter lifting magnet for loading material and a 500-HP motor for driving the forge train, which with various auxiliary installations completed the electrification of the plant.

Lighting for Layout Reproduction

Fluorescent tubes are proving most effective for the lighting of layout reproduction rooms. Layout reproduction, a process largely developed in America, has in the past year been used with conspicuous success by the aircraft industry in this country. By its use full-scale drawings of aircraft components are made on metal sheets which are subsequently photographed, the originals serving as "masters" and the prints as working drawings. In some cases metal sheet with a sensitized surface is used ; this is exposed and developed and is used in the manufacturing process, thereby obviating "marking-off."

The rooms generally are composed of a staging raised about 3 ft. 6 in. from floor level and made up of a series of tables 8 ft. by 4 ft. If required, these can be used independently or joined together to form one huge table. The one illustrated is about 160 ft. by 20 ft. wide. The draughtsmen move about on top of this table when making drawings and wear special sandals or slippers made of thick felt.

The illumination must be uniform over the whole area and as shadowless as possible, the lighting intensity must be high and the fittings mounted sufficiently high to allow free movement of the draughtsmen and, since the work is carried out on metal sheets, a low brightness light source is imperative even though the sheets are treated to minimise the specular reflection.



" Osram " fluorescent tubes used for lighting a Jayout reproduction room

There is no other light source that fulfils these requirements so well as the fluorescent tube, the low temperature of which is another advantage when one considers the high-intensity illumination (35-40 ft.-candles) that must be provided. In the room illustrated this intensity is provided by two rows of continuous troughing spaced at 8 ft. centres with "Osram" fluorescent tubes in twin tube circuits mounted 10 ft. from the table area.

Lamp Publicity

Thorn Electrical Industries, Ltd., are offering retailers a window display service for "Atlas" lamps, in spite of the continued shortage of labour and materials. A photograph of this



"Atlas " lamp window display

season's standard window display, built up with cartons and poster, is reproduced herewith. This is one of several attractive sales aids which the company is supplying to retailers and, in

addition, increased national and provincial Press advertising is being carried out.

Restoring Dnieper Plant

It is reported by *Reuter* that nine hydro-electric turbogenerators for the Dnieper plant in the Soviet Union are to be manufactured in the United States. They are to replace those destroyed by the Russians when they retreated before the Germans in 1941. Their manufacture and installation will require at least four years for completion. This machinery will not be provided through lendlease but will be financed by the Soviet Government.

E.I.B.A. Donations

A number of handsome donations, ranging from ± 50 to ± 250 , were sent to the Electrical Industries Benevolent Association in the period from May to August. The list sent 4

5

-

1

in a la

har

1 2

ģī

日日日日の湯田

us by the secretary includes the names of wellknown people in the industry, several of the leading manufacturing companies and no fewer than eight more electricity supply undertakings company and municipal.

In a message to the electrical industry, Mr. J. N. Stephens, the new president, says it is hoped that the next twelve months will be a period of great excitement and good news and will therefore present more than ordinary possibilities and more than ordinary dangers. The E.I.B.A. Council asks that at this time of good omen, and later when present high hopes are realised, all should mark their relief and gratitude by assisting both with money and work, to an even greater extent than before, the E.I.B.A., which is an example of that social decency for which the war is being fought.

Facts About the Railways

So far 2,387 miles of railway in Great Britain have been electrified at a cost of over \pounds 50,000,000. In a normal year main line electric trains run over 51 million miles. This information is given under one of the 48 alphabetical headings in an interesting booklet just issued by the

British Railways and London Transport. In addition, there is a list of outstanding events from 1825 to 1943, and a section on railway finance and statistics.

Northampton Electrical Association

The annual general meeting of the Northampton and District Electrical Association was held at the Northampton College of Technology on October 11th. Mr. O. F. Bailey, Principal of the College, was in the chair and was re-elected for the ensuing year. Mr. W. P. Barnell, one of the prime movers in the formation of the Association, who acted as owing to pressure of business, and a vote of thanks was passed to him for the services rendered. After the election of officers and and other business, two sound films of topical interest were shown. Anyone who is engaged in any branch of the electrical industry and is interested in the Association can obtain details from the College of Technology, St. George's Avenue.

Production Control

The second of three booklets dealing with production control (B.S.1100, Pt. 2, 1944, price 2s. post free) published by the British Standards Institution, 28, Victoria Street, London, S.W.1, gives advice on production control technique in the small factory, with the over-riding object of stressing the need for control if production is to be economically increased and waste of time and effort eliminated. The booklet may be found of greatest use in the factory employing 50 to 200 people, but it is recognised that for production control purposes a factory employing 200 people may be simpler than one employing 50 if the type of product in the former is less complex than in the latter.

The text of the booklet is illustrated with specimen schedules, cards, record sheets and a comprehensive order flow chart which shows the various stages through which an order will pass.

House Service Units

A combined house service unit produced by Siemens Electric Lamps & Supplies, Ltd., for post-war houses was described in our issue of May 19th last. The company has now produced models of two further types, shown in the accompanying illustrations. The one with a hardwood front is to the design of Mr. R. Plummer, A.M.I.E.E., and is specially dimensioned to suit standard brickwork, an important point to be considered when mounting the unit flush into the wall. The white enamelled unit is one of two manufactured for the Ministry of

2

Works show houses at Northolt, and is also intended for flush mounting. The service fuse and sealing box is housed under the bolted-on panel extending down to floor level.

The inteflor equipment of both of these models is well planned and provides for easy cabling both for the service cable and the outgoing conduits. These new units will make a noteworthy contribution to the tidying-up of service arrangements.



White enamelled service unit (above) and model with hardwood front (right)

Mechanised Farming

The need for greater mechanisation of farming after the war was emphasised by Mr. Tom Williams, M.P., Joint Parliamentary Secretary to the Ministry of Agriculture, at an agricultural and horticultural machinery demonstration arranged by the Surrey County War Agricultiral Executive Committee at Eashing Farm, Godalming, last week. Since 1939, he said, British farmers had spent £100 million on farming



Farmers watching a demonstration of welding at Godalming

machinery and equipment and two-thirds of it had been supplied by manufacturers in this country.

When the war had ended, Great Britain, which had disposed of practically all its overseas investments, would more than ever need to utilise machinery to maintain and expand home production. British machinery makers would, besides supplying the requirements of this country, be in a good position to meet the needs of farmers on the Continent.

Apparatus displayed included dairy equipment, pumping plant, sheep shearers and various equipment concerned with the cultivation and harvesting of potatoes and other root crops. Particular interest was shown in a demonstration of welding as applied to the repair of agricultural machinery.

New Westinghouse Publication

The Westinghouse Electric International Company announces the publication of a new technical magazine for Latin America, *El Ingeniero Westinghouse*. Printed in Spanish and issued bi-monthly, it contains articles from recent issues of *Westinghouse Engineer*, together with additional engineering information of special interest to technical readers in Latin America.

Philips Lamp Publicity

Philips lamp advertising this season will develop still further the theme of the lamp as a transformer of electricity into light. The method of presentation, however, has been changed. In place of the humorous sketches, scraper-board drawings are being used, and the advertisements are intended to have more of a prestige appeal. For example, one illustration shows a 45,000-ton battleship travelling at speed, with a large lamp superimposed, the copy explaining that the Philips lamp is a transformer of electricity into light, no less efficient in its way than the turbines of a battleship, which transform steam into the power which gives the battleship its speed. Other illustrations are of a submarine, Spitfire aeroplane and the "Coronation"

plane and the "Coronation" locomotive, the copy theme being similar in each case.

These advertisements will appear in the London evening and a large number of provincial daily and evening newspapers, as well as in two of the national Sunday papers. Two national periodicals have again been included, and a new departure is the inclusion of two women's journals. The trade, technical and industrial journals will again be well represented, and the campaign will open in these with a bold and simple prestige announcement. The now famous "Fig" poster ("See it Through with Philips Lamps") will again be well in evidence in the London Underground, in the form of lift and escalator cards, and 20 in. by 30 in., 60 in. by 40 in. and 16-sheet posters.

Two window display pieces will be available this year. One is a two-sided display card, 18 in. by 12 in., suitable either for window

or counter use, which has been reproduced by a paint transfer process on to pressed board made from scrap leather. The other is a larger display which again is two-sided, and has been reproduced by offset on to linen. Measuring 45 in. by 34 in. this will provide a most striking and effective centre-piece for a complete window display. A new general lamp catalogue will cover all lamps still being supplied, giving revised prices and details of purchase tax.

South African Brush Subsidiary

The Brush Electrical Engineering Co., Ltd., has set up a subsidiary company under the title of Brush (South Africa) (Pty.), Ltd., (P.O. Box 7995), 20, Bitcon Road, Johannesburg. This company will initially build buses and coaches and certain electrical equipment in South Africa and will handle the sale of the following products of the Brush Company in the Union :--Turbo-alternators, transformers, switchgear, motors, generators, transformers, switchgear trucks. It will also superintend the distribution of Petter oil, paraffin and petrol engines in the Union.

Changes of Address

The Passenger Transport Journal, has returned to its pre-war address at Avenue Chambers, Vernon Place, Southampton Row, London, W.C.1 (telephone: Holborn 9914).

The Chorlmet Radio Electric, Ltd., is moving next Monday to 64–66, Shudehill, Manchester, 4 (telephone: Blackfriars 1054).

Rectifiers for Battery Charging

Calculation of AC Voltage from Required Output

By F. T. Bennell,

Graduate I.E.E.

HE somewhat difficult mathematical problem presented in arriving at the voltage that must be applied to a batterycharging rectifier in order to obtain a certain charging rate is usually solved by means of a graph. For ease and accuracy, however, reference to a form of trigonometrical table

is to be preferred, the problem being thus resolved finally into trigonometrical ratios. In addition to providing

a solution on these lines,

= (

¥1

1

this article also attempts to reduce the problem and its solution to their simplest forms and to make them applicable to rectifiers with any number of phases. As much calculation as possible is carried out in the preparation of the tables referred to, leaving a minimum of work to be done in the application to particular cases.

In practice, a simple empirical formula may be used for the majority of cases, any inaccuracies being covered by the adjustable resistances or transformer tapping switches usually incorporated in battery charging equipments.

An exact means of calculation is, nevertheless, required for the following purposes: As a guide when developing an approximate empirical rule; for determining the limits of output between which that rule will give best



Fig. 1. — Output voltage wave-forms (a) from each rectifier phase; (b) from three-phase rectifier (p = 3); (c) from single-phase full-wave rectifier (p = 2) when connected to battery (Case I)

results for average cases (the accuracy becoming progressively less as those limits are approached); for border-line cases where the ability of a particular size of rectifier element to deal with the required output is in doubt; and when standard designs are being developed for the purposes of bulk production. Only the basic calculation

Only the basic calculation is here dealt with and no account is taken of the voltage drop in the rectifier element, the slight reverse

current or the distortion of wave-form caused by the inductance of the transformer. Allowances must be made separately for such of



Fig. 2.—Output voltage wave-form from threephase rectifier when connected to battery and the minimum rectifier voltage is higher than the battery voltage (Case 2)

these factors as will appreciably affect the result.

Sometimes, when there are three or more rectifier phases, the output voltage is unaffected by the battery. A different method of calculation must then be employed and, for the sake of completeness, this case is also dealt with.

In designing a rectifier, the battery voltage and charging current being specified, the charging voltage (*i.e.* the average excess of the rectifier output voltage over the battery voltage) is calculated from the charging current and the resistance of the charging circuit. The voltage wave-form from each rectifier phase consists of half a sine wave as shown in Fig. 1 (a), the other half being obstructed by the rectifier, and the rectifier output voltage is the maximum voltage obtaining in any of the phases, Fig. 1 (b). Finally, when the rectifier is connected to a battery the output voltage is the maximum voltage obtaining in either the rectifier or the battery, Fig. 1 (c).

Two distinct cases arise which will call for different treatment. Case 1 is when the output voltage is affected by the battery voltage, *i.e.* when the minimum value of the rectifier voltage is lower than the battery voltage, as in Fig. 1 (c). Case 2 is when the output voltage is not affected by the battery voltage, as shown in Fig. 2.

Case 1 includes all single-phase and most three-phase battery-charging rectifiers. In

this instance, when the rectifier voltage is below the battery voltage the battery tends to feed back, but is prevented from so doing by the one-way character of the rectifier. It is only during the periods—shown shaded in Fig. 1 (c)—when the rectifier voltage exceeds the battery voltage that a charging current flows.

The average charging voltage corresponds to the average height of the shaded portions. An expression for this voltage can therefore be obtained by dividing the sum of the shaded areas by the total distance along the time axis, or more specifically the amount of shaded area per cycle by 2π radians.

The charging periods occur once per cycle for each rectifier phase; the wave-form of each period is symmetrical. For simplicity, therefore, the areas in only a half of one

Т	A	BI	L.E	1	

р	No. of Recti- fier Phases	1	2	3	4	6
K1	-π/P	3.142	1.571	1.047	·7854	·5236
K	$\frac{\pi/\mathbf{P}}{\sqrt{2}\sin \pi/\mathbf{P}}$	-	-	·8551	-7854	·7404

period will be found, and account will be taken of the number of times the half period occurs per cycle for various numbers of rectifier phases. I have found by trial that the solution is simplified slightly by considering the wave-form of the rectifier voltage as cosine instead of, as usual, sine, and the datum line along the time axis will therefore be at a point of maximum voltage. The element to be integrated therefore lies between O and α in Fig. 1 (c).

Reverting to the design calculations, the position is that B (the battery voltage) and C (the charging voltage required) are known, and it is required to find R (the maximum value of the AC voltage).

The rectifier voltage = $\mathbf{R} \cos \theta$, where \mathbf{R} is the voltage at the datum line, *i.e.* the maximum voltage, and θ is any angle between O and $\pi/2$ measured from this line.

Let B = the battery voltage and α the angle in radians, measured from the datum line, at which the rectifier voltage curve crosses the battery voltage line, *i.e.* where the rectifier and battery voltages are equal. Then

$$R \cos \alpha = B, \quad R = \frac{D}{\cos \alpha}$$
(1)

and R r.m.s. =
$$\frac{B}{\sqrt{2} \cos \alpha} = \frac{B}{X}$$
....(2)
where X = $\sqrt{2} \cos \alpha$.

It now remains to obtain an expression for α , or preferably $\sqrt{2} \cos \alpha$, in terms of B and the other variable, C. The total area between O and $\alpha = \int_{0}^{\alpha} R \cos \theta \, d \, \theta$(3)

The area below the battery voltage line and between O and $\alpha = B \alpha$(4) The area above the battery voltage line, which represents the charging voltage = (3) - (4) = $\int_{0}^{\alpha} R \cos \theta \, d \theta - B \alpha$.

Reference to Fig. 1 will show that there are two of these areas per rectifier phase per cycle. The total shaded area per cycle is therefore $2 P \int_{0}^{\alpha} R \cos \theta \, d\theta - B \alpha$, where P is the number of rectifier phases.

Dividing the area thus obtained by the horizontal axis—the value of which, for one cycle, is 2 π radians—we get the average vertical ordinate, which represents the average charging voltage. Therefore

$\mathbf{C} = \frac{2\mathbf{P}}{2\pi} \left[\int_0^{\alpha} \mathbf{R} \cos \theta \mathrm{d} \theta - \mathbf{B} \alpha \right] =$
$\frac{\mathbf{P}}{\pi} \left[\int_0^\infty \mathbf{R} \cos \theta \mathrm{d} \theta - \mathbf{B} \alpha \right] \dots $
$= \frac{P}{\pi} (R \sin \alpha - B \alpha) \therefore R \sin \alpha - B \alpha =$
[#] − C.

It has been shown (equation (1)) that R =

$$B/\cos \alpha \stackrel{.}{\leftrightarrow} \frac{B}{\cos \alpha} \frac{-B}{\alpha} = \frac{\pi}{P}C$$

$$\therefore \tan \alpha - \alpha = \frac{\pi}{P} \cdot \frac{C}{B} \therefore Y = K_1 \frac{C}{B} \dots (6)$$

where $Y = \tan \alpha - \alpha$ and $K_2 = \frac{\pi}{2}$

where $Y = \tan \alpha - \alpha$ and $K_1 = \overline{P}$

A straightforward expression for α or $\sqrt{2} \cos \alpha$ cannot be obtained from this formula, and it is recommended that a modified trigonometrical table—Table 2—be prepared, to enable $\sqrt{2} \cos \alpha$ to be obtained from $\tan \alpha - \alpha$. This table can be derived from a standard trigonometrical table.

The figures for angles approaching 90 deg. will not be required as they do not occur in

α degrees	α. radians	$\sqrt{\frac{2}{X}} \cos \alpha$	$ ad {ad } {\mathfrak A} - {\mathfrak A} Y$
0 10 20	0 •1745 •3491	1-414 1-393 1-329	0 •0018 •0149
30	$\cdot 5236\left(\frac{\pi}{6}\right)$	1.225	-0538
45	$\cdot 7854\left(\frac{\pi}{4}\right)$	1 000	·2146
60	$1.047\left(\frac{\pi}{3}\right)$	•7071	·6849

TABLE 2 (Sample figures)

practice. Also, the figures for each degree need not be calculated for low angles as they increase very slowly. A table for angles of 0, 10, 14, 17, 20, 22, 24, 26, 28 and 30 to 60 (inclusive) degrees, will therefore be found adequate. $\pi/6$, $\pi/4$ and $\pi/3$ marked against the radian figures corresponding to 30, 45 and 60 deg. respectively will facilitate checking whether α is greater or less than π/P , when this is necessary.

The method of calculation is first to calculate Y from the known values of B and C, using equation (6) (the appropriate value of K_1 is obtainable from Table 1); X is then 17

obtained from Y. using Table 2 and this value is substituted in equation (2), enabling R r.m.s. to be determined.

The foregoing method of calculation is not applicable to Case 2, as an essential requirement is that there shall be an instant (z) when the rectifier voltage equals the battery voltage.

The calculation is, however, simpler than for Case 1, as the output voltage wave-form is not affected by the battery voltage, and the absence of this complication enables a direct formula to be derived.

This formula is derived as follows:-The element to be integrated lies between O and τ P in Fig. 2, from which it will be seen that equation (5) for Case 1 is applicable except that = P must be substituted for x, i.e.,

$$C = -\frac{P}{\pi} \left[\int_{0}^{\frac{\pi}{P}} R \cos \theta \, d \theta - -\frac{\pi}{P} B \right] =$$

$$\frac{P}{\pi}\left(R\sin\frac{\pi}{\bar{P}}-\frac{\pi}{\bar{P}}B\right); \quad R = \frac{\bar{P}}{\sin\frac{\pi}{\bar{P}}}(B + C)$$

and R r.m.s. =

$$\frac{P}{\sqrt{2\sin \frac{1}{2}}} (B - C) = K_{2} (B - C) \dots (7)$$

where $K_s = \frac{P}{\sqrt{2 \sin \frac{P}{P}}}$ and is obtainable from

Table 1.

出し

4

「「「見夜夜

31

日月 四日 四日 四日 日日 日日

Via Vi

If there is doubt whether a particular example should be treated as Case 1 or Case 2. Y should first be calculated, using equation (6). Table 2 should then be referred to, to see whether z is more or less than z P. If less, Case 1 applies: if the same or more. Case 2.

Forthcoming Events

Friday, October 20th.—London.—At Institu-tion of Electrical Engineers, 5.30 p.m. Measure-ments Section. Inaugural address by Dr. W. G. Radley.

London .- Institution of Mechanical Engineers.

 Lohdon.—Institution of Mechanical Engineers.
 5.30 p.m. Presidential address on "Applied Research," by Dr. H. R. Ricardo.
 London.—39, Victoria Street, S.W.1, 6.30
 p.m. Junior Institution of Engineers. Informal meeting. "Humidity and its Control." by M. R. G. Morton.

Newcastle-on-True.-Neville Hall, Westgate Road, 6.30 p.m. I.E.E. North-Eastern Students' Section. Inaugural address by the chairman. G. E. Topping.

Newcastle-on-Tyne.—At Literary and Philo-sophical Society's Lecture Theatre, 6 p.m. North East Coast Institution of Engineers and Shipbuilders. Annual general meeting and presidential address.

Sheffield. — At Metallurgical Club, West Street, 6.30 p.m. Junior Institution of Engineers (Shemeld Section). Annual meeting and informal discussion.

Saturday, October 21st.—London —At Light-ing Service Bureau, 2, Savoy Hill, W.C.2, 2.15 p.m. Association of Supervising Electrical Engineers. Technical film display and

Engineers. Technical mile and presidential address. Birmingham.—Grand Hotel, 12.30 for 1 p.m. I.E.E. South Midland Centre. Wartime lunch. Chairman's address and visit of Institution president.

Wakefield.-Strafford Arms. 3 p.m. Asso-ciation of Mining Electrical and Mechanical Engineers. Presidential address by J. T.

Engineers. Presidential address by J. 1. Green and visit by the national president. *Cardiff.*—At South Wales Institute of En-gmeers, 5 p.m. Association of Mining Elec-trical and Mechanical Engineers (South Wales Branch). "Electrical Aspects of American Mechanical Loading of Coal" fillustrated by sound film and slides), by R. Crawford.

Sound him and slides), by R. Crawford. Monday, October 23rd.—London.—At I.F.E. 5.30 p.m. Informal meeting. Discussion on "The Engineer's Part in Certain Post-War Problems," to be opened by the president. Birmingham.—Grand Hotel, 6 p.m. Birming-ham Electric Club. Paper on "High-frequency Induction Heating," by T. G. Tanner. Newcastle-on-Tyne.—Neville Hall, 6.15 p.m. I.E.E. North-Eastern Centre. "Design and Performance of Domestic Electrical Appli-ances," by W. N. C. Clinch and F. Lynn. Tmeeder, Ontober 24th London 15 June 15 June 2010.

Tuesday. October 24th. - London. - At I.E.E. Council Room, 2.30 p.m. British Society for International Bibliography. The Application international Biolography. The Application of Universal Decimal Classification to Tele-communication Literature," by Mr. J. E. Wright, and "Document Classification in a limited Field-Radiocommunication and Allied Subjects," by Mr. L. S. Harley.

Wednesday, October 25th.-London.-At I.E.E., 5.30 p.m. Radio Section. "Develop-ment of Polythene as a High-frequency Di-electric," by Prof. Willis Jackson and J. S. A. Forsyth.

Edinburgh.—Heriot-Watt College, 6 p.m. I.E.E. Scottish Centre. Exploratory wireless meeting. Paper: "Survey of the Performance of Post-War Television." by B. J. Edwards. Birminghum.—At James Watt Institute, 6:30

Birmingham.—At James Walt Institute, o.e.o p.m. I.E.E. South Midland Students' Section. "Diesel Electric Traction." by F. L. Toombs. *Doncaster.*—Technical College, 3 p.m. Asso-ciation of Mining Electrical and Mechanical Engineers (Yorkshire S.E. and N.W. Branches). Visit by H.M. Electrical Inspector of Mines and dissussion on his protect.

and discussion on his report. Newcastle-on-Tyne.-Bolbec Hall, 6.45 p.m. North East Coast Institution Student Section. Chairman's address.

Friday, October 27th.—London.—At Institu-tion of Civil Engineers, 3 p.m. Institution of Chemical Industry, Chemical Engineering Group, Fifth Hinchley Memorial Lecture Hydro-electric Development in Great Britain and its Influence on Chemical and Allied Industries," by Sir Alexander Gibb. London.—Institution of Mechanical Engineers,

5.30 p.m. Informal discussion on "The Influence of Engineering on Social Advance-ment." to be introduced by E. Reeve.

Monday, October 30th.—Birminghom.—At James Watt Institute, 6 p.m. I.E.E. South Midland Centre Radio Group. Discussion on Industrial Applications of High-frequency Power," to be opened by E. May.

RECENT INTRODUCTIONS Notes on New Electrical and Allied Products

Signalling Torch

A MARINE torch for night signalling is announced by the GENERAL ELECTRIC CO., LTD., Magnet House, Kingsway, London, W.C.2. It is weatherproof and made partly of steel specially treated to resist rust. The head ring



Marine signalling torch]

and base cap, which embody screw threads, are made of brass. The whole is finished in black rivelling enamel.

The head of the torch is fitted with a lightrestricting cowl and colour screen for night signalling. These are detachable and, without either or both of them, the large diameter reflector with focusing device gives a strong spotlight beam. The bulb holder has a spring plunger, so that the bulb can be unscrewed to the last thread before contact is broken.

The torch is fitted with a Morse tapper key and a thumb switch; with the former locked in the closed position by means of a sliding tube, the torch may be used in the normal way. The thumb switch also acts as a safety feature to prevent accidental flashing of the tapper key. Additional refinements include a carrying handle, which also forms a stand for signalling, and a spare bulb holder.

It has an overall length of 11 in., and is designed to take an "Osram" 2-V, 0 3-A bulb, operating from two L.6103 battery cells. It has been approved by the Admiralty for use as a night signalling torch on merchant ships, and by the Ministry of War Transport for lifeboats and for use in similar circumstances.

Larder Conditioner

To provide safe food storage conditions in kitchens not large enough to accommodate refrigerators, FRIGDAIRE, LID., 401, Edgware Road, The Hyde, London, N.W.9, has designed a "larder conditioner." A small fan over a specially designed cooling coil contained within the unit circulates the air within the larder and removes all food odours. Clean cool air then flows round the larder maintaining the temperature at less than 50 deg. F. with appropriate relative humidity both winter and summer. Under these conditions even bread and green vegetables can, it is claimed, be kept for reasonable periods in perfect condition.

The apparatus, which will cool an entire larder of 25-30 cu. ft., is operated by an electrical rotary sealed compressor designed to run for years without attention. There are no switches to set, no oiling to be carried out and no periodic de-frosting. Larders need to be lightly insulated, and have standard flush doors.packed internally with kapok. It is anticipated that the cost of the unit will be considerably less than the pre-war family model refrigerator. Electricity consumption is approximately 2 kWh a day.

This equipment and a proposed standard 3-kW fused plug are two of the outstanding electrical items in an exhibition now running at Birmingham under the auspices of the Ministry of Works. It is a display of housing equipment to illustrate those parts of the "Housing Manual, 1944" which deal with interior installations and fittings. The exhibition is complementary to the demonstration houses at Northolt, which illustrate Government recommendations on the planning and construction of houses. It has been arranged with the co-operation of the Ministry of Health and the Ministry of Fuel and Power. The exhibition is being held at the West End Hall, 92, Suffolk Street (near the Civic Centre). From October 16th to 21st inclusive admission



Frigidaire "larder conditioner"

will be by ticket only. From October 23rd to November 4th, inclusive, the exhibition will be open to the public from 10 a.m. to 5 p.m. each day (including Saturdays).

West Hartlepool Model Kitchen

THE borough electrical engineer of West Hartlepool (Mr. S. Tillotson) has designed a model kitchen which includes suggestions made by housewives who inspected a previous model. Mr. Tillotson's model, which is open for public inspection, can be incorporated in the houses of 900 sq. ft. proposed by the Government. The kitchen covers 164 sq. ft. and has a laundry adjoining. a the a lot a will be a lot a

I C.L.

24

à

CHERER'S

BLECTRICITY SUPPLY

Bradford .- POWER STATION EXTENSIONS .-The Electricity Commissioners have approved a The incentially commissioners have approved a scheme for extensions at Valley Power station estimated to cost $\pounds 1,000,000$. Half of the extensions have to be completed by 1946 and the remainder by 1948. The contract has been let for a new turbo-alternator, and preparations are being made for the installation of two new

Cardiff.—SUBSTATION.—The Electricity Com-mittee is to obtain a substation site in Grand Avenue, Elv.

Chesterfield.-BULK SUPPLY ARRANGEMENTS--In connection with a scheme for additional bulk supplies from the Derbyshire & Notting-hamshire Electric Power Co., involving the erection of an additional 5,000-kW bulk supply plant, the Electricity Committee has decided to seek sanction to borrow £12,365.

SUPPLY TO PUMPING STATION.—The borough electrical engineer has reported to the Electricity Committee that as the Electricity Commissioners are not prepared to grant the necessary licence for the erection of steel lattice towers for the high-voltage line to the Holmebrook pumping station, a new scheme has been prepared incorporating wooden poles and this, with a revised schedule of costs, has been submitted to the Commissioners.

Douglas (I.O.M.) .- ACCIDENT AT POWER STATION -A flywheel, weighing about 20 tons, dew off the generator at the power station on October 10th and, as a result, the whole of the island was deprived of a supply of electricity. The flywheel wrecked part of the station as it hurtled through the roof, then it broke up in mid air and fell in various parts of Douglas after travelling nearly half a mile. Many people had narrow escapes but nobody was hurt. Workmen in the station suffered from shock. Two pieces of the flywheel badly damaged the office of the *Isle of Man Times*. One piece went through the five-storey building and destroyed a Diesel engine, and another piece wrecked much of the building. An electricity supply was later brought into operation in the island by means of emergency plant.

Essex. - ELECTRICITY FAILURE. - Southend and most of the S.E. Essex towns and villages were affected by a failure of the electricity supply last Saturday night. There was a complete black-out for twenty-five minutes.

Dumbarton. — ADMINISTRATION OF UNDER-TAKING.—There are indications that Dum-barton Town Council intends to exercise its option to terminate its agreement with the Electric Supply Corporation for the supply of electricity in the burgh. In reply to an inquiry the Chyde Valley Electrical Power Co. has submitted proposals in the event of the Council's creations in the event of the Council's exercising its option. One proposal is that the Council should continue to be the electricity undertakers and enter into an agree-ment for the Clyde Valley Co. to operate the undertaking, the company to provide the capital for the acquisition and future extension with a 40 years' agreement. The second is that the Dumbarton Electric Lighting Order of 1920 should be transferred to and merged into the whole undertaking of the Clyde Valley

Breakdown at Douglas. Hamilton Ban Removed.

Co. without expenditure by the Council. the event of either proposal being accepted the supply to consumers would be at the standard rates operating throughout the area served by the Clyde Valley Co.

Glasgow.-SUPPLY TO FARMS.-It is recommended that the Corporation shall contribute £250 towards the cost of a high-voltage over-head line to be erected by the Clyde Valley Electrical Power Co. to supply farms in the East Kilbride area. The proposed contribution is in respect of the inclusion of one of the Corporation's farms.

Hamilton.—BAN ON CHOICE REMOVED.—In 1934 the Town Council approved resolutions of a joint meeting of the Gas and Electricity Committees as a result of which tenants of new houses were not allowed to use electricity for heating and cooking. At its last meeting the Council decided to lift this ten-year ban by rescinding the former resolutions. It was agreed that, in all houses belonging to the Council, tenants should be free, subject to the approval of the Housing Committee, to introduce electricity and to make whatever use of that medium they choose.

Hull.—POWER STATION EXTENSIONS. — The Electricity Committee has obtained sanction to borrow £750,000 for extensions at the power station. It is also applying for permission to borrow £20,000 for mains and £10,000 for substations.

INDUSTRIAL SUPPLIES .- To meet the increased demand from industrial consumers in suburban areas works are to be carried out by the Committee at an estimated cost of $\pounds 9,213$.

Lichfield. — PRICE INCREASE WAIVED. — The Electricity Committee recommends that the 10 per cent. war increase in prices shall be not charged in respect of the September quarter.

Newport (Mon.).—Lower CHARGES RECOM-MENDED.—Following a report by Mr. T. H. Wood, who was appointed borough electrical engineer and manager earlier this year, the Electricity and Transport Committee has recommended the halving of the temporary 10 per cent. increase in charges made in 1940. The Com-mittee has congratulated Mr. Wood and his staff on the results shown in the report on the past year's trading.

Northern Ireland.-DEVELOPMENT SCHEME.-The Electricity Board for Northern Ireland has submitted to the Ministry of Commerce for confirmation under the Electricity (Supply) Act (Northern Ireland), 1931, a development scheme in parts of Antrim and Derry. The scheme is made with the general object of promoting. co-ordinating and improving the supply, distribution and sale of electricity in the development area as and when conditions permit, and gives the Board power to acquire and link-up with its main transmission lines all existing undertakings as and when desirable.

Notice has been given that authorised undertakings or other persons interested may make representations to the Ministry of Commerce with respect to the scheme within a month. A resolution protesting strongly against the proposal of the Board to acquire the municipallyowned Portstewart undertaking as part of the scheme has been passed at a special meeting of Portstewart Council.

Stretford.—CHARGES REDUCED.—The Stretford and District Electricity Board has reduced the lighting flat rate from $4\frac{1}{2}d$. plus 5 per cent. to $3\frac{3}{4}d$. per kWh; the heating rate from $1\frac{1}{4}d$. to Id.; power charges from 65 to 50 per cent. over the sliding scale; and the domestic "allin" tariff running charge from $\frac{3}{4}d$.

Tynemouth.—SUPPLY TO TRADING ESTATE.— In connection with electricity supply to the Chirton Trading Estate, the Electricity Committee has agreed that until experience has been gained of the manufacturers' requirements the electricity supplied to their new premises shall be charged on the maximum demand terms, namely, £4 5s. per kW of m.d. per annum plus ½d. per kWh subject to an addition or reduction of 0 01d. per kWh supplied for each shilling by which the cost of coal for the calendar year is above or below 12s. per ton.

West Bromwich.—SHOWROOM ALTERATIONS.— Proposed alterations to the electricity showrooms and reconstruction of adjoining premises at an estimated cost of £11,000 have been approved by the Town Council. The scheme is now being submitted to the Electricity Commissioners.

Wigan.—FARM ELECTRIFICATION.—The Rural District Council has approved plans of the Lancashire Electric Power Company for supplying electricity to seven farms.

Overseas

Belgium. — ELECTRICITY IN BRUSSELS RE-STRICTED. — Warning has been given that electricity in Brussels is to be cut off from sunrise to sunset because of the coal shortage. Supplies will continue to vital services such as hospitals, flour mills, bakeries and newspapers. If coal supplies permit, the electricity services will be restored at certain hours of the day for cooking.— Reuter.

New Zealand.—PLANT EXTENSIONS.—It is reported in *Tenders* that the Auckland Electric Power Board is supplying its consulting engineers in London with specifications and orders covering various items of electrical equipment required for proposed extensions, together with instructions for inviting tenders.

FINANCIAL SECTION

Company News. Stock Exchange Activities.

Reports and Dividends

The Calcutta Tramways Co., Ltd. —No estimate of the purchase price which the Calcutta Corporation will pay on acquiring the undertaking on January 1st next could be given by Sir Geoffrey R. Clarke, the chairman, at the company's annual general meeting on October 10th. The purchase price is to be based on the income and working expenses for a period of years ending with the current year; when the accounts have been completed the price will be ascertained and settled either by agreement or, if necessary, by arbitration. Sir Geoffrey said that apart from the separate Howrah system, which was constructed under agreement with the Howrah municipality, there were certain portions of the Calcutta system vital to its working which lay outside the scope of the contract and did not therefore fall within the terms of purchase. Acquisition of these portions would involve legislation. During the year two extensions were completed and opened for traffic, one to Ballygunge and the other to Howrah station across the new Howrah bridge.

A. Reyrolle & Co., Ltd., are offering ordinary stockholders 189,330 new £1 ordinary shares at 60s. each in the proportion of one new share for each complete multiple of £4 7s. 6d. of ordinary stock held. The proceeds of the issue are to be used to repay bank loans and to provide for commitments now in hand.

Telephone Properties, Ltd., report an income amounting to £87,309 for the year 1943, as compared with £94,216 for 1942. Almost all of this sum was in respect of dividends and interest from the Venezuelan subsidiary. The net profit was £30,968 (£24,503). A dividend of 6 per cent. (nil) is to be paid, and reserve for contingencies again receives £5,000, leaving £42,549 (£40,450) to be carried forward. Mr. A. N. Rye, the deputy chairman, stated at the general meeting on October 24th that there was a wide field for telephone expansion in Venezuela, and the Nacional Company planned large extensions immediately equipment became available.

The British Vacuum Cleaner & Engineering Co., Ltd., reports a gross profit of £155,059 for the year ended September 30th last, as compared with £149,730 in the previous year. After the deduction of bank interest, directors' fees, income tax and N.D.C., the net profit is £88,640 (against £95,888). A sum of £54,000 (£55,000) is transferred to income tax reserve, while the staff pension fund receives £7,500 (£10,000). A final dividend of $17\frac{1}{2}$ per cent. makes 30 per cent. for the year (same) and £12,202 (£11,687) is carried forward.

The United River Plate Telephone Co., Ltd., in a preliminary statement for the six months ended June 30th. 1944, records gross earnings amounting to £2,659,604, as compared with £2,504,603 for the first half of 1943, the net income being £588,054 (£542,511).

Erinoid, Ltd., proposes to increase its capital from \pounds 330,000 to \pounds 750,000 by the creation of 420,000 \pounds 1 shares. No immediate issue is proposed. The net profit for 1943-44 was \pounds 16,802 (against \pounds 15,974) and the dividend is being maintained at 10 per cent.

Electric & Musical Industries, Ltd., state that the group's net profit for the past year was $\pounds 182,024$, comparing with $\pounds 174,357$ for the preceding twelve months. The ordinary dividend is maintained at 8 per cent. (including 2 per cent. bonus) less tax at 8s. 6d. in the \pounds .

Strand Electric Holdings, Ltd., besides maintaining its dividend at 10 per cent. is paying a bonus of $2\frac{1}{2}$ per cent.
Veritys manufactures offer a wide choice from an extensive range of industrial electrical equipment.

L

25-

Εş

RHE

41

Install "Verity" manufactures and guarantee your maximum war effort.

VERITYS LTD. ASTON BIRMINGHAM 6 Sales Headquarters : BRETTENHAM HOUSE, LANCASTER PLACE, W.C.2 (A short series of open letters by L.S.E., commenting on some notable letters of the past.)

To King Darius III, who wrote to Alexander the Great, telling him to get back home and to take his gang of robbers with him.



Norwich, 1944

Your Late Majesty,

So Alexander ignored your warning and eventually defeated your armies. At the age of 25 he had conquered the known world and you lay slain.

Perhaps, before being so rude to Alexander, it would have been wise to have looked to your readiness for war. If only you had boasted a little less; toned down, for instance, your claim that the King of Heaven had bestowed on you the dominion of the earth.

In our business we do not waste much time hurling abuse and defiance at our competitors. We even admit that some of them make good electric motors—but we do our level best to make ours better and we have steadily enlarged our kingdom for sixty years.

With great respect for your late eminence,

Yours truly,

LAURENCE, SCOTT & ELECTROMOTORS LTD. Marconi's Wireless Telegraph Co., Ltd., has declared an interim dividend of 33 per cent. (same).

The Marconi International Marine Communication Co., Ltd., is again paying an interim dividend of $2\frac{1}{2}$ per cent.

The Skefko Ball Bearing Co., Ltd., has declared an interim dividend of 6_3^2 per cent., tax free (same).

The River Plate Electricity & Other Securities Corporation, Ltd., is again to pay an interim dividend of 2 per cent.

Callender's Cable & Construction Co., Ltd., is maintaining its interim dividend at 5 per cent.

The John Thompson Engineering Co., Ltd., is paying an interim dividend of 5 per cent. (same).

The British Thermostat Co., Ltd., proposes to maintain its interim dividend at $7\frac{1}{2}$ per cent.

W. B. Dick & Co. (Holdings), Ltd., has maintained its dividend at 4 per cent.

New Companies

R. J. Stearn & Sons (Luton), Ltd.—Private company. Registered October 4th. Capital, £3,000. Objects: To acquire the business of electricians formerly carried on by the late R. J. Stearn and F. C. White at 19, Upper George Street, Luton, and to carry on the business of electrical and wireless engineers and dealers, etc. Directors: R. G. Stearn, 16, Sharpenhoe Road, Barton, Beds., H. L. Stearn and W. A. Stearn, both of 38, Westbourne Road, Luton. Registered office: 19, Upper George Street, Luton.

Insuloid Manufacturing Co., Ltd.—Private company. Registered October 5th. Capital, £5,000. Objects: To carry on the business of manufacturers of, and dealers in, insulating plastic and other paper materials, rubber, synthetic rubber and covered textile yarns, and goods made therefrom or treated therewith, radio sets, electrical goods, etc. Directors: E. F. Emery, West Lodge, Butley Road, Adlington, Cheshire; and F. D. Emery, 6, Beech Road, Cheadle Hulme, Cheshire. Registered office: Ford Street Mill, Chestergate, Stockport.

Genmill Radio and Electrical Co., Ltd.— Private company. Registered October 5th. Capital, £2,000. Objects: To carry on the business of manufacturers of, and dealers in, wireless, television and electrical goods, etc. Directors: Lieut. G. W. Brown Mills (formerly Gerald W. Brown), 16, Linden Road, Gosforth, Newcastle-on-Tyne and W. R. Bell, 81, Selsea Avenue, Herne Bay. Registered office: 109a, Mortimer Street, Herne Bay.

Companies' Returns Statements of Capital

Burgess Hill Electricity, Ltd. — Capital, £65,000 in £1 shares (all ordinary). Return dated May 3rd. 52,250 shares taken up. £50,400 paid. £1,850 considered as paid. Mortgages and charges: Nil.

Prince's Electrical Clocks, Ltd.—Capital, £3,000 in £1 shares. Return dated May 16th All shares taken up. £1,000 paid. £2,000 considered as paid. Mortgages and charges: Nil. East Suffolk Electricity Distribution Co., Ltd. – Capital, £125,000 in £1 shares. Return dated March 28th (filed May 3rd). All shares taken up. £135,000 paid (including 16s. 8d. per share premium on 12,000 shares). Mortgages and charges: £7,900.

Increase of Capital

Electroway Heaters, Ltd.—The nominal capital has been increased by the addition of $\pounds 5,000$ beyond the registered capital of $\pounds 5,000$. The additional capital is divided into 2,000 ordinary and 3,000 6 per cent. preference shares of $\pounds 1$ each.

Mortgages and Charges

C. O. Ericsson Engineering Works, Ltd.— Debenture charged on deeds and documents relating to properties in King's Norton and Sutton Coldfield, and the company's undertaking and other property, present and future, including uncalled capital, dated September 23rd, 1944, to secure all moneys due or to become due from the company to Lloyds Bank, Ltd.

Sunderland Engineering Equipment Co., Ltd.— Assignment of proceeds of contracts, dated September 14th, 1944, to secure all moneys due or to become due from the company to Martins Bank, Ltd.

General Installation Co., Ltd.—Satisfaction in full on August 22nd, of debenture dated October 1st, 1931, and registered October 8th, 1931, securing £100.

Liquidations

Dome Electric Co., Ltd.—Meeting October 21st, at the office of Harry L. Price & Co., 47, Mosley Street, Manchester, to receive an account of the winding up by the liquidator, Mr. A. T. Eaves.

Bankruptcies

T. Smith, Jun., radio dealer, carrying on business at 19, Risborough Lane, Charlton, as the Risborough Radio Service, and at 5, Prospect Road, Hythe, as Hythe Music Stores. —Application for discharge to be heard on November 14th at the Guildhall, Canterbury.

R. E. Pearcey, motor and electrical engineer, 105, Arthur Street, Withernsea.—Discharged as from September 20th, 1944.—Proofs for dividends by October 27th to the trustee, Mr. J. E. D. Stickney, 1, Parliament Street, Hull.

H. A. Mayhew, electrical contracting engineer, 96, London Road, Apsley, Herts and 30, Elmer Gardens, Edgware.—Order made September 19th for discharge subject to debtor's consenting to judgment for £25 being entered against him by the Official Receiver.

J. H. Matthews, electrical dealer, 232 Town Street, Bramley, near Leeds.—Supplemental dividend of 5s. 2d. in the £ payable October 27th at the Official Receiver's Office, 24A, Bond Street, Leeds.

K. G. Burfield, electrical contractor, Espere, Couchmore Avenue, Clayhall Avenue, Ilford. —Receiving order made October 6th, on a creditor's petition.

STOCKS AND SHARES

TUESDAY EVENING.

TOCK Exchange prices are better than the amount of business which is now going on in the House, for prices are well maintained though the volume of business being transacted is certainly small. Every now and then a spasm of activity occurs in one market or another. This week it has been the radio department that has attracted most attention, a sharp rise in Electric & Musical Industries giving impetus to the list as a whole. For the best-class industrial shares a consistent demand continues.

Price Fluctuations

The variation in prices this week is comparatively slight. Home Railway firmness is reflected in a point rise, to 75, in Southern 5 per cent. preferred. The prior-charge group is better, too, but nominal quotations have been left unchanged. London Passenger Transport issues show no alteration, although to buy the fixed-interest stocks is a matter of increasing difficulty. Preference shares in the Home electricity supply group are also none too easy to come by. Montreal Power at 22½ is 1 lower, but Shawinigans hardened to 16½. Tokyo Electric sixes, the recent speculative buyers being satisfied, went back to 26. Cawnpore Electrics at 39s. 3d. have lost 9d. Calcutta Electric Supply remain at 47s.

Miscellaneous Movements

The Strand Electric surprised and pleased its proprietors by declaring a bonus of 23 per cent. in addition to 10 per cent. dividend. This is $2\frac{1}{2}$ per cent. better than last year's distribution. The price of the 5s. shares at 10s. 9d. is 2s. higher. Murex at $4\frac{3}{4}$ have recovered the deduction of the dividend. British Insulated at 58 and Mather & Platt at $2\frac{5}{16}$ are both $\frac{1}{16}$ up. Automatic Telephones and Walsall Conduits gained 6d. Cable & Wireless stocks are easier. Marconi Marines held to 36s. upon announcement of the usual interim dividend of 2½ per cent. Telephone Properties at 21s. 3d. are quoted ex dividend. British Vacuum Cleaner are also ex dividend at 29s. The year's accounts show a slight decrease in the .trading profits, but the 30 per cent. dividend on the ordinary shares is comfortably covered. Peto Scott Electrical Instruments at 4s. 9d. have fallen a trifle.

Callender's Cable

Callender's Cable & Construction Co., in declaring the usual 5 per cent. interim dividend, continues a rate which has been distributed annually for years past. The final, in each of the past two years, has been 10 per cent., plus a bonus of 5 per cent., making in all 20 per cent. for the year, this being the same rate as was declared for 1936 and 1937. For 1938 to 1941 inclusive, the annual dividend was 15 per cent., all these dividends having been paid out of earnings substantially greater. The company's year ends with December and the last-published accounts showed Callender's to be in an extremely strong financial position, the net liquid assets being rather over £1,000,000. The shares afford a yield of £3 16s. 2d. per cent. on the money at the present price of $5\frac{1}{4}$, which, by the way, compares with $1\frac{7}{8}$ touched in the dark days of 1941.

E.M.I.

Electric & Musical Industries shares rose to 37s. an hour or two before the company announced a dividend and bonus making, as before, 8 per cent. for the year. By some misunderstanding the figures were not sufficiently clearly stated for them to be readily comparable with those of the previous year. The result was a fall next morning to 35s. 6d. and, although the company promptly telephoned to the Stock Exchange a re-statement of the announcement, making clear what was previously obscure, the price of the shares failed to recover to the overnight level. At 36s., they show a gain of $\frac{1}{16}$ on the week.

The market in radio shares is tolerably active. Cossor at 25s. 6d. and E. K. Cole at 33s. are 6d. and 1s. better respectively. Pye deferred shares are unchanged at 33s. 9d. So far as E. M.I. is concerned, it really matters little what current dividend the company pays or what the earnings are under present conditions; supporters of the shares look to the future development of television as likely to justify the faith which they repose in their investment.

De La Rue

Thomas De La Rue shares have risen to the highest price reached for many years, the £1 shares advancing to 9⁸/₈. This is connected with the drastic action of the Belgian Government in withdrawing all the previous notes in circulation, and substituting fresh notes. De La Rue has interests in the plastics business and, after the war, this branch is expected to yield substantial results. But in the meantime the security printing is that part of the company's activities which produces the major part of its profits. De La Rue shares stood at 25s. three years ago and are now, as just mentioned, 192s. 6d. For the year ended March 31st, 1941, no dividend was paid. In the following year, the dividend was 25 per cent., and for the period ending last March, 40 per cent. The yield on the shares at the present price is about 4¹/₄ per cent.

Atlas Electric

With a fall of 3d., Atlas Electric & General Trust eased off to 7s. 3d. Two or three thousand of the Trust's 7 per cent. preference shares have come on offer at 26s. 3d., showing

(Continued on page 574)

4

山田市

ELECTRICAL REVIEW

BLECTRICAL INVESTMEENTS

Prices, Dividends and Yields

	Dividend		Middle			377.1.1		-	Dividend		Middle	D			
Company	Pre-		Oct.	HISC OT		p.c	u L	Company	Pre-	_	Oct.	or		Fiel p.c	.d.
	rious	Last	17	Fall		· ·	_		vious	Last	17	Fall			
Hor	me Ele	ctricity C	omoanie	25	Overseas Electricity Companies										
									£	s.	đ.				
Bournemouth and	1.11	1.11						Atlas Elec	Nil	Nil	7/3	—3d.		—	
Poole	123	122	64,6		3	17	4	Calcutta Elec	6¢	6*	47/-		2	11	1
British Power and	-	7	2210			2	~	Cawnpore Elec.	10	7	39/3	— 9d.	3	11	4
City of London	7	51	20/	• •	1	12	6	East African Powe	r 7	7	34/6		4	1	4
Chy of London		6 93	42/-	•••	2	1.6 1.6	4	Jerusalem Elec	7	5	29/-xd	3.0	3	9	0
Clyue valley	3	8	42/-		2	10	1	Kalgoorlie (10/-)	5	õ	11/6		4	7	0
Edmundsone :	0	0	44/0		9	13	1	Madras Elec	Nil	4	29/6xd	2	2	14	4
70/ Drof	7	7	35/6		2	10	0	Montreal Power	Ik	15	221	-1	_		
Ord	13	6	31/-		2	17	5	PalestineElec."A"	20	50	40/-		2	10	0
Flee Dis Yorkshire	q	q	45/6	• •	3	19	6	Perak Hydro-elec.	6	1	13/6	- C.		_	
Elec Fin and Se-		U	1010		U	7.0		Shawinigan Power	agets.	guets.	16±	+ 5			
curities	123	131	60/		4	10	0	TORYO Elec. 6%	0 . 15	15	26	-1	9	10	7
Elec. Supply Cor-	100	70 B	0.07	•••		A **	Ŭ.	VictoriaralisPowe	619	10	12		3	10	1
noration	10	10	48/6		4	•2	4	w mienaninv. Prei.		0	20/0		4	14	0
Iste of Thanet	Nil	Nil	19/6		÷.	_	-	Equi	pment a	nd Mani	facturin	g			
Lancs, Light and								Aron Elec. Ord.	10	15	61/-		4	18	4
Power	71	71	37/-		4	1	1	Assoc. Elec. :			,				
Llanelly Elec	6	6	26/6		4	10	7	Ord	10	10	51/6	+6d,	3	17	4
Lond.Assoc.Electri	ic 3	4	26/-		3	1	6	Pref	8	8	39/-		4	2	0
London Electric	6	6	30/6		3	18	8	Automatic Tel.&E	1.128	121	61/	+6d.	4	2	0
LondonPowerRed.								Babcock & Wilcox	11	11	49/6	10	4	8	9
Deb	5	5	1031		4	16	7	British Aluminium	10	10	47/-		4	5	1
Metropolitan E.S.	8	8	44/-		3	12	9	British Insul. Ord.	20	20	51	+ 10	3	14	6
Midland Counties	8	8	41/6		3	17	0	British Thermosta	t.						
Mid. Elec. Power	9	9	44/6		4	1	0	(5/-)	188	181	20/-		4	12	6
Newcastle Elec	7	7	31/6		4_	9	0	British Vac. Clean	er						
North Eastern Elec	с.							(õ/)	30	30	29/- x d	+6d.	5	3	ō
Ordinary	7	7	35/-		4	0	0	Brush Ord. (5/~)	8	9	10/9		4	3	9
7% Pref.	7	7	35/-		4	0	0	Burco (5/)	15	175	17/-		5	3	0
Northampton	10	10	50/-		4	0	0	Callender's	15	20	$5\frac{1}{4}$	• •	3	16	2
Notting Hill 6%								ChlorideElec.Stora	ge 15	15	87/6	• •	3	8	7
Pref. (£10)	6	Nil	$10\frac{3}{4}$					Cole, E. K. $(5/-)$.	10	15	33/-	+6d.	2	5	G
Northmet Power :								Consolidated Signa	1 24	275	61		4	3	6
Ordinary	7	7	-43/6		3	-1	4	Cossor, A. C. $(5/-)$	710	10%	25/6	+6d.	I	19	4
6% Pref.	6	6	30/6	• •	3	18	8	Crabtree (10/-)	175	178	41/-	•••	4	Ð	4
Richmond Elec.	6	6	26/-		4	12	4	Crompton Parkins	on	0.01	0.01		D	~	2
Scottish Power	8	8	40/6		3	19	0	Ord. $(\mathfrak{d}/-)$	20	228	32/-		3	4	J C
Southern Areas	5	ő	23/-	• •	4	7	0	E.M.I. (10/-)	- tj 7.0	8	30/	+0	2	3	0
South London	7	7	29/-		4	16	4	Elec. Construction	101	136	01/- 61	• •	*	9	9
West Devon	ē	G	23/6		4	0	1	Ennelia Caule Ord.	128	123	50/6	•••	2	10	0
West Glos.	42	3호	20/-	+60.	2	10	5	English Electric	10	15	91/2	••	2	10	8
iorkshire Elec	8	8	43/-		2	1-#	9	Emission Tal (5/-)	998 998	200	51/3		1	19	1
	D	ublic Rea	rde					Errer Beady (5/-)	40	40	41/-	•••	ī	17	ä
Control Electricity								Falk Stadelmann	71	74	34/6	• •	4	7	0
1955_60 (Cimil	-							Ferranti Pref.	7	7	31/3		4	9	7
Defence)	3	3	100		3	0	0	G.E.C. :							
1955_75	ŭ	5	1144		4	7	4	Pref.	61	63	32/9		3	19	4
1951-72	11	41	107		4	4	1	Ord	171	171	93/3		3	15	1
1062 03	21	31	1041		3	7	0	General Cable (5/-) 15	15	15/-		õ	0	0
1071_01	31	24	100	10	3	5	0	Greenwood& Batley	7 15	15	43/9		6	17	0
London Elec Tran	nd of	~ <u>4</u>						HallTelephone(10/-	-)121	121	31/-		4	0	8
Ltd	21	21	981		2	10	9	Henley's (5/-)	20	20	25/6xd		3	18	8
London & Home	20							41% Pref	41	41	24/-		3	15	0
Counties 1955-7	5 41	41	112		4	0	4	Hopkinsons	15	171 .	69/3		õ	1	1
Lond Pass Trans F	3d.	12						India Rubber Pref.	53	51	23/-		4	15	9
A	47	43	1201	41	3	14	8	Intl. Combustion	30	30	63		4	10	8
B	5	5	1211		4	2	4	Johnson & Phillips	15	15	74/-	-1/-	4	1	0
0	3	31	68		4	15	7	Lancashire Dynam	0223	22불	96/6		4	13	õ
WestMidlands.I.E.	A.							Laurence, Scott(5/-	-)121	121	13/-		1	16	2
1948-68	5	5	1061		4	14	0	((continue	d on nex	t page)				

* Dividends are paid free of Income Tax.

	Dividend		Middle Price Rise		Y	Yield			Dividend		Middle Price	Rise	Yiel		ld
Company	Pre- vious	Last	Oct. 17	or Fall	p.c.		Company		Pre- vious	Last	Oct. 17	or Fall	p.e.		e.
Equipment and Ma	nufactu	ring (C	ontinued)							£	s.	d,			
					£s	5. d.		Bristol Trams	10	10	57/		3	10	2
London Elec. Wire	e 71	71	37/6		4	0 0		Brazil Traction	12	2	26 3 xd	- 1	7	-9	7
Mather & Platt	10	10	52/6	+ 1	3 1	6 2		Calcutta Trams	61	72	65/6	-2/-	2	5	9
Metal Industries (B) 8	83	50/6		3	76		Cape Elec. Trams	ā	6	25/6		4	14	1
Met.Elec.CablePre	f. 51	51	21/3		õ	3 6		Lancs. Transport	10	10	45/6		4	8	0
Murex	20	20	95/-xd	++	4 .	4 4		Mexican Light :							
Pye Deferred (5/-)	25	25	33/9		3 I	4 5		1st Bonds	5	5	1051		4	14	9
Revo (10/-)	171	171	40/-		4	7 6		Rio 5% Bonds	5	5	1061		4	14	0
Reyrolle	12 §	123	70/-	-1	3 1	I 5		Southern Rlv. :							
Siemens Ord.	71	74	35/-		4	5 9		5% Prefd.	5	5	75	+1	6	13	A
Strand Elec. (5/-)	10	121	10/9	+21-	5 1	6 3		5% Pref.	5	5	7144	1-	4	7	A
Switchgear & Cow-			,_	,				T. Tilling	10	10	60/-		3	6	9
ans (5/-)	20	20	18/6	-6d.	5	8 1		West Riding	10	10	46/-		A	7	0
T.C.C. (10/-)	5	74	22/6	U.L.	3	6 8		WOOD TEIGTED	10	10	101		*		0
T.C. & M.	10	10	56/-		3 1	1 6		T	elegraph	and Te	elephone				
TelephoneMfg (5/-	9	q	11/6		2 1	6 3 • •		Anglo-Am. Tel :	0 1						
Thorn Elec. $(5/-)$	20	20	25/~		4			Pref.	6	6	123		4	17	7
Tube Investments	20	20	95/6		Ā	2 Q		Def	11	11	30		5	0	0
Vactric (5/_)	20	991	16/0		°±	00 00		Anglo-Portuguese	8	8	28/-	_	5	14	đ
Veritys (5/-)	71	71	Q/	~ ~	4 1	0 J 2 D		Cable & Wireless :							-
Walcall Conduito(4	1 355	6 <u>9</u> 5 5	50/	103	4 1	0 0		51% Pref	53	54	115	-1	A	15	10
Ward & Coldstone		00	<i>b0/</i> –	ou.	4	8 U		Ord	4	4	81	_1	A	10	10
(5/)		20	201					CanadianMarconis	a xa	Anto	Q/		~	10	3
WortinghomeoDaub	20	20	30/~	4.4	3	6 8		Globe Tel & Tel		300.025	01				
Westinghouse Brak	e 12g	14.	10/-		3 1	1 X		Ord Ord	016	5.0	20/ =7		0	7.7	
west, Allen (o/-)	· 12	金	7/6	- 3d.	5	0 0		Druf	C C	6	20/Cad	123	2	10	4
1	raction	and Tu	ransnort			Great Northern To	1	0	30/0XU	+au,	a	10	9		
Anglo-Arg Trans	mappin		(PIO)	N743	NT CI	20									
First Prof (65)	NI	NH	9/6					(210)	13.18	DAT 11	00				
4% Inc	NU	Nil	71					Managai Maning	NII 71	1811	212	< +	,		,
Brit Elec Tratio	n i	NII I	12		-			Marcom-Marine.	7.0	10	36/-	11	4	3	4
Dof Ord	45	45	1102		0 1			Unental Tel. Ord.	16	10	-/06	1.2	-		
Drof Ord	10	10	1139	***	3 1	94		Telephone Props.	NII	6	21/3±d		5	13	0
r rei. Ord	8	8	180		4	9 0		Tele. Rentals (5/-)	10	10	11/9		4	5	0

Dividends are paid free of Income Tax.

Stocks and Shares (Continued from page 572)

a yield at that price of £5 6s. 6d. per cent. The margin of protection for the preference dividend, as measured by last year's profits, is somewhat thin. The annual meeting is to be held on November 2nd, and a shareholder, Mr. J. E. Elwyn Jones, has notified his intention of proposing a revision of the Trust's capital structure. This the same gentleman has done on two previous occasions, the proposal being defeated each time. There would seem to be no greater necessity at the present time for a change to be made than there was when the earlier proposals were put forward.

Calcutta Trams

The directors of the Calcutta Tramways Company prudently hesitate to express any view as to the price which the company will be paid by the Calcutta Corporation when the latter takes over the tramway undertaking next January. The chairman said at the meeting last week that the purchase money cannot be ascertained until the current year's results are known, because the price will be based on figures of income and working expenses over a period of years. It appears that the Calcutta Corporation's contract refers only to a part of the Calcutta Tramways undertaking, and that a portion of the system lies outside the agreement. Presumably the whole of the system necessary for the Calcutta Corporation to acquire control of the tramways will be included in the transaction. The shares have dropped back to 65s. 6d. at the prospect of the sale negotiations being delayed by possible need of legislation to confirm them.

Isle of Thanet

The interesting part about the offer of Margate and Birchington to purchase the undertaking of the Isle of Thanet Electric Supply Company is, in the first place, whether the Electricity Commissioners will approve the transfer, and, in the second, provided they give their consent, at what price the preference shares will be paid off. The basis of purchase is known already, but whether the preference holders will receive more than the par value, 20s., for the shares is a matter for doubt. Curiously enough, no provision was made in the original articles for this contingency, and it remains to be seen whether the preference are paid out at a higher price than 20s. if the sale goes through. The question of principle involved is one of importance to many companies. . .

1

- ----

and and

金田

1 Be

11 11

「日日日」

たの

日田田

NEW PATENTS

Electrical Specifications Recently Published

The numbers under which the specifications will be printed and abridged are given in parentheses. Copies of any specification (1s. each) may be obtained from the Patent Office, 25, Southampton Buildings, London, W.C.2.

A UTOMATIC Telephone & Electric Co., Ltd., and E. E. Comfort.—"Automatic switches as used in telephone or like systems." 4688. March 23rd, 1943. (564431.) A. F. Bound and A. Rankin.— Electricity

generating plant, particularly adapted for use in train control systems." 4612. March 22nd, 1943. (564429.)

1943. (564429.)
British Insulated Cables, Ltd., and W. C.
Handley.—" Terminal arrangement for electric condensers." 9046. June 5th, 1943. (564455.)
British Insulated Cables, Ltd., London Passenger Transport Board, J. Holland and H. J. Powell.—" Tool for straightening or bending metal wire, tube, bar and the like." 7079.
May 5th, 1943. (564401.)
British Thompson Houston Co. Ltd. " Dish

May 5th, 1943. (564401.) British Thomson-Houston Co., Ltd.—" Dish-washing apparatus." 10751/43. July 3rd, 1942. (564470.) "Terminal structures for electric lamps." 5474/43. April 9th, 1942. (564493.) "Gas turbine power plants." 10672/43. July 1st, 1942. (564498.) " Electron-discharge cir-cuits." 11151/43. July 11th, 1942. (564504.) "Switching mechanism particularly suitable for electric discharge lamps." 11775/43. July 21st, 1942. (564531.)

British Thomson-Houston Co., Ltd. (General Electric Co.).—" Electric valve converting apparatus." 4773. March 24th, 1943. (564396.) E. G. Budd Manufacturing Co.—" Protective systems for electrical apparatus." 10702/43.

July 4th, 1942. (564469.) Chamberlain & Hookham, Ltd., S. James, E. A. Webb and W. F. Braines.— Totalising E. A. webb and W. F. Branes.—" Iotalising means for use with a group of electricity meters or other electrical instruments." 8411. May 26th, 1943. (564453.) E. K. Cole, Ltd., and J. N. I. Evans.— "Fluorescent low-pressure mercury vapour electric discharge lamps." 7227. May 7th, 1943. (564449.)

1943. (564449.)

1943. (564449.)
E. S. Conradi.—" Electric coupling devices, particularly of the plug-and-socket type, and anchoring means therefor." 621. January 13th, 1943. (564419.)
L. P. C. J. Dudley and R. L. Mansi.—
"Methods of and means for making stereoscopic bacteries of an device of the plug.

X-ray photographs." 4908. March 26th, 1943. (564490.)

J. Forman and Pye, Ltd.—" Radio range-finders and altimeters." 3045. March 6th, 1941. (564505.)

Frigidaire, Ltd., and F. A. S. Abbott.— "Household refrigerator." 6480. April 22nd, 1943. (564398.)

Frigidaire, Ltd., W. B. Daniels and F. A. S. Abbott.—" Refrigerator." 4729. March 23rd, 1943. (564433.)

General Electric Co., Ltd., and H. C. E Jacoby.—" Electric suction cleaners." 9347 9347. June 10th, 1943. (564459.)

P. S. Harper and Harper Automatic Machine Manufacturing Co., Ltd.—" Coin-operated elec-tric switch." 15937. November 11th, 1942. (564479.)

S. I. Hitchcock.—" Permanent magnets." 18278. December 23rd, 1942. (564508.) S. R. R. Kharbanda and Pye, Ltd.—" Com-bined television and sound systems." 320. January 7th. 1943. (564511.) Landis & Gyr Soc. Anon.—" Maximum-demand measuring device." 17742/42. Decem-ber 15th, 1941. (564482.) J. Lucas, Ltd., and H. E. Whitehouse.—" Fly-wheel magnetos." 4601. March 22nd, 1943. (564428.)

(564428.)

(564428.) Marconi's Wireless Telegraph Co., Ltd., and E. Green.—" Radio beacons." 4866. March 25th, 1943. (564445.) Marconi's Wireless Telegraph Co., Ltd., and G. I. Hitchcox.—" Automatic gain control systems for radio receivers." 4865. March 25th, 1943. (564444.) Morris Motors, Ltd., R. J. Brown and J. H. Bridle.—" Electromagnetic apparatus for use in the examination of ferrous articles." 8049.

May 20th, 1943. (564451.) Mullard Radio Valve Co., Ltd., R. G. Clark and L. M. Myers.—"Electron-discharge tubes."

and L. M. Myers.—" Electron-discharge tubes." 11689. August 19th, 1942. (564441.) J. F. O'Brien.—" Operating means for electric switches." 4925'43. March 26th, 1942. Addition to 544435. (564491.) Philco Radio & Television Corporation.— "Cathode-ray television tube." 4414'43. March 30th 1942. (564425.)

30th. 1942. (564425.)

Radio Corporation of America.—" Current control systems." 4497 43. March 24th, 1942. (564427.)

A. I. Rochmann.—" Electrically heated solder-ing irons." 461. January 9th. 1943. (564388.) Standard Telephones & Cables, Ltd.—

" Method of reclaiming selenium elements of the

W. E. Stilwell, jnr.—" Overhead protective electromagnetic switch." 4845 [43. March 12th,

1942. (564443.) W. W. Triggs (Akt.-Ges. Brown, Boveri & Cie).—" Apparatus for the transmission of messages." 9880,41. April 13th, 1943. Con-

vention date not granted. (564475.) W. W. Triggs (Philips-Lampen Akt.-Ges).— "Electrical remote control." 8059. June 12th,

1942. (564410.) United States Rubber Co.—" Insulated electrical conductors and method of making the same." 10762/43. August 5th, 1942. (564471.) Western Electric Co., Inc.—" Electron-dis-charge devices." 6390/43. April 21st, 1942.

(564494.)

Westinghouse Electric International Co.— "Electrical measuring systems for X-ray apparatus." 10903/43. July 4th, 1942. (564500.) "Method of producing corrosion-resistant phosphate coatings on metal and alloy metal surfaces." 3661/43. March 6th, 1942. (564521.) "Method of producing compositions for activating metal and alloy surfaces to improve the vating metal and alloy surfaces to improve the process of forming corrosion-resistant phosphate coatings thereon." 3662/43. March 6th, 1942. (564522.) "Electric current conversion sys-tems." 11620/43. August 8th, 1942. (564530.) H. Ziebolz.—"Electronic translating devices."

16478,42. April 22nd, 1942. (564382.)

CONTRACT INFORMATION

Accepted Tenders and Prospective Electrical Work

Contracts Open

Where "Contracts Open" are advertised in our "Official Notices" section the date of the issue is given in parentheses.

Australia.—NEW SOUTH WALES.—November 2nd. Sydney County Council Electricity Undertaking. L.v. feeder voltage regulating transformer. Spec. 717. QUEENSLAND.—November 15th. Motor-

driven and turbine-driven boiler feed pumps. Spec. 375. City Electric Light Co. Ltd., Boundary Street, Brisbane.

Lanark.—County Council. Various works, including electric lighting, in eight houses; S. McColl, county housing architect and engineer, 29, Clydesdale Street, Hamilton.

Manchester.-October 23rd. Electricity Dept. Water cooling tower, mercury arc rectifier equipment, and traction switchgear. (October 13th.)

Montgomeryshire.-October 23rd. Education Committee. Electric lighting installation, etc., Bryn Street Centre, Newtown. Director of Education, County Education Offices, Newtown.

Portsmouth.—October 23rd. E epartment. 33-kV underground Electricity Department. cable. (October 13th.)

Orders Placed

Blackburn.—Corporation. Accepted. Electric motor and switchgear at Blackburn Sewage Works.—C. T. Briscoe & Son.

Hull.-Electricity Committee. Accepted. Ashhandling plant (£8,225).—John Thompson (Wolverhampton). Water softening plant (£709).—Permutit. Civil engineering works at Sculcoates power station (£37,698). Quibell & Son. High-pressure water fire-extinguishing equipment (£3,059).—Mather & Platt.

Newcastle-on-Tyne.—City Council. Accepted. Electrical repairs to Council houses (£160).— R. H. Patterson.

Salford. — Electricity Committee. 125-kW mercury-arc rectifier (£791).—Metropolitan-Vickers.

Contracts in Prospect

Particulars of new works and building schemes for the use of electrical installation contractors and traders. Publication in this section is no guarantee that electrical work is definitely included. Alleged inaccuracies should be reported to the Editors.

Anglesey.—Intermediate school, Amlwch, for E. C.; J. E. Rees, county education architect, Glanaber, Llangefni, Anglesey.

Chesterfield.-Works - additions, Sheffield Road; Brocklehurst Motors, Ltd.

Ealing.—Additions and alterations, Uxbridge Road, for V.A.B. Products, Ltd.; W. H. Read & Co., architects, Haven Green, W.5.

Frodsham.-Extensions to homes; superintendent National Children's Home and Orphanage, Beaconshurst, Netherton, Frodsham, via Warrington.

Hebburn-on-Tyne.-Canteen for the Bushing Co., Ltd.; Alex. Anderson, Ltd., Stanmore Road, Newcastle.

Office extensions for A. Reyrolle & Co., Ltd.; Alex. Anderson, Ltd., Stanmore Road, Newcastle.

Jarrow-on-Tyne.--Factory, for the Jarrow Boiler & Welding Co., Ltd.; G. W. Smith, Wansbeck Road.

Manchester.—Tuberculosis sanatorium, Wy-thenshawe; G. Noel Hill, city architect, Town Hall, Albert Square.

Moston.--Moulding shop and kiln bay at works, St. Mary's Road; W. Thorpe & Son, Ltd., Chester Road, Cornbrook, Manchester, 16.

Newbiggin (Northumberland).—Houses (10) for Northumberland Aged Miners' Homes Associa-tion; W. Dixon & Son, architects, Collingwood Street, Newcastle.

Newcastle-under-Lyme. — Dairy, Hempstalls Lane, for Associated Dairymen (Staffs.) Ltd.; Adams & Edwards, architects, 3, Brook Street, Stoke-on-Trent.

New school for managers of St. Giles' and St. George's School; Rev. C. J. Watkins, Seabridge Road

Newcastle-on-Tyne.-Reinstatement of Muscott Grove School; city estate and property surveyor, Town Hall.

Northumberland.—School kitchens: Bam-burgh C.E.; T. Gardner, Berwick. Beadnell C.E.; T. B. Gregory, Seahouses. Carham Wark; Patterson Bros., Branxton. Seghill Infants'; J. M. Reid, Seaton Delaval. Slaley Council; M. Hogarth & Son, Corbridge. New-ton-on-the-Moor Council; J. G. Green & Son, Warkworth.

Oxford.-Houses (10) Quarry High Street, Beaumont Road and Purcell Road; J. A. Pye, Ltd., builders.

Rowley Regis.-Rebuilding ten houses; City Road, Tividale; borough engineer, Municipal Buildings, Old Hill, Staffs.

Sheffield.—New church and (£18,000); Rev. P. Tuckwell, St. parsonage Tuckwell, St. Cyprian's, Frecheville, Sheffield.

Sunderland.—Alterations, Hendon Road, for St. John's Maltings, Ltd.; Page, Son & Brad-bury, architects, King Street, South Shields.

Swindon.-Waterworks (£17,500); borough engineer.

Tynemouth.—Premises, new trading estate; Flemings, cleaners, Newcastle; De La Rue Plastics, Ltd.; Linklaters, patent ship fittings; North Shields Co-operative Society bakery; Charles Clay & Co., clothing manufacturers; Knitwear, woollen goods manufacturers; Welch & Sons, Ltd., confectionery manufacturers.

Warrington.—Additions to tannery; Union Tanneries, Ltd., Holmefield Tannery.

Two secondary schools ; J. Y. Hughes, borough surveyor, Municipal Buildings, Bank Park.

Wellington.—Ambulance station, Donnington, for R.D.C.; J. B. Cooper, architect, 177, Corporation Street, Birmingham.

h

A Spire assembly is a tight assembly—and nobody need trouble to send us any jokes about the word 'tight'. It's no joke fumbling and fitting washers and nuts on to invisible bolts. It's no joke knowing that the things will probably shake loose anyway inside a few weeks. If you use a Spire fixing these worries disappear along with the nuts and washers. There are a few thousand firms making motor vehicles and radio sets and hundreds of other products who know that for light assembly Spire means strength. If you don't know but would care to find out, send us your drawings or the parts of an assembly. We'll see what Spire can do and let you have the answer in a couple of weeks—more or less.



-THAT'S Fixed THAT!

Here's aSpire Nutofthe Utype that is doing noble work for cerned with cable assembly. The NU 1381 replaces the normal nut and washer used for holding the cable close on perforated cable trays. The U fixing makes such blind assembly easy. The Spire Nut slips into position gripping the tray and there it is, ready — no more fumbling about with a nut that you can't see.



through SPIRE

A BETTER way of fixing

Simmonds Aerocessories Limited · Great West Road · London · A Company of the Simmonds Group

October 20, 1944



11

R

6

Ū.

T

1

I

ø

45



CONNOLLY'S Super ENAMELLED WIRE

VIBRATION PROOF FUSES

To those interested in 5-100 Ampere size fuse units for any purpose whatsoever, but particularly for positions subject to vibration, the SLYDLOK fuse answers all problems. Get your name on our mailing list for advance information of new developments as they are available.



dm1168





SHUTTERLOCKED SWITCH

ົ

Sanders exclusive "Shutterlock "feature prevents access to the live Socket tubes by locking the Shutter while the Switch is in the "on" position. The plug can be withdrawn with the Switch in either position. For the highest-class installations these Switch Sockets represent the ultimate in safety and refinement.

SANDERS

WM. SANDERS & CO. (WEDNESBURY) LTD., WEDNESBURY, STAFFS.

October 20, 1944



RESISTANCES

Although present circumstances render it difficult for us to give our pre-war service to all customers we are still working in their interests.

New materials and manufacturing processes which we are now using to increase output also contribute in large measure to improved performance and reliability of our products. Thus, when normal times return, all users of Berco Resistances will benefit by our work to-day.

THE BRITISH ELECTRIC RESISTANCE CO. LTD. QUEENSWAY, PONDERS END, MIDDLESEX Telephone : HOWARD 1492. Telegrams : "VITROHM, ENFIELD."

R.1.



C.M.CHURCHOUSE LTD.

CLARENDON WORKS, CLARENDON CROSS, LONDON, WIL Telephone PARK 8517-8 Telegrams: "LITEFITINS NOTARCH AN ANNOUNCEMENT BY HOOVER LIMITED

During the war, the manufacture of the Hoover, the World's Best Cleaner, has of course ceased.

Instead, the whole of our resources, very considerably extended, have been devoted to the manufacture of many types of electrical machines, produced in very large quantities, including Rotary Transformers.

For obvious reasons we are not able to give full details of the wide range of these products, but it can be said they have fulfilled a large variety of purposes. The experience thus gained during the war will be at the disposal of all demanding precision engineering both for postwar Home and Export Trade.



Limited

Manufacturers of the World's Best Cleaner PERIVALE · GREENFORD · MIDDLESEX

The BULBS that give nice blooms

VOU can grow a useful crop of £££'s if you follow these simple instructions. Plant out with the finest "bulbs " you can get-Ekco Lamps-(as they say in the Catalogues "No Better Quality Anywhere * * * * "). You'll find that they will be well "fertilised " with forceful publicity. The results will surprise and delight you ! But you must start now with a little spadework-write at once for details of the Ekco Lamp proposition. A new simplified discount system is now operating. Saves time, prevents headaches !

YOU CAN T DO

BETTER THAN

INVEST IN

EKCO LAMPS

E. K. Cole, Ltd., Lighting Division, Ekco Works, Southend-on-Sea

For the MANUFACTURE of LAMINATED SHEETS and

TUBES

16-17 NEW BRIDGE STREET

ELMET

ARCING

CONTACTS

Write .

or ring : ABBEY 1939

October 20, 1944

Impregnated and Coated)

COPELMET (Copper-tungsten)

AND SILVELMET

(Silver-tungsten)

42 PALL MALL, S.W.I

For Switchgear and Circuit-breakers operating

in air or under oil.

COMPOUND ELECTRO METALS LTD.

Makers of Synthetic



50

It's EASY to telephone in this ACOUSTI-BOOTH

Put your shop phones in Burgess Acoustibooths and you'll be able to hear clearly in spite of nearby noise.

There are no doors because no doors are needed. Patented sound-absorbing walls soak up factory noise and provide a "zone of silence" for easy telephoning.

Open construction makes these booths easy to keep clean and obviates any ventilation problem. Hundreds of these doorless booths are in constant use in all types of factories. Write for Bulletin BP.131/E.R.

BURGESS ACOUSTI-BOOTH

BURGESS PRODUCTS CO. LTD. Acoustical Division, HINCKLEY, LEICS. Phone : Hinckley 700 (3 lines) London Office : 72 Horseferry Road, S.W.I Phone : ABBey 1868 Soottish Representatives : R. MoCartney & Co., 142 Queen Street, Glasgow, C.1



I,000-kVA Power Transformer for a Dominion Government PLEASE ADDRESS ENQUIRIES TO : Grams : "Vitrohm, Enfield"

Phone : Howard 1492

ET

10

SUT

31

QUEENSWAY, PONDERS END, MIDDX.

AXÚN

October 20, 1944

MOTORS Fractional H.P. and Geared Motor Units; Synchronous Motors Unlimited range. Unique features. 25 years' leadership.

Accent on Quality

SIGNALS Industrial & Marine Warning Signals. Indispensable to safety and efficiency ashore and afloat. Types to meet all conditions.

ELECTRICAL PRODUCTS

KLAXON, LTD., 201, Holland Park Avenue, London, W.11.



PERFORATED METALS

Perforated Lead for Batteries CABLE-TRAYS AND BENDS FOR ELECTRICAL WIRING

TRAY BEND W. BARRNS & SON (Established 1860) CLOBE WORKS, QUEENSLAND ROAD HOLLOWAY, LONDON, N.7 Telephone : NORTH 3347/8 Telegrams : "PERFORATION, HOLWAY, LONDON "

Unusual Undertakings



by the Tank People"

THE illustration shews pontoons built of standard Braithwaite Pressed Steel Tank Plates being used to float into position the main spans of a bridge in India. This is yet another example of the unusual purposes to which the Braithwaite method of sectional construction has been applied. Tanks for special uses and all normal liquid storage needs are fully described in the latest Braithwaite brochure. You are invited to apply for a copy.



BRAITHWAITE & CO. ENGINEERS LTD., 45 KINGS HOUSE, HAYMARKET, LONDON, S.W.1 . TEL.: WHILEBARD 3993

October 20, 1944



-1

FOR nearly half a century we have been making apparatus for the removal of dust and grit from every kind of building, by large or small fixed plants or portable cleaners. B.V.C. installations have solved the dust problem in factories, workshops, warehouses, public buildings, and have helped to produce greater efficiency and more healthful working conditions. If dust is your problem, the solution is its removal by B.V.C. plant. We welcome enquiries from responsible executives.

We specialise in Dust Control Systems for the Electrical Industries

THE BRITISH VACUUM CLEANER & ENGINEERING CO. LTD. (Dept. 4B) - GOBLIN WORKS - LEATHERHEAD SURREY Telephone : Ashtead 844

Maxers of the famous GCBLIN ELECTRIC CLEANERS



M. K. E L

ELECIKIC EDMONTON N.IB

ELECTRICAL REVIEW



LTD.

86 & 88 of 1939/40 catalogue.

M.K. 007

55

56

October 20, 1944



Disabar 20, 1944

)(

10.15

2001

ILEY

NG

TŠ

TIMELAGS

The important part in so many processes played by delayed action timing mechanisms, has led to a demand for much greater accuracy than is afforded by the Oil Dash Pot Method. Many engineers have found such problems completely answered by Rotherham Time Lags. For accuracy and reliability these ingenious instruments are worthy products of the famous House of Rotherham & Sons of Coventry.

Details of the various types available, and also of Instruments, Recording Clocks, etc., will gladly be supplied on request. We also welcome enquiries or Wheels and Pinions, but these can only be supplied in quantity to customers' own designs as no stock lines are held.

ROTHERHAM & SONS LTD. COVENTRY. Tele. : 4154 PRECISION MANUFACTURERS SINCE 1750

fine finishes with speed in production for Post War requirements PLAN NOW! Consult us on -FREE AIDS to Processing, Mechanical Handling and Infra-Red Stoving - etc

57

ELECTRICAL REVIEW

Fine Finishes

DONALD MACPHERSON & CO. LTD. Albion Street, Manchester 1 and Mitcham, London

The post-war SADIA

In the near future, the housewife will demand hot water in any part of the house. The new SADIA Type UDB (Under Draining Board) is the reply to that demand. It combines two heaters into one.

(1) It provides hot water ready for use as required, whether it be a few gallons at the sink or a full bath.

(2) Simple to install: it can work with an existing bot water system.

(3) It can be placed "Under the Draining Board" or in a cuphoard out of sight, saving space where space is valuable.

(4) It needs the minimum of maintenance: the SADIA once fitted can be forgotten.

(5) It is economical of current and therefore cheap to run. It has the highest efficiency yet attained in electric water heaters.

The SADIA Type **UDB** will be available in two sizes, 15 gallons and 20 gallons capacity, for installation in post-war homes. Write for further particulars.



At ¹/₂d. per unit it compares favourably with any other type of water heating.



 Aidas Electric Limited, Sadia Works, Rowdell Rd., Northolt, Middx. Phone: WAXlow 1607.
 Scottish Agents: W. Brown & Co. (Engineers) Ltd., 89 Douglas Street, Glasgow, C.2.







INSTRUMENT WORK METER TEST ROOM AND REPAIR WORK ETC. We are always ready to advise upon the adaptation of Pultra Lathes to meet special requirements.

for WATCH, CLOCK AND

Write for Catalogue CA4.

24 GRAVEL LANE

SALFORD 3

MANCHESTER

Phone BLA 9181

Micro-Capstan Lathe Model HU 42 Centre Height: 50 mm. Spindle Bore: 10 mm. Speed Range : 400 r.p.m. to 6,000 r.p.m. for motorised model. British Made to highest International Standards

MANY ACCESSORIES AVAILABLE



IN! OUT! IN! OUT!_ thousands of times. This machine, designed and made in the Wylex works, simulates the action of actual usage of a Wylex plug in its socket, and does it thousands of times more than in a normal life-time. These tests are one reason why

"Wylex must be good

GEORGE H. SCHOLES & CO. LTD. WYLEX WORKS, WYTHENSHAWE, MANCHESTER Tel: Wythenshawe 2251/2 Grams: "Kilowatt," Manchester.

WINDING

EVANS LIFTS

EVANS LIFTS LTD. HEAD OFFICE --LEICESTER 61138 LONDON VIC. 6713

> AS suppliers of Waxes and De-Government specifications to the leaders in the Electrical Industry, we have established a reputation second to none for our





Consult us -Tempie Bar 5927

As specialists in the manufacture of Wates, our Research facilities are at the disposal of those who require a Wate for any technical purpose. Our Wates are used for Service components.

ALD. AND CLEME TYPE APPROVED FOR ARCTIC AND TROPICAL CONDITIONS.





MANUFACTURING ELECTRICAL ENGINEERS

LEGG (Industries) LTD., WILLIAMSON ST., WOLVERMANPTON





ACCURACY IN LEAD SHEATHING. The lead sheathing of Crompton Paper Cable is extruded by presses such as this—one of the largest of its kind in the country. A high standard of accuracy in the radial thickness and concentricity of the lead sheath is maintained by this press and its associated equipment. Crompton Cables comply with the specifications of the British Standards Institution, Government Departments, and of the Cable Makers Association—of which we are Members.



WRITE CATALOGUE ER/201 Öctober 20, 1944



CONVERANCE BY AIR Faced with the problems of wood refuse removal, and the need for fuel economy, a large factory installed a special Airscrew System. Refuse is collected from various workshops, including an adjacent factory, involving long runs of ducting and the spanning of a roadway. No mechanical conveyors are used ; the refuse is airborne throughout the system. Cyclones separate the refuse which is fed to two water tube boilers through specially designed hoppers and damper controls.

> Approximately 10 tons of refuse are conveyed daily, saving about £10,000 in fuel per year. On a peak load this is considerably increased.

> This is one of many Airscrew Fan Systems designed for the economical removal and collection of valuable salvage.



CONSTRUCTORS LIMITED CONSTRUCTORS AND BE SURE AND BE SURE CONSTRUCTORS AND DURAWIRES DURATUBE & WIRE LTD COUSTORS AND DURAWIRES LIMITED CONSTRUCTORS AND BE SURE CONSTRUCTORS AND DURAWIRES LIMITED CONSTRUCTORS AND BE SURE CONSTRUCTORS AND DURAWIRES LIMITED CONSTRUCTORS AND BE SURE CONSTRUCTORS AND DURAWIRES LIMITED AND BE SURE AND BE SURE AND DURAWIRES AND DURAWIRE

GRELCO Ltd., Greico Works, Honcott, Minehead, Somersel

Fully illustrated descriptive folder on application

ELECTRICAL PRECISION INSTRUMENTS FOR AIRCRAFT

THE RECORD ELECTRICAL CO LTD. BROADHEATH-ALTRINCHAM-CHESHIRE











ELECTRICAL REVIEW

65

"It Pays to Standardise"

DIE SET BUSHES

Tel. Hinckley 695-6



Groms: Aeroports, Hinckley.

Cosen

October 20, 1944

COUPLINGS

The simplest form of flexible coupling for transmitting rotary movement is shown above.

PATENTEO

The Metalastik rubber-to-metal weld permits the transmission of heavy loads, with a torsional cushioning effect which extends over an appreciable angle. Note the 'V' section which gives uniform stress. These couplings are used for many purposes and can be supplied with natural or synthetic rubber of various degrees of flexibility; and in any ordinary metals, including light alloys.

Other Metalastik couplings shown are — on the left, the 'ZPU' type: on the right, the 'ZVS', both have vanes which give a positive drive beyond a certain deflection and are capable of accommodating angular and parallel mis-alignment. All these patent couplings are of great value in damping out torsional vibrations, in fact many of them are used expressly for this purpose where all other expedients have failed.

METALASTIK

METALASTIK LTD . LEICESTER

METALASTI

Ι





This illustration shows W. & G. Switch Lampholders, some of many types of insulated Switch L a m p h o l d e r s supplied with and without porcelain interior.

A wide and comprehensive range of electrical accessories is available to customers for National Service.

WARD& GOLDSTONE LTD. PENDLETON, MANCHESTER, 6

Dependability is the keynote of the design and construction of Scott motors.

SCOTT OF BE

Under present-day conditions of continuous performance and constant effort, every model can amply justify its title of one of "Britain's best motors."

Every size from $\frac{1}{2}$ H.P.-250 B.H.P. conforms to the same standard of quality.

We are now in a position to despatch ex-stock 3-phase squirrel cage motors up to 25 b.h.p.

Scott motors

HUGH J. SCOTT & CO. (BELFAST) LTD., Volt Works, Ravenhill Rd., Belfast, N. Ireland

October 20, 1944



complete rectifier sub-station of unit construction

— comprising a rectifier, transformer and switchgear on



one base to provide a D.C. supply wherever it is wanted. The unit can be put down in a corner of a yard, works or other convenient place and connected directly to an A.C. supply.

PLEASE GIVE

SIMPLE, QUICK AND INEXPENSIVE ERECTION AND INSTALLATION The Rectifier is completely screened.

WRITE for illustrated Technical Description No. 353

Advt. of The General Electric Co., Ltd. Head Office : Magnet House, Kingsway, London, W.C.2

sity 7 the noise received with received with

SITU!

Ser Low Saint 1

HUITY

ilan

Hall.

good drical drical

ELECTRICAL REVIEW

CLASSIFIED ADVERTISEMEN'

ADVIRTISEMENTS for insertion in the following Friday's ssor are accepted up to First post on Monday, at Dorset House, Stamford Street, London,

S.E.1 THE for advertisements in this section, is ne (approx. 8 words) per insertion, minimum 2 in the minimum of one inch. Where the advertisement includes a Box Number there is an addition under this heading can be obtained for the price of two if ordered and prepaid with the first insertion.

REPLIES TO advertisements published under a Box Number if not to be delivered to any particular firm or individual should be accompanied by Instruc-tions to this effect, addressed to the Manager of the ELECTRICAL REVIEW. Letters of applicants in such cases cannot be returned to them. The name of an advertiser using a Box Number will not be disclosed. All replies to Box Numbers should be addressed to the Box Number in the advertisement, c/o ELECTRICAL REVIEW, Dorset House, Stam-ford Street, London, S.E.I. Cheques and Postal Orders should be made payable to ELECTRICAL REVIEW LTD, and crossed.

Original testimonials should not be sent with applications for employment.

SITUATIONS VACANT

ASHFORD (KENT) URBAN DISTRICT COUNCIL

Appointment of Chief Electrical Engineer and Manager

A PPLICATIONS are invited for the above appointment from engineers not exceeding 45 years of age, who are experienced in the management and administration of the same of the same of the same of the same made by the National Joint Committee of Local Authori-tion of the Same of the Same of the same of the same same of the Same of the same of the same of the same same of the Same of the same of the same of the same type of the same of the same of the same of the same of the the comment Superannuation Act. 1937, and the person superimed will be required to pass a medical examination. Applications, with copies of two recent testimonials and saticulars of age, education and experimee, to be returned to the undersigned not later than Monday. 30th October. 1944.

1944.

Canvassing, either directly or indirectly, will disqualify

The Cedars, Church Road, Ashford, Kent.

J. SUDLOW, Clerk to the Council.

COUNTY BOROUGH OF HUDDERSFIELD

Electricity Department

Appointment of Deputy Borough Electrical Engineer

A PPLICATIONS are invited for the position of Deputy Borough Electrical Engineer at a salary of £750 per annum, plus war bonus, at present £33 165. per annum. The appointment will be subject to the Local Govern-ment Superannuation Act, 1937, and the successful appli-cant will be required to pass a medical examination. Rowledge of the operation of a large Power Station. Keetifier Substations and Mains Distribution Systems, will be required. The successful candidate will also be expected to generally assist the Borough Electrical Engineer in administrative work. Applications. endorsed Deputy Hornun Electrical

administrative work. Applications, endorsed Deputy Borough Flectrical Engineer, 'stating age and giving full particulars of tech-nical and practical training and experience, together with copies of not more than three recent testimonials, must be diverse to the understand not liter than 8th Normality of the adjoint literation. and will be a disqualification.

BAMUEL PROCTER. Town Clerk. 761

Town Hall, Huddersfield

15

E

00

CLERK required, male, as assistant to general manager, good pondence and figures, knowledge of electrical trade and export desirable but not essential. Letters only. 796

THE ASSOCIATION OF SUPERVISING

ELECTRICAL ENGINEERS

A PPLICATIONS are invited for the post of ORGAN-ISING SECRETARY at, a commencing salary of \$500 per annum.

Applicants should possess organising ability, works and contracting experience, good knowledge of the electrical industry and of trade union work, ability to speak in public, and have received an electrical engineering educa-tion. Successful candidate may be stationed in the Manchester district.

Applications, giving details of age, education, quali-fications and experience, should be sent to the General Secretary, A.S.E.E. Aldwych House, London, W.C.2, not later than October 31st, 1944. 783

A N old-established engineering firm, Midlands, requires the services of a Trained Technical Assistant to be responsible for tenders and contracts for steam turbines and condensing plants. Permanent position with post-war prospects. Pension scheme. Salary from £500 according to qualifications and experience. Applicants should write, quoting C.2188XA, to the Ministry of Labour and National Service. Room 432, Alexandra House, Kingsway, London, W.C.2, for the necessary forms, which should be returned completed on or before 31st October, 1944. 789 DEFUELOPMENT Engineer for investigation of pew

Completed on or before 31st October, 1944. 789 DEVELOPMENT Engineer for investigation of new applications of electric heat and power. Must have first-class technical education, initiative and ability to solve a wide variety of problems from first principles, also practical knowledge of equipment design. Experience with power co. or similar organisation desirable. State present salary and age, under 35 preferred. Our own staff have been advised. Location London.—Box 785, c/o The Elec-trical Review.

trical Review. The Action of the Manager to take complete control. Must have had previous managerial experience in established wholesale electrical concern. Box No. 746, Dorlands, 18/20, Regent Street, S.W.I. PLECTRICAL Plant Engineer, Important Lancashire chemical engineering textile firm, scheduled under chemical engineering textile firm, scheduled under remire thoroughly capable Electrical Engineer with first-class represented Work Orders, making extensions of plant, re-remire thoroughly capable Electrical Engineer with first-class represence of both L.T. and H.T. equipment. Good general and technical education equivalent to A.M.I.E.E. Age Commencing salary £450 approx, plus war-time allowance, the pay2XA, to the Ministry of Labour and National Service. Room 432, Alexandra House, Kingsway, London, W.C.2. for the necessary forms, which should be returned com-pleted on or before 2nd November, 1944. WYAR STANDARD Works, Manager for elec, mfg, and

pieted on or before 2nd November, 1944. 809 EXPERIENCED Works Manager for elec. mfg. and repair business in Midlands, conversant with small quantity manufacturing methods and machining speeds. motors and transformers up to 500 h.p., lifting magnets and magnetic clutches. Staff 50-60. Salary 5700 to 21,000, according to qualifications, continuing post-war with good prospects. Replies treated confidentially and Elec. Review advised if post filled within four weeks.—Box 794, c/o The Electrical Review.

S ALES Engineer Assistant, able to take charge of office S staff, correspondence, contracts, etc., required by West London firm manufacturing electrical measuring in-struments. Write, stating age, experience and salary required —Box 811, c/o The Electrical Review.

LARGE concern in the light engineering industry has post-war vacancies for Mechanical and Electrical Engineers, preferably with engineering degrees. Appli-cants, age about 30, should have experience in quantity production and sound general engineering and administra-tive knowledge, for supervisory positions in manufacturing departments. Applications will be considered from persons available at the cessation of hostilities. Write, stating age, full details of previous experience and salary required. to Box 782, c/o The Electrical Review.

SALES Engineer Assistant required for Glasgow branch of large manufacturing firm making heavy electrical equipment. State age, salary, experience.—Box 719, c/o The Electrical Review.

SALES Engineer for post-war development, manufacturers of lighting equipment, South England. State age, experience and salary expected.—Box 6380, c/o The Electrical Review.

Theal Review. SALES Representatives required for Atlas Electric Lamps. Remunerative position with excellent post-war pros-pects for keen, energetic men experienced in selling to large users, trade, municipalities, etc. Salary, commission and expenses. Write in confidence, with details of past experience, to-Box D.H.7, Thorn Electrical Industries, 105, Judd Street, London, W.C.1. [71]

105, 500d Street, London, W.C.T. (11) GWITCHBOARD Attendant required for steel works power station in North-East area. Musb be experienced in operation of E.H.T. switchear, synchronising and con-trol of turbo-alternators. Salary 2314 12s. per annum. Apply Manager, Employment Exchange, South Bank, Yorks. 779

Yorks. 779 SwitcHGEAR Engineer for Consultants. Applicants should preferably hold H.N.C. or better qualifications. have served apprenticeship, including D.O., with manu-facturer of H.V. switchgear, transformers, etc., and have a knowledge of transmission systems, power stalion lay-outs and short-circuit calculations. Location, Surrey. Salary £400 to £500, according to qualifications. Appli-cants should write quoting D 952XA, to the Ministry of Labour and National Service. Room 432, Alexandra House, Kingsway, London, W.C.2, for the necessary forms, which should be returned completed on or before 2nd November, 1944. 810 1944

1944. 810 TECHNICAL Manager (Electrical) required, to take in firm manufacturing F.H.P. and H.F. motors and appli-ances. The post requires a young electrical engineer not afraid of responsibility and prepared to keep abreast of the times. Firm employs 400 and post-war prospects are excellent. Write in first instance, stating experience, salary, etc. -- Box 805, c/o The Electrical Review.

APPOINTMENTS FILLED

Dissatisfaction having been so often expressed that un-successful applicants are left in ignorance of the fact that the position applied for has been filled, may we suggest that Advertisers notify us to that effect when they have arrived at a decision? We will then insert a notice free of charge under this heading.

SITUATIONS WANTED

A DVERTISER, energetic, 23 years' experience contract-ing, seeks position as Sales Representative, prefer London and South Coast.—Box 6376, c/o The Electrical Review

CHARTERED Electrical Engineer, A. M. I. E. E., CHARTERED Electrical Engineer, A. M. I. E. E., A.I. Mech. E., versatile technician with 15 years' in-dustrial experience. design, administration, planning, lec-turing, technical journalism, etc., seeks responsible and progressive position, immediate or post-war.—Box 6378. c/o The Electrical Review.

C of the Electrical Review. C LERK, age 38, ex-service, knowledge of showroom. Full parts, to-H. H. P., 1, Amberley Grove, S.E.26, 6364 D UBLIN Electrical Engineering Contractor open to act as Representative. Distributor. Assembler, or in maintenance capacity for electrical or mechanical manufac-turing engineers.- Box 6371, c/o The Electrical Review.

ELECT. Mech. Engineer-Foreman, 28 yrs. exp. con-struction, maintenance installations, steam and diesel plants, factory, ships, hospitals, home and abroad.—Box 6334, c/o The Electrical Review.

ELECTRICAL Engineer (45) seeks responsible post, 30 years' experience installation and maintenance. used to organising, planning, supervision, Government specs. Manchester area preferred. -Box 6345, c/o The Electrical Review

ELECTRICIAN desires position as Maintenance Engi-neer, age 46, disengaged, all round elec, experience, also commercial, refrigeration and air conditioning, -5. Lady Margaret Road, N.W.5.

E NGINEER (35) desires appointment to permanent progressive position, post war or immediate. Electrical. mechanical and administrative training, good general education, fluent French, A.M.I.E.E. examination. Experienced in supply distribution, plant manufacture and technical representation. Minimum salary 2500 p.a. Would consider investment.—Box 6343, c/o The Electrical Review.
 G RAD. I.E.E., public school, 29 years, requires progressive post, preferably on sales side, 6 years' experience of aircraft instruments and light engineering.—Box 6350, c/o The Electrical Review.
 P RODUCTION Control Manager desires change, experience enced all branches (progress, production planning).

Proportion of the second secon Revie

PROGRESSIVE Elec. Engineer and Designing Draughts-man are interested in Domestic Appliances. etc. Free to accent outside development work. Any other sugges-tions welcomed. — Box 6311, c/o The Electrical Review.
 PROGRESSIVE young man desires Foreman's or Mana-ger's position in fluorescent lamp or neon sign factory, only position with large firm considered. Many new ideas for production; 13 years' experience in vacuum industry. — Box 6383, c/o The Electrical Review.
 RADIO Technician. 20 years' experience, 15 yrs. execu-tive posts. convertant varied types, including radio location, etc., desires change. Write—Box 6396, c/o The Electrical Review.
 TECHNICAL Engineer, age 25, desires change. 3 years' experience in design. manufacture and testing of auto-matic control gear, good organiser and accustomed to responsibility. Release obtainable.—Box 6384, e/o The Electrical Review.

matic control gear, good organiser and accustomed to responsibility. Release obtainable.—Box 6384, c/o The Electrical Review. YoUNG Engineer (25), discharged soldier, requires responsible position with a London firm. Technical qualifications, national diploma.—Box 6377, c/o The Elec-trical Review. YOUNG man (23), exempt, seeks a progressive electrical Technical Assistant's position. Secondary education, excellent testimonials, intelligent and reliable. North London area preferred but others considered. Replies to —Box 6381, c/o The Electrical Review.

FOR SALE

Traders buying and selling hereunder must observe the Restriction of Resale Order, S. R. & O. 1942 No. 958.

GEORGE COHEN, SONS & CO. LTD

for

GUARANTEED ELECTRICAL

PLANT.

GENERATORS. MOTORS

SWITCHGEAR,

etc.

WOOD LANE, LONDON, W.12. Telephone: Shepherds Bush 2070

and STANNINGLEY, NEAR LEEDS.

Telephone: Pudsey 2241.

Established 1834.

27

WATER TUBE BOILERS IN STOCK

Two 12,000 lbs. evaporation, 200 lbs. W.P. One 12,000 .. 160 ..

We install complete, including brickwork. Economisers. Pumps, Piping Valves, Generating Sets and Motors in stock. Please send us your enquiries; we can give immediate delivery.

BURFORD, TAYLOR & CO. LTD.,

Boiler Specialists, Middlesbrough, Telephone, Middlesbrough 2622.
1000

100

1000

.....

100

100

State of the local division of the local div

1.11

er dans, Al. No.

i dent i SCA 5

10

REBUILT MOTORS AND GENERATORS

I ONG deliveries can often be avoided by purchasing rebuilt secondhand plant. We can redesign or replace surplus plant of any size.

SEND US YOUR ENQUIRIES.

OVER 1.000 RATINGS ACTUALLY IN STOCK HERE.

DYNAMO & MOTOR REPAIRS LTD., Wembley Park, Middlesex. Telephone: Wembley 3121 (4 lines).

Also at Phœnix Works, Belgrave Terrace, Soho Road, Handsworth, Birmingham, Telephone: Northern 0898.

26

35

ELECTRICAL REVIEW

"CANNING " PLATING MOTOR GENERATOR SETS FOR DISPOSAL

Three — 1,000 amp., 7 volts Two — 500 amp., 6 volts Two — 250 amp., 6/8 volts

All with 400-volt, 3-phase, 50-cycles, ball bearing, squirrel-cage driving motors and switchgear.

Box, 775, c/o The Electrical Review.

ELECTRIC MOTORS AND DYNAMOS

hold one of the largest stocks of New and Second-hand Motors. Secondhand machines are thoroughly overhauled. Inspection and tests can be made at our Works.

For Sale or Hire. Send your enquiries to :-

BRITANNIA MANUFACTURING CO. LTD.. 22-23. BRITANNIA STREET, CITY ROAD, LONDON, N.1. Telephone: 5512-3 Clerkenwell,

ARC WELDING MACHINES FROM STOCK

WE offer our latest type No. 2 Max-Arc Welder for immediate delivery, 15/250 amperes. Operates off any A.C. supply voltage. Send for details.

MAX-ARC WELDERS LTD.. 190. THORNTON ROAD, CROYDON THOrnton Heath 4276-8.

ECONOMISERS IN STOCK

TWO Green's Economisers, 208 tubes, 250 lbs. W.P. Guaranteed re-insurable and first-class condition only. low prices. Quotations per return. Installations delivered and erected complete.

BURFORD, TAYLOR & CO. LTD., 7. Commercial Street, Middlesbrough. Telephone 2622.

MODINSTAL ELECTRIC COMPANY LIMITED INDUSTRIAL INFRA-RED APPARATUS FOR PANT DRYING. COMPLETE EQUIPMENTS OR SINGLE UNITS REOVIDED. GUARANTEED HEAT GENERATORS. OLDHAM WORKS, OLDHAM TERRACE, ACTON, W.3, LONDON. Telephone: Acord 3504/5. M.E.C. APPARATUS, DULL EMITTER SYSTEM 59

A.C. MOTORS, 400/440/3/50

All Complete with Starting Gear

I.P.	Make.	Speed.	Type.	Brgs.	Price
75	Mather & Platt.	720	Slipring	RO	£170
10	MetVick.	580	Sa Cago	R.O.	2170
40	B Peebles	720	oq. casc	P.O.	200
30	Mather & Platt	720	Slipping	R.U.	280
30	Met .Vick	720	Supring	R.U.	2100
20	Mother & Diett	1 500	Sq. Cage	R.U.	£60
-0	D D L	1,000	A11 1	R.O.	£30
	b. Feebles	790	Slipring	R.O.	£80
19	Mather & Platt	1,450	-+4	R.O.	£65
la	Mather & Platt	750		R.O.	£60
0	Mather & Platt	750		R.O.	£50
10	Harland	720	Sq. Cage	R.O.	£18
	NO LIC	TINCE	PFOUDED		

ELECTRIC MACHINERY CO. (M/CR) LTD.,

New Union Works, New Islington, Aucoats, Manchester 801

FOR SALE

- 1 150-kVA Transformer, 10.750/400 volts, 3-phase, 50 cycles. D.C. Motors
- 400 volts, 3 h.p., 450 r.p.m.,
 400 volts, 5 h.p., 1,270 r.p.m., with reduction gear to 127 r.p.m.
 220 volts, 3 h.p., 1,100 r.p.m.
 - - All complete with starting gear and slide rails.

JOHNSON, MATTHEY & CO., LIMITED, 71/3, Vittoria Street, Birmingham, 1

BRASS NUTS

0, 2, 4, 6, 8 and 10 BA, Full and Lock, 1" and 5/16" Whit.

STEEL NUTS 0, 2, 4 and 6 BA, Full and Lock; 10 BA, Full. \$" and 5/16" Whit. and B.S.F.

STEEL AND BRASS STUDDING AND SCREWS.

APEX SALES, 6. Leaside Road, London, E.5. STA, 7131.

6336

400

BURDETTE & CO. LTD.

Stock

Reconditioned A.C. and D.C. Motors and Starters Equal to New.

STONHOUSE STREET, CLAPHAM, S.W.4.

Day and night service.

MACaulay 4555.

A large stock of surplus Carbon Rods, Ebonite, Fibre, A.D. Turnbuckles, etc., also Searchlights (sele or ine), Mirrors, Lenses, also Winches of our well-known self-sustaining types. Hundreds of thousands supplied during the last 40 years to Govt, depts, corporations and in-numerable traders.—London Electric Firm, Croydon, 55 A quartity of Eng. Materials to clear, such as Packing. Tape, Bolts, Nuts, Piping, Tubing, Conduit, Wire, teatheroid, Fittings, and many other items.—J. Gerber & Co. Ltd., Wembley. 80 A quarted, Fittings, and many other items.—J. Gerber & Co. Ltd., Wembley. 80 A quartent for the start of the start of the start and prepayment, reconditioned, guaranteed one year. Teattersca High Stretc, S.W.11. Tel, Baitersca 0780. 19 A.C. and D.C. Motors, all sizes, large stocks, fully guaranteed.—Milo Engineering Works. Milo Road, East Dulwich, S.E.22 (Forest Hill 4422). 6115 A.C. Storts, J./Solth h.p. to 3 h.p., form stock, for essential work only.—The Johnson Engineering Co. 5, Spencer Street, Leamiligton Sps. A Effall, Cables, all sizes, quartef for: good deliveries against Government contract numbers.—Edwardes Fros., 20, Blackfirias Road, London, S.E.1. 6385 A LTERNATING Petrol/parafin Sets, 400/3/50, direct

ALTERNATING Petrol/parafin Sets. 400(3/50, direct coupled on bed. First-class order. 25 kVA. 35 kVA. 50 kVA. 70 kVA. Fully tested, for quick delivery.— Gerber & Co. Ltd., Wembley, Middx. 804

ALTERNATOR, 500 kVA, 3-p., 50 c., 400/440 v., 750 revs., direct coupled exciter, 2 brgs., on bedplate. -Stewart Thomson & Sons, Fort Road, Seaforth, Liverpool

ALTERNATOR, 600 kVA, 400/3/50, 300 r.p.m., with erciter, for coupling. Like new, bargain.—J. Gerber & Co. Ltd., Wembley. BAKELITE Accessories, Switch-Plugs, B/C Adaptors, Lampholders, Iron Connectore, Better Hold

BAKELITE Accessories, Switch-Plugs, B/C Adaptors, Lampholders, Iron Connectors, Batten Holders, In-sulation Tape, etc. We carry large stocks. Wholesalers' enquiries and export orders solicited. Send 1d. stamp for complete list.—Marcus Fisher & Co. Ltd., 37. Aylmer Parade, London, N.2. BELT Grinders or Sanders, 4" wide belt, £5 5s.; 6 wide belt, £10 10s.—John E. R. Steel, Clyde Mills, Bingley. Phone 1066. DEREP V Transformer, 150 bVA, input 6 200 m 52

BERRY Transformer, 150 kVA, input 6.300 v., 3-phase, 50 cycles; secondary 410 v., 3-phase, 50 cycles; 210 v., single-phase. As new. Offers-O. A. Miller Last Co. Ltd.,

b) cycles; secondary 410 v., 3 pinase, 30 cycles; 240 v., single-phase. As new. Offers-O. A. Miller Last Co. Ltd., Northampton. 733 BEST English Cables; 1/.044 up to 127/.103, deliverics against M.O.S. requirements.—Edwardes Bros., 20, Blacktriars Road, London, S.E.1. 6394 CARBONS, large stocks assorted sizes, solid and cored.— Edwarder Brow 20, Blacktriars Road London S.E.1

Edwardes Bros., 20, Blackfriars Road, London, S.E.1

CARBONS, large stocks assorted sizes, solid and cored. Edwardes Bros., 20, Blackfriars Road, London, S. E 1. 6386 Cherrory, immediate deliveries.—Sloan Electrical Co. Ltd., 41, Kingsway, London, W.C.2. Solution, C. Cenerator, compounded, 4 kW, 110 volts, by Siemens. Apply—Avery & Vincent Ltd., Hartington Road, Southal. ELECTRIC Conveyor Furnace, suitable for vitreous enameling, annealing or stoving, length 75 ft., fring space 8" high, 6" wide. Three automatically controlled heating zones, accuracy ± 5°, temperatures 0 to 900° C. Five sneeds between 6 and 15 hours, but easily adaptable for other speeds. May be seen working, London area.— Boy 759, c/o The Electrical Review. ELECTRIC Light Check Meters for A.C. mains, 200/250-tion, electrically guaranteed, 108 6d, each.—London area.— Boy 759, c/o The Electrical Review. EV, 50 crycle, 3 phase, 5 amp. load. First-class condi-tion, electrically guaranteed, 108 6d, each.—London Central Radio Stores, 22, Lisle Street, London, W.C.2. FOUR identical 150 kW. "Weir Sulzer/E.C.C." Disseldriven Generating Sets, 220 volt D.C.—Stewart Thomson & Sons, Fort Rd, Seaforth, L'pool, 21. 24 ANCASHIRE Boilers, 30' × 9', for 160 lbs. (1922): 30' × 6' 6' and 15', bingley. Phone 1066. 50 ANCASHIRE Boilers, 30' × 9', for 160 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. (2022): 30' × 6' 6' and 16', for 100 lbs. and 300 lbs. Boiler Storage Tanks, all sizes. Enquiries

TeAD-covered and Armoured Cables, P.I. and V.I.R., various special lines at low prices.—Edwardes Brcs., 20, Blackfriars Road, London, S.E.I. 6387
 MOTOR Generator Sets and Convertors, all sizes and voltages from 4 kW up to 500 kW in stock.— Britanoia Manufacturing Co. Ltd., 22/26, Britannia Walk. City Road, London, N.I. Telephone, Clerkenwell 5512, 5513 & 5514.

MOTORISED 1" Bench Drilling Machine, 13 speeds, fill 11s.-John E. R. Steel, Clyde Mills, Bingley. Phone 1066. 51

Phone 1066. 51 MULTPLX Your Man Power1—with Morgan Electric Hoist Blocks, capacities from 5 cwt. to 10 tons, push. geared, or electric travelling, A.C. and D.C. supply-Delivery from 2.3 weeks.—Morgan Liftways & Powerways. 50, Wilkin Street, N.W.5. Gul. 1147. 795 NAMEPLATES. Engraving, Diesinking, Stencils, Steel Punches.—Stilwell & Sons Ltd., 152, Far Gosford Street, Coventry. 14 MEVENCE Detable Electric Drills in stock in sizes 47 MEVENCE Street and Street

Street, Coventry. NEW Portable Electric Drills in stock in sizes 4", 8", and 3". Immediate delivery for essential work. Write for quotation.—George Cohen, Sons & Co. Ltd., Wood Lane, London, W.12, and Stanningley, near Leeds. 29 PHONE 98 Staines. 60-kW crude oil Generating Set. 20 volts D.C.: 35-kW crude oil Generating Set. 20 volts D.C.: 250-kW Browett Steam Set. 220 volts D.C.: Weir Feed Pump, 94" × 7" × 21"; 35-h.p. Ruston Twin Vertical Diesel; cylindrical pressure Tank, 30" × 7" dia.— Harry H. Gardam & Co. Ltd., Staines. PORCELAIN Cleats, 2 and 3 groove, various sizes ex stock, price list.—Edwardes Bros., 20, Blackfriars Road, London, S.E.I.

PORCELAIN Insulators and Spindles, also Cleats, cheap.—Edwardes Bros., 20, Blackfriars Road, London, S.E.1.

ROTARY 000, S.F.1. DTARY Converters in stock, all sizes; enquirier invited.—Universal Electrical, 221, City Road lon, E.C.1. enquiries

Kither and State and St

SINGLE-core V.I.R., Braided Flexible, heavy insulation, carry 24 amps., cheap.—Edwardes Bros., 20, Black-friars Road, London, S.E.I. SPECIAL line, Beil and Telephone Wires, also screened wires, large quantity, cheap.—Edwardes Bros., 20, Blackfriars Road, London, S.E.I. STAFF Time Checking and Job Costing Time Recorders (all makes) for quick cash sale. Exceptional con-dition. Write—Box 528, Smiths, 100, Fleet Street. Jondon, E.C.4.

Chill indices for 528, Smiths, 100, Fleet Street.
 London, E.C.4.
 SWITCH and Fuse Units, Conduits and fittings, works requirements stocked.—Edwardes Bros., 20, Black-friars Road, London, S.E.1.
 TRANSFORMERS, single and three-phase. All types Diston 41959), Moxley Road, Bliston, Staffs.
 TUDOR Batteries for sale. 55 cells, L.F., 792 ampere hour, 110 cells, L.E., 370 ampere hour. Complete with charging board, regulator, automatic cut out and meters. Inspection can be made at the Cornwall Mental Hospital, Bodmin. All offers to be made in writing to the Steward.

Taspital, Bodmin. All offers to be made in which are the steward. Transformed to M.O.S. requirements.—Edwardes Bros., 20, Black-frars Road, London, S.E.I. WO dish-ended Lancashire Bollers by Danks, 30' \times 7' 6'', for 125 lbs. working pressure.—Thomas Mitchell & Sons Limited, Bolton. VARIABLE speed, A.C. Motors, Metro-Vick, 1.3 h.p. 618-1.830 r.p.m., 400 v., 3.phase, 50 cycles, perfect order.—Gillett Industries Ltd., Great West Rd., Isle-worth, Middx.

Worth, Midx. Bot Stat., Great west Rd., Bot Stat., Great Rd., Great Rd

field, Hants

field, Hants. 6374 250 kVA Alternator. 400 volts, 3-phase, 50 cycles, 750 revs., with direct coupled exciter.—Midland Coun-ties Electrical Engineering Co. Ltd., Grice Street. Spon Lane, West Bromwich. 36 1,000 h.p. Metro-Vickers Rolling Mill Motor. 36,015.050 volts. 184 r.p.m., low price.— 50x 769, c/o The Electrical Review. 2,000 kW, 440/500 volt D.C. Howden/English Elec-tric geared Turbo Generator Set, surface condenser, circulating pumps and switch panel.—Thomas Mitchell & Sons Limited, Bolton. 746

ARTICLES WANTED

A DVERTISER would be glad to get in touch with firms dealing with materials, wire frames and tools (hand and machine) for lamp shade manufacture.—Box 6397. c/o The Electrical Review. ELECTROLVIIC Condensers, 8 ml., 350 v. and above, any quantity, regular supply 144 pm. required.—Box 6366, c/o The Electrical Review.

10

Et

NR

NGINEERING Technical Books (new or secondhand) Biogramma and the second and the sec Two th.n. 440-volt, 120-r.p.m. D.C. Motors; one 3-h.p., 200 volt, T.E. D.C. Motor, 800 r.p.m. Full particulars references the state of the state of the state of the state WANTED, Rotary Converters, any size.—Universal, 221, City Road, London, E.C.I. 222, City Road, London, E.C.I. 220, ANTED, 800-watt or 1.000-watt., 3-h.p. Kohler Petrol Electric Lighting Set. State condition and price.—Bradley, "Ravenswood, Oakwood Drive, East Vorsley, Surrey." (Ravenswood, Oakwood Drive, East Vorsley, Surrey." (Ravenswood, Oakwood Drive, East Vorsley, Surrey." (Ravenswood, Oakwood Drive, East Vorsley, Surrey.") (Ravenswood, Oakwood Drive, Caster, Surrey.") (Ravenswood, Oakwood Drive, East Vorsley, Surrey.") (Ravenswood, Vorsley, Surrey, Market, Surrey, Norsley, Surrey, Surey, Surrey, Surrey, Surrey, Surrey, Surrey, Surrey, Surrey,

price - Diadey, Horsley, Surrey, 1 gross E.S.C. Lampholders, cord grip type. Particulars to 2 — Edward Matthews Ltd., Bradley, Bilston, Staffs, 799

WORK WANTED AND OFFERED

MOTOR REPAIRS

REWINDING and Repairs. Small Motors and Electric RETOOLS rewound and repairs. Ginan account and income experience in this work. Guaranteed work and prompt service. Large assortment of Motors available from stock.

> SOUTHERN IGNITION CO. LTD., 190, THORNTON RD., CROYDON. THOrnton Heath 4276-8

37

REWINDING AND REPAIRS

WE rewind and repair any motors, A.C. or D.C., from 1 h.p. to 500 h.p. Motors lent while repairs are being carried out. Established over 24 years.

W. H. SUGDEN & CO. LTD., Glenny Road, Barking, Essex. Phone, Rippleway 3302.

DESIGNS AND INSTALLATIONS CO., GUILDFORD

THE above company can undertake design and development work from specification, sketches or rough models of small electrical and mechanical equipment, also production of finished drawings and technical data. Production of artists' free-hand sketches, photographs and enlargements of models, etc. Specialists in radio and switchgear. All work undertaken in strictest confidence.

6337

48

A RMATURE, Rotor and Stator rewinds and repairs. fractional to 60 h.p. Prompt deliveries.—T. A. Boxall & Co., Horley, Surrey. Phone 654. G373 ELECTRICAL Measuring Instruments skilfully repared and recalibrated.—Electrical Instruments Repair Service. "Stainmede." Forlease Road, Maidenhead. 6340 MACHINING Work, for Centre Lathes up to 63 in. centres and medium-sized milling (good grade work preferred).—The London Electric Firm, Croydon. Up and 4871 lands 4871

Iands 4871.
 Image: Construct and the second state of the sec

AGENCIES

A Young Man, with good connection in all branches, wishes to contact manufacturers desiring representa-tion in London and Home Counties.—Box 6342, c/o The

A GENCIES for Domestic Electrical Appliances, Northern Counties and Scotland. Immediate turnover guaran-teed, commission or buying basis. Apply—Box 790, c/o The Electrical Review.

A DVERTISERS having a very extensive clientele in the A DVERTISERS having a very extensive clientele in new electrical trade with local authorities, supply and distributive companies, invite contact with reputable Electrical and Mechanical Appliances Manufacturers with a view to representation or sole selling rights in Great Britain or London and Home Counties. Territories already covered by own representatives. Prepared to initiate and conduct an energetic sales policy either on a commission or huying basis. Post-war arrangements welcomed.—Box 791, e/o The Electrical Review.

GENCIES required for London, South of England, for A GENULES required for London, South of England, for the following: (1) Domestic electrical appliances; (2) Brass electrical accessories, switch plugs, etc.: (3) Con-duit. Advertisers have clientele with every wholesaler in the territory mentioned. Immediate turnover can be guaranteed. Either commission or buying basis. Post-war arrangements considered.—Box 64, c/o The Elec-trical Review.

GENCIES required. South of England, including the London area: (a) Cables; (b) Small Switchgear; (c) Transformers; or any lines suitable for distribution for wholesalers' business.—Box 40, c/o The Electrical Review.

A GENT required for the Lancashire, Cheshire and/or Yorkshire area by manufacturers of Electrical Measur-ing Instruments. Must he technically qualified and have existing connection in the electrical manufacturing and radio trade.—Box 755, c/o The Electrical Review.

ONDON Wholesalers (Manufacturers' Agents and UNDUN Wholesalers (Manufacturers' Agents and Import Exporters), with excellent connections and representatives throughout the U.K., require new lines for home trade: Electrical articles, fancy goods, fancy jewellery, etc. Prepared to act as distributing agents. Showrooms available if necessary, Write—Box 749, c/o The Electrical Review.

MANUFACTURERS' Agents, covering the whole of Great Britain and Colonies, are desirous of contact-ing manufacturers with a view to sole selling rights (either commission or buying), post-war arrangements considered. —Box 23, c/o The Electrical Review.

MANUFACTURERS of electro-magnetic relays require MARGFACTORERS of electro-magnetic relays require an Agent for each of the following areas: Home Councies, South Coast, West of England, South Wales, Northern Ireland, Eire. Must be technically qualified and have connections in the industrial and supply companies field. Give full details, stating territory covered and agencies held.—Box 710, c/o The Electrical Review.

OLD-established Electrical Wholesale Firm, with sound O Libestatusiand Electrical Wildesale Firm, with south finances, large industrial connections, everal branches, showrooms and watchcuses in London and the Provinces, open to accept agencies, buying or selling. Opportunity for first-class manufacturers to establish close contacts for post-war development.—Box 738, c/o The Electrical Review.

RADIO, Electrical Dealer desires agencies: equipment, spares, solder irons, tools, instruments, radios, lamps, etc., etc. Write-Goldies Radio, 359, Paul Kruger Street, Pretoria, South Africa. 6375

TECHNICAL Representative, employed for 10 years by Jarge electrical manufactures, excellent to operate by South Midlands, requires post-war agencies in the electrical trade. Office and warehouse will be available for stocks.— Box 6372, c /o The Electrical Review.

BUSINESS OPPORTUNITIES

THE CHARTERHOUSE INDUSTRIAL DEVELOPMENT COMPANY LIMITED

is a pioneer in the specialised business of providing capital for established industrial undertakings still in the develop-ment stage and not yet ready to appeal for public subscriptions.

The post-war period promises to be one of considerable industrial activity and Charterhouse Industrial Develop-ment Company Limited, with its experience and powerful connections, is prepared to discuss with industrialists their plans for development where the introduction of new central forme next of the programme. capital forms part of the programme.

> Enquiries should be addressed. by post in the first instance, to

CHARTERHOUSE INDUSTRIAL DEVELOPMENT COMPANY LIMITED.

6, Old Jewry, London, E.C.2.

784

ELECTRICAL REVIEW

October 20, 1944

MISCELLANEOUS

BATTERY Chargers Modernised. Your old Charger made like new by specialists. Conversion from valve to metal service. --Runbaken Electrical Products. Manchester, 1. 45 ON'T Disclose Your Plans. Produce blue prints and black line copies, etc., in your own office, without glass frame, privately and economically. -''Arcofler.'' Copier from 28 shillings. As supplied to H.M. Government.--W.A. Houghton, 53. Kenley Road, Merton, S.W.19. 43 L ESLIE Dixon & Co. for Dynamos, Motors. Switchgear. Chargers and Telephones.--214. Queenstown Road, Battersea. S.W.S. Telephone, Macaulay 2159. Nearest RIA, Sta.: Queen's Road, Battersea (S.R.). Marterst Development from engineers' roughs, etc., etc., and production of finished drawings. 60 hrs. per week. Strictess confidence and accurate, high quality work assured.--Box 6338, c/o The Electrical Review. Broncore and securate holographs arys more than a thousand words. Realistic photographs for cata-foresent and after-the-war uses. Records made of present work, premises, etc. --Miles & Kaye Ltd., Industrial Photo present and after-the-war uses. Records made of present work, premises, etc.--Miles & Kaye Ltd., Industrial Photo problems, 100, Southampton Row, London, W.C.1. Telephone, Holborn 6858. Established over 50 years. 723 BATTERY Chargers Modernised. Your old Charger made

EDUCATIONAL NOTICES

LATEST A.M.I.E.E. RESULTS

TN the recent Examinations held by the Institution of IN the recent Examinations held by the Institution of Electrical Engineers 47? Candidates sat who had taken B.I.E.T. courses. Of these 45? were successful in passing the examinations. We believe this record of 45? successes out of 47? entrants has never before been approached by any oral or correspondence tutorial organisation, and indicates the very high efficiency of the modern system of Technical Training which we have laid down.

The B.I.E.T. tutorial organisation is waiting to assist you either with a short specialist course or complete training for a recognised examination.

We have available a large full-time staff of instructors, while the efficiency of dur extensive organisation is a byword among engineers.

WE GUARANTEE-" NO PASS-NO FEE"

May we send a copy of "ENGINEERING OPPOR-TUNITIES"? Containing a great deal of useful advice and detailed information on over 200 Home-Study Courses and examinations, this handbook is of very real value to the ambitious engineer.

Our highly informative handbook will be sent FREE and without obligation on request.

BRITISH INSTITUTE OF ENGINEERING TECHNOLOGY.

Established 1927-over 200,000 students. 12. Shakespeare House, 17, 18 & 19. Stratford Place, Oxford Street, London, W.I.

> Great Possibilities for TECHNICALLY QUALIFIED ENGINEERS

Key Men In War-Time and Afterwards

THE finest posts and the great majority of posts in THE finest posts and the great majority of posts in Great Britain in this war are technical. The same will be the case when the war is over. The vast increase in mechanisation now being applied to war purposes will then be suitably utilised in reconstruction, and in trade and commerce. Take a recognised Engineering Quali-fication through home-study with the T.G.B., whose Students have gained 35 FIRST PLACES in the A.M.Inst.C.E., A.M.I.E.E. A.M.I.Mech.E., A.F.R.A.S., etc., examinations. Write to-day for "The Engineer's Guide to Success." containing the world's widest choice of engineering Course-over 200-covering all branches: Electrical, Aeronautical, Mechanical, Wireless, etc.

THE TECHNOLOGICAL INSTITUTE OF GT. BRITAIN. 35, Temple Bar House, London, E.C.4.



He end Jerrules & with Identity Discs in CASEIN PLASTICS

Plain or engraved to customers' requirements. Standard Colours : black, white, blue, green, red and yellow.

The brilliant and permanent colours obtainable in casein plastics make this material pre-eminent for identification under poor lighting conditions.

Manufacturers :





ELECTRICAL REVIEW Derset House, Stamford Street LONDON, S.E.I



77

D

-

ELECTRICAL REVIEW

(Supplement) 75



Every type of wire which RICHARD JOHNSON & NEPHEW LTD. manufacture is the very best for its purpose that modern methods and science can produce. . . . RICHARD JOHNSON & NEPHEW LTD. have a proud record of unfailing service—worthy of your confidence.

Richard JOHNSON & NEPHEW Limited

You can Rely on Service & Satisfaction

if you deal with E. Dawson (Lamp Factors) Ltd., Wholesale Distributors to the Electrical Trade for 30 years, with an unsurpassed reputation for personal attention to all your electrical requirements even under present day conditions. Large stocks of all available types of E.L.M.A. Lamps, C.M.A. Cables, Fluorescent Fittings, etc.

"If it's to be got — we'll get it !" E. Dawson (Lamp Factors) Ltd. 10 Gray's Inn Road, London, W.C.1 HOLborn 5341-2. Grams: "Edawsicko, Holb, London "



— a creative force in Britain's post-war engineering renaissance

ELECTRICAL REVIEW

October 20, 1944



ELECTRICAL REVIEW

(Supplement) 77



ELECTRICAL REVIEW

Index to Advertisers

		PAGE
Aidas Electric Ltd		. 58
Airscrew Co. Ltd		. 62
Astor Boisselier & Lawrence Ltd		. 60
Automatic Coil Winder & Elecl. Equipment Co.	Ltd	. 77
Babcock & Wilcox Ltd.		. 38
Barns, W., & Son		. 52
Belling & Co. Ltd		12
Black & Decker I td		22
Braithwaite & Co. Engineers I td.		53
Bray George & Co. Ltd		56
British Aero Components Itd		69
British Electric Pasistance Co. Ltd		48
Diffish Mion Co. Ltd		
British Bower Transformer Co. Ltd	• • • •	
British Thomson Houston Co. Ltd.	5	8, 19
British Vanuum Classics & Engineering Co. Ltd.		64 I C
British vacuum Cleaner & Engineering Co. Ltd.		
Burgess Products Co. Ltd		. 30
Burt, Boulton & Haywood Ltd		. 04
Cable Makers' Association	Cov	er 1
Canning, W., & Co. Ltd		. 14
Carter & James, H. W., Ltd		. 56
Churchouse, C. M., Ltd		. 48
City Electrical Co		. 80
Cole, E. K., Ltd.		. 49
Compound Electro Metals Ltd		. 50
Connolly's (Blackley) Ltd		. 46
Constructors Ltd		. 62
Corrugated Packing & Sheet Metal Co. Ltd		. 54
Cox-Walkers Ltd		. 54
Critchley Bros. Ltd		. 74
Crompton Parkinson LtdCover i,	20	& 61
Cryseico Ltd		. 30
Dalvte Electrical Co. Ltd.		. 64
Davidson & Co. Ltd.		. 9
Davis & Timmins Ltd.		82
Dawson, E., (Lamp Factors) Ltd.		75
Desoutter Bros. Ltd.		3
Dopoyan Electrical Co. Ltd.		87

	PA	GE
Dorman & Smith Ltd		55
Drake & Gorham Ltd		37
Dryden, Thomas, & Sons Ltd		82
Duratube & Wire Ltd		62
Durham Cables Ltd		79
E. & M. Developments Ltd		54
Edison Swan Electric Co. Ltd		35
Electric Construction Co. Ltd		34
Evans Lifts Ltd.		60
Everett, Edgcumbe & Co. Ltd		40
Ferranti Ltd	8	23
Geinel, William, Ltd.		63
General Electric Co. Ltd. 16	2	68
Gent & Co. Ltd	~	24
Glenfield & Kennedy 1 td Cox	Ier	iv
Glover W T & Co Itd	-	10
Grelco I td		62
Harboro' Rubber Co. Ltd		82
Hartley & Baldwin I td		70
Hartrop Ltd	*	10
Henlau's W/T Telegraph Works Co. Ltd		12
Higgs Motors 1td		20
Hoover Itd		40
Honkinsons I td	•	70
Howells (Electric Motors) Ltd		19
Inovens (Electric Motors) Ltd	ver	111
Igrame Electric Co. Ltd	•	20
Tokenen Dishand & Manham Lad		27
Johnson, Kichard, & Nephew Ltd	•	13
Vidde Welter Co.	1.00	20
Kidde, walter, Co		10
Klaxon Ltd	•	32
Lancashire Cables Ltd	•	44
Lancashire Dynamo & Crypto Ltd	•	20
Laurence, Scott & Electromotors Ltd	•	42
Legg (Industries) Ltd.	•	60
Litholite Insulators & St. Albans Mouldings Ltd		11
Liverpool Electric Cable Co. Ltd	•	28
London Electric Firm		60
London Electrical Co. (Blackfriars) Ltd		17

(Continued on page 80)



MIDDLESEX



WE MANUFACTURE AN EXTENSIVE RANGE OF SCREWED FITTINGS. WRITE FOR CATALOGUE NOW

HARTLEY & BALDWIN LTD. ARBAL HOUSE 7 NEWHALL ST., BIRMINGHAM 3 WHOLESALE ONLY

ELECTRICAL REVIEW

(Supplement) 79





PAGE

October 20, 1944

Index to Advertisers

(Continued from page 78)

Macpherson, Donald, & Co. Ltd	. 57
Matthews & Yates Ltd	. 80
McGregor, Robert, & Co	. 58
M.C.L. & Repetition Ltd.	. 1
Metalastik Ltd.	. 66
Metropolitan-Vickers Electrical Co. Ltd21	& 45
Metway Electrical Industries Ltd	44
Midland Electric Mfg Co Ltd	33
MK Electric Ltd	. 55
Nalder Bros & Thompson Ltd	25
Newman Motors	. 40
Non Femous Die Costine Co. 1td	. 0
Demites Here & Conder Ltd.	. 04
Parmiter, Piope & Sugden Ltd	. 01
Parsons, C. A., & Co. Lto	
P. & B. Engineering Co. Ltd.	. 64
Premier Electric Heaters Ltd	, 32
Pultra Ltd.	. 59
Radchiffe, Henry, & Co. Ltd	. 46
Ratcliffe, F. S., (Rochdale) Ltd.	. 74
Record Electrical Co. Ltd	. 63
Reyrolle, A., & Co. Ltd.	. 31
Riley, Robert, Ltd	. 44
Rival Lamps Ltd.	. 76
Rix, G. A.	. 56
Ross Courtney & Co. Ltd.	1
Rotherham & Sons I td	57
Sanders Wm & Co (Wedneshury) I td	47
Scholes George H & Co. Ltd	59
Scott Hugh] & Cot (Belfast) Ltd	67
Shaffeld Smalting Co. Ltd	. 50
Siemens Brothers & Co. Ltd.	. 50
Simmondo Appagaganias I td	. 13
Sima E D Ltd	. 43
Shins, F. D., Ltd.	- 32
Standard Telephones & Cables Ltd	- 20
Stering varnish Co. Ltd.	. 10
Stone, W. H., & Co. (Cardiff) Ltd	. 11
Sturtevant Engineering Co. Ltd.,	
Sutcliffe, Speakman & Co. Ltd	. /6
Thew, Edward H., Ltd	. 82
Tube Products Ltd	. 27
Tyne Truck & Trolley Co. Ltd	. 58
Varley Magnet Co	. 77
Veritys Ltd	. 41
Ward & Goldstone Ltd	. 67
Wardle Engineering Co. LtdCo	ver iii
Welwyn Electrical Laboratories Ltd.	. 76
Westminster Engineering Co. Ltd.	. 1
Westool Ltd.	. 80
Wilcox, Edward, & Co. Ltd.	. 46
Wilmot-Breeden Ltd.	75
Wolf, S., & Co. Ltd.	19
Young Accumulator Co. Ltd.	56
Zenith Electric Co. Ltd.	81

The fact that goods made of raw materials in short supply owing to war conditions are advertised in this Journal should not be taken as an indication that they are necessarily available for export





LTD





UNIT TYPE BOARDS

PARMITER, HOPE & SUGDEN, LTD. Fluvent Electrical Works

Longsight, Manchester 12

(REGD. TRADE-MARK)



Improved Type

CERAMIC EMBEDDED RESISTORS

of the highest quality, complying with all Government Specifications

Please allow us to send you a copy of our descriptive catalogue

THE ZENITH ELECTRIC CO. LTD. Zenith Works, Villiers Road Willesden Green, London, N.W.2

Villesden Green, London, N.W.

Phone : WiLlesden 4087-8-9 Grams : "Voltachm, Phone, London "

ELECTRICAL REVIEW

October 20, 1944

• We are now able to supply Brass or Steel Studding from stock in the following sizes :

> 0-8 BA [∦][″]−¹⁄₄[″] Whitworth

Supplied in 12 inch lengths in gross bundles. Special lengths supplied to order.

We are manufacturers of Screws, Small Turned Parts and Inserts. Enquiries invited.



WALTHAMSTOW ·

Telephone : Larkswood 2244 and 4464

LONDON

E.17

Engravea Inn and CAST IDULOFU PURRER PART ENAMELLED PLATES Enquiries are invited by the Empire's largest general engravers for present we can deal only ror the present we can deal only with Enguines for permitted essen tial Moulded Rubbers and look ahead and prepare for the future restoration of the complete "DAINITE" Service ENGRAVED BRASS, CAST BRASS AND ALUMINIUM. tial look ENAMELLED BRONZE AND CHEMICALLY ENGRAVED PLATES of all types In all languages Samples and quotations for large or small quantities HARBORG' RUBBER CO.LTO upon request. Phone or write, MARKET HARBOROUGH EDWARD H. THEW LTD 1866 Telephone 20221 ARTHING ITH SPE *mature* ITE AND GRIP RMOURING Note the tongue which ensures perfect and permanent contact. Easy Nuts cannot to fix. Nuts cannot turn. All sizes from half to two inches THE DONOVAN ELECTRICAL CO. LTD Thos DRYDEN & Sons Ltd. 467 **BIRMINGHAM 9** Electrical Manufacturers and Stockholders

Head Office: BILLET

ROAD

Printed in Great Britain at THE CHAPEL RIVER PRESS, Andover, Hants, and published by ELECTRICAL REVIEW, LIMITED, at Dorset House, Stamford Street, London, S.E.1.

HOWELLS (ELECTRIC MOTORS) LTD. stoke-on-trent, england





All sizes from ¹/₂ to 5 h.p. now available

- No larger than protected type
- Supersedes all fan-cooled types

LONDON : Palmers Green 5428 MANCHESTER : Didsbury 4709 BRISTOL : 43409 BIRMINGHAM : Central 7909 STOKE-ON-TRENT : 29624



WARDLE ENGINEERING CO. LTD.

LONDON 34 VICTORIA STREET, SW.I

111

WATER

Kennedy Hot Water Meters are specially designed for measuring boiler feed, and are extensively used for this purpose in all parts of the world. They are extremely accurate at all speeds, since they measure the actual distance travelled by the piston, and not the number of strokes. Thus long or short strokes, due to rapid or slow working, do not affect their accuracy, which is guaranteed to be within 1%

Kennedy POSITIVE METERS

FCID21C/

A KENNEDY POSITIVE FEED WATER METER INSTALLED ON BOILER PLANT.

iv



at all rates of flow. They cause very little extra back pressure on the pumps on account of their large delivering capacity, for which reason a smaller nominal size of meter than the size of pipe can often be employed. All parts are of substantial construction, and there is no delicate mechanism exposed to the action of the water. If oiled and cleaned periodically, the meters can be maintained almost indefinitely at a very small cost, and we have records of these meters working continuously for eighteen

years without being dismantled or requiring repair. All parts are made accurately to gauge so that spares can be easily and quickly substituted, and parts subject to pressure are tested to 500 lb. per square inch.

